



## FCC TEST REPORT

**FCC ID: 2ATQZ-GE1000**

On Behalf of

Shenzhen Mooer Audio Co.,Ltd

Guitar Multi Effect

Model No.: GE1000, GE1000Li

Prepared for : Shenzhen Mooer Audio Co.,Ltd  
Address : 5F/2F, Unit B and 6F, Unit D, Jinghang Building, Liuxian 3rd Road,  
Baoan 71 District, Shenzhen

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.  
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,  
Shenzhen, Guangdong, China

Report Number : A2308014-C05-R06  
Date of Receipt : October 13, 2023  
Date of Test : October 13, 2023 - December 18, 2023  
Date of Report : December 18, 2023  
Version Number : V0  
**Result Pass**

## TABLE OF CONTENTS

Description	Page
<b>TABLE OF CONTENTS</b> -----	<b>2</b>
<b>1. Summary of Standards And Results</b> -----	<b>6</b>
1.1. Description of Standards and Results -----	6
<b>2. General Information</b> -----	<b>7</b>
2.1. Description of Device (EUT) -----	7
2.2. Accessories of Device (EUT) -----	8
2.3. Tested Supporting System Details-----	8
2.4. Block Diagram of connection between EUT and simulators-----	8
2.5. Test Mode Description -----	8
2.6. Test Conditions -----	9
2.7. Test Facility -----	9
2.8. Measurement Uncertainty -----	9
2.9. Test Equipment List-----	10
<b>3. Spurious Emission</b> -----	<b>11</b>
3.1. Test Limits-----	11
3.2. Test Procedure-----	11
3.3. Test Setup-----	12
3.4. Test Results-----	13
<b>4. Power Line Conducted Emission</b> -----	<b>20</b>
4.1. Test Limits-----	20
4.2. Test Procedure-----	20
4.3. Test Setup-----	20
4.4. Test Results-----	20
<b>5. Conducted Maximum peak Output Power</b> -----	<b>25</b>
5.1. Test limits-----	25
5.2. Test Procedure-----	25
5.3. Test Setup-----	25
5.4. Test Results-----	25
<b>6. Peak Power Spectral Density</b> -----	<b>26</b>
6.1. Test limits-----	26
6.2. Test Procedure-----	26
6.3. Test Setup-----	26
6.4. Test Results-----	26
<b>7. Bandwidth</b> -----	<b>29</b>
7.1. Test limits-----	29
7.2. Test Procedure-----	29
7.3. Test Setup-----	29
7.4. Test Results-----	29
<b>8. Band Edge Check</b> -----	<b>33</b>
8.1. Test limits-----	33
8.2. Test Procedure-----	33
8.3. Test Setup-----	33
8.4. Test Results-----	33
<b>9. Antenna Requirement</b> -----	<b>37</b>
9.1. Standard Requirement-----	37
9.2. Antenna Connected Construction -----	37
9.3. Results-----	37

<b>10. Test setup photo</b> -----	<b>38</b>
10.1. Photo of Radiated Emission test-----	38
10.2. Photo of Conducted Emission test -----	39

### TEST REPORT DECLARATION

Applicant : Shenzhen Mooer Audio Co.,Ltd  
 Address : 5F/2F, Unit B and 6F, Unit D, Jinghang Building, Liuxian 3rd Road, Baoan 71 District, Shenzhen  
 Manufacturer : Shenzhen Mooer Audio Co.,Ltd  
 Address : 5F/2F, Unit B and 6F, Unit D, Jinghang Building, Liuxian 3rd Road, Baoan 71 District, Shenzhen  
 EUT Description : Guitar Multi Effect  
 (A) Model No. GE1000, GE1000Li  
 (B) Trademark **MOOER**


Measurement Standard Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.247**  
**ANSI C63.10-2013**

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Yannis Wen  
 Project Engineer 

Approved by (name + signature).....: Reak Yang  
 Project Manager 

Date of issue.....: December 18, 2023

**Revision History**

Revision	Issue Date	Revisions	Revised By
V0	December 18, 2023	Initial released Issue	Yannis Wen

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Test Requirement	Standards Paragraph	Result
Conducted Emission	FCC PART 15	15.207	P
6dB Bandwidth	FCC PART 15	15.247 (a)(2)	P
Conducted Maximum Peak Output Power	FCC PART 15	15.247 (b)(3)	P
Radiated Spurious Emission	FCC PART 15	15.247 (c)	P
Conducted Spurious & Band Edge Emission	FCC PART 15	15.247 (d)	P
Power Spectral Density	FCC PART 15	15.247 (e)	P
Radiated Band Edge Emission	FCC PART 15	15.205	P
Antenna Requirement	FCC PART 15	15.203	P

Note: 1. P is an abbreviation for Pass.

2. F is an abbreviation for Fail.

3. N/A is an abbreviation for Not Applicable.

4. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

Description	: Guitar Multi Effect
Model Number	: GE1000, GE1000Li
Diff	: There is no difference except for the appearance color and GE1000 without battery, GE1000Li with battery. All tests were conducted using the GE1000 model.
Power supply	: DC 9V from adapter and DC 7.4V from battery.
Radio Technology	: 2.4G
Operation frequency	: 2415-2455MHz
Channel No.	: 3 Channels
Modulation type	: GFSK
Antenna Type	: Internal antenna, Maximum Gain is 1.5dBi. (Antenna information is provided by applicant.)
Software version	: V1.0
Hardware version	: V1.0
Connector cable loss	: N/A
Intend use environment	: Residential, commercial and light industrial environment

Remark: The EUT has two RF antennas, one of which is a PIFA antenna with a maximum gain of -0.58dBi, and the other is a chip antenna with a maximum gain of 1.5dBi, so this report evaluates the antenna with the largest gain, which is the worst data..


## 2.2. Accessories of Device (EUT)

Accessories : SWITCHING ADAPTER  
 Manufacturer : Shenzhen Roadsunny Technology Co., Ltd.  
 Model : RS-09030001D  
 Ratings : INPUT: 100-240V~50/60Hz 1.0A MAX  
 OUTPUT: 9V=3.0A

## 2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDoC
1.	Notebook PC	Lenovo	ThinkPad E14	/	/
2.	Guitar	Mooer	/	/	/
3.	Microphone	Sony	/	/	/
4.	Speaker	VDL	MASS 1	G130101010136	/

## 2.4. Block Diagram of connection between EUT and simulators



## 2.5. Test Mode Description

Duty cycle :100%		
Mode	Channel	Frequency (MHz)
GFSK	Low :CH1	2415
	Middle: CH2	2435
	High: CH3	2455



## 2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	24°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	980kPa

## 2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd  
 Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,  
 Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission  
 Registration Number: 293961

July 25, 2017 Certificated by IC  
 Registration Number: 12135A

## 2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.13dB(Polarize: H)
	4.16dB(Polarize: V)
Uncertainty for radio frequency	$5.4 \times 10^{-8}$
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

## 2.9. Test Equipment List

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	/	N/A	2022.05.17	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	2.3	102137	2023.08.16	1Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY499100060	2023.08.16	1Year
Receiver	ROHDE&SCHWARZ	ESR	2.28 SP1	1316.3003K03-10 2082-Wa	2023.08.16	1Year
Receiver	R&S	ESCI	4.42 SP1	101165	2023.08.16	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	/	VULB 9168#627	2023.08.28	1Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	/	2106	2023.08.19	1Year
Loop Antenna	SCHWARZBECK	FMZB 1519B	/	00128	2023.08.19	1Year
RF Cable	Resenberger	Cable 1	/	RE1	2023.08.16	1Year
RF Cable	Resenberger	Cable 2	/	RE2	2023.08.16	1Year
RF Cable	Resenberger	Cable 3	/	CE1	2023.08.16	1Year
Pre-amplifier	HP	HP8347A	/	2834A00455	2023.08.16	1Year
Pre-amplifier	Agilent	8449B	/	3008A02664	2023.08.16	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	/	8126-466	2023.08.16	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	101043	2023.08.16	1Year
Horn Antenna	SCHWARZBECK	BBHA 9170	/	00946	2023.08.19	1Year
Preamplifier	SKET	LNPA_1840 -50	/	SK2018101801	2023.08.16	1 Year
Power Meter	Agilent	E9300A	/	MY41496628	2023.08.16	1 Year
Power Sensor	DARE	RPR3006W	/	15100041SNO91	2023.08.16	1 Year
Temp. & Humid. Chamber	Teelong	TL-HW408S	/	TL-20191205-01	2023.07.25	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	/	20140927-6	2023.08.16	1 Year
Adjustable attenuator	MWRFtest	N/A	/	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	/	N/A	N/A	N/A

## Software Information

Test Item	Software Name	Manufacturer	Version
RE	EZ-EMC	EZ	Alpha-3A1
CE	EZ-EMC	EZ	Alpha-3A1
RF-CE	MTS 8310	MW	V2.0.0.0

### 3. SPURIOUS EMISSION

#### 3.1. Test Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

**NOTE:**

- a) The tighter limit applies at the band edges.
- b) Emission Level(dB uV/m)=20log Emission Level(uv/m)

#### 3.2. Test Procedure

The measuring distance of 3m shall be used for measurements at frequency up to 1GH and above 1GHz, The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above1GHz testing, The table was rotated 360 degrees to determine the position of the highest radiation


The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set of make measurement.

The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Qusia Peak Detector mode premeasured


If Peak value comply with QP limit Below 1GHz.The EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.

For the actual test configuration, please see the test setup photo.


### 3.3. Test Setup



Below 30MHz Test Setup



Above 30MHz Test Setup



Above 1GHz Test Setup

### 3.4. Test Results

Test Condition

Continual Transmitting in maximum power.

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHz~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

We have scanned the 10th harmonic from 9 kHz to the EUT.


Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: 1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

2. All EUTs, modes and channels have been tested, only show the test data of the worst Channel in this report.

**Antenna polarity: Horizontal**




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		47.4197	10.50	14.07	24.57	40.00	-15.43			peak
2		101.6087	16.21	11.01	27.22	43.50	-16.28			peak
3		133.1667	15.20	13.82	29.02	43.50	-14.48			peak
4	*	158.0569	23.34	15.04	38.38	43.50	-5.12			peak
5		172.1555	22.04	13.78	35.82	43.50	-7.68			peak
6		363.4090	13.66	15.50	29.16	46.00	-16.84			peak

Note: 1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Antenna polarity: Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	30.0491	21.83	13.52	35.35	40.00	-4.65			peak
2		49.0030	16.11	14.03	30.14	40.00	-9.86			peak
3		67.7384	18.41	11.79	30.20	40.00	-9.80			peak
4		105.4072	18.69	11.38	30.07	43.50	-13.43			peak
5		158.0200	22.18	15.04	37.22	43.50	-6.28			peak
6		172.1757	24.28	13.77	38.05	43.50	-5.45			peak

Note: 1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Notes: Above is below 1GHz test data. This report only shall the worst case mode for TX 2415MHz.


From 1G-25GHz

Test Mode: TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	45.95	V	33.95	10.18	34.26	55.82	74	-18.18	PK
4804	36.89	V	33.95	10.18	34.26	46.76	54	-7.24	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	45.13	H	33.95	10.18	34.26	55.00	74	-19.00	PK
4804	34.66	H	33.95	10.18	34.26	44.53	54	-9.47	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: TX Mid									
4880	44.81	V	33.93	10.2	34.29	54.65	74	-19.35	PK
4880	36.84	V	33.93	10.2	34.29	46.68	54	-7.32	AV
7320	/	/	/	/	/	/	/	/	/
9760	/	/	/	/	/	/	/	/	/
4880	42.96	H	33.93	10.2	34.29	52.80	74	-21.20	PK
4880	36.26	H	33.93	10.2	34.29	46.10	54	-7.90	AV
7320	/	/	/	/	/	/	/	/	/
9760	/	/	/	/	/	/	/	/	/
Test Mode: TX High									
4960	45.70	V	33.98	10.22	34.25	55.65	74	-18.35	PK
4960	34.42	V	33.98	10.22	34.25	44.37	54	-9.63	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	42.34	H	33.98	10.22	34.25	52.29	74	-21.71	PK
4960	33.73	H	33.98	10.22	34.25	43.68	54	-10.32	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									




Conducted RF Spurious Emission

Tx. Spurious NVNT GFSK 2415MHz Ant1 Ref




Date: 28.NOV.2023 11:08:45

Tx. Spurious NVNT GFSK 2415MHz Ant1 Emission




Date: 28.NOV.2023 11:09:03

Tx. Spurious NVNT GFSK 2435MHz Ant1 Ref




Date: 28.NOV.2023 11:20:34

Tx. Spurious NVNT GFSK 2435MHz Ant1 Emission




Date: 28.NOV.2023 11:20:52

Tx. Spurious NVNT GFSK 2455MHz Ant1 Ref



Date: 28.NOV.2023 11:23:38

Tx. Spurious NVNT GFSK 2455MHz Ant1 Emission



Date: 28.NOV.2023 11:23:56

## 4. POWER LINE CONDUCTED EMISSION

### 4.1. Test Limits

Frequency MHz	Limits dB( $\mu$ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. \*Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


3. The limit decreases in line with the logarithm of the frequency in rang of 0.15 to 0.50 MHz.

### 4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9 kHz.

### 4.3. Test Setup



### 4.4. Test Results

Pass

Model : GE1000

Polarity: L




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	30.21	9.94	40.15	66.00	-25.85	peak	
2		0.4050	29.32	9.94	39.26	57.75	-18.49	peak	
3		2.0100	31.69	9.88	41.57	56.00	-14.43	peak	
4	*	3.7170	34.91	9.97	44.88	56.00	-11.12	peak	
5		7.2480	38.62	10.13	48.75	60.00	-11.25	peak	
6		9.9146	37.26	10.21	47.47	60.00	-12.53	peak	

\*:Maximum data    x:Over limit    !:over margin

(Reference Only)

Note: Measurement=Reading Level+Correc Factor.    Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Polarity: N



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1620	28.72	9.93	38.65	65.36	-26.71	peak	
2		0.4020	25.99	9.94	35.93	57.81	-21.88	peak	
3		2.1509	31.68	9.88	41.56	56.00	-14.44	peak	
4	*	3.7890	35.80	9.96	45.76	56.00	-10.24	peak	
5		9.8610	38.81	10.21	49.02	60.00	-10.98	peak	
6		20.0518	24.35	10.47	34.82	60.00	-25.18	peak	

\*:Maximum data    x:Over limit    !:over margin


<Reference Only

Note: Measurement=Reading Level+Correc Factor.    Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Note: All modes and channels have been tested and only the 2415MHz mode with the worst data is listed.

Model : GE1000Li

Polarity: L




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	36.71	9.94	46.65	66.00	-19.35	peak	
2		0.1710	36.41	9.93	46.34	64.91	-18.57	peak	
3	*	0.4050	34.82	9.94	44.76	57.75	-12.99	peak	
4		3.1440	31.63	9.96	41.59	56.00	-14.41	peak	
5		7.1730	35.54	10.13	45.67	60.00	-14.33	peak	
6		9.9146	36.76	10.21	46.97	60.00	-13.03	peak	

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

Note: Measurement=Reading Level+Correc Factor.    Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Polarity: N



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.2129	37.26	9.93	47.19	63.09	-15.90	peak	
2		0.4020	31.99	9.94	41.93	57.81	-15.88	peak	
3		2.1419	32.33	9.88	42.21	56.00	-13.79	peak	
4	*	4.2808	33.83	9.99	43.82	56.00	-12.18	peak	
5		7.3948	36.57	10.13	46.70	60.00	-13.30	peak	
6		9.8610	36.81	10.21	47.02	60.00	-12.98	peak	

\*:Maximum data    x:Over limit    !:over margin    <Reference Only

Note: Measurement=Reading Level+Correc Factor.    Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Note: All modes and channels have been tested and only the 2415MHz mode with the worst data is listed.



## 5. CONDUCTED MAXIMUM PEAK OUTPUT POWER

### 5.1. Test limits

Please refer section RSS-247 & 15.247.

### 5.2. Test Procedure


Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

5.2.1 Place the EUT on the table and set it in transmitting mode.

5.2.2 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

### 5.3. Test Setup



### 5.4. Test Results

GFSK

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Ant (dBi)	EIRP (dBm)	Limit (dBm)	Verdict
NVNT	GFSK	2415	Ant1	-0.499	-0.58	-1.079	30	Pass
NVNT	GFSK	2435	Ant1	-0.122	-0.58	-0.702	30	Pass
NVNT	GFSK	2455	Ant1	0.114	-0.58	-0.466	30	Pass

## 6. PEAK POWER SPECTRAL DENSITY

### 6.1. Test limits

6.1.1 Please refer section RSS-247 & 15.247.

6.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

6.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

### 6.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

6.2.1 Place the EUT on the table and set it in transmitting mode.


6.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

6.2.3 Set the spectrum analyzer as RBW = 3kHz(Set the RBW to:  $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .), VBW = 10kHz(Set the  $\text{VBW} \geq 3 \times \text{RBW}$ ), span= $1.5 \times \text{DTS bandwidth}$ ., detail see the test plot.

6.2.4 Record the max reading.

6.2.5 Repeat the above procedure until the measurements for all frequencies are completed.

### 6.3. Test Setup




### 6.4. Test Results

Pass

The test results are listed in next pages.


Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	GFSK	2415	Ant1	-1.038	8	Pass
NVNT	GFSK	2435	Ant1	-0.516	8	Pass
NVNT	GFSK	2455	Ant1	-0.41	8	Pass

PSD NVNT GFSK 2415MHz Ant1




Date: 28.NOV.2023 11:08:28

PSD NVNT GFSK 2435MHz Ant1



Date: 28.NOV.2023 11:15:25

### PSD NVNT GFSK 2455MHz Ant1



Date: 28.NOV.2023 11:23:18

## 7. BANDWIDTH

### 7.1. Test limits

Please refer section RSS-247 & 15.247

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.


### 7.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

a) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

b) The test receiver set RBW = 100kHz, VBW $\geq$ 3\*RBW =300kHz, sweep time set auto, detail see the test plot.


### 7.3. Test Setup



### 7.4. Test Results


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	GFSK	2415	Ant 1	0.821	0.528	0.5	Pass
NVNT	GFSK	2435	Ant 1	0.717	0.504	0.5	Pass
NVNT	GFSK	2455	Ant 1	0.503	0.521	0.5	Pass

### -6dB Bandwidth NVNT GFSK 2415MHz Ant1




Date: 21.FEB.2024 20:30:33

### -6dB Bandwidth NVNT GFSK 2435MHz Ant1




Date: 21.FEB.2024 20:31:33

### -6dB Bandwidth NVNT GFSK 2455MHz Ant1




Date: 21.FEB.2024 20:46:54

### OBW NVNT GFSK 2415MHz Ant1




Date: 21.FEB.2024 20:29:48

### OBW NVNT GFSK 2435MHz Ant1



Date: 21.FEB.2024 20:27:59

### OBW NVNT GFSK 2455MHz Ant1



Date: 21.FEB.2024 20:41:44



## **8. BAND EDGE CHECK**

### **8.1. Test limits**

Please refer section RSS-GEN&15.247.

### **8.2. Test Procedure**

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

8.2.1 Put the EUT on a 0.8m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission

8.2.2 Check the spurious emissions out of band.

8.2.3 RBW 1MHz, VBW 3MHz, peak detector for peak value, RBW 1MHz, VBW 3MHz, RMS detector for AV value.

### **8.3. Test Setup**


Same as 5.2.2.

### **8.4. Test Results**


Pass

The test results are listed in next pages.


### Band Edge NVNT GFSK 2415MHz Ant1 Ref



### Band Edge NVNT GFSK 2415MHz Ant1 Emission




Band Edge NVNT GFSK 2455MHz Ant1 Ref



Date: 28.NOV.2023 11:23:25


Band Edge NVNT GFSK 2455MHz Ant1 Emission




Date: 28.NOV.2023 11:23:30

Radiated Method: GFSK

Test Mode: CH-L



Test Mode: CH-H



## **9. ANTENNA REQUIREMENT**

### **9.1. Standard Requirement**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **9.2. Antenna Connected Construction**


The antenna is internal antenna and no consideration of replacement. Please see EUT photo for details.

### **9.3. Results**

The EUT antenna is Internal Antenna. It complies with the standard requirement.

## 10. TEST SETUP PHOTO

### 10.1. Photo of Radiated Emission test



10.2.Photo of Conducted Emission test



-----END OF REPORT-----