



FCC TEST REPORT

**Test report
On Behalf of
SHENZHEN EASYN TECHNOLOGIES
For
IP Camera
Model No.: 189,154,165,118,109,110,115,125,126,127,128,129,
138,188,163,158,182,183,192,310**

FCC ID: 2ATSW-189

Prepared for : SHENZHEN EASYN TECHNOLOGIES
BLK 3, The 3rd industry zone, Huangmabu Hangcheng Baoan Shenzhen China

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: Jun. 10, 2019 ~ Jun. 18, 2019

Date of Report: Jun. 18, 2019

Report Number: HK1906121312E



TABLE OF CONTENTS

1. Test Result Summary	4
1.1. TEST PROCEDURES AND RESULTS	4
1.2. TEST FACILITY	4
1.3. MEASUREMENT UNCERTAINTY	5
2. EUT Description	6
2.1. GENERAL DESCRIPTION OF EUT	6
2.2. CARRIER FREQUENCY OF CHANNELS	7
2.3. OPERATION OF EUT DURING TESTING.....	7
2.4. DESCRIPTION OF TEST SETUP	8
3. General Information.....	9
3.1. TEST ENVIRONMENT AND MODE	9
3.2. DESCRIPTION OF SUPPORT UNITS	10
4. Test Results and Measurement Data.....	11
4.1. CONDUCTED EMISSION.....	11
4.2. MAXIMUM CONDUCTED OUTPUT POWER.....	15
4.3. EMISSION BANDWIDTH	17
4.4. POWER SPECTRAL DENSITY	25
4.5. CONDUCTED BAND EDGE AND SPURIOUS EMISSION MEASUREMENT	31
4.6. RADIATED SPURIOUS EMISSION MEASUREMENT	37
4.7. ANTENNA REQUIREMENT	66
4.8. PHOTOGRAPH OF TEST	67



1. Test Result Summary

1.1. TEST PROCEDURES AND RESULTS

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3) §2.1046	PASS
6dB Emission Bandwidth	§15.247 (a)(2) §2.1049	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§15.247(d) §2.1051, §2.1057	PASS
Restricted bands	§15.205	PASS
Spurious Emission	§15.205/§15.209 §2.1053, §2.1057	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

1.2. TEST FACILITY

Test Firm : Shenzhen HUAK Testing Technology Co., Ltd.

Address 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China



1.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^\circ\text{C}$
7	Humidity	$\pm 1.0\%$



2. EUT Description

2.1. GENERAL DESCRIPTION OF EUT

Equipment	IP Camera
Model Name	189
Serial No.	154,165,118,109,110,115,125,126,127, 128,129,138,188,163,158,182,183,192,310
Model Difference	All model's the function, software and electric circuit are the same, only with Exterior and product color and model named different. Test sample model: 189.
Trade Mark	N/A
Antenna Type	FPC Antenna
Antenna Gain	1dBi
Operation frequency	802.11b/g/n 20:2412~2462 MHz 802.11n 40: 2422~2452MHz
Number of Channels	802.11b/g/n20: 11CH 802.11n 40: 7CH
Modulation Type	CCK/OFDM/DBPSK/DAPSK
Power Source	DC5V by Adapter AC 120V/60Hz
Power Rating	DC5V by Adapter AC 120V/60Hz



2.2. Carrier Frequency of Channels

Channel List for 802.11b/802.11g/802.11n (HT20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List For 802.11n (HT40)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
--	--	04	2427	07	2442	--	--
--	--	05	2432	08	2447	--	--
03	2422	06	2437	09	2452		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

2.3. Operation of EUT during testing

Operating Mode

The mode is used: **Transmitting mode for 802.11b/802.11g/802.11n (HT20)**

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

The mode is used: **Transmitting mode for 802.11n (HT40)**

Low Channel: 2422MHz


Middle Channel: 2437MHz

High Channel: 2452MHz




2.4. DESCRIPTION OF TEST SETUP

Operation of EUT during conducted and Radiation testing:



Operation of EUT Above 1GHz Radiation testing:



- Adapter information
Model: SJ-05010001
Input: 100-240V, 50/60Hz, 0.2A
Output: 5VDC, 1.0A



3. General Information

3.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%)
The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. For the full battery state and The output power to the maximum state.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps
802.11n(H40)	13.5Mbps
Final Test Mode:	
Operation mode:	Keep the EUT in continuous transmitting with modulation
1. For WIFI function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.	
2. According to ANSI C63.10 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20), 13.5Mbps for 802.11(H40). Duty cycle setting during the transmission is 98.5% with maximum power setting for all modulations.	



3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*
- 3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.*



4. Test Results and Measurement Data

4.1. Conducted Emission

Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	<p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Mode:	Charging + transmitting with modulation														
Test Procedure:	<ol style="list-style-type: none"> 1. The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 														
Test Result:	PASS														

**Test Instruments**

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Receiver	R&S	ESCI 7	HKE-010	Dec. 27, 2019
LISN	R&S	ENV216	HKE-002	Dec. 27, 2019
Conducted test software	Tonscend	TS+ Rev 2.5.0.0	HKE-081	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).




Test data

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)

EUT :	IP Camera	Model Name. :	189
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2019-06-17
Test Mode :	802.11b Low Channel	Phase :	L
Test Voltage :	DC5V by Adapter AC 120V/60Hz		

Test Graph



Suspected List						
NO.	Freq. [MHz]	Level [dBµV]	Factor [dB]	Limit [dBµV]	Margin [dB]	Detector
1	0.1500	50.66	10.03	66.00	15.34	PK
2	0.4245	43.96	10.04	57.36	13.40	PK
3	1.2120	39.66	10.09	56.00	16.32	PK
4	2.1480	41.50	10.16	56.00	14.50	PK
5	4.2090	41.86	10.25	56.00	14.14	PK
6	29.7780	37.67	10.26	60.00	22.33	PK

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.



EUT :	IP Camera	Model Name. :	189
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2019-06-17
Test Mode :	802.11b Low Channel	Phase :	N
Test Voltage :	DC5V by Adapter AC 120V/60Hz		

Test Graph



Suspected List						
NO.	Freq. [MHz]	Level [dBµV]	Factor [dB]	Limit [dBµV]	Margin [dB]	Detector
1	0.1545	50.12	10.03	65.75	15.63	PK
2	0.4155	43.51	10.03	57.54	14.03	PK
3	2.0580	39.89	10.15	56.00	16.11	PK
4	6.2070	37.14	10.22	60.00	22.86	PK
5	13.2315	34.45	9.96	60.00	25.55	PK
6	29.0220	36.88	10.26	60.00	23.12	PK

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

**Test Data**

TX 802.11b Mode			
Test Channel	Frequency	Maximum Peak Conducted Output Power	LIMIT
	(MHz)	(dBm)	dBm
CH01	2412	10.59	30
CH06	2437	10.81	30
CH11	2462	11.13	30
TX 802.11g Mode			
CH01	2412	10.84	30
CH06	2437	10.62	30
CH11	2462	11.18	30
TX 802.11n20 Mode			
CH01	2412	10.3	30
CH06	2437	11.31	30
CH11	2462	10.76	30
TX 802.11n40 Mode			
CH03	2422	10.72	30
CH06	2437	10.18	30
CH09	2452	10.89	30



4.3. Emission Bandwidth

Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB 558074
Limit:	>500kHz
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v05. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2019
RF Cable (9KHz-26.5GHz)	Tonscend	170660	N/A	Dec. 27, 2019
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 27, 2019


Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



Test data

Test channel	6dB Emission Bandwidth (MHz)			
	802.11b	802.11g	802.11n(H20)	802.11n(H40)
Lowest	9.116	16.40	17.64	35.98
Middle	9.566	16.39	17.64	36.13
Highest	9.137	16.44	17.61	35.95
Limit:	>500kHz			
Test Result:	PASS			

Test plots as follows:






6dB Bandwidth_11B_2437_Ant1




6dB Bandwidth_11B_2462_Ant1






6dB Bandwidth_11G_2412_Ant1



6dB Bandwidth_11G_2437_Ant1






6dB Bandwidth_11G_2462_Ant1




6dB Bandwidth_11N20SISO_2412_Ant1






6dB Bandwidth_11N20SISO_2437_Ant1




6dB Bandwidth_11N20SISO_2462_Ant1






6dB Bandwidth_11N40SISO_2422_Ant1




6dB Bandwidth_11N40SISO_2437_Ant1





6dB Bandwidth_11N40SISO_2452_Ant1



**Test data**

EUT Set Mode	Channel	Result (dBm/30kHz)	Result (dBm/3kHz)
802.11b	Lowest	-3.93	-13.93
	Middle	-4.49	-14.49
	Highest	-1.36	-11.36
802.11g	Lowest	-13.36	-23.36
	Middle	-13.74	-23.74
	Highest	-12.2	-22.2
802.11n(H20)	Lowest	-13.45	-23.45
	Middle	-12.02	-22.02
	Highest	-12.65	-22.65
802.11n(H40)	Lowest	-16.52	-26.52
	Middle	-17.45	-27.45
	Highest	-16.28	-26.28
PSD test result (dBm/3kHz)= PSD test result (dBm/30kHz)-10			
Limit: 8dBm/3kHz			
Test Result:	PASS		

Test plots as follows:



802.11b Modulation

Lowest channel



Middle channel



Highest channel





802.11g Modulation


Lowest channel



Middle channel



Highest channel





802.11n (HT20) Modulation

Lowest channel



Middle channel




Highest channel






802.11n (HT40) Modulation


Lowest channel



Middle channel




Highest channel





4.5. Conducted Band Edge and Spurious Emission Measurement

Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 <p>The diagram illustrates the test setup. On the left is a Spectrum Analyzer with a green screen and a red cursor. A cable connects it to a small white attenuator box. Another cable connects the attenuator to a yellow rectangular device labeled 'FIT'.</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none">1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05.2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.3. Set to the maximum power setting and enable the EUT transmit continuously.4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).5. Measure and record the results in the test report.6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS

**Test Instruments**


RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2019
Signal generator	Agilent	N5183A	HKE-071	Dec. 27, 2019
RF Cable (9KHz-26.5GHz)	Tonscend	170660	N/A	Dec. 27, 2019
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 27, 2019

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).




Test Data

802.11b Modulation






802.11g Modulation






802.11n (HT20) Modulation





802.11n (HT40) Modulation







4.6. Radiated Spurious Emission Measurement

Test Specification

Test Requirement:	FCC Part15 C Section 15.209																																			
Test Method:	ANSI C63.10: 2013																																			
Frequency Range:	9 kHz to 25 GHz																																			
Measurement Distance:	3 m																																			
Antenna Polarization:	Horizontal & Vertical																																			
Operation mode:	Transmitting mode with modulation																																			
Receiver Setup:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Detector</th> <th>RBW</th> <th>VBW</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>9kHz- 150kHz</td> <td>Quasi-peak</td> <td>200Hz</td> <td>1kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>150kHz- 30MHz</td> <td>Quasi-peak</td> <td>9kHz</td> <td>30kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>30MHz-1GHz</td> <td>Quasi-peak</td> <td>100KHz</td> <td>300KHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td rowspan="2">Above 1GHz</td> <td>Peak</td> <td>1MHz</td> <td>3MHz</td> <td>Peak Value</td> </tr> <tr> <td>Peak</td> <td>1MHz</td> <td>10Hz</td> <td>Average Value</td> </tr> </tbody> </table>	Frequency	Detector	RBW	VBW	Remark	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value						
Frequency	Detector	RBW	VBW	Remark																																
9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value																																
150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value																																
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																																
Above 1GHz	Peak	1MHz	3MHz	Peak Value																																
	Peak	1MHz	10Hz	Average Value																																
Limit:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Field Strength (microvolts/meter)</th> <th>Measurement Distance (meters)</th> </tr> </thead> <tbody> <tr> <td>0.009-0.490</td> <td>2400/F(KHz)</td> <td>300</td> </tr> <tr> <td>0.490-1.705</td> <td>24000/F(KHz)</td> <td>30</td> </tr> <tr> <td>1.705-30</td> <td>30</td> <td>30</td> </tr> <tr> <td>30-88</td> <td>100</td> <td>3</td> </tr> <tr> <td>88-216</td> <td>150</td> <td>3</td> </tr> <tr> <td>216-960</td> <td>200</td> <td>3</td> </tr> <tr> <td>Above 960</td> <td>500</td> <td>3</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Frequency</th> <th>Field Strength (microvolts/meter)</th> <th>Measurement Distance (meters)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Above 1GHz</td> <td>500</td> <td>3</td> <td>Average</td> </tr> <tr> <td>5000</td> <td>3</td> <td>Peak</td> </tr> </tbody> </table>	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	0.009-0.490	2400/F(KHz)	300	0.490-1.705	24000/F(KHz)	30	1.705-30	30	30	30-88	100	3	88-216	150	3	216-960	200	3	Above 960	500	3	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	Above 1GHz	500	3	Average	5000	3	Peak
Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)																																		
0.009-0.490	2400/F(KHz)	300																																		
0.490-1.705	24000/F(KHz)	30																																		
1.705-30	30	30																																		
30-88	100	3																																		
88-216	150	3																																		
216-960	200	3																																		
Above 960	500	3																																		
Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector																																	
Above 1GHz	500	3	Average																																	
	5000	3	Peak																																	
Test setup:	<p>For radiated emissions below 30MHz</p> <p>30MHz to 1GHz</p>																																			



Above 1GHz



Test Procedure:

1. For the radiated emission test below 1GHz:
 The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
 For the radiated emission test above 1GHz:
 Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which



	<p>maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <ol style="list-style-type: none">3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.5. Use the following spectrum analyzer settings:<ol style="list-style-type: none">(1) Span shall wide enough to fully capture the emission being measured;(2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;(3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement. <p>For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
Test results:	PASS

**Test Instruments**

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Receiver	R&S	ESCI-7	HKE-010	Dec. 27, 2019
Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2019
Preamplifier	EMCI	EMC051845 SE	HKE-015	Dec. 27, 2019
Preamplifier	Agilent	83051A	HKE-016	Dec. 27, 2019
Loop antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 26, 2019
Broadband antenna	Schwarzbeck	VULB 9163	HKE-012	Dec. 26, 2019
Horn antenna	Schwarzbeck	9120D	HKE-013	Dec. 26, 2019
Antenna Mast	Keleto	CC-A-4M	N/A	N/A
Position controller	Taiwan MF	MF7802	HKE-011	Dec. 27, 2019
Radiated test software	Tonscend	TS+ Rev 2.5.0.0	HKE-082	N/A
RF cable (9KHz-1GHz)	Times	381806-001	N/A	N/A
RF cable	Times	1-40G	HKE-034	Dec. 27, 2019

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).




Test Data

Please refer to following diagram for individual
Below 1GHz

EUT :	IP Camera	Model Name. :	189
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2019-06-17
Test Mode :	802.11b Low Channel	Phase :	Horizontal
Test Voltage :	DC5V by Adapter AC 120V/60Hz		

Test Graph



Suspected List

Suspected List								
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	76.5600	21.55	-18.85	50.00	28.45	100	170	Horizontal
2	171.620	34.59	-17.23	53.50	18.91	100	110	Horizontal
3	214.300	42.10	-14.70	53.50	11.40	100	10	Horizontal
4	257.950	33.10	-13.50	56.00	22.90	100	260	Horizontal
5	386.960	32.20	-10.70	56.00	23.80	100	310	Horizontal
6	945.680	32.59	-1.36	56.00	23.41	100	340	Horizontal


Final Data List

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level



EUT :	IP Camera	Model Name. :	189
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2019-06-17
Test Mode :	802.11b Low Channel	Phase :	Vertical
Test Voltage :	DC5V by Adapter AC 120V/60Hz		

Test Graph



Suspected List

Suspected List								
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	78.5000	28.36	-19.20	50.00	21.64	100	80	Vertical
2	153.190	27.72	-18.71	53.50	25.78	100	350	Vertical
3	257.950	34.52	-13.50	56.00	21.48	100	350	Vertical
4	450.980	36.42	-8.96	56.00	19.58	100	320	Vertical
5	558.650	34.03	-6.72	56.00	21.97	100	60	Vertical
6	878.750	31.35	-2.09	56.00	24.65	100	310	Vertical

Final Data List

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

**Above 1GHz****RADIATED EMISSION TEST**

LOW CH1 (802.11b Mode)/2412

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4824	63.47	-3.64	59.83	74	-14.17	Peak
4824	42.13	-3.62	38.51	54	-15.49	AVG
7236	63.54	-0.95	62.59	74	-11.41	Peak
7236	41.92	-0.95	40.97	54	-13.03	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4824	64.13	-3.64	60.49	74	-13.51	Peak
4824	43.56	-3.62	39.94	54	-14.06	AVG
7236	62.78	-0.95	61.83	74	-12.17	Peak
7236	40.29	-0.95	39.34	54	-14.66	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



MID CH6 (802.11b Mode)/2437

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4874	62.57	-3.51	59.06	74	-14.94	Peak
4874	43.69	-3.51	40.18	54	-13.82	AVG
7311	61.45	-0.82	60.63	74	-13.37	Peak
7311	39.64	-0.82	38.82	54	-15.18	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4874	61.39	-3.51	57.88	74	-16.12	Peak
4874	42.87	-3.51	39.36	54	-14.64	AVG
7311	59.26	-0.82	58.44	74	-15.56	Peak
7311	39.74	-0.82	38.92	54	-15.08	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



HIGH CH11 (802.11b Mode)/2462

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4924	62.43	-3.43	59	74	-15	Peak
4924	41.08	-3.43	37.65	54	-16.35	AVG
7386	59.34	-0.75	58.59	74	-15.41	Peak
7386	40.29	-0.75	39.54	54	-14.46	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4924	61.79	-3.43	58.36	74	-15.64	Peak
4924	42.06	-3.43	38.63	54	-15.37	AVG
7386	59.62	-0.75	58.87	74	-15.13	Peak
7386	40.51	-0.75	39.76	54	-14.24	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



Remark:

(1) Measuring frequencies from 1 GHz to the 25 GHz.

(2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.

(3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.

(4) Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

(5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.

(6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.



LOW CH1 (802.11g Mode)/2412

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4824	62.18	-3.64	58.54	74	-15.46	Peak
4824	43.52	-3.64	39.88	54	-14.12	AVG
7236	61.47	-0.95	60.52	74	-13.48	Peak
7236	39.86	-0.95	38.91	54	-15.09	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4824	60.86	-3.64	57.22	74	-16.78	Peak
4824	42.07	-3.64	38.43	54	-15.57	AVG
7236	59.74	-0.95	58.79	74	-15.21	Peak
7236	40.52	-0.95	39.57	54	-14.43	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



MID CH6 (802.11g Mode)/2437

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4874	61.75	-3.51	58.24	74	-15.76	Peak
4874	42.16	-3.51	38.65	54	-15.35	AVG
7311	60.03	-0.82	59.21	74	-14.79	Peak
7311	40.81	-0.82	39.99	54	-14.01	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4874	63.54	-3.51	60.03	74	-13.97	Peak
4874	44.17	-3.51	40.66	54	-13.34	AVG
7311	62.92	-0.82	62.1	74	-11.9	Peak
7311	43.64	-0.82	42.82	54	-11.18	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



HIGH CH11 (802.11g Mode)/2462

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4924	63.51	-3.43	60.08	74	-13.92	Peak
4924	43.12	-3.43	39.69	54	-14.31	AVG
7386	62.97	-0.75	62.22	74	-11.78	Peak
7386	41.28	-0.75	40.53	54	-13.47	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4924	62.39	-3.43	58.96	74	-15.04	Peak
4924	42.16	-3.43	38.73	54	-15.27	AVG
7386	61.83	-0.75	61.08	74	-12.92	Peak
7386	41.05	-0.75	40.3	54	-13.7	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



Remark:

(1) Measuring frequencies from 1 GHz to the 25 GHz.

(2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.

(3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.

(4) Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

(5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.

(6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.



LOW CH1 (802.11n/H20 Mode)/2412

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4824	62.48	-3.64	58.84	74	-15.16	Peak
4824	43.29	-3.64	39.65	54	-14.35	AVG
7236	63.54	-0.95	62.59	74	-11.41	Peak
7236	42.16	-0.95	41.21	54	-12.79	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4824	63.28	-3.64	59.64	74	-14.36	Peak
4824	44.56	-3.64	40.92	54	-13.08	AVG
7236	63.14	-0.95	62.19	74	-11.81	Peak
7236	43.52	-0.95	42.57	54	-11.43	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



MID CH6 (802.11n/H20 Mode)/2437

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4874	62.06	-3.51	58.55	74	-15.45	Peak
4874	42.79	-3.51	39.28	54	-14.72	AVG
7311	61.94	-0.82	61.12	74	-12.88	Peak
7311	41.83	-0.82	41.01	54	-12.99	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4874	64.13	-3.51	60.62	74	-13.38	Peak
4874	43.52	-3.51	40.01	54	-13.99	AVG
7311	63.97	-0.82	63.15	74	-10.85	Peak
7311	42.56	-0.82	41.74	54	-12.26	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



HIGH CH11 (802.11n/H20 Mode)/2462

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4924	62.57	-3.43	59.14	74	-14.86	Peak
4924	42.86	-3.43	39.43	54	-14.57	AVG
7386	61.93	-0.35	61.58	74	-12.42	Peak
7311	42.26	-0.35	41.91	54	-12.09	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4924	61.86	-3.43	58.43	74	-15.57	Peak
4924	43.64	-3.43	40.21	54	-13.79	AVG
7386	60.28	-0.35	59.93	74	-14.07	Peak
7311	41.05	-0.35	40.7	54	-13.3	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



LOW CH3 (802.11n/H40 Mode)/2422

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4844	63.75	-3.63	60.12	74	-13.88	Peak
4844	43.61	-3.63	39.98	54	-14.02	AVG
7266	62.89	-0.94	61.95	74	-12.05	Peak
7266	42.73	-0.94	41.79	54	-12.21	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4844	63.59	-3.63	59.96	74	-14.04	Peak
4844	42.75	-3.63	39.12	54	-14.88	AVG
7266	63.91	-0.94	62.97	74	-11.03	Peak
7266	41.06	-0.94	40.12	54	-13.88	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



MID CH6 (802.11n/H40 Mode)/2437

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4874	63.52	-3.63	59.89	74	-14.11	Peak
4874	43.69	-3.63	40.06	54	-13.94	AVG
7311	62.48	-0.94	61.54	74	-12.46	Peak
7311	42.03	-0.94	41.09	54	-12.91	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4874	64.25	-3.63	60.62	74	-13.38	Peak
4874	43.51	-3.63	39.88	54	-14.12	AVG
7311	63.74	-0.94	62.8	74	-11.2	Peak
7311	42.86	-0.94	41.92	54	-12.08	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



HIGH CH9 (802.11n/H40 Mode)/2452

Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4904	63.87	-3.43	60.44	74	-13.56	Peak
4904	42.09	-3.43	38.66	54	-15.34	AVG
7356	61.57	-0.75	60.82	74	-13.18	Peak
7356	41.06	-0.75	40.31	54	-13.69	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
4904	64.08	-3.43	60.65	74	-13.35	Peak
4904	43.56	-3.43	40.13	54	-13.87	AVG
7356	62.84	-0.75	62.09	74	-11.91	Peak
7356	41.73	-0.75	40.98	54	-13.02	AVG
-	-	-	-	74	-	Peak
-	-	-	-	54	-	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



Remark:

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.

**Test Result of Radiated Spurious at Band edges and restricted bands**

Operation Mode:
802.11b Mode TX CH Low (2412MHz)

Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2310	55.43	-5.81	49.62	74	-24.38	peak
2310	47.25	-5.81	41.44	54	-12.56	AVG
2390	54.32	-5.84	48.48	74	-25.52	peak
2390	45.68	-5.84	39.84	54	-14.16	AVG
2400	56.24	-5.84	50.4	74	-23.6	peak
2400	45.06	-5.84	39.22	54	-14.78	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2310	54.39	-5.81	48.58	74	-25.42	peak
2310	46.29	-5.81	40.48	54	-13.52	AVG
2390	55.16	-5.84	49.32	74	-24.68	peak
2390	46.17	-5.84	40.33	54	-13.67	AVG
2400	54.31	-5.84	48.47	74	-25.53	peak
2400	45.84	-5.84	40	54	-14	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Operation Mode: TX CH High (2462MHz)

Horizontal

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
2483.5	54.39	-5.65	48.74	74	-25.26	Peak
2483.5	44.32	-5.65	38.67	54	-15.33	AVG
2500	56.93	-5.65	51.28	74	-22.72	Peak
2500	45.08	-5.65	39.43	54	-14.57	AVG

Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
2483.5	55.37	-5.65	49.72	74	-24.28	Peak
2483.5	44.92	-5.65	39.27	54	-14.73	AVG
2500	56.14	-5.65	50.49	74	-23.51	Peak
2500	43.27	-5.65	37.62	54	-16.38	AVG

Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier



Operation Mode: 802.11g Mode TX CH Low (2412MHz)

Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2310	54.92	-5.81	49.11	74	-24.89	peak
2310	46.13	-5.81	40.32	54	-13.68	AVG
2390	56.87	-5.84	51.03	74	-22.97	peak
2390	43.39	-5.84	37.55	54	-16.45	AVG
2400	55.19	-5.84	49.35	74	-24.65	peak
2400	44.73	-5.84	38.89	54	-15.11	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2310	57.43	-5.81	51.62	74	-22.38	peak
2310	47.29	-5.81	41.48	54	-12.52	AVG
2390	56.03	-5.84	50.19	74	-23.81	peak
2390	46.52	-5.84	40.68	54	-13.32	AVG
2400	56.37	-5.84	50.53	74	-23.47	peak
2400	45.28	-5.84	39.44	54	-14.56	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Operation Mode: TX CH High (2462MHz)

Horizontal

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
2483.5	57.19	-5.65	51.54	74	-22.46	Peak
2483.5	44.65	-5.65	39	54	-15	AVG
2500	56.92	-5.65	51.27	74	-22.73	Peak
2500	43.48	-5.65	37.83	54	-16.17	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
2483.5	57.64	-5.65	51.99	74	-22.01	Peak
2483.5	46.23	-5.65	40.58	54	-13.42	AVG
2500	56.42	-5.65	50.77	74	-23.23	Peak
2500	45.85	-5.65	40.2	54	-13.8	AVG
Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier						



Operation Mode: 802.11n/H20 Mode TX CH Low (2412MHz)

Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2310	56.29	-5.81	50.48	74	-23.52	peak
2310	46.74	-5.81	40.93	54	-13.07	AVG
2390	57.13	-5.84	51.29	74	-22.71	peak
2390	45.82	-5.84	39.98	54	-14.02	AVG
2400	56.17	-5.84	50.33	74	-23.67	peak
2400	45.39	-5.84	39.55	54	-14.45	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2310	56.32	-5.81	50.51	74	-23.49	peak
2310	46.74	-5.81	40.93	54	-13.07	AVG
2390	55.29	-5.84	49.45	74	-24.55	peak
2390	45.73	-5.84	39.89	54	-14.11	AVG
2400	55.31	-5.84	49.47	74	-24.53	peak
2400	45.72	-5.84	39.88	54	-14.12	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Operation Mode: TX CH High (2462MHz)

Horizontal

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
2483.5	55.37	-5.65	49.72	74	-24.28	Peak
2483.5	42.96	-5.65	37.31	54	-16.69	AVG
2500	54.76	-5.65	49.11	74	-24.89	Peak
2500	43.52	-5.65	37.87	54	-16.13	AVG

Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
2483.5	57.28	-5.65	51.63	74	-22.37	Peak
2483.5	44.39	-5.65	38.74	54	-15.26	AVG
2500	56.12	-5.65	50.47	74	-23.53	Peak
2500	43.06	-5.65	37.41	54	-16.59	AVG

Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier



Operation Mode: 802.11n/H40 Mode TX CH Low (2422MHz)

Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2310	56.32	-5.81	50.51	74	-23.49	peak
2310	45.27	-5.81	39.46	54	-14.54	AVG
2390	55.16	-5.84	49.32	74	-24.68	peak
2390	43.29	-5.84	37.45	54	-16.55	AVG
2400	55.19	-5.84	49.35	74	-24.65	peak
2400	43.02	-5.84	37.18	54	-16.82	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2310	56.17	-5.81	50.36	74	-23.64	peak
2310	45.92	-5.81	40.11	54	-13.89	AVG
2390	55.06	-5.84	49.22	74	-24.78	peak
2390	44.86	-5.84	39.02	54	-14.98	AVG
2400	56.29	-5.84	50.45	74	-23.55	peak
2400	43.46	-5.84	37.62	54	-16.38	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Operation Mode: TX CH High (2452MHz)

Horizontal

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
2483.5	55.39	-5.65	49.74	74	-24.26	Peak
2483.5	44.17	-5.65	38.52	54	-15.48	AVG
2500	56.28	-5.65	50.63	74	-23.37	Peak
2500	43.15	-5.65	37.5	54	-16.5	AVG

Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier

Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
2483.5	56.34	-5.65	50.69	74	-23.31	Peak
2483.5	43.92	-5.65	38.27	54	-15.73	AVG
2500	55.73	-5.65	50.08	74	-23.92	Peak
2500	42.58	-5.65	36.93	54	-17.07	AVG

Remark:Factor=Antenna Factor+Cable Loss-Pre-amplifier

4.7. ANTENNA REQUIREMENT

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The antenna used in this product is a PCB Antenna, The directional gains of antenna used for transmitting is 1dBi.

WIFI ANTENNA



4.8. PHOTOGRAPH OF TEST

Radiated Emission





Conducted Emission

