

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

|                     |             |
|---------------------|-------------|
| Product Description | Comfy       |
| Model Name          | KEP-004     |
| FCC ID              | 2ATUZKEP001 |

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

BLE:

$$P_t = 2.288 \text{ dBm} = 1.69 \text{ mW}$$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47

§15.247.

The result for RF exposure evaluation  $\text{SAR} = (1.69 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.44}(\text{GHz})] = 1.48 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

BR/EDR:

$$P_t = 1.232 \text{ dBm} = 1.32 \text{ mW}$$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47

§15.247.

The result for RF exposure evaluation  $\text{SAR} = (1.32 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.402}(\text{GHz})] = 0.41 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.