

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-198-RWD-003
AGR No : A195A-399
Applicant : DiaDent Group International
Address : 16, Osongsaengmyeong 4-ro, Osong-eup, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, 28161, Republic of Korea
Manufacturer : DiaDent Group International
Address : 16, Osongsaengmyeong 4-ro, Osong-eup, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, 28161, Republic of Korea
Type of Equipment : Wireless Charger
FCC ID. : 2ATVL-DLUXPLUS
Model Name : D-Lux+
Multiple Model Name : N/A
Serial number : N/A
Total page of Report : 25 pages (including this page)
Date of Incoming : June 18, 2019
Date of issue : August 01, 2019

SUMMARY

The equipment complies with the regulation; **FCC CFR47 Part 15 Subpart C Section 15.207 and 15.209**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:



Ha-Ram Lee / Assistant Manager
ONETECH Corp.

Approved by:



Jae-Ho Lee / Chief Engineer
ONETECH Corp.

CONTENTS**PAGE**

1. VERIFICATION OF COMPLIANCE	5
2. TEST SUMMARY	6
2.1 TEST ITEMS AND RESULTS	6
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	6
2.3 RELATED SUBMITTAL(S) / GRANT(S)	6
2.4 PURPOSE OF THE TEST	6
2.5 TEST METHODOLOGY.....	6
2.6 TEST FACILITY.....	6
3. GENERAL INFORMATION	7
3.1 PRODUCT DESCRIPTION.....	7
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	7
4. EUT MODIFICATIONS.....	7
5. SYSTEM TEST CONFIGURATION	8
5.1 JUSTIFICATION.....	8
5.2 PERIPHERAL EQUIPMENT	8
5.3 MODE OF OPERATION DURING THE TEST	8
5.4 CONFIGURATION OF TEST SYSTEM.....	9
5.5 ANTENNA REQUIREMENT	9
6. PRELIMINARY TEST	10
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	10
7. 20 DB BANDWIDTH	11
7.1 OPERATING ENVIRONMENT	11
7.2 TEST SET-UP	11
7.3 TEST DATA.....	12
8. SPURIOUS EMISSION TEST	13
8.1 REGULATION.....	13
8.2 TEST SET-UP	13
8.3 TEST DATA FOR USING MAX LOAD (1 000 MA).....	14
8.3.1 Spurious Radiated Emission Below 30 MHz	14
8.3.2 Spurious Radiated Emission below 1 GHz.....	15

8.4 TEST DATA FOR USING MID. LOAD (500 MA).....	16
8.4.1 Spurious Radiated Emission Below 30 MHz	16
8.4.2 Spurious Radiated Emission below 1 GHz.....	17
8.5 TEST DATA FOR USING MIN. LOAD (100 MA).....	18
8.5.1 Spurious Radiated Emission Below 30 MHz	18
8.6 TEST PLOT.....	19
8.6.1 Spurious Radiated Emission Below 30 MHz (1000 mA)	19
8.6.2 Spurious Radiated Emission Below 30 MHz (500 mA)	20
8.6.3 Spurious Radiated Emission Below 30 MHz (100 mA)	21
9. CONDUCTED EMISSION TEST.....	22
9.1 OPERATING ENVIRONMENT	22
9.2 TEST SET-UP	22
9.3 TEST EQUIPMENT USED.....	22
9.4 TEST DATA.....	23
10. LIST OF TEST EQUIPMENT	25

Revision History

Issue Report No.	Issued Date	Revisions	Effect Section
OT-198-RWD-003	August 01, 2019	Initial Release	All

1. VERIFICATION OF COMPLIANCE

APPLICANT : DiaDent Group International
ADDRESS : 16, Osongsaengmyeong 4-ro, Osong-eup, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, 28161, Republic of Korea
CONTACT PERSON : Myeong-Eun KIM / Representative
TELEPHONE NO : +82-43-712-2849
FCC ID : 2ATVL-DLUXPLUS
MODEL NAME : D-Lux+
BRAND NAME : N/A
SERIAL NUMBER : N/A
DATE : August 01, 2019

EQUIPMENT CLASS	DCD – Part 15 Low Power Transmitter Below 1 705 kHz
KIND OF EQUIPMENT	Wireless Charger
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC&IC RULES PART(S)	FCC CFR47 Part 15 Subpart C Section 15.207 and 15.209
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	No
FINAL TEST WAS CONDUCTED ON	3 m, Semi Anechoic Chamber

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. The equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.209, 15.209(a)	Radiated emission, Spurious Emission and Field Strength of Fundamental	Met the Limit / PASS
2.1049	20 dB Bandwidth	Met the Limit / PASS
15.207	Transmitter AC Power Line Conducted Emission	Met the Limit / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC CFR47 Part 15 Subpart C Section 15.207 and 15.209, 2.1049.

2.5 Test Methodology

Radiated testing was performed according to the procedures in ANSI C63.10: 2013 at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The ONETECH Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 301-14, Daessangnyeong-ri, Chowol-eup, Gwangju-si, Gyeonggi-do, 464-862 Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-4112/ C-4617/ G-666/ T-1842

IC (Industry Canada) – Registration No. Site# 3736-3

-. Site Accreditation:

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085


FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The DiaDent Group International, Model: D-Lux+ (referred to as the EUT in this report) is a Wireless Charger. Product specification information described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Wireless Charger
OPERATING FREQUENCY	<p>111 kHz ~ 205 kHz</p> 
RATED RF OUTPUT POWER	67.6 dB μ V/m
ANTENNA TYPE	Coil Antenna
MODULATION	ASK
RATED SUPPLY VOLTAGE	DC 6.0 V

3.2 Alternative type(s)/model(s); also covered by this test report.

- None

4. EUT MODIFICATIONS

- None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	N/A	N/A	N/A
Key Board	N/A	N/A	N/A

5.2 Peripheral equipment

Model	Manufacturer	Description	Connected to
N/A	N/A	DUMMY load	N/A

5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting is programmed.

For final testing, the EUT was set at Max. load (132 kHz), Mid. load (137 kHz), and Min. load (148 kHz) for 6V.

To get a maximum emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is "XY" axis.

Mode	Charging current	Description
Charging Mode With load	1 000 mA	Using Max. load
	500 mA	Using Mid. load
	100 mA	Using Min. load

5.4 Configuration of Test System

Line Conducted Test

: The EUT was tested in a charging mode. The EUT was connected to Adapter. All supporting equipment were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.4: 2014 7.3.3 to determine the worse operating conditions.

Radiated Emission Test

: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

According to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The antenna of the EUT is a Coil Antenna on the main board in the EUT, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Tests, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
Charging & Transmitting mode	X

6.2 General Radiated Emissions Tests

During Preliminary Tests, the following operating modes were investigated

Operation Mode	The Worse operating condition (Please check one only)
Charging & Transmitting mode	X

7. 20 dB BANDWIDTH


7.1 Operating environment

Temperature : 24 °C
Relative humidity : 48 % R.H.

7.2 Test set-up

- a. Span = approximately 2 to 3 times the 20 dB bandwidth, RBW = greater than 1 % of the 20 dB bandwidth, VBW = RBW, Sweep = auto, Detector = peak, Trace = max hold.
- b. The marker-to-peak function to set the mark to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level.

The marker-delta reading at this point is 20 dB bandwidth of the emission.




7.3 Test data

Test Date : July 09, 2019

Frequency : 132.43 kHz

20 dB Bandwidth : 257.10 Hz



Tested by: Sieon Lee / Assistant Manager

8. Spurious Emission Test

8.1 Regulation

According to §15.209(a), for an intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency [MHz]	Field strength [μ V/m]	Field strength [dB μ V/m]	Measurement distance [m]
0.009 ~ 0.490	2 400 / F (kHz)	48.52 ~ 13.80	300
0.490 ~ 1.705	24 000 / F (kHz)	33.8 ~ 22.97	30
1.705 ~ 30	30	29.50	30
30 ~ 88	*100	40.00	3
88 ~ 216	*150	43.52	3
216 ~ 960	*200	46.02	3
Above 960	500	53.98	3

*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

8.2 Test set-up

The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from 30 kHz to 1 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

8.3 Test data for Using Max load (1 000 mA)

8.3.1 Spurious Radiated Emission Below 30 MHz

Humidity Level : 48 % R.H. Temperature: 24 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.209
 Frequency Range : 9 kHz ~ 30 MHz
 Result : PASSED

EUT : Wireless Charger Date: July 20, 2019

Operating Condition : Transmitting Mode

Frequency (MHz)	Reading (dB μ V)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
0.015	39.0	H	19.10	0.1	58.20	124.08	65.88
0.031	38.9	H	19.40	0.2	58.50	117.78	59.28
0.064	35.0	H	19.40	0.2	54.60	111.48	56.88
0.132*	45.0	H	19.40	0.2	64.60	105.19	40.59
0.389	26.1	H	19.40	0.3	45.80	95.81	50.01
0.807	22.8	V	19.30	0.3	42.40	69.47	27.07

- Remark: "H" Horizontal, "V" Vertical

- "*" Means Fundamental frequency

- Emission Level [dB μ V/m] = Reading [dB μ V] + Ant. Factor [dB/m] + Cable Loss [dB]

- Margin [dB] = Emission Level [dB μ V/m] - Limit [dB μ V/m]

- Limit calculation: Limit at specified distance + 40log (300/3) = Limit + 80 dB for up to 0.49 MHz

Limit at specified distance + 40log (30/3) = Limit + 40 dB for above 0.49 MHz, Below 30 MHz



Tested by: Sieon Lee / Assistant Manager


8.3.2 Spurious Radiated Emission below 1 GHz

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.

Humidity Level : 48 % R.H. Temperature: 24 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.209
 Frequency range : 30 MHz ~ 1 000 MHz
 Result : PASSED

EUT : Wireless Charger Date: July 20, 2019

Operating Condition : Transmitting Mode



No.	FREQ [MHz]	READING QP	ANT FACTOR	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA TABLE	
									[dB]	[cm]
----- Horizontal -----										
1	243.400	50.1	12.4	3.6	32.9	33.2	46.0	12.8	200	359
2	322.940	43.1	14.0	4.1	33.0	28.2	46.0	17.8	100	5
----- Vertical -----										
3	36.790	42.0	13.6	1.4	33.1	23.9	40.0	16.1	300	197
4	117.300	39.1	10.7	2.5	33.0	19.3	43.5	24.2	300	163
5	397.630	35.5	15.8	4.6	33.1	22.8	46.0	23.2	200	359
6	864.190	31.6	21.9	6.9	32.7	27.7	46.0	18.3	300	256

Tested by: Sieon Lee / Assistant Manager

8.4 Test data for Using Mid. load (500 mA)

8.4.1 Spurious Radiated Emission Below 30 MHz

Humidity Level : 48 % R.H. Temperature: 24 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.209
 Frequency Range : 9 kHz ~ 30 MHz
 Result : PASSED

EUT : Wireless Charger Date: July 20, 2019

Operating Condition : Transmitting Mode

Frequency (MHz)	Reading (dB μ V)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
0.015	38.2	H	19.10	0.1	57.40	124.08	66.68
0.031	37.6	H	19.40	0.2	57.20	117.78	60.58
0.064	35.0	H	19.40	0.2	54.60	111.48	56.88
0.137*	48.0	H	19.40	0.2	67.60	104.87	37.27
0.389	26.4	H	19.40	0.3	46.10	95.81	49.71
0.807	22.0	V	19.30	0.3	41.60	69.47	27.87

- Remark: "H" Horizontal, "V" Vertical

- "*" Means Fundamental frequency

- Emission Level [dB μ V/m] = Reading [dB μ V] + Ant. Factor [dB/m] + Cable Loss [dB]

- Margin [dB] = Emission Level [dB μ V/m] – Limit [dB μ V/m]

- Limit calculation: Limit at specified distance + 40log (300/3) = Limit + 80 dB for up to 0.49 MHz

Limit at specified distance + 40log (30/3) = Limit + 40 dB for above 0.49 MHz, Below 30 MHz



Tested by: Sieon Lee / Assistant Manager


8.4.2 Spurious Radiated Emission below 1 GHz

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.

Humidity Level : 48 % R.H. Temperature: 24 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.209
 Frequency range : 30 MHz ~ 1 000 MHz
 Result : PASSED

EUT : Wireless Charger Date: July 20, 2019

Operating Condition : Transmitting Mode



No.	FREQ [MHz]	READING QP	ANT FACTOR	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA TABLE	
									[dB]	[cm]
----- Horizontal -----										
1	242.430	47.9	12.4	3.6	32.9	31.0	46.0	15.0	100	0
2	335.550	40.3	14.4	4.3	33.0	26.0	46.0	20.0	100	0
----- Vertical -----										
3	36.790	35.4	13.6	1.4	33.1	17.3	40.0	22.7	200	359
4	91.110	31.0	11.3	2.2	33.0	11.5	43.5	32.0	200	359
5	397.630	36.7	15.8	4.6	33.1	24.0	46.0	22.0	200	359
6	864.190	32.1	21.9	6.9	32.7	28.2	46.0	17.8	200	359

Tested by: Sieon Lee / Assistant Manager

8.5 Test data for Using Min. load (100 mA)

8.5.1 Spurious Radiated Emission Below 30 MHz

Humidity Level : 48 % R.H. Temperature: 24 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.209
 Frequency Range : 9 kHz ~ 30 MHz
 Result : PASSED

EUT : Wireless Charger Date: July 20, 2019

Operating Condition : Transmitting Mode

Frequency (MHz)	Reading (dB μ V)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
0.015	38.5	H	19.10	0.1	57.70	124.08	66.38
0.031	37.6	H	19.40	0.2	57.20	117.78	60.58
0.064	35.1	H	19.40	0.2	54.70	111.48	56.78
0.148*	45.1	H	19.40	0.2	64.70	104.20	39.50
0.419	25.1	H	19.40	0.3	44.80	95.16	50.36
0.687	22.0	V	19.30	0.3	41.60	70.87	29.27

- Remark: "H" Horizontal, "V" Vertical

- "*" Means Fundamental frequency

- Emission Level [dB μ V/m] = Reading [dB μ V] + Ant. Factor [dB/m] + Cable Loss [dB]

- Margin [dB] = Emission Level [dB μ V/m] - Limit [dB μ V/m]

- Limit calculation: Limit at specified distance + 40log (300/3) = Limit + 80 dB for up to 0.49 MHz

Limit at specified distance + 40log (30/3) = Limit + 40 dB for above 0.49 MHz, Below 30 MHz



Tested by: Sieon Lee / Assistant Manager


8.6 Test Plot

8.6.1 Spurious Radiated Emission Below 30 MHz (1000 mA)

Humidity Level : 48 % R.H. Temperature: 24 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.209
 Frequency Range : 9 kHz ~ 30 MHz

EUT : Wireless Charger Date: July 20, 2019

Operating Condition : Transmitting Mode



No.	FREQ [MHz]	READING QP	ANT FACTOR	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA TABLE	
									[dB]	[cm]
----- Horizontal -----										
1	0.015	39.0	19.1	0.1	0.0	58.2	124.1	65.9	100	0
2	0.031	38.9	19.4	0.2	0.0	58.5	117.8	59.3	100	180
3	0.064	35.0	19.4	0.2	0.0	54.6	111.5	56.9	100	0
4	0.132	45.0	19.4	0.2	0.0	64.6	105.2	40.6	100	0
5	0.389	26.1	19.4	0.3	0.0	45.8	95.8	50.0	100	359
----- Vertical -----										
6	0.807	22.8	19.3	0.3	0.0	42.4	69.5	27.1	100	247

Tested by: Sieon Lee / Assistant Manager

8.6.2 Spurious Radiated Emission Below 30 MHz (500 mA)

Humidity Level : 48 % R.H.

Temperature: 24 °C


Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.209

Frequency Range : 9 kHz ~ 30 MHz

EUT : Wireless Charger

Date: July 20, 2019

Operating Condition : Transmitting Mode



No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA TABLE							
									[MHz]	[dBuV]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]
----- Horizontal -----																
1	0.015	38.2	19.1	0.1	0.0	57.4	124.1	66.7	100	0						
2	0.031	37.6	19.4	0.2	0.0	57.2	117.8	60.6	100	0						
3	0.064	35.0	19.4	0.2	0.0	54.6	111.5	56.9	100	0						
4	0.137	48.0	19.4	0.2	0.0	67.6	104.9	37.3	100	0						
5	0.389	26.4	19.4	0.3	0.0	46.1	95.8	49.7	100	20						
----- Vertical -----																
6	0.807	22.0	19.3	0.3	0.0	41.6	69.5	27.9	100	72						

Tested by: Sieon Lee / Assistant Manager

8.6.3 Spurious Radiated Emission Below 30 MHz (100 mA)

Humidity Level : 48 % R.H.

Temperature: 24 °C


Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.209

Frequency Range : 9 kHz ~ 30 MHz

EUT : Wireless Charger

Date: July 20, 2019

Operating Condition : Transmitting Mode



No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA TABLE [cm]	TABLE [DEG]
----- Horizontal -----										
1	0.015	38.5	19.1	0.1	0.0	57.7	124.1	66.4	100	41
2	0.031	37.6	19.4	0.2	0.0	57.2	117.8	60.6	100	0
3	0.064	35.1	19.4	0.2	0.0	54.7	111.5	56.8	100	0
4	0.148	45.1	19.4	0.2	0.0	64.7	104.2	39.5	100	113
5	0.419	25.1	19.3	0.3	0.0	44.7	95.2	50.5	100	108
----- Vertical -----										
6	0.687	22.0	19.3	0.3	0.0	41.6	70.9	29.3	100	359

Tested by: Sieon Lee / Assistant Manager

9. CONDUCTED EMISSION TEST

9.1 Operating environment

Temperature : 24 °C

Relative humidity : 48 % R.H

9.2 Test set-up


The EUT was placed on a wooden table, 0.8 m height above the floor. Power was fed to the EUT through a $50 \Omega / 50 \mu\text{H} + 5 \Omega$ Artificial Mains Network (AMN). The ground plane was electrically bonded to the reference ground system and all power lines were filtered from ambient.

9.3 Test equipment used

All test equipment used is calibrated on a regular basis.

9.4 Test data


- Test Date : July 24, 2019
- Resolution bandwidth : 9 kHz
- Frequency range : 0.15 MHz ~ 30 MHz
- Tested Line : HOT LINE



NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN [dBuV]	PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]		
1	0.15900	43.5	----	10.1	53.6	----	65.5	----	11.9	----
2	0.25700	35.0	----	10.1	45.1	----	61.5	----	16.4	----
3	0.43800	25.7	----	10.1	35.8	----	57.1	----	21.3	----
4	0.64200	17.4	----	10.1	27.5	----	56.0	----	28.5	----
5	7.28000	14.9	----	10.2	25.1	----	60.0	----	34.9	----
6	24.96000	23.3	----	10.4	33.7	----	60.0	----	26.3	----
7	0.15900	14.3	10.1	----	24.4	----	55.5	----	31.1	H (CAV)
8	0.25700	14.6	10.1	----	24.7	----	51.5	----	26.8	H (CAV)
9	0.43800	13.0	10.1	----	23.1	----	47.1	----	24.0	H (CAV)
10	0.64200	6.6	10.1	----	16.7	----	46.0	----	29.3	H (CAV)
11	7.28000	3.0	10.2	----	13.2	----	50.0	----	36.8	H (CAV)
12	24.96000	12.0	10.4	----	22.4	----	50.0	----	27.6	H (CAV)

- Tested Line

: NEUTRAL LINE



NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15300	44.0	----	10.1	54.1	----	65.8	----	11.7	----	N (QP)
2	0.25600	33.8	----	10.1	43.9	----	61.6	----	17.7	----	N (QP)
3	0.43700	24.7	----	10.1	34.8	----	57.1	----	22.3	----	N (QP)
4	8.24000	13.8	----	10.2	24.0	----	60.0	----	36.0	----	N (QP)
5	24.13000	19.9	----	10.4	30.3	----	60.0	----	29.7	----	N (QP)
6	27.11000	17.4	----	10.5	27.9	----	60.0	----	32.1	----	N (QP)
7	0.15300	14.7	10.1	----	24.8	----	55.8	----	31.0	----	N (CAV)
8	0.25600	15.1	10.1	----	25.2	----	51.6	----	26.4	----	N (CAV)
9	0.43700	11.8	10.1	----	21.9	----	47.1	----	25.2	----	N (CAV)
10	8.24000	4.0	10.2	----	14.2	----	50.0	----	35.8	----	N (CAV)
11	24.13000	7.5	10.4	----	17.9	----	50.0	----	32.1	----	N (CAV)
12	27.11000	4.1	10.5	----	14.6	----	50.0	----	35.4	----	N (CAV)

Remark: Margin (dB) = Limit – Level (Result)

The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.

Tested by: Sieon Lee / Assistant Manager

10. LIST OF TEST EQUIPMENT

No.	EQUIPMENTS	MFR.	MODEL	SER. NO.	LAST CAL	DUE CAL	USE
1.	Test receiver	R/S	ESCI	101420	Mar. 28, 2019	One Year	■
2.		R/S	ESR	101470	Oct. 22, 2018	One Year	■
3.	Spectrum analyzer	R/S	FSV30	101200	Aug. 23, 2018	One Year	■
4.	Amplifier	Sonoma Instrument	310N	312544	Mar. 18, 2019	One Year	■
5.	TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-255	Jun 05, 2018	Two Years	■
6.	Controller	Innco System	CO2000	619/27030611/L	N/A	N/A	■
7.	LISN	Schwarzbeck	NSLK8126	8126-404	Mar. 19, 2019	One Year	■
		Schwarzbeck	NSLK8128	8128-216	Mar. 20, 2019	One Year	■
8.	Turn Table	Innco System	DT3000	930611	N/A	N/A	■
9.	Antenna Master	Innco System	MA4000XPET	MA4000/509	N/A	N/A	■
10.	Loop Antenna	Schwarzbeck	FMZB 1513	1513-235	May. 13, 2018	Two Years	■
11.	AMN	EMCO	3825/2	9109-1867	Mar. 27, 2019	One Year	■
12.	Environmental Test Chamber	ESPEC	PSL-2KP	14009407	Feb. 22, 2019	One Year	■
13.	DC Power Supply	Protek	PWS-3003D	4020409	Aug. 24, 2018	One Year	■