



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.225

Report Reference No.: CTA24080801605

FCC ID.: 2ATVQ-D802

Compiled by

(position+printed name+signature) ... File administrators Jinghua Xiao

Jinghua Xiao



Xudong Zhang

Approved

Eric Wang

Supervised by

(position+printed name+signature) ... Project Engineer Xudong Zhang

Approved by

(position+printed name+signature) ... RF Manager Eric Wang

Date of issue: Aug. 19, 2024

Testing Laboratory Name: Shenzhen CTA Testing Technology Co., Ltd.

Address: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name: SHENZHEN BLOVEDREAM TECHNOLOGY CO.,LTD

Address: 4th Floor, A-Building, Fenghuang Zhigu Building, Tiezai Rd, Xixiang Street, Bao'an District ShenZhen China

Test specification:

Standard: FCC Part 15.225

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Handheld terminal

Trade Mark: N/A

Manufacturer: SHENZHEN BLOVEDREAM TECHNOLOGY CO.,LTD

Model/Type reference: D802

Listed Models: D801, D803, D804, D1001, D1002, D1003, D1004, N60, N60H, N60A, N60B, BlovedreamN60, N60C, P50, P80, P90, F501, F502, F503, F504, F505, P501, P502, P503, R501, R502, R503, X501, X502, X503, F601, F602, F603, H501, H502, H503, H601, H602, H603, S60, U9000, U9100U

Modulation Type: ASK

Operation Frequency: 13.56MHz

Rating: DC 3.8V From battery and DC 5.0V From external circuit

Result: PASS

TEST REPORT

Equipment under Test : Handheld terminal

Model /Type : D802

Listed Models : D801, D803, D804, D1001, D1002, D1003, D1004, N60, N60H, N60A, N60B, BlovedreamN60, N60C, P50, P80, P90, F501, F502, F503, F504, F505, P501, P502, P503, R501, R502, R503, X501, X502, X503, F601, F602, F603, H501, H502, H503, H601, H602, H603, S60, U9000, U9100U

Applicant : SHENZHEN BLOVEDREAM TECHNOLOGY CO.,LTD

Address : 4th Floor, A-Building, Fenghuang Zhigu Building, Tiezai Rd, Xixiang Street, Bao'an District ShenZhen China

Manufacturer : SHENZHEN BLOVEDREAM TECHNOLOGY CO.,LTD

Address : 4th Floor, A-Building, Fenghuang Zhigu Building, Tiezai Rd, Xixiang Street, Bao'an District ShenZhen China

| | |
|---------------------|-------------|
| Test Result: | PASS |
|---------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

| | | |
|----------|--|----|
| <u>1</u> | <u>TEST STANDARDS</u> | 4 |
| <u>2</u> | <u>SUMMARY</u> | 5 |
| 2.1 | General Remarks | 5 |
| 2.2 | Product Description | 5 |
| 2.3 | Equipment Under Test | 6 |
| 2.4 | Block Diagram of Test Setup | 6 |
| 2.5 | Special Accessories | 6 |
| 2.6 | Related Submittal(s) / Grant (s) | 6 |
| 2.7 | Modifications | 6 |
| <u>3</u> | <u>TEST ENVIRONMENT</u> | 7 |
| 3.1 | Address of the test laboratory | 7 |
| 3.2 | Test Facility | 7 |
| 3.3 | Environmental conditions | 7 |
| 3.4 | Test Description | 8 |
| 3.5 | Statement of the measurement uncertainty | 8 |
| 3.6 | Equipments Used during the Test | 8 |
| <u>4</u> | <u>TEST CONDITIONS AND RESULTS</u> | 10 |
| 4.1 | AC Power Conducted Emission | 10 |
| 4.2 | Radiated Emission | 13 |
| 4.3 | 20dB Bandwidth | 18 |
| 4.4 | Frequency Stability | 19 |
| <u>5</u> | <u>TEST SETUP PHOTOS OF THE EUT</u> | 21 |
| <u>6</u> | <u>PHOTOS OF THE EUT</u> | 22 |

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.225: Operation within the band 13.110–14.010 MHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices

2 SUMMARY

2.1 General Remarks

| | | |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | Aug. 03, 2024 |
| Testing commenced on | : | Aug. 03, 2024 |
| Testing concluded on | : | Aug. 19, 2024 |

2.2 Product Description

| | |
|-----------------------|---|
| Product Description: | Handheld terminal |
| Model/Type reference: | D802 |
| Power supply: | DC 3.8V From battery and DC 5.0V From external circuit |
| Adapter information: | Model: SW-050300 Input: AC 100-240V 50/60Hz 0.6A Max Output: DC 5.0V 3000mA |
| Software version: | V1.0 |
| Hardware version: | V1.0 |
| Testing sample ID: | CTA240808016-1# (Engineer sample) CTA240808016-2# (Normal sample) |

13.56MHz RFID

| | |
|----------------------|--------------|
| Operation frequency: | 13.56MHz |
| Modulation : | ASK |
| No. of Channel : | 1 |
| Antenna type: | Loop antenna |
| Antenna gain: | 0.00 dBi |


2.3 Equipment Under Test

Power supply system utilised

| | | | | | |
|----------------------|---|----------------------------------|----------------------------------|-----------------------|-------------|
| Power supply voltage | : | <input type="radio"/> | 230V / 50 Hz | <input type="radio"/> | 120V / 60Hz |
| | | <input type="radio"/> | 12 V DC | <input type="radio"/> | 24 V DC |
| | | <input checked="" type="radio"/> | Other (specified in blank below) | | |

DC 3.8V From battery and DC 5.0V From external circuit

2.4 Block Diagram of Test Setup



2.5 Special Accessories

Follow auxiliary equipment(s) test with EUT that provided by the manufacturer or laboratory is listed as follow:

| Description | Manufacturer | Model | Technical Parameters | Certificate | Provided by |
|-------------|--------------|-------|----------------------|-------------|-------------|
| / | / | / | / | / | / |
| / | / | / | / | / | / |
| / | / | / | / | / | / |

2.6 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the EUT filing to comply with Section 15.225 of the FCC Part 15, Subpart C Rules.

2.7 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 517856 Designation Number: CN1318

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6534.01

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

| | |
|-----------------------|--------------|
| Temperature: | 24 ° C |
| Humidity: | 45 % |
| Atmospheric pressure: | 950-1050mbar |

AC Power Conducted Emission:

| | |
|-----------------------|--------------|
| Temperature: | 25 ° C |
| Humidity: | 46 % |
| Atmospheric pressure: | 950-1050mbar |

Conducted testing:

| | |
|-----------------------|--------------|
| Temperature: | 25 ° C |
| Humidity: | 44 % |
| Atmospheric pressure: | 950-1050mbar |

3.4 Test Description

| FCC PART 15 .225 | | |
|----------------------------|-------------------------------|------|
| FCC Part 15.207 | AC Power Conducted Emission | PASS |
| FCC Part 2.1049 | 20dB Bandwidth | PASS |
| FCC Part 15.225(a) (b) (c) | In-band Emissions | PASS |
| FCC Part 15.225(d)/15.207 | Out-of-band Emissions | PASS |
| FCC Part 15.225(e) | Frequency Stability Tolerance | PASS |

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device. Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

| Test | Range | Measurement Uncertainty | Notes |
|--|-------------|-------------------------|-------|
| Radiated Emission | 9KHz~30MHz | 3.02 dB | (1) |
| Radiated Emission | 30~1000MHz | 4.06 dB | (1) |
| Radiated Emission | 1~18GHz | 5.14 dB | (1) |
| Radiated Emission | 18-40GHz | 5.38 dB | (1) |
| Conducted Disturbance | 0.15~30MHz | 2.14 dB | (1) |
| Output Peak power | 30MHz~18GHz | 0.55 dB | (1) |
| Power spectral density | / | 0.57 dB | (1) |
| Spectrum bandwidth | / | 1.1% | (1) |
| Radiated spurious emission (30MHz-1GHz) | 30~1000MHz | 4.10 dB | (1) |
| Radiated spurious emission (1GHz-18GHz) | 1~18GHz | 4.32 dB | (1) |
| Radiated spurious emission (18GHz-40GHz) | 18-40GHz | 5.54 dB | (1) |

(1)This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test

| Test Equipment | Manufacturer | Model No. | Equipment No. | Calibration Date | Calibration Due Date |
|-------------------|--------------|-----------|---------------|------------------|----------------------|
| LISN | R&S | ENV216 | CTA-308 | 2024/08/03 | 2025/08/02 |
| LISN | R&S | ENV216 | CTA-314 | 2024/08/03 | 2025/08/02 |
| EMI Test Receiver | R&S | ESPI | CTA-307 | 2024/08/03 | 2025/08/02 |
| EMI Test Receiver | R&S | ESCI | CTA-306 | 2024/08/03 | 2025/08/02 |
| Spectrum Analyzer | Agilent | N9020A | CTA-301 | 2024/08/03 | 2025/08/02 |
| Spectrum Analyzer | R&S | FSP | CTA-337 | 2024/08/03 | 2025/08/02 |


| | | | | | |
|-------------------------------------|------------------------|-------------|---------|------------|------------|
| Vector Signal generator | Agilent | N5182A | CTA-305 | 2024/08/03 | 2025/08/02 |
| Analog Signal Generator | R&S | SML03 | CTA-304 | 2024/08/03 | 2025/08/02 |
| WIDEBAND RADIO COMMUNICATION TESTER | CMW500 | R&S | CTA-302 | 2024/08/03 | 2025/08/02 |
| Temperature and humidity meter | Chigo | ZG-7020 | CTA-326 | 2024/08/03 | 2025/08/02 |
| Ultra-Broadband Antenna | Schwarzbeck | VULB9163 | CTA-310 | 2023/10/17 | 2024/10/16 |
| Horn Antenna | Schwarzbeck | BBHA 9120D | CTA-309 | 2023/10/13 | 2024/10/12 |
| Loop Antenna | Zhinan | ZN30900C | CTA-311 | 2023/10/17 | 2024/10/16 |
| Horn Antenna | Beijing Hangwei Dayang | OBH100400 | CTA-336 | 2023/10/17 | 2024/10/16 |
| Amplifier | Schwarzbeck | BBV 9745 | CTA-312 | 2024/08/03 | 2025/08/02 |
| Amplifier | Taiwan chengyi | EMC051845B | CTA-313 | 2024/08/03 | 2025/08/02 |
| Directional coupler | NARDA | 4226-10 | CTA-303 | 2024/08/03 | 2025/08/02 |
| High-Pass Filter | XingBo | XBLBQ-GTA18 | CTA-402 | 2024/08/03 | 2025/08/02 |
| High-Pass Filter | XingBo | XBLBQ-GTA27 | CTA-403 | 2024/08/03 | 2025/08/02 |
| Automated filter bank | Tonscend | JS0806-F | CTA-404 | 2024/08/03 | 2025/08/02 |
| Power Sensor | Agilent | U2021XA | CTA-405 | 2024/08/03 | 2025/08/02 |
| Amplifier | Schwarzbeck | BBV9719 | CTA-406 | 2024/08/03 | 2025/08/02 |

| Test Equipment | Manufacturer | Model No. | Version number | Calibration Date | Calibration Due Date |
|-------------------|--------------|-------------|----------------|------------------|----------------------|
| EMI Test Software | Tonscend | TS®JS32-RE | 5.0.0.2 | N/A | N/A |
| EMI Test Software | Tonscend | TS®JS32-CE | 5.0.0.1 | N/A | N/A |
| RF Test Software | Tonscend | TS®JS1120-3 | 3.1.65 | N/A | N/A |
| RF Test Software | Tonscend | TS®JS1120 | 3.1.46 | N/A | N/A |

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

| Frequency range (MHz) | Limit (dBuV) | |
|-----------------------|--------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.


TEST RESULTS


Remark:

1. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn





4.2 Radiated Emission


LIMIT

- a The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.
- b Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- c Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- d The field strength of any emissions appearing outside of the 13.110– 14.010 MHz band shall not exceed the general radiated emission limits in §15.209.


| Frequency (MHz) | Distance (Meters) | Radiated (dBuV/m) | Radiated (μ V/m) |
|-----------------|-------------------|--|-----------------------|
| 0.009-0.49 | 3 | $20\log(2400/F(\text{KHz}))+40\log(300/3)$ | $2400/F(\text{KHz})$ |
| 0.49-1.705 | 3 | $20\log(24000/F(\text{KHz}))+40\log(30/3)$ | $24000/F(\text{KHz})$ |
| 1.705-13.110 | 3 | 69.54 | 30 |
| 13.110-13.410 | 3 | 80.50 | 106 |
| 13.410-13.553 | 3 | 90.47 | 334 |
| 13.553-13.567 | 3 | 124.00 | 15848 |
| 13.567-13.710 | 3 | 90.47 | 334 |
| 13.710-14.010 | 3 | 80.50 | 106 |
| 14.010-30.0 | 3 | 69.54 | 30 |
| 30-88 | 3 | 40.0 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46.0 | 200 |
| Above 960 | 3 | 54.0 | 500 |

TEST CONFIGURATION

Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 1GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type | Test Distance |
|----------------------|-------------------------|---------------|
| 9KHz-30MHz | Active Loop Antenna | 3 |
| 30MHz-1GHz | Ultra-Broadband Antenna | 3 |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting | Detector |
|----------------------|--|----------|
| 9KHz-150KHz | RBW=200Hz/VBW=3KHz,Sweep time=Auto | QP |
| 150KHz-30MHz | RBW=9KHz/VBW=100KHz,Sweep time=Auto | QP |
| 30MHz-1GHz | RBW=120KHz/VBW=1000KHz,Sweep time=Auto | QP |

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

| | |
|---------------------------|--|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | AG = Amplifier Gain |
| AF = Antenna Factor | |

$$Transd=AF + CL - AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.


| Frequency (MHz) | Distance (Meters) | Radiated (dB μ V/m) | Radiated (μ V/m) |
|-----------------|-------------------|----------------------------------|-----------------------|
| 0.009-0.49 | 3 | 20log(2400/F(KHz))+40log(300/3) | 2400/F(KHz) |
| 0.49-1.705 | 3 | 20log(24000/F(KHz))+ 40log(30/3) | 24000/F(KHz) |
| 1.705-30 | 3 | 20log(30)+ 40log(30/3) | 30 |
| 30-88 | 3 | 40.0 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46.0 | 200 |
| Above 960 | 3 | 54.0 | 500 |

TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. We measured Radiated Emission at ASK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
3. For below 1GHz testing recorded worst at GFSK DH5 middle channel.
4. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
5. We tested the Adapter Powering Mode and POE Port Powering Mode and recorded the worst case at the Adapter Powering Mode.

For 30MHz-1GHz




Suspected Data List

| NO. | Freq. [MHz] | Reading [dB μ V] | Level [dB μ V/m] | Factor [dB/m] | Limit [dB μ V/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|-------------|----------------------|----------------------|---------------|----------------------|-------------|-------------|-----------|------------|
| 1 | 51.34 | 35.58 | 24.33 | -11.25 | 40.00 | 15.67 | 100 | 85 | Horizontal |
| 2 | 73.7712 | 45.37 | 29.63 | -15.74 | 40.00 | 10.37 | 100 | 0 | Horizontal |
| 3 | 104.326 | 38.57 | 25.54 | -13.03 | 43.50 | 17.96 | 100 | 189 | Horizontal |
| 4 | 174.408 | 46.91 | 32.07 | -14.84 | 43.50 | 11.43 | 100 | 212 | Horizontal |
| 5 | 308.753 | 44.98 | 34.10 | -10.88 | 46.00 | 11.90 | 100 | 178 | Horizontal |
| 6 | 630.793 | 30.13 | 24.45 | -5.68 | 46.00 | 21.55 | 100 | 212 | Horizontal |

Note: 1).Level (dB μ V/m)= Reading (dB μ V)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Limit (dB μ V/m) - Level (dB μ V/m)



In-band Emissions

| Frequency(MHz): | | | 13.56 | | | Polarity: | | / | |
|-----------------|-----------------|-------------------------|----------|----------------|-------------|------------------|-----------------------|-------------------|--------------------------|
| No. | Frequency (MHz) | Emission Level (dBuV/m) | Detector | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Correction Factor (dB/m) |
| 1 | 13.15 | 57.93 | PK | 80.50 | 22.57 | 53.21 | 5.21 | -0.49 | 4.72 |
| 2 | 13.55 | 80.11 | PK | 90.47 | 10.36 | 75.34 | 5.26 | -0.49 | 4.77 |
| 3 | 13.56 | 100.20 | PK | 124.00 | 23.80 | 95.43 | 5.26 | -0.49 | 4.77 |
| 4 | 13.57 | 79.39 | PK | 90.47 | 11.08 | 74.62 | 5.26 | -0.49 | 4.77 |
| 5 | 13.75 | 58.06 | PK | 80.50 | 22.44 | 53.26 | 5.29 | -0.49 | 4.80 |

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)
3. Margin value = Limit value- Emission level.
4. The other emission levels were very low against the limit.

Out-of-band Emissions

| Frequency(MHz): | | | 13.56 | | | Polarity: | | HORIZONTAL | |
|-----------------|-----------------|-------------------------|----------|----------------|-------------|------------------|-----------------------|-------------------|--------------------------|
| No. | Frequency (MHz) | Emission Level (dBuV/m) | Detector | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Correction Factor (dB/m) |
| 1 | 27.12 | 41.38 | PK | 69.54 | 28.16 | 33.88 | 7.25 | 0.25 | 7.50 |
| 2 | 40.68 | 30.76 | PK | 40.00 | 9.24 | 22.13 | 8.12 | 0.51 | 8.63 |
| 3 | 54.24 | 29.44 | PK | 40.00 | 10.56 | 20.36 | 8.36 | 0.72 | 9.08 |
| 4 | 67.8 | 26.81 | PK | 40.00 | 13.19 | 17.28 | 8.57 | 0.96 | 9.53 |

| Frequency(MHz): | | | 13.56 | | | Polarity: | | VERTICAL | |
|-----------------|-----------------|-------------------------|----------|----------------|-------------|------------------|-----------------------|-------------------|--------------------------|
| No. | Frequency (MHz) | Emission Level (dBuV/m) | Detector | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Correction Factor (dB/m) |
| 1 | 27.12 | 38.55 | PK | 69.54 | 30.99 | 31.05 | 7.25 | 0.25 | 7.50 |
| 2 | 40.68 | 28.58 | PK | 40.00 | 11.42 | 19.95 | 8.12 | 0.51 | 8.63 |
| 3 | 54.24 | 27.73 | PK | 40.00 | 12.27 | 18.65 | 8.36 | 0.72 | 9.08 |
| 4 | 67.8 | 26.57 | PK | 40.00 | 13.43 | 17.04 | 8.57 | 0.96 | 9.53 |

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)
3. Margin value = Limit value- Emission level.
4. The other emission levels were very low against the limit.

4.3 20dB Bandwidth

Limit


No limit for 20dB bandwidth.

Test Procedure

The 20dB bandwidth is measured with a spectrum analyzer connected via a receive antenna placed near the EUT while the EUT is operating in transmission mode.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration



Test Results

| Modulation | Frequency(MHz) | 20dB bandwidth (KHz) | Result |
|------------|----------------|----------------------|--------|
| ASK | 13.56MHz | 8.633 | Pass |




4.4 Frequency Stability

LIMIT

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

TEST CONFIGURATION



Note : Measurement setup for testing on Antenna connector




TEST PROCEDURE

1. The equipment under test was connected to an external DC power supply and input rated voltage.
2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators.
3. The EUT was placed inside the temperature chamber.
4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency.
5. Turn EUT off and set the chamber temperature to -20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency.
6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.
7. Reduce the input voltage to specified extreme voltage variation (+/- 15%) or endpoint, record the maximum frequency change.

TEST RESULTS

| Reference Frequency: 13.56MHz | | | | |
|-------------------------------|------------------|-----------------|-------------------------|---------------|
| Voltage (V) | Temperature (°C) | Frequency (MHz) | Frequency Deviation(Hz) | Deviation (%) |
| DC 3.80 | +20(Ref) | 13.560059 | 59 | 0.000438% |
| | -20 | 13.560172 | 172 | 0.01267% |
| | -10 | 13.560152 | 152 | 0.001121% |
| | 0 | 13.560136 | 136 | 0.001000% |
| | 10 | 13.560124 | 124 | 0.000916% |
| | 20 | 13.560199 | 199 | 0.001470% |
| | 25 | 13.560109 | 109 | 0.000804% |
| | 30 | 13.560116 | 116 | 0.000857% |
| | 40 | 13.560110 | 110 | 0.000810% |
| | 50 | 13.560087 | 87 | 0.000641% |
| DC 4.20 | 20 | 13.560151 | 151 | 0.001115% |
| DC 3.40 | 20 | 13.560161 | 161 | 0.001186% |

5 Test Setup Photos of the EUT



6 Photos of the EUT

Reference to the test report No. CTA24080801601

***** End of Report *****