

FCC TEST REPORT

FCC ID: 2ATVUPDI350UFP01

Product	:	TFT display
Model Name	:	PDI350UFP01
Brand	:	N/A
Report No.	:	PTC19052501302E-FC01
Prepared for		
Perfect Intelligent Technology Limited		
Flat 903, 9/F New Lee Wah Centre, No. 88 ToKwaWan Road, ToKwaWan, Kowloon, Hong Kong		
Prepared by		
Dongguan Precise Testing & Certification Corp., Ltd.		
Building D, Baoding Technology Park, Guangming Road 2, Guangming Community, Dongcheng District, Dongguan, Guangdong, China		

1 TEST RESULT CERTIFICATION

Applicant's name : Perfect Intelligent Technology Limited

Address : Flat 903, 9/F New Lee Wah Centre, No. 88 ToKwaWan Road, ToKwaWan, Kowloon, Hong Kong

Manufacture's name : I.A.Technology(Dong Guan)Company Ltd

Address : Building A, No.478,You Yi Road,Qiao Tou Town,DongGuan,GuanDongProvince,China

Product name : TFT display

Model name : PDI350UFP01

Standards : FCC CFR47 Part 15 Section 15.247

Test procedure : ANSI C63.10:2013

Test Date : June 05, 2019 to June 19, 2019

Date of Issue : June 24, 2019

Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:



Leo Yang / Engineer

Technical Manager:



Chris Du / Manager

Contents

	Page
1 TEST RESULT CERTIFICATION.....	2
2 TEST SUMMARY	5
3 GENERAL INFORMATION.....	6
3.1 GENERAL DESCRIPTION OF E.U.T.....	6
3.2 CHANNEL LIST	7
3.3 TEST SITE.....	11
4 EQUIPMENT DURING TEST	12
4.1 EQUIPMENTS LIST	12
4.2 MEASUREMENT UNCERTAINTY.....	14
4.3 DESCRIPTION OF SUPPORT UNITS.....	15
5 CONDUCTED EMISSION.....	16
5.1 E.U.T. OPERATION	16
5.2 EUT SETUP	16
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	17
5.4 MEASUREMENT PROCEDURE.....	17
5.5 CONDUCTED EMISSION LIMIT.....	17
5.6 MEASUREMENT DESCRIPTION	17
5.7 CONDUCTED EMISSION TEST RESULT.....	17
6 RADIATED SPURIOUS EMISSIONS.....	20
6.1 EUT OPERATION.....	20
6.2 TEST SETUP	21
6.3 SPECTRUM ANALYZER SETUP	22
6.4 TEST PROCEDURE.....	23
6.5 SUMMARY OF TEST RESULTS	24
7 CONDUCTED SPURIOUS EMISSION.....	29
7.1 TEST PROCEDURE.....	29
7.2 TEST RESULT	29
8 BAND EDGE MEASUREMENT	36
8.1 TEST PROCEDURE.....	36



8.2	TEST RESULT	37
9	6DB BANDWIDTH MEASUREMENT	41
9.1	TEST PROCEDURE.....	41
9.2	TEST RESULT	41
10	MAXIMUM PEAK OUTPUT POWER	48
10.1	TEST PROCEDURE.....	48
10.2	TEST RESULT	48
11	POWER SPECTRAL DENSITY	49
11.1	TEST PROCEDURE.....	49
11.2	TEST RESULT	49
12	ANTENNA APPLICATION	56
12.1	ANTENNA REQUIREMENT	56
12.2	RESULT	56
13	TEST SETUP	57
14	EUT PHOTOS.....	59



2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious Emission	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Power Spectral Density	15.247(e)	PASS
Antenna Requirement	15.203	PASS
Remark: N/A: Not Applicable		

3 General Information

3.1 General Description of E.U.T.

Product Name	:	TFT display
Model Name	:	PDI350UFP01
Specification	:	802.11b/g/n HT20/n HT40
Operation Frequency	:	2412-2462MHz for 802.11b/g; 2412-2462MHz for 802.11n(HT20); 2422-2452MHz for 802.11n(HT40);
Number of Channel	:	11 channels for 802.11b/g; 11 channels for 802.11n(HT20); 7 channels for 802.11n(HT40);
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	Internal PCB Antenna
Antenna Gain	:	0 dBi
Power supply	:	For Adapter: Model: CZH024120200EUWM Input: 100-240V~50/60Hz 0.8 Max Output: 12.0 V $\overline{=}$ 2.0 A
Hardware Version	:	V1.0
Software Version	:	V1.0

3.2 Channel List

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS8) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Frequency and Channel list for 802.11 n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	8	2447
4	2427	6	2437	9	2452
		7	2442		

Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11 n (HT40):


Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

The maximum duty cycle as following table:


Test Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle(%)
802.11b	100	100	100%
802.11g	100	100	100%
802.11n(HT20)	100	100	100%
802.11n(HT40)	100	100	100%

Test Plots:


802.11b




802.11g



802.11n(HT20)



802.11n(HT40)





PRECISE TESTING

Report No.: PTC19052501302E-FC01

3.3 Test Site

Dongguan Precise Testing & Certification Corp., Ltd.

Building D, Baoding Technology Park, Guangming Road2, Dongcheng District, Dongguan, Guangdong,
China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A-1

4 Equipment During Test

4.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
MXG Signal Analyzer	Agilent	N9020A	MY56070279	10Hz-30GHz	Sep. 19, 2019
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Sep. 19, 2019
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Sep. 19, 2019
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Sep. 19, 2019

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Sep.19, 2019
Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	Sep.19, 2019
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Sep.19, 2019
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	1MHz-1GHz	Sep.19, 2019
Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	Sep.19, 2019
Spectrum Analyzer	Agilent	E4407B	MY45109572	9KHz-40GHz	Sep.19, 2019
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	1GHz-18GHz	Sep.19, 2019
Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	1GHz-26.5GHz	Sep.19, 2019
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-181	14GHz-40GHz	Sep.25, 2019
Amplifier	SCHWARZBECK	BBV 9721	9721-205	18GHz-40GHz	Sep.19, 2019
Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	Sep.19, 2019
RF Cable	R&S	R204	R21X	1GHz-40GHz	Sep.19, 2019



PRECISE TESTING

Report No.: PTC19052501302E-FC01

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Sep. 19, 2019
Artificial Mains Network	Rohde&Schwarz	L2-16B	000WX31025	9KHz-300MHz	Sep. 19, 2019
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz-300MHz	Sep. 19, 2019



4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$



4.3 Description of Support Units

Equipment	Model No.	Series No.
Adapter	Model: CZH024120200EUWM Input: 100-240V~50/60Hz 0.8 Max Output: 12.0 V $\Rightarrow$ 2.0 A	N/A



5 Conducted Emission

Test Requirement: : FCC CFR 47 Part 15 Section 15.207
Test Method : ANSI C63.10: 2013
Test Result : PASS
Frequency Range : 150kHz to 30MHz
Class/Severity : Class B


5.1 E.U.T. Operation

Operating Environment :


Temperature : 23.8 °C
Humidity : 51 % RH
Atmospheric Pressure : 101.14kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


5.7 Conducted Emission Test Result

Pass.

Please refer to the following pages.




Line-AC 120V/60Hz



No.	Freq MHz	Cable Loss dB	Clamp Factor dB	Receiver Reading dBpW	Emission Level dBpW	Limit dBpW	Over Limit dB	Remark
1.	0.154	10.60	9.53	23.44	43.57	55.78	-12.21	Average
2.	0.154	10.60	9.53	42.44	62.57	65.78	-3.21	QP
3.	0.194	10.61	9.61	14.27	34.49	53.84	-19.35	Average
4.	0.194	10.61	9.61	35.27	55.49	63.84	-8.35	QP
5.	0.486	10.64	9.80	23.38	43.82	46.23	-2.41	Average
6.	0.486	10.64	9.80	33.38	53.82	56.23	-2.41	QP
7.	1.753	10.69	9.87	17.49	38.05	46.00	-7.95	Average
8.	1.753	10.69	9.87	29.49	50.05	56.00	-5.95	QP
9.	3.623	10.72	9.93	15.64	36.29	46.00	-9.71	Average
10.	3.623	10.72	9.93	27.64	48.29	56.00	-7.71	QP
11.	10.564	10.76	10.01	13.17	33.94	50.00	-16.06	Average
12.	10.564	10.76	10.01	25.17	45.94	60.00	-14.06	QP



Neutral-AC 120V/60Hz



No.	Freq MHz	Cable Loss dB	Clamp Factor dB	Receiver Reading dBpW	Emission Level dBpW	Limit dBpW	Over Limit dB	Remark
1.	0.154	10.60	9.50	23.12	43.22	55.78	-12.56	Average
2.	0.154	10.60	9.50	39.12	59.22	65.78	-6.56	QP
3.	0.242	10.62	9.63	20.96	41.21	52.04	-10.83	Average
4.	0.242	10.62	9.63	32.96	53.21	62.04	-8.83	QP
5.	0.494	10.64	9.78	23.70	44.12	46.10	-1.98	Average
6.	0.494	10.64	9.78	30.71	51.13	56.10	-4.97	QP
7.	1.790	10.69	9.85	19.76	40.30	46.00	-5.70	Average
8.	1.790	10.69	9.85	30.76	51.30	56.00	-4.70	QP
9.	3.642	10.72	9.89	14.59	35.20	46.00	-10.80	Average
10.	3.642	10.72	9.89	27.59	48.20	56.00	-7.80	QP
11.	10.790	10.76	9.97	13.75	34.48	50.00	-15.52	Average
12.	10.790	10.76	9.97	25.75	46.48	60.00	-13.52	QP



6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247
 Test Method : ANSI C63.10:2013
 Test Result : PASS
 Measurement Distance : 3m
 Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1 EUT Operation


Operating Environment :

Temperature: : 24.6 °C
 Humidity: : 49.5 % RH
 Atmospheric Pressure: : 101.21kPa
 Test Voltage : 12.0 V $\Rightarrow$ 2.0 A


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

Below 30MHz			
IF Bandwidth	:	10kHz	
Resolution Bandwidth	:	10kHz	
Video Bandwidth	:	10kHz	
30MHz ~ 1GHz			
Detector	:	PK	QP
Resolution Bandwidth	:	100kHz	120kHz
Video Bandwidth	:	300kHz	300kHz
Above 1GHz			
Detector	:	PK	AV
Resolution Bandwidth	:	1MHz	1MHz
Video Bandwidth	:	3MHz	10Hz



6.4 Test Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.
8. The test above 1GHz must be use the fully anechoic room, and the test below 1GHz use the half anechoic room



6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.


Test Frequency: 30MHz ~ 1GHz

All the modulation modes were tested the data of the worst mode (TX 802.11b Low Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following test plots:



Antenna Polarization: Horizontal




No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dBuV	Preamp Factor dB	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	109.412	0.00	11.02	44.15	30.42	24.75	43.50	-18.75	QP
2.	142.824	0.00	13.52	43.30	30.51	26.31	43.50	-17.19	QP
3.	190.405	0.00	11.07	46.88	30.61	27.34	43.50	-16.16	QP
4.	289.002	0.00	12.98	50.42	30.76	32.64	46.00	-13.36	QP
5.	357.929	0.00	14.36	47.23	30.83	30.76	46.00	-15.24	QP
6.	672.845	0.00	19.80	40.77	31.05	29.52	46.00	-16.48	QP

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor



Antenna Polarization: Vertical



No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dBuV	Preamplifier Factor dB	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	67.675	0.00	10.83	44.99	30.25	25.57	40.00	-14.43	QP
2.	96.436	0.00	9.89	48.59	30.38	28.10	43.50	-15.40	QP
3.	133.619	0.00	12.90	43.96	30.49	26.37	43.50	-17.13	QP
4.	189.074	0.00	11.22	47.55	30.61	28.16	43.50	-15.34	QP
5.	283.979	0.00	12.89	48.37	30.75	30.51	46.00	-15.49	QP
6.	863.056	0.00	22.05	42.65	31.14	33.56	46.00	-12.44	QP

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor

**Test Frequency: From 1GHz to 18GHz****Low Channel (2412MHz) Worst case 802.11b**

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4824	28.24	AV	V	9.13	8.06	8.52	36.91	54	-17.09
4824	27.74	AV	H	9.13	8.06	8.52	36.41	54	-17.59
4824	30.24	PK	V	9.13	8.06	8.52	38.91	74	-35.09
4824	31.14	PK	H	9.13	8.06	8.52	39.81	74	-34.19
17246	28.18	AV	V	10.22	8.39	10.44	36.35	54	-17.65
17246	29.75	AV	H	10.22	8.39	10.44	37.92	54	-16.08
17246	31.54	PK	V	10.22	8.39	10.44	39.71	74	-34.29
17246	33.41	PK	H	10.22	8.39	10.44	41.58	74	-32.42

Middle Channel (2437MHz) Worst case 802.11b

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4874	29.34	AV	V	9.35	8.72	9.36	38.05	54	-15.95
4874	29.14	AV	H	9.35	8.72	9.36	37.85	54	-16.15
4874	30.12	PK	V	9.35	8.72	9.36	38.83	74	-35.17
4874	31.71	PK	H	9.35	8.72	9.36	40.42	74	-33.58
16854	29.74	AV	V	12.08	9.27	11.05	40.04	54	-13.96
16854	30.65	AV	H	12.08	9.27	11.05	40.95	54	-13.05
16854	32.47	PK	V	12.08	9.27	11.05	42.77	74	-31.23
16854	31.35	PK	H	12.08	9.27	11.05	41.65	74	-32.35

High Channel (2462MHz) Worst case 802.11b

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4924	29.72	AV	V	9.28	8.35	9.36	37.99	54	-16.01
4924	28.45	AV	H	9.28	8.35	9.36	36.72	54	-17.28
4924	31.18	PK	V	9.28	8.35	9.36	39.45	74	-34.55
4924	30.24	PK	H	9.28	8.35	9.36	38.51	74	-35.49
17546	29.34	AV	V	10.26	8.46	9.13	38.93	54	-15.07
17546	27.43	AV	H	10.26	8.46	9.13	37.02	54	-16.98
17546	30.25	PK	V	10.26	8.46	9.13	39.82	74	-34.18
17546	32.44	PK	H	10.26	8.46	9.13	42.03	74	-31.97

Note:

1. The testing has been conformed to $10 \times 2462\text{MHz} = 24620\text{MHz}$.
2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor
Margin=Emission Level-Limit
4. X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Test Frequency: From 18GHz to 25GHz

The measurements were more than 20dB below the limit and not reported.

7 Conducted Spurious Emission


Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2013
Test Limit	:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

7.2 Test Result


802.11 b
Low Channel



Middle Channel




High Channel




802.11g


Low Channel



Middle Channel




High Channel




802.11n-HT20


Low Channel



Middle Channel




High Channel




802.11n-HT40


Low Channel



Middle Channel



High Channel





8 Band Edge Measurement

Test Requirement	: Section 15.247(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

8.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold





PRECISE TESTING



Report No.: PTC19052501302E-FC01

8.2 Test Result



802.11b





802.11g



802.11n-HT20



802.11n-HT40



9 6dB Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013

Test Limit : Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.


9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz


9.2 Test Result

Modulation	Bandwidth(MHz)			Limit
	Low Channel	Middle Channel	High Channel	
802.11b	10.24	9.76	10.24	≥500kHz
802.11g	15.68	15.60	15.28	≥500kHz
802.11n-HT20	15.36	15.28	15.36	≥500kHz
802.11n-HT40	35.52	35.52	35.52	≥500kHz

802.11b Low Channel



802.11b Middle Channel



Ref 16.5 dBm Att 20 dB RBW 100 kHz Delta 2 [T1] 1.45 dB VSW 300 kHz SWT 5 ms 10.24000000 MHz

Offset 5.5 dB Marker 1 [T1] -10.03 dBm

1.99 MHz

2.462 GHz

Center 2.462 GHz 4 MHz/ Span 40 MHz

Ref 16.5 dBm Att 20 dB RBW 100 kHz VBW 300 kHz SWT 5 ms Delta 2 [T1] 15.68000000 MHz

Offset 8.5 dB



Marker 1 [T1] -6.52 dBm 2.404320000 GHz

p1 2.28 dBm


p2 -8.72 dBm

Center 2.412 GHz 4 MHz/ Span 40 MHz


802.11g Middle Channel




802.11n-HT20 Low Channel



802.11n-HT20 Middle Channel





Ref 16.5 dBm Att 20 dB SW 5 ms 15.36000000 MHz
 Offset 6.5 dB Marker 1 [T1] -3.62 dBm
 2.454320000 GHz
 p1 2.38 dBm p2 -3.62 dBm
 Center 2.462 GHz 4 MHz/ Span 40 MHz

Ref 16.5 dBm Att 20 dB RBW 100 kHz VSW 300 kHz Delta 2 [T1] 0.43 dB 35.52000000 MHz

Offset 6.5 dB

Marker 1 [T1] 2.40424000 GHz

P1 = -1.45 dBm

P2 = -7.45 dBm

Center 2.422 GHz 8 MHz/ Span 80 MHz

10 Maximum Peak Output Power

Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2013
Test Limit	:	Regulation 15.247 (b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

10.1 Test Procedure

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

10.2 Test Result

Modulation	Maximum Peak Output Power (dBm)			Limit
	Low Channel	Middle Channel	High Channel	
802.11b	15.66	16.44	16.28	1W(30dBm)
802.11g	13.86	13.73	13.70	1W(30dBm)
802.11n-HT20	13.80	13.89	13.70	1W(30dBm)
802.11n-HT40	12.86	11.85	11.98	1W(30dBm)

11 Power Spectral density

Test Requirement	: FCC CFR47 Part 15 Section 15.247
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


11.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz, Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.


11.2 Test Result

Modulation	Power Spectral density (dBm/3kHz)			Limit
	Low Channel	Middle Channel	High Channel	
802.11b	6.64	6.66	6.46	8dBm/3kHz
802.11g	2.51	2.37	1.94	8dBm/3kHz
802.11n-HT20	2.16	2.07	1.91	8dBm/3kHz
802.11n-HT40	-1.34	-1.63	-2.23	8dBm/3kHz



802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11n-HT20 High Channel




802.11n-HT40 Low Channel



802.11n-HT40 Middle Channel



802.11n-HT40 High Channel



12 Antenna Application

12.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2 Result

The EUT'S antenna, permanent attached antenna, is internal PCB antenna. The antenna's gain is 0 dBi and meets the requirement.

13 Test Setup

Conducted Emissions




Radiated Spurious Emissions
From 30MHz-1000MHz







Test frequency from Above 1GHz




14 EUT Photos



















RF Antenna







*******THE END REPORT*******