

RF EXPOSURE EVALUATION

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

EUT Specification

| | |
|-----------------------------------|--|
| FCC ID | 2ATVW-P1 |
| EUT | Air Quality Monitor |
| Frequency band (Operating) | <input checked="" type="checkbox"/> BT: 2.402GHz ~ 2.480GHz <input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> RLAN: 5.180GHz ~ 5.240GHz <input type="checkbox"/> RLAN: 5.260GHz ~ 5.320GHz <input type="checkbox"/> RLAN: 5.500GHz ~ 5.700GHz <input type="checkbox"/> RLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Lora:911MHz, 915MHz, 919MHz |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____ |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²) |
| Antenna diversity | <input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Antenna gain (Max) | BLE: -3.89dBi SRD: 3.92dBi: |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm ²) | Average Time |
|---|------------------------------|------------------------------|------------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/Uncontrol Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100000 | -- | -- | 1 | 30 |

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

 P_d = Power density in mW/cm² P_{out} =output power to antenna in mW

G= gain of antenna in linear scale

 $\pi=3.1416$

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.**Max Measurement Result**

| Operating Mode | Measure d Power | Tune up tolerance | Max. Tune up Power | Max. Tune up Power | Antenna Gain | Antenna Gain in linear | Power density at 20cm | Power density Limits |
|----------------|-----------------|-------------------|--------------------|--------------------|--------------|------------------------|------------------------|-----------------------|
| | (dBm) | (dBm) | (dBm) | (mW) | (dBi) | (Numerical value) | (mW/ cm ²) | (mW/cm ²) |
| BLE | 3.07 | 3.07 ±1 | 4.07 | 2.5527 | -3.89 | 0.4083 | 0.0002 | 1 |
| SRD | 5.86 | 5.86 ±1 | 6.86 | 4.8529 | 3.92 | 2.4660 | 0.0024 | 0.6073 |

The simultaneous transmission for BLE+SRD:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$=S_{BLE}/S_{limit} + S_{SRD}/S_{limit}$$

$$=0.0002/1+0.0024/0.6073$$

$$=0.0042$$

$$< 1.0$$

Result: PASS.**Shenzhen Anbotek Compliance Laboratory Limited**