

FCC ID: 2ATVX-YSD008806

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

Operation Frequency: EDR: 2402MHz~2480MHz;

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna

Antenna gain:0.07dBi,

R=20cm

EDR:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)		
				tune-up power		Gain					
				(dBm)	(mW)	(dBi)	Numeric				
2402	GFSK	4.968	5±1	6	3.981	0.07	1.02	0.0008	1		
2441		5.152	5±1	6	3.981	0.07	1.02	0.0008	1		
2480		4.777	5±1	6	3.981	0.07	1.02	0.0008	1		
2402		5.553	5±1	6	3.981	0.07	1.02	0.0008	1		
2441		5.796	5±1	6	3.981	0.07	1.02	0.0008	1		
2480		5.396	5±1	6	3.981	0.07	1.02	0.0008	1		

Conclusion:

For the max result : 0.0008≤ 1.0, compliance with FCC's RF Exposure.

Signature:

ZEN ZHI PEI

Date: 2019-08-01

NAME AND TITLE (Please print or type): ZEN ZHI PEI/Manager

COMPANY (Please print or type): Shen Zhen YU Senda Electronics CO,LTD / Second floor of three buildings in Fuhai Industrial Zone, Qiaotou Village, Fuyong Town, Bao'an District, Shenzhen, China