

FCC MPE TEST REPORT

FCC ID: 2ATWUWI055

Product: wireless 6700mAH power bank super charger

Trade Name: N/A

Model Name: WI-055

Serial Model: KP-Super, KP-Super2, KP-Super3, KP-Super4, KP-Super5

Report No.: UNIA19102110FR-02

Prepared for

Mei Shun He Electronic Limited

301,8th Building, No.69 Xikeng Road, Xikeng Community, Fucheng Street, Longhua District, 518110, Shenzhen City, China

Prepared by

Shenzhen United Testing Technology Co., Ltd.

2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang Community, Xixiang Str, Bao'an District, Shenzhen, China

TEST RESULT CERTIFICATION

Applicant's name : Mei Shun He Electronic Limited

Address..... : 301,8th Building,No.69 Xikeng Road,Xikeng Community,Fucheng Street,Longhua District,518110,Shenzhen City,China

Manufacture's Name : Mei Shun He Electronic Limited

Address..... : 301,8th Building,No.69 Xikeng Road,Xikeng Community,Fucheng Street,Longhua District,518110,Shenzhen City,China

Product description

Product name : wireless 6700mAH power bank super charger

Trade Mark..... : N/A

Model and/or type reference : WI-055, KP-Super, KP-Super2, KP-Super3, KP-Super4, KP-Super5

Standards..... : FCC KDB 680106 D01 RF Exposure Wireless Charging Apps v03

This device described above has been tested by Shenzhen United Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of UNI, this document may be altered or revised by Shenzhen United Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests : Oct. 21, 2019 ~ Oct. 31, 2019

Date of Issue..... : Oct. 31, 2019

Test Result..... : Pass

Prepared by:

Bob liao

Bob liao/Editor

Reviewer:

Kahn yang

Kahn yang/Supervisor

Approved & Authorized Signer:

Liuze

Liuze/Manager

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

| Channel List | | | |
|--------------|----------------|---------|----------------|
| Channel | Frequency(KHz) | Channel | Frequency(MHz) |
| 01 | 125 | | |
| | | | |
| | | | |
| | | | |

The EUT antenna is Coil Antenna. No antenna other than that furnished by the responsible party shall be used with the device.

1. SUMMARY OF TEST RESULTS

1.1 Test procedures according to the technical standards:

FCC KDB 680106 D01 RF Exposure Wireless Charging Apps v03

| FCC CFR 47 | | | |
|--|-----------------------------------|----------|--------|
| Standard Section | Test Item | Judgment | Remark |
| FCC CFR 47 part1, 1.1310 KDB680106 D01 v03(3)(3) | Electric Field Strength (E) (V/m) | PASS | |
| | Magnetic Field Strength (H) (A/m) | PASS | |

Compliant with KDB680106 D01 RF Exposure Wireless Charging Apps v03 section 5,b:

- a) Power transfer frequency is less than 1 MHz.
- b) Output power from each primary coil is less than or equal to 15 watts.
- c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
- d) Client device is placed directly in contact with the transmitter.
- e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
- f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | Uncertainty |
|-----|-----------------------------------|-------------------------|
| 1 | Radiated Measurement (9KHz-30MHz) | $\pm 2.50\text{dB}$ |
| 2 | Temperature | $\pm 0.5^\circ\text{C}$ |
| 3 | Humidity | $\pm 2\%$ |

1.3 Test Instruments

| Description | Brand | Model No. | Frequency Range | Calibrated Until |
|-----------------------|-----------|-----------|-----------------|------------------|
| Broadband Field Meter | NARDA | NBM-550 | — | Jan. 01, 2020 |
| Magnetic Field Meter | NARDA | ELT-400 | 1–400kHz | Jan. 01, 2020 |
| Magnetic Probe | NARDA | HF-3061 | 300kHz–30MHz | Jan. 01, 2020 |
| Magnetic Probe | NARDA | HF-0191 | 27–1000MHz | Jan. 01, 2020 |
| Broadband Field Meter | NARDA | NBM-550 | — | Jan. 01, 2020 |
| Electric Field Meter | COMBINOVA | EFM 200 | 5Hz–400kHz | Jan. 01, 2020 |
| E-Field Probe | NARDA | EF-0391 | 100kHz–3GHz | Jan. 01, 2020 |
| E-Field Probe | NARDA | EF-6091 | 100MHz–60GHz | Jan. 01, 2020 |

NOTE: The calibration interval of the above test instruments is 12 months.

2. MAXIMUM PERMISSIBLE EXPOSURE

2.1 MAXIMUM PERMISSIBLE EXPOSURE

Limit of Maximum Permissible Exposure

| Limits for Occupational / Controlled Exposure | | | | |
|---|-----------------------------------|-----------------------------------|--|---|
| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-100,000 | | | 5 | 6 |
| Limits for General Population / Uncontrolled Exposure | | | | |
| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180 / f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-100,000 | | | 1 | 30 |

Note 1: f = frequency in MHz ; *Plane-wave equivalent power density.


2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v03.

3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.


2.2 TEST PROCEDURE

For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be at 15 cm surrounding the device and 20 cm above the top surface. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair at 15 cm surrounding the device and 20 cm above the top surface.

2.3 SET UP



2.4 TEST PHOTO



3. RESULT OF MAXIMUM PERMISSIBLE EXPOSURE

For Full load mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

| Frequency Range (MHz) | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Reference Limit (V/m) | Limits Test (V/m) |
|-----------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------|-------------------|
| 0.125 | 1.20 | 1.18 | 1.16 | 1.15 | 1.10 | 307 | 614 |

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

| Frequency Range (MHz) | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Reference Limit (A/m) | Limits Test (A/m) |
|-----------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------|-------------------|
| 0.125 | 0.18 | 0.18 | 0.20 | 0.16 | 0.18 | 0.815 | 1.63 |

For Half Load for wrist band mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

| Frequency Range (MHz) | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Reference Limit (V/m) | Limits Test (V/m) |
|-----------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------|-------------------|
| 0.125 | 1.20 | 1.19 | 1.18 | 1.18 | 1.16 | 307 | 614 |

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

| Frequency Range (MHz) | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Reference Limit (A/m) | Limits Test (A/m) |
|-----------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------|-------------------|
| 0.125 | 0.20 | 0.18 | 0.22 | 0.20 | 0.20 | 0.815 | 1.63 |

For Half Load for shopped mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

| Frequency Range (MHz) | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Reference Limit (V/m) | Limits Test (V/m) |
|-----------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------|-------------------|
| 0.125 | 1.20 | 1.18 | 1.18 | 1.16 | 1.18 | 307 | 614 |

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

| Frequency Range (MHz) | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Reference Limit (A/m) | Limits Test (A/m) |
|-----------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------|-------------------|
| 0.125 | 0.17 | 0.20 | 0.16 | 0.16 | 0.18 | 0.815 | 1.63 |

For No load mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

| Frequency Range (MHz) | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Reference Limit (V/m) | Limits Test (V/m) |
|-----------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------|-------------------|
| 0.125 | 1.17 | 1.17 | 1.16 | 1.20 | 1.16 | 307 | 614 |

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

| Frequency Range (MHz) | Test Position A | Test Position B | Test Position C | Test Position D | Test Position E | Reference Limit (A/m) | Limits Test (A/m) |
|-----------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------|-------------------|
| 0.125 | 0.16 | 0.16 | 0.18 | 0.18 | 0.20 | 0.815 | 1.63 |

※※※※※ THE END ※※※※※