

SAR TEST REPORT

For

Shenzhen Youmi Intelligent Technology Co., Ltd

406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China

FCC ID: 2ATZ4-A115X

IC: 26074-A115X

Report Type: Original Report		Product Type: A11	
Report Number:	SZ1210426-13944E-SA		
Report Date:	2021-06-07		
Reviewed By:	Seven Liang SAR Engineer	<i>Seven Liang</i>	
Bay Area Compliance Laboratories Corp. (Shenzhen) 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn			

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".
BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Attestation of Test Results			
EUT Information	EUT Description	A11	
	Tested Model	A11	
	Multiple Model	A11 Pro Max, A11 Pro, Power 5, Power 5X, Power 5 Max	
	FCC ID	2ATZ4-A115X	
	IC	26074-A115X	
	Serial Number	SZ1210426-13944E-SA-S_2P0	
	Test Date	2021/05/10 to 2021/05/19	
MODE		Max. SAR Level(s) Reported(W/kg)	Limit (W/kg)
GSM 850	1g Head SAR	0.18	1.6
	1g Body SAR	0.34	
PCS 1900	1g Head SAR	0.03	
	1g Body SAR	0.78	
WCDMA Band 2	1g Head SAR	0.05	
	1g Body SAR	0.54	
WCDMA Band 5	1g Head SAR	0.17	
	1g Body SAR	0.28	
LTE Band 2	1g Head SAR	0.05	
	1g Body SAR	0.66	
LTE Band 5	1g Head SAR	0.15	
	1g Body SAR	0.09	
LTE Band 7	1g Head SAR	0.98	
	1g Body SAR	0.23	
LTE Band 40Lower	1g Head SAR	0.30	
	1g Body SAR	0.06	
LTE Band 40Upper	1g Head SAR	0.31	
	1g Body SAR	0.06	
LTE Band 41&38	1g Head SAR	0.53	
	1g Body SAR	0.13	
WIFI 2.4G	1g Head SAR	0.72	
	1g Body SAR	0.23	
WIFI 5.2G	1g Head SAR	0.85	
	1g Body SAR	0.53	
WIFI 5.8G	1g Head SAR	0.68	
	1g Body SAR	0.64	
Simultaneous	1g Head SAR	1.47	
	1g Body SAR	0.99	
	1g Body SAR	0.99(Hotspot)	

Note:

1. 5G wifi SAR refer to the SAR report which issued by Bay Area Compliance Laboratories Corp(Dongguan)

Applicable Standards	RSS-102 Issue 5 March 2015 Radio Frequency (RF) Exposure Compliance of Radio communication Apparatus (All Frequency Bands).
	FCC 47 CFR part 2.1093 Radiofrequency radiation exposure evaluation: portable devices
	IEEE1528:2013 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
	IEC 62209-1:2016 Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)
	KDB procedures KDB 447498 D01 General RF Exposure Guidance v06 KDB 648474 D04 Handset SAR v01r03 KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04 KDB 865664 D02 RF Exposure Reporting v01r02 KDB 941225 D01 3G SAR Procedures v03r01 KDB 941225 D05 SAR for LTE Devices v02r05 KDB 941225 D06 Hotspot Mode v02r01 KDB 248227 D01 802.11 Wi-Fi SAR v02r02
Note: This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in FCC 47 CFR part 2.1093 and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures. The results and statements contained in this report pertain only to the device(s) evaluated.	

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY.....	5
EUT DESCRIPTION	6
TECHNICAL SPECIFICATION	7
REFERENCE, STANDARDS, AND GUIDELINES	8
SAR LIMITS.....	9
FACILITIES	10
DESCRIPTION OF TEST SYSTEM.....	11
EQUIPMENT LIST AND CALIBRATION.....	17
EQUIPMENTS LIST & CALIBRATION INFORMATION.....	17
SAR MEASUREMENT SYSTEM VERIFICATION	18
LIQUID VERIFICATION	18
SYSTEM ACCURACY VERIFICATION.....	21
SAR SYSTEM VALIDATION DATA.....	22
EUT TEST STRATEGY AND METHODOLOGY.....	27
TEST POSITIONS FOR DEVICE OPERATING NEXT TO A PERSON'S EAR	27
CHEEK/TOUCH POSITION	28
EAR/TILT POSITION	28
TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS.....	29
TEST DISTANCE FOR SAR EVALUATION.....	29
SAR EVALUATION PROCEDURE	30
CONDUCTED OUTPUT POWER MEASUREMENT	31
PROVISION APPLICABLE	31
TEST PROCEDURE	31
RADIO CONFIGURATION	31
MAXIMUM TARGET OUTPUT POWER	35
TEST RESULTS:.....	37
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	55
ANTENNA DISTANCE TO EDGE.....	55
SAR TEST EXCLUSION FOR THE EUT EDGE CONSIDERATIONS RESULT	56
CORRECTED SAR EVALUATION	57
SAR MEASUREMENT RESULTS	59
SAR TEST DATA	59
SAR MEASUREMENT VARIABILITY.....	72
SAR SIMULTANEOUS TRANSMISSION DESCRIPTION.....	73
SAR PLOTS	84
APPENDIX A MEASUREMENT UNCERTAINTY	85
APPENDIX B EUT TEST POSITION PHOTOS.....	87
APPENDIX C PROBE CALIBRATION CERTIFICATES	88
APPENDIX D DIPOLE CALIBRATION CERTIFICATES	89

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	SZ1210426-13944E-SA	Original Report	2021-06-07

EUT DESCRIPTION

This report has been prepared on behalf of **Shenzhen Youmi Intelligent Technology Co., Ltd** and their product **A11**, Model: **A11**, FCC ID: **2ATZ4-A115X**; IC: **26074-A115X** or the EUT (Equipment under Test) as referred to in the rest of this report.

** Notes: This series products model: A11(SZ1210426-13944E-SA-S_2P0) and A11 Pro Max ·A11 Pro ·Power 5 ·Power 5X · Power 5 Max are identical schematics Model A11 was selected for fully testing, the detailed information can be referred to the attached declaration which was stated and guaranteed by the manufacturer.*

**All measurement and test data in this report was gathered from production sample serial number: SZ1210426-13944E-SA-S_2P0 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2021-04-29.*

Technical Specification

Device Type:	Portable
Exposure Category:	Population / Uncontrolled
Antenna Type(s):	Internal Antenna
DTM Type:	Class B
Multi-slot Class:	GPRS/EGPRS (Class 12)
Proximity sensor for SAR reduction:	None
Body-Worn Accessories:	Headset
Face-Head Accessories:	None
Operation Mode :	GSM Voice, GPRS/ EDGE Data, WCDMA(R99 (Voice+Data), HSDPA/HSUPA/HSPA+), FDD-LTE, TDD-LTE,WLAN, Bluetooth
Frequency Band:	GSM 850: 824-849 MHz(TX); 869-894 MHz(RX) PCS 1900: 1850-1910 MHz(TX); 1930-1990 MHz(RX) WCDMA Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX) WCDMA Band 5: 824-849 MHz(TX); 869-894 MHz(RX) LTE Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX) LTE Band 5: 824-849 MHz(TX) ; 869-894 MHz (RX) LTE Band 7: 2500-2570 MHz(TX); 2620-2690MHz (RX) LTE Band 38: 2570-2620 MHz(TX); 2570-2620 MHz(RX) LTE Band 40: 2305-2315MHz& 2350-2360MHz(TX/RX) LTE Band 41: 2555-2655 MHz(TX); 2555-2655 MHz(RX) 2.4GWi-Fi:2412~2472MHz/2422-2462MHz 5.2GWi-Fi:5150-5250MHz(TX&RX) 5.8GWi-Fi:5725-5850MHz(TX&RX) Bluetooth : 2402 MHz-2480 MHz
Conducted RF Power:	GSM 850 : 32.5 dBm PCS 1900: 29.8 dBm WCDMA Band 2: 22.93 dBm WCDMA Band 5: 22.80 dBm LTE Band 2: 23.18 dBm LTE Band 5: 23.88 dBm LTE Band 7: 23.91 dBm LTE Band 38: 23.03 dBm LTE Band 40lower: 22.58 dBm LTE Band 40Upper: 22.57 dBm LTE Band 41: 23.89 dBm WLAN (2.4G): 19.93 dBm WLAN (5.2G): 11.48 dBm WLAN (5.8G): 12.19 dBm Bluetooth(BDR/EDR): 6.23 dBm BLE_1M: -1.50 dBm BLE_2M: -1.39 dBm
Power Source:	Rechargeable Battery
Normal Operation:	Head and Body-worn

REFERENCE, STANDARDS, AND GUIDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

CE:

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 2 mW/g as recommended by EN62209-1 for an uncontrolled environment. According to the Standard, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in Europe is 2 mW/g average over 10 gram of tissue mass.

The test configurations were laid out on a specially designed test fixture to ensure the reproducibility of measurements. Each configuration was scanned for SAR. Analysis of each scan was carried out to characterize the above effects in the device.

SAR Limits**FCC Limit(1g Tissue)**

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

CE Limit(10g Tissue)

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 10 g of tissue)	2.0	10
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg (FCC) & 2 W/kg (CE) applied to the EUT.

FACILITIES


The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect data is located at 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.


DESCRIPTION OF TEST SYSTEM

These measurements were performed with the automated near-field scanning system DASY6 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



DASY6 System Description

The DASY6 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot (Staubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

DASY6 Measurement Server

The DASY6 measurement server is based on a PC/104 CPU board with a 400 MHz Intel ULV Celeron, 128 MB chip-disk and 128 MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16-bit AD converter system for optical detection and digital I/O interface are contained on the DASY6 I/O board, which is directly connected to the PC/104 bus of the CPU board.



The measurement server performs all real-time data evaluations of field measurements and surface detection, controls robot movements, and handles safety operations. The PC operating system cannot interfere with these time-critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port, which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Connection of devices from any other supplier could seriously damage the measurement server.

Data Acquisition Electronics

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

EX3DV4 E-Field Probes

Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

SAM Twin Phantom

The SAM Twin Phantom (shown in front of DASY6) is a fiberglass shell phantom with shell thickness 2 mm, except in the ear region where the thickness is increased to 6 mm. The phantom has three measurement areas: 1) Left Head, 2) Right Head, and 3) Flat Section. For larger devices, the use of the ELI-Phantom (shown behind DASY6) is required. For devices such as glasses with a wireless link, the Face Down Phantom is the most suitable (between the SAM Twin and ELI phantoms).

When the phantom is mounted inside allocated slot of the DASY6 platform, phantom reference points can be taught directly in the DASY5 V5.2 software. When the DASY6 platform is used to mount the


Phantom, some of the phantom teaching points cannot be reached by the robot in DASY5 V5.2. A special tool called P1a-P2aX-Former is provided to transform two of the three points, P1 and P2, to reachable locations. To use these new teaching points, a revised phantom configuration file is required.

In addition to our standard broadband liquids, the phantom can be used with the following tissue simulating liquids:

Sugar-water-based liquids can be left permanently in the phantom. Always cover the liquid when the system is not in use to prevent changes in liquid parameters due to water evaporation.

DGBE-based liquids should be used with care. As DGBE is a softener for most plastics, the liquid should be taken out of the phantom, and the phantom should be dried when the system is not in use (desirable at least once a week).

Do not use other organic solvents without previously testing the solvent resistivity of the phantom. Approximately 25 liters of liquid is required to fill the SAM Twin phantom.




ELI Phantom

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30MHz to 6 GHz. ELI is fully compatible with the latest draft of the standard IEC 62209-2 and the use of all known tissue simulating liquids. ELI has been optimized for performance and can be integrated into a SPEAG standard phantom table. A cover is provided to prevent evaporation of water and changes in liquid parameters. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points.

The phantom can be used with the following tissue simulating liquids:

- Sugar-water-based liquids can be left permanently in the phantom. Always cover the liquid when the system is not in use to prevent changes in liquid parameters due to water evaporation.
- DGBE-based liquids should be used with care. As DGBE is a softener for most plastics, the liquid should be taken out of the phantom, and the phantom should be dried when the system is not in use (desirable at least once a week).
- Do not use other organic solvents without previously testing the solvent resistivity of the phantom.

Approximately 25 liters of liquid is required to fill the ELI phantom.



Robots

The DASY6 system uses the high-precision industrial robots TX60L, TX90XL, and RX160L from Staubli SA (France). The TX robot family - the successor of the well-known RX robot family - continues to offer the features important for DASY6 applications:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The robots are controlled by the Staubli CS8c robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is provided

Calibration Frequency Points for EX3DV4 E-Field Probes SN: 7441 Calibrated: 2021/02/23

Calibration Frequency Point(MHz)	Frequency Range(MHz)		Conversion Factor		
	From	To	X	Y	Z
750 Head	650	850	10.28	10.28	10.28
900 Head	850	1000	9.80	9.80	9.80
1450 Head	1350	1550	8.61	8.61	8.61
1750 Head	1650	1850	8.39	8.39	8.39
1900 Head	1850	1950	8.02	8.02	8.02
2000 Head	1950	2100	8.07	8.07	8.07
2300 Head	2200	2400	7.92	7.92	7.92
2450 Head	2400	2550	7.63	7.63	7.63
2600 Head	2550	2700	7.33	7.33	7.33
3300 Head	3200	3400	7.21	7.21	7.21
3500 Head	3400	3600	6.96	6.96	6.96
3700 Head	3600	3800	6.65	6.65	6.65
3900 Head	3800	4000	6.66	6.66	6.66
4400 Head	4300	4500	6.45	6.45	6.45
4600 Head	4500	4700	6.30	6.30	6.30
4800 Head	4700	4900	6.24	6.24	6.24
4950 Head	4900	5050	5.95	5.95	5.95

Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm 2 step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm, with the side length of the 10g cube is 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x 7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEC 62209-1:2016

Recommended Tissue Dielectric Parameters for Head and Body

Table A.3 – Dielectric properties of the head tissue-equivalent liquid

Frequency MHz	Relative permittivity ϵ_r	Conductivity (σ) S/m
300	45,3	0,87
450	43,5	0,87
<i>750</i>	<i>41,9</i>	<i>0,89</i>
835	41,5	0,90
900	41,5	0,97
1 450	40,5	1,20
<i>1 500</i>	<i>40,4</i>	<i>1,23</i>
<i>1 640</i>	<i>40,2</i>	<i>1,31</i>
<i>1 750</i>	<i>40,1</i>	<i>1,37</i>
1 800	40,0	1,40
1 900	40,0	1,40
2 000	40,0	1,40
<i>2 100</i>	<i>39,8</i>	<i>1,49</i>
<i>2 300</i>	<i>39,5</i>	<i>1,67</i>
2 450	39,2	1,80
<i>2 600</i>	<i>39,0</i>	<i>1,96</i>
3 000	38,5	2,40
<i>3 500</i>	<i>37,9</i>	<i>2,91</i>
<i>4 000</i>	<i>37,4</i>	<i>3,43</i>
<i>4 500</i>	<i>36,8</i>	<i>3,94</i>
<i>5 000</i>	<i>36,2</i>	<i>4,45</i>
<i>5 200</i>	<i>36,0</i>	<i>4,66</i>
<i>5 400</i>	<i>35,8</i>	<i>4,86</i>
<i>5 600</i>	<i>35,5</i>	<i>5,07</i>
<i>5 800</i>	<i>35,3</i>	<i>5,27</i>
6 000	35,1	5,48

NOTE For convenience, permittivity and conductivity values at those frequencies which are not part of the original data provided by Drossos et al. [33] or the extension to 5 800 MHz are provided (i.e. the values shown *in italics*). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6 000 MHz that were linearly extrapolated from the values at 3 000 MHz and 5 800 MHz.


EQUIPMENT LIST AND CALIBRATION

Equipments List & Calibration Information

Equipment	Model	S/N	Calibration Date	Calibration Due Date
DASY5 Test Software	DASY52 52.10.2	N/A	NCR	NCR
DASY6 Measurement Server	DASY6 6.0.31	N/A	NCR	NCR
Data Acquisition Electronics	DAE4	1562	2021/01/19	2022/01/18
E-Field Probe	EX3DV4	7441	2021/02/23	2022/02/22
Mounting Device	MD4HHTV5	SD 000 H01 KA	NCR	NCR
SAM Twin Phantom	SAM-Twin V8.0	1962	NCR	NCR
Dipole, 750MHz	D750V3	1194	2020/01/13	2023/01/12
Dipole, 1900MHz	D1900V2	5d231	2020/01/14	2023/01/13
Dipole, 2300MHz	D2300V2	1103	2020/01/13	2023/01/12
Dipole, 2450MHz	D2450V2	751	2020/10/13	2023/10/12
Dipole, 2600MHz	D2600V2	1162	2019/10/2	2022/10/01
Simulated Tissue Liquid Head(500-9500MHz)	HBBL600-10000V6	180622-2	Each Time	
Network Analyzer	8753D	3410A08288	2020/07/31	2021/07/30
Dielectric Assessment Kit	DAK-3.5	1248	NCR	NCR
MXG Analog Signal Generator	N5181A	MY48180408	2020/07/31	2021/07/30
USB wideband power sensor	U2021XA	MY54250003	2020/07/31	2021/07/30
Power Amplifier	5S1G4	71377	NCR	NCR
Directional Coupler	4242-10	3307	NCR	NCR
Attenuator	6dB	773-6	NCR	NCR
Wireless communication tester	8960	MY48367501	2020/07/31	2021/07/30
WIDEBAND RADIO COMMUNICATION TESTER	CMW500	116218	2020/07/31	2021/07/30

SAR MEASUREMENT SYSTEM VERIFICATION

Liquid Verification



Liquid Verification Setup Block Diagram

Liquid Verification Results

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$	
750	Simulated Tissue Liquid Head	42.808	0.877	41.90	0.89	2.17	-1.46	± 5
824.2	Simulated Tissue Liquid Head	41.632	0.883	41.55	0.90	0.2	-1.89	± 5
826.4	Simulated Tissue Liquid Head	41.996	0.893	41.54	0.90	1.1	-0.78	± 5
829	Simulated Tissue Liquid Head	41.668	0.896	41.53	0.90	0.33	-0.44	± 5
836.5	Simulated Tissue Liquid Head	41.55	0.925	41.5	0.90	0.12	2.78	± 5
836.6	Simulated Tissue Liquid Head	42.321	0.929	41.5	0.90	1.98	3.22	± 5
844	Simulated Tissue Liquid Head	41.883	0.936	41.5	0.91	0.92	2.86	± 5
846.6	Simulated Tissue Liquid Head	41.457	0.937	41.5	0.91	-0.1	2.97	± 5
848.8	Simulated Tissue Liquid Head	41.363	0.953	41.5	0.91	-0.33	4.73	± 5

*Liquid Verification above was performed on 2021/05/10.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$	
1850.2	Simulated Tissue Liquid Head	39.392	1.386	40.0	1.40	-1.52	-1	± 5
1852.4	Simulated Tissue Liquid Head	39.462	1.382	40.0	1.40	-1.34	-1.29	± 5
1860	Simulated Tissue Liquid Head	40.052	1.39	40.0	1.40	0.13	-0.71	± 5
1880	Simulated Tissue Liquid Head	40.038	1.401	40.0	1.40	0.09	0.07	± 5
1900	Simulated Tissue Liquid Head	40.008	1.406	40.0	1.40	0.02	0.43	± 5
1907.6	Simulated Tissue Liquid Head	40.19	1.418	40.0	1.40	0.47	1.29	± 5
1909.8	Simulated Tissue Liquid Head	40.209	1.426	40.0	1.40	0.52	1.86	± 5

*Liquid Verification above was performed on 2021/05/12.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$	
2300	Simulated Tissue Liquid Head	39.69	1.658	39.50	1.67	0.48	-0.72	± 5
2310	Simulated Tissue Liquid Head	39.85	1.669	39.48	1.67	0.94	-0.06	± 5
2355	Simulated Tissue Liquid Head	39.45	1.663	39.39	1.71	0.15	-2.75	± 5

*Liquid Verification above was performed on 2021/05/19.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$	
2412	Simulated Tissue Liquid Head	38.822	1.812	39.28	1.77	-1.17	2.37	± 5
2442	Simulated Tissue Liquid Head	38.587	1.833	39.22	1.79	-1.61	2.4	± 5
2450	Simulated Tissue Liquid Head	38.582	1.853	39.20	1.80	-1.58	2.94	± 5
2472	Simulated Tissue Liquid Head	38.435	1.875	39.17	1.82	-1.88	3.02	± 5
2506	Simulated Tissue Liquid Head	38.238	1.891	39.13	1.86	-2.28	1.67	± 5
2510	Simulated Tissue Liquid Head	38.693	1.912	39.12	1.86	-1.09	2.8	± 5
2535	Simulated Tissue Liquid Head	37.938	1.939	39.09	1.89	-2.95	2.59	± 5

*Liquid Verification above was performed on 2021/05/13.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/ m)	ϵ_r	σ (S/ m)	$\Delta\epsilon_r$	$\Delta\sigma$	
2565	Simulated Tissue Liquid Head	38.021	1.958	39.05	1.92	-2.64	1.98	± 5
2605	Simulated Tissue Liquid Head	38.264	1.97	39.01	1.95	-1.91	1.03	± 5
2600	Simulated Tissue Liquid Head	38.38	1.978	39.00	1.96	-1.59	0.92	± 5
2655	Simulated Tissue Liquid Head	38.391	1.981	38.90	2.04	-1.31	-2.89	± 5

*Liquid Verification above was performed on 2021/05/11.


System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

The spacing distances in the **System Verification Setup Block Diagram** is given by the following:

- $s = 15 \text{ mm} \pm 0,2 \text{ mm}$ for $300 \text{ MHz} \leq f \leq 1\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $1\,000 \text{ MHz} < f \leq 3\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $3\,000 \text{ MHz} < f \leq 6\,000 \text{ MHz}$.

System Verification Setup Block Diagram



System Accuracy Check Results

Date	Frequency Band (MHz)	Liquid Type	Input Power (mW)	Measured SAR (W/kg)		Normalized to 1W (W/kg)	Target Value (W/Kg)	Delta (%)	Tolerance (%)
2021/05/10	750	Head	50	1g	0.418	8.36	8.55	-2.222	± 10
2021/05/12	1900	Head	25	1g	0.935	37.4	40.3	-7.196	± 10
2021/05/19	2300	Head	200	1g	8.58	42.9	47.1	-8.917	± 10
2021/05/13	2450	Head	25	1g	1.36	54.4	53.0	2.642	± 10
2021/05/11	2600	Head	25	1g	1.45	58.0	55.4	4.693	± 10

*The SAR values above are normalized to 1 Watt forward power.

SAR SYSTEM VALIDATION DATA

System Performance 750 MHz

DUT: Dipole 750MHz; Type: D750V3; Serial: 1194

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750$ MHz; $\sigma = 0.877$ S/m; $\epsilon_r = 42.808$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(10.28, 10.28, 10.28)
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 1/19/2021
- Phantom: SAM-Twin V8.0 P1aP2a; Type: QD 000 P41 AA ; Serial: 1962
- Measurement SW: DASY52, Version 52.10 (2);

Head 750MHz Pin=50mW/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.429 W/kg


Head 750MHz Pin=50mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.25 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.678 W/kg

SAR(1 g) = 0.418 W/kg; SAR(10 g) = 0.262 W/kg

Maximum value of SAR (measured) = 0.442 W/kg



0 dB = 0.442 W/kg = -3.55 dBW/kg

System Performance 1900 MHz Head**DUT: Dipole 1900MHz; Type: D1900V2; Serial: 5d231**


Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.406 \text{ S/m}$; $\epsilon_r = 40.008$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.02, 8.02, 8.02)
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 1/19/2021
- Phantom: SAM-Twin V8.0 P1aP2a; Type: QD 000 P41 AA ; Serial: 1962
- Measurement SW: DASY52, Version 52.10 (2);

Head 1900MHz Pin=25mW/Area Scan (81x121x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$ Maximum value of SAR (interpolated) = 1.08 W/kg **Head 1900MHz Pin=25mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 26.18 V/m ; Power Drift = -0.02 dB Peak SAR (extrapolated) = 1.66 W/kg **SAR(1 g) = 0.935 W/kg ; SAR(10 g) = 0.502 W/kg** Maximum value of SAR (measured) = 1.19 W/kg  $0 \text{ dB} = 1.19 \text{ W/kg} = 0.76 \text{ dBW/kg}$

System Performance 2300 MHz Head**DUT: Dipole 2300MHz; Type: D2300V2; Serial: 1103**

Communication System: UID 0, CW (0); Frequency: 2300 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2300$ MHz; $\sigma = 1.669$ S/m; $\epsilon_r = 39.85$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.92, 7.92, 7.92)
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 1/19/2021
- Phantom: SAM-Twin V8.0 P1aP2a; Type: QD 000 P41 AA ; Serial: 1962
- Measurement SW: DASY52, Version 52.10 (2);

Head 2300MHz Pin=200mW/Area Scan (81x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 9.33 W/kg


Head 2300MHz Pin=200mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 70.29 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 14.5 W/kg

SAR(1 g) = 8.58 W/kg; SAR(10 g) = 4.16 W/kg

Maximum value of SAR (measured) = 9.52 W/kg



0 dB = 9.52 W/kg = 9.79 dBW/kg

System Performance 2450 MHz Head**DUT: Dipole 2450MHz; Type: D2450V2; Serial: 751**

Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.853$ S/m; $\epsilon_r = 38.582$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.63, 7.63, 7.63)
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 1/19/2021
- Phantom: SAM-Twin V8.0 P1aP2a; Type: QD 000 P41 AA ; Serial: 1962
- Measurement SW: DASY52, Version 52.10 (2);

Head 2450MHz Pin=25mW/Area Scan (81x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.68 W/kg


Head 2450MHz Pin=25mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 28.09 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.15 W/kg

SAR(1 g) = 1.36 W/kg; SAR(10 g) = 0.641 W/kg

Maximum value of SAR (measured) = 1.53 W/kg



0 dB = 1.53 W/kg = 1.85 dBW/kg

System Performance 2600 MHz Head**DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1073**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.981$ S/m; $\epsilon_r = 38.391$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.33, 7.33, 7.33)
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 1/19/2021
- Phantom: SAM-Twin V8.0 P1aP2a; Type: QD 000 P41 AA ; Serial: 1962
- Measurement SW: DASY52, Version 52.10 (2);

Head 2600MHz Pin=25mW/Area Scan (81x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.64 W/kg


Head 2600MHz Pin=25mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 29.65 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 2.59 W/kg

SAR(1 g) = 1.45 W/kg; SAR(10 g) = 0.686 W/kg

Maximum value of SAR (measured) = 1.77 W/kg





0 dB = 1.77 W/kg = 2.48 dBW/kg

EUT TEST STRATEGY AND METHODOLOGY

Test Positions for Device Operating Next to a Person's Ear

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper ¼ of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point”. The “test device reference point” should be located at the same level as the center of the earpiece region. The “vertical centerline” should bisect the front surface of the handset at its top and bottom edges. A “ear reference point” is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the “phantom reference plane” defined by the three lines joining the center of each “ear reference point” (left and right) and the tip of the mouth.

A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the “N-F” line defined along the base of the ear spacer that contains the “ear reference point”. For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The “test device reference point” is aligned to the “ear reference point” on the head phantom and the “vertical centerline” is aligned to the “phantom reference plane”. This is called the “initial ear position”. While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:



Cheek/Touch Position

The device is brought toward the mouth of the head phantom by pivoting against the “ear reference point” or along the “N-F” line for the SCC-34/SC-2 head phantom.


This test position is established:

When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.

(or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

Cheek /Touch Position




Ear/Tilt Position

With the handset aligned in the “Cheek/Touch Position”:

1) If the earpiece of the handset is not in full contact with the phantom’s ear spacer (in the “Cheek/Touch position”) and the peak SAR location for the “Cheek/Touch” position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the “initial ear position” by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.

2) (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both “ear reference points” (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the “test device reference point” until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15 80°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both “ear reference points” until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.

If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the “Cheek/Touch” and “Ear/Tilt” positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tilt/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s). If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.

Ear /Tilt 15° Position**Test positions for body-worn and other configurations**

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 – Test positions for body-worn devices

Test Distance for SAR Evaluation

For this case the EUT(Equipment Under Test) is set 10mm away from the phantom, the test distance is 10mm.

SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or radiating structures of the EUT, the horizontal grid spacing was 15 mm x 15 mm, and the SAR distribution was determined by integrated grid of 1.5mm x 1.5mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

- 1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
- 2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.

All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.


CONDUCTED OUTPUT POWER MEASUREMENT

Provision Applicable

The measured peak output power should be greater and within 5% than EMI measurement.

Test Procedure

The RF output of the transmitter was connected to the input of the EMI Test Receiver through Connector.



GSM/WCDMA/LTE

Radio Configuration

The power measurement was configured by the Wireless Communication Test Set.

GSM/GPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + GPRS or GSM + EGSM

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

> Slot configuration > Uplink/Gamma

> 33 dBm for GPRS 850

> 30 dBm for GPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desired test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel

Hopping > Off

Main Timeslot > 3

Network Coding Scheme > CS4 (GPRS)

Bit Stream > 2E9-1 PSR Bit Stream

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal on to turn on the signal and change settings

WCDMA Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	$\beta_d(\text{SF})$	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specifi c Setting s	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{cc}	209/225	12/15	30/15	2/15	5/15
	β_c / β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs} = \beta_{hs} / \beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18		E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27

FDD-LTE

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3

Modulation	Channel bandwidth / Transmission bandwidth (N_{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (subclause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	N/A
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
NS_05	6.6.3.3.1	1	10, 15, 20	Table 6.2.4-4	
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	≥ 50	≤ 1
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 5.6-1	N/A
NS_08	6.6.3.3.3	19	10, 15	Table 6.2.4-2	
NS_09	6.6.3.3.4	21	10, 15	> 44	≤ 3
				> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	
NS_11	6.6.2.2.1	23	1.4, 3, 5, 10, 15, 20	Table 6.2.4-5	
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table 6.2.4-6	
NS_13	6.6.3.3.6	26	5	Table 6.2.4-7	
NS_14	6.6.3.3.7	26	10, 15	Table 6.2.4-8	
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	Table 6.2.4-9 Table 6.2.4-10	
NS_16	6.6.3.3.9	27	3, 5, 10	Table 6.2.4-11, Table 6.2.4-12, Table 6.2.4-13	
NS_17	6.6.3.3.10	28	5, 10	Table 5.6-1	N/A
NS_18	6.6.3.3.11	28	5	≥ 2	≤ 1
			10, 15, 20	≥ 1	≤ 4
NS_19	6.6.3.3.12	44	10, 15, 20	Table 6.2.4-14	
NS_20	6.2.2 6.6.2.2.1 6.6.3.2	23	5, 10, 15, 20	Table 6.2.4-15	
...					
NS_32	-	-	-	-	-

Maximum Target Output Power

Max Target Power(dBm)			
Mode/Band	Channel		
	Low	Middle	High
GSM 850	32.6	32.6	32.6
GPRS 1 TX Slot	32.5	32.5	32.5
GPRS 2 TX Slot	31.5	31.5	31.5
GPRS 3 TX Slot	30.0	30.0	30.0
GPRS 4 TX Slot	28.5	28.5	28.5
EGPRS 1 TX Slot	30.0	30.0	30.0
EGPRS 2 TX Slot	29.0	29.0	29.0
EGPRS 3 TX Slot	27.0	27.0	27.0
EGPRS 4 TX Slot	26.0	26.0	26.0
PCS 1900	30.0	30.0	30.0
GPRS 1 TX Slot	26.5	26.5	26.5
GPRS 2 TX Slot	25.5	25.5	25.5
GPRS 3 TX Slot	23.0	23.0	23.0
GPRS 4 TX Slot	21.5	21.5	21.5
EGPRS 1 TX Slot	26.5	26.5	26.5
EGPRS 2 TX Slot	25.0	25.0	25.0
EGPRS 3 TX Slot	23.0	23.0	23.0
EGPRS 4 TX Slot	22.0	22.0	22.0
WCDMA Band 2	23.0	23.0	23.0
WCDMA Band 5	23.0	23.0	23.0
LTE Band 2	23.5	23.5	23.5
LTE Band 5	24.0	24.0	24.0
LTE Band 7	24.0	24.0	24.0
LTE Band 38	23.5	23.5	23.5
LTE Band 40Lower	23.0	23.0	23.0
LTE Band 40Upper	23.0	23.0	23.0
LTE Band 41	24.0	24.0	24.0
WLAN 2.4G	15.5	15.5	15.5
Bluetooth BDR/EDR	6.5	6.5	6.5
Bluetooth BLE_1M	-1.0	-1.0	-1.0
Bluetooth BLE_2M	-1.0	-1.0	-1.0

Max Target Power(dBm)			
Mode/Band	Channel		
	Low	Middle	High
WLAN 5.2G(802.11a)	11.5	11.5	11.5
WLAN 5.2G(802.11n20)	11.5	11.5	11.5
WLAN 5.2G(802.11n40)	11	/	11
WLAN 5.2G(802.11ac20)	11	11	11
WLAN 5.2G(802.11ac40)	11.5	/	11.5
WLAN 5.2G(802.11ac80)	/	11.5	/
WLAN 5.8G(802.11a)	12.2	12.2	12.2
WLAN 5.8G(802.11n20)	12.2	12.2	12.2
WLAN 5.8G(802.11n40)	12	/	12
WLAN 5.8G(802.11ac20)	12	12	12
WLAN 5.8G(802.11ac40)	12	/	12
WLAN 5.8G(802.11ac80)	/	12	/

Test Results:**GSM:**

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
GSM 850	128	824.2	32.5
	190	836.6	32.4
	251	848.8	32.4
PCS 1900	512	1850.2	29.8
	661	1880	29.6
	810	1909.8	29.4

GPRS:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM 850	128	824.2	32.39	31.43	29.56	28.25
	190	836.6	32.26	31.12	29.15	27.84
	251	848.8	32.42	31.44	29.27	28.12
PCS 1900	512	1850.2	26.43	25.05	22.77	21.26
	661	1880	26.28	24.90	22.56	21.09
	810	1909.8	25.97	24.40	22.35	20.78

EGPRS:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM 850	128	824.2	29.73	28.66	26.71	25.49
	190	836.6	29.59	28.55	26.40	25.28
	251	848.8	29.47	28.37	26.33	25.06
PCS 1900	512	1850.2	25.47	24.23	22.05	20.86
	661	1880	25.54	24.32	22.26	20.91
	810	1909.8	26.24	24.84	22.91	21.69

For SAR, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.25 dB	-3 dB
Crest Factor	8	4	2.66	2

The time based average power for GPRS

Band	Channel No.	Frequency (MHz)	Time based average Power (dBm)			
			1 slot	2 slot	3 slots	4 slots
GSM 850	128	824.2	23.39	25.43	25.31	25.25
	190	836.6	23.26	25.12	24.90	24.84
	251	848.8	23.42	25.44	25.02	25.12
PCS 1900	512	1850.2	17.43	19.05	18.52	18.26
	661	1880	17.28	18.70	18.31	18.09
	810	1909.8	16.97	18.40	18.10	17.78

The time based average power for EGPRS

Band	Channel No.	Frequency (MHz)	Time based average Power (dBm)			
			1 slot	2 slot	3 slots	4 slots
GSM 850	128	824.2	20.73	22.66	22.46	22.49
	190	836.6	20.59	22.55	22.15	22.28
	251	848.8	20.47	22.37	22.08	22.06
PCS 1900	512	1850.2	16.47	18.23	17.80	17.86
	661	1880	16.54	18.32	18.01	17.91
	810	1909.8	17.24	18.84	18.66	18.69

Note:

1. Rohde & Schwarz Radio Communication Tester (CMU200) was used for the measurement of GSM peak and average output power for active timeslots.
2. For GSM voice, 1 timeslot has been activated with power level 5 (850 MHz band) and 0 (1900 MHz band).
3. For GPRS, 1, 2, 3 and 4 timeslots has been activated separately with power level 3(850 MHz band) and 3(1900 MHz band).

WCDMA Band 2:

Test Condition	Test Mode	3GPP Sub Test	Averaged Mean Power (dBm)		
			Low Frequency	Mid Frequency	High Frequency
Normal	RMC12.2k		22.89	22.93	22.83
	HSDPA	1	22.22	22.08	21.94
		2	22.39	22.16	22.07
		3	22.33	22.27	22.08
		4	22.38	22.28	22.06
	HSUPA	1	21.96	21.66	21.59
		2	21.97	21.82	21.72
		3	21.98	21.90	21.84
		4	22.14	21.81	21.85
		5	22.15	21.87	21.82
	HSPA+	1	22.20	22.08	21.90

WCDMA Band 5:

Test Condition	Test Mode	3GPP Sub Test	Averaged Mean Power (dBm)		
			Low Frequency	Mid Frequency	High Frequency
Normal	RMC12.2k		21.70	21.97	22.80
	HSDPA	1	20.79	21.48	21.20
		2	20.89	21.55	21.31
		3	21.03	21.49	21.40
		4	20.98	21.61	21.49
	HSUPA	1	20.22	20.79	20.64
		2	20.29	20.97	20.73
		3	20.28	20.97	20.73
		4	20.39	20.95	20.77
		5	20.43	21.12	20.81
	HSPA+	1	20.45	21.11	20.89

Note:

1. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model 1.
2. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/HSPA+ when the maximum average output of each RF channel is less than ¼ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.

LTE Band 2:

BW (MHz)	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1850.7MHz	1880MHz	1909.3MHz
1.4	QPSK	RB Size=1, RB Offset=0	0	0	22.80	22.99	22.75
		RB Size=1, RB Offset=3	0	0	22.85	22.81	22.56
		RB Size=1, RB Offset=5	0	0	22.72	22.80	22.47
		RB Size=3, RB Offset=0	1	1	22.29	22.63	22.36
		RB Size=3, RB Offset=3	1	1	22.38	22.25	22.28
		RB Size=6, RB Offset=0	1	1	22.27	22.24	21.88
	16QAM	RB Size=1, RB Offset=0	1	1	22.27	22.46	22.37
		RB Size=1, RB Offset=3	1	1	22.45	22.18	22.28
		RB Size=1, RB Offset=5	1	1	22.10	22.11	21.91
		RB Size=3, RB Offset=0	2	2	22.19	22.39	22.54
		RB Size=3, RB Offset=3	2	2	21.85	22.12	22.14
		RB Size=6, RB Offset=0	2	2	21.89	22.39	22.17
BW (MHz)	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1851.5MHz	1880MHz	1908.5MHz
3	QPSK	RB Size=1, RB Offset=0	0	0	22.71	22.98	23.18
		RB Size=1, RB Offset=8	0	0	22.62	22.49	22.71
		RB Size=1, RB Offset=14	0	0	22.69	22.56	22.41
		RB Size=6, RB Offset=0	1	1	22.43	22.21	22.36
		RB Size=6, RB Offset=9	1	1	22.54	22.38	21.98
		RB Size=15, RB Offset=0	1	1	22.14	21.92	22.18
	16QAM	RB Size=1, RB Offset=0	1	1	22.45	22.27	22.36
		RB Size=1, RB Offset=8	1	1	22.31	22.42	22.45
		RB Size=1, RB Offset=14	1	1	21.76	21.70	22.13
		RB Size=6, RB Offset=0	2	2	22.36	22.07	22.45
		RB Size=6, RB Offset=9	2	2	21.83	21.65	22.15
		RB Size=15, RB Offset=0	2	2	22.26	21.89	22.29

BW (MHz)	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M PR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1852.5MHz	1880MHz	1907.5MHz
5	QPSK	RB Size=1, RB Offset=0	0	0	22.59	22.91	22.89
		RB Size=1, RB Offset=13	0	0	22.54	22.90	22.61
		RB Size=1, RB Offset=24	0	0	22.60	22.54	22.52
		RB Size=15, RB Offset=0	1	1	22.48	22.47	22.31
		RB Size=15, RB Offset=10	1	1	22.40	22.33	22.35
		RB Size=25, RB Offset=0	1	1	22.08	22.28	22.31
	16QAM	RB Size=1, RB Offset=0	1	1	22.19	22.29	22.34
		RB Size=1, RB Offset=13	1	1	22.04	22.18	22.22
		RB Size=1, RB Offset=24	1	1	21.92	21.71	22.08
		RB Size=15, RB Offset=0	2	2	21.96	22.22	22.12
		RB Size=15, RB Offset=10	2	2	21.70	21.88	21.69
		RB Size=25, RB Offset=0	2	2	22.21	21.93	22.01
BW (MHz)	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M PR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1855MHz	1880MHz	1905MHz
10	QPSK	RB Size=1, RB Offset=0	0	0	22.53	22.87	22.75
		RB Size=1, RB Offset=25	0	0	22.63	22.67	22.61
		RB Size=1, RB Offset=49	0	0	22.35	22.55	22.27
		RB Size=25, RB Offset=0	1	1	22.34	22.28	21.96
		RB Size=25, RB Offset=25	1	1	22.20	21.97	22.11
		RB Size=50, RB Offset=0	1	1	21.92	22.04	21.82
	16QAM	RB Size=1, RB Offset=0	1	1	22.34	22.18	21.97
		RB Size=1, RB Offset=25	1	1	22.20	22.26	21.98
		RB Size=1, RB Offset=49	1	1	21.52	21.83	21.91
		RB Size=25, RB Offset=0	2	2	22.14	21.96	22.19
		RB Size=25, RB Offset=25	2	2	21.92	21.39	21.59
		RB Size=50, RB Offset=0	2	2	22.15	22.14	21.95

BW (MHz)	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M PR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1857.5MHz	1880MHz	1902.5MHz
15	QPSK	RB Size=1, RB Offset=0	0	0	22.61	22.95	22.99
		RB Size=1, RB Offset=38	0	0	22.80	22.36	22.31
		RB Size=1, RB Offset=74	0	0	22.37	22.64	22.67
		RB Size=36, RB Offset=0	1	1	22.20	22.06	22.02
		RB Size=36, RB Offset=39	1	1	22.02	22.15	22.42
		RB Size=75, RB Offset=0	1	1	22.17	22.04	21.98
	16QAM	RB Size=1, RB Offset=0	1	1	22.22	22.21	22.27
		RB Size=1, RB Offset=38	1	1	22.08	22.24	22.33
		RB Size=1, RB Offset=74	1	1	21.75	21.71	21.80
		RB Size=36, RB Offset=0	2	2	21.97	22.19	21.95
		RB Size=36, RB Offset=39	2	2	21.73	21.87	21.80
		RB Size=75, RB Offset=0	2	2	21.79	21.78	21.90
BW (MHz)	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M PR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1860MHz	1880MHz	1900MHz
20	QPSK	RB Size=1, RB Offset=0	0	0	22.31	22.81	22.46
		RB Size=1, RB Offset=50	0	0	22.67	22.70	22.33
		RB Size=1, RB Offset=99	0	0	22.22	22.41	22.22
		RB Size=50, RB Offset=0	1	1	22.16	21.90	22.28
		RB Size=50, RB Offset=50	1	1	21.92	22.05	22.25
		RB Size=100, RB Offset=0	1	1	21.82	21.61	21.71
	16QAM	RB Size=1, RB Offset=0	1	1	22.12	21.86	21.85
		RB Size=1, RB Offset=50	1	1	22.17	21.91	22.05
		RB Size=1, RB Offset=99	1	1	21.59	21.76	21.78
		RB Size=50, RB Offset=0	2	2	22.08	21.96	21.74
		RB Size=50, RB Offset=50	2	2	21.52	21.83	21.33
		RB Size=100, RB Offset=0	2	2	21.83	21.61	21.94

LTE Band 5:

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					824.7MHz	836.5MHz	848.3MHz
1.4	QPSK	RB Size=1, RB Offset=0	0	0	23.48	23.47	23.72
		RB Size=1, RB Offset=3	0	0	23.39	23.42	23.63
		RB Size=1, RB Offset=5	0	0	23.51	23.18	23.61
		RB Size=3, RB Offset=0	1	1	23.20	22.97	23.33
		RB Size=3, RB Offset=3	1	1	22.89	23.02	23.04
		RB Size=6, RB Offset=0	1	1	22.84	22.72	23.00
	16QAM	RB Size=1, RB Offset=0	1	1	23.38	23.11	23.28
		RB Size=1, RB Offset=3	1	1	23.29	22.76	22.99
		RB Size=1, RB Offset=5	1	1	22.89	22.96	22.63
		RB Size=3, RB Offset=0	2	2	22.90	22.79	22.82
		RB Size=3, RB Offset=3	2	2	22.83	22.84	22.67
		RB Size=6, RB Offset=0	2	2	22.87	23.22	22.94
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					825.5MHz	836.5MHz	847.5MHz
3	QPSK	RB Size=1, RB Offset=0	0	0	23.59	23.78	23.71
		RB Size=1, RB Offset=8	0	0	23.78	23.52	23.69
		RB Size=1, RB Offset=14	0	0	23.27	23.48	23.55
		RB Size=6, RB Offset=0	1	1	23.31	23.16	23.32
		RB Size=6, RB Offset=9	1	1	23.42	23.11	23.39
		RB Size=15, RB Offset=0	1	1	23.23	23.07	23.14
	16QAM	RB Size=1, RB Offset=0	1	1	23.01	23.31	23.33
		RB Size=1, RB Offset=8	1	1	23.34	23.13	23.16
		RB Size=1, RB Offset=14	1	1	22.93	22.64	22.63
		RB Size=6, RB Offset=0	2	2	23.22	23.23	23.23
		RB Size=6, RB Offset=9	2	2	22.93	23.02	23.02
		RB Size=15, RB Offset=0	2	2	23.15	22.88	22.83

BW (MHz)	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M PR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					826.5MHz	836.5MHz	846.5MHz
5	QPSK	RB Size=1, RB Offset=0	0	0	23.54	23.67	23.81
		RB Size=1, RB Offset=13	0	0	23.83	23.41	23.48
		RB Size=1, RB Offset=24	0	0	23.35	23.60	23.73
		RB Size=15, RB Offset=0	1	1	23.01	23.27	23.35
		RB Size=15, RB Offset=10	1	1	23.25	23.19	22.91
		RB Size=25, RB Offset=0	1	1	23.09	23.05	22.93
	16QAM	RB Size=1, RB Offset=0	1	1	23.20	23.04	23.00
		RB Size=1, RB Offset=13	1	1	22.96	23.22	23.24
		RB Size=1, RB Offset=24	1	1	22.93	22.92	22.94
		RB Size=15, RB Offset=0	2	2	23.08	23.24	23.05
		RB Size=15, RB Offset=10	2	2	22.67	22.69	22.89
		RB Size=25, RB Offset=0	2	2	23.09	23.06	22.89
BW (MHz)	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M PR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					829MHz	836.5MHz	844MHz
10	QPSK	RB Size=1, RB Offset=0	0	0	23.37	23.87	23.88
		RB Size=1, RB Offset=25	0	0	23.54	23.62	23.27
		RB Size=1, RB Offset=49	0	0	23.32	23.39	23.55
		RB Size=25, RB Offset=0	1	1	23.02	23.16	22.81
		RB Size=25, RB Offset=25	1	1	22.90	23.29	22.86
		RB Size=50, RB Offset=0	1	1	22.67	23.00	22.72
	16QAM	RB Size=1, RB Offset=0	1	1	23.05	22.86	22.84
		RB Size=1, RB Offset=25	1	1	23.04	23.11	23.14
		RB Size=1, RB Offset=49	1	1	22.66	22.60	22.71
		RB Size=25, RB Offset=0	2	2	22.78	22.93	23.14
		RB Size=25, RB Offset=25	2	2	22.48	22.84	22.70
		RB Size=50, RB Offset=0	2	2	22.86	22.88	22.71

LTE Band 7:

BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2502.5MHz	2535MHz	2567.5MHz
5M	QPSK	RB Size=1, RB Offset=0	0	0	23.59	23.65	23.68
		RB Size=1, RB Offset=13	0	0	23.59	23.69	23.76
		RB Size=1, RB Offset=24	0	0	23.36	23.77	23.39
		RB Size=15, RB Offset=0	1	1	23.13	23.32	23.48
		RB Size=15, RB Offset=10	1	1	23.18	23.37	23.23
		RB Size=25, RB Offset=0	1	1	22.93	22.82	22.82
	16QAM	RB Size=1, RB Offset=0	1	1	23.17	23.41	23.04
		RB Size=1, RB Offset=13	1	1	23.21	22.97	22.91
		RB Size=1, RB Offset=24	1	1	22.60	22.74	22.93
		RB Size=15, RB Offset=0	2	2	23.00	23.30	22.89
		RB Size=15, RB Offset=10	2	2	22.82	23.01	22.87
		RB Size=25, RB Offset=0	2	2	22.96	23.13	23.31
BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2505MHz	2535MHz	2565MHz
10M	QPSK	RB Size=1, RB Offset=0	0	0	23.32	23.45	23.82
		RB Size=1, RB Offset=25	0	0	23.60	23.24	23.40
		RB Size=1, RB Offset=49	0	0	23.35	23.41	23.31
		RB Size=25, RB Offset=0	1	1	23.28	23.19	22.80
		RB Size=25, RB Offset=25	1	1	23.22	22.96	22.91
		RB Size=50, RB Offset=0	1	1	22.99	23.06	22.71
	16QAM	RB Size=1, RB Offset=0	1	1	22.92	23.10	23.08
		RB Size=1, RB Offset=25	1	1	22.76	22.78	22.78
		RB Size=1, RB Offset=49	1	1	22.55	22.34	22.63
		RB Size=25, RB Offset=0	2	2	22.77	23.01	23.09
		RB Size=25, RB Offset=25	2	2	22.73	22.75	22.66
		RB Size=50, RB Offset=0	2	2	23.07	22.76	22.78

BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2507.5MHz	2535MHz	2562.5MHz
15M	QPSK	RB Size=1, RB Offset=0	0	0	23.35	23.91	23.39
		RB Size=1, RB Offset=38	0	0	23.63	23.44	23.23
		RB Size=1, RB Offset=74	0	0	23.31	23.27	23.19
		RB Size=36, RB Offset=0	1	1	23.07	23.02	23.10
		RB Size=36, RB Offset=39	1	1	23.14	23.10	22.88
		RB Size=75, RB Offset=0	1	1	22.74	22.96	23.14
	16QAM	RB Size=1, RB Offset=0	1	1	23.12	22.87	23.15
		RB Size=1, RB Offset=38	1	1	22.84	23.06	23.08
		RB Size=1, RB Offset=74	1	1	22.40	22.95	22.68
		RB Size=36, RB Offset=0	2	2	22.88	22.75	22.93
		RB Size=36, RB Offset=39	2	2	22.77	22.59	22.92
		RB Size=75, RB Offset=0	2	2	22.87	23.05	22.95
BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2510MHz	2535MHz	2560MHz
20M	QPSK	RB Size=1, RB Offset=0	0	0	23.33	23.76	23.57
		RB Size=1, RB Offset=50	0	0	23.59	23.35	23.46
		RB Size=1, RB Offset=99	0	0	23.32	23.07	23.27
		RB Size=50, RB Offset=0	1	1	23.20	22.93	22.86
		RB Size=50, RB Offset=50	1	1	23.01	22.71	23.13
		RB Size=100, RB Offset=0	1	1	22.68	22.94	22.59
	16QAM	RB Size=1, RB Offset=0	1	1	22.84	22.79	22.99
		RB Size=1, RB Offset=50	1	1	23.04	22.65	22.75
		RB Size=1, RB Offset=99	1	1	22.75	22.58	22.78
		RB Size=50, RB Offset=0	2	2	23.21	22.80	22.95
		RB Size=50, RB Offset=50	2	2	22.55	22.55	22.41
		RB Size=100, RB Offset=0	2	2	22.92	22.92	23.08

LTE Band 38:

BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2572.5MHz	2595MHz	2617.5MHz
5M	QPSK	RB Size=1, RB Offset=0	0	0	22.71	23.03	22.94
		RB Size=1, RB Offset=12	0	0	22.86	22.93	23.01
		RB Size=1, RB Offset=24	0	0	22.79	22.87	22.74
		RB Size=12, RB Offset=0	1	1	22.53	22.27	22.61
		RB Size=12, RB Offset=6	1	1	22.30	22.59	22.14
		RB Size=12, RB Offset=11	1	1	22.43	22.49	22.23
		RB Size=25, RB Offset=0	1	1	22.50	22.60	22.54
	16QAM	RB Size=1, RB Offset=0	1	1	22.22	22.32	22.28
		RB Size=1, RB Offset=12	1	1	21.97	21.92	21.98
		RB Size=1, RB Offset=24	1	1	22.47	22.11	22.40
		RB Size=12, RB Offset=0	2	2	21.87	22.06	22.25
		RB Size=12, RB Offset=6	2	2	22.21	21.95	22.23
		RB Size=12, RB Offset=11	2	2	22.19	22.34	22.52
		RB Size=25, RB Offset=0	2	2	22.66	22.85	22.85
BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2575MHz	2595MHz	2615MHz
10M	QPSK	RB Size=1, RB Offset=0	0	0	22.48	22.75	22.94
		RB Size=1, RB Offset=24	0	0	22.72	22.75	22.63
		RB Size=1, RB Offset=49	0	0	22.64	22.44	22.31
		RB Size=25, RB Offset=0	1	1	22.35	22.43	22.16
		RB Size=25, RB Offset=12	1	1	22.08	22.13	22.22
		RB Size=25, RB Offset=24	1	1	21.81	22.09	21.96
		RB Size=50, RB Offset=0	1	1	22.35	22.08	22.39
	16QAM	RB Size=1, RB Offset=0	1	1	22.12	22.19	22.19
		RB Size=1, RB Offset=24	1	1	21.85	21.96	21.87
		RB Size=1, RB Offset=49	1	1	21.94	22.12	21.95
		RB Size=25, RB Offset=0	2	2	21.99	21.89	21.77
		RB Size=25, RB Offset=12	2	2	22.20	21.92	22.19
		RB Size=25, RB Offset=24	2	2	22.39	22.13	22.48
		RB Size=50, RB Offset=0	2	2	22.47	22.49	22.72

BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2577.5MHz	2595MHz	2612.5MHz
15M	QPSK	RB Size=1, RB Offset=0	0	0	22.35	22.71	22.50
		RB Size=1, RB Offset=37	0	0	22.24	22.46	22.36
		RB Size=1, RB Offset=74	0	0	22.31	22.36	22.36
		RB Size=36, RB Offset=0	1	1	22.24	22.22	21.91
		RB Size=36, RB Offset=18	1	1	22.22	22.03	22.24
		RB Size=36, RB Offset=37	1	1	21.91	21.76	22.02
		RB Size=75, RB Offset=0	1	1	22.11	21.97	22.25
	16QAM	RB Size=1, RB Offset=0	1	1	22.13	22.11	21.83
		RB Size=1, RB Offset=37	1	1	21.54	21.75	21.98
		RB Size=1, RB Offset=74	1	1	22.13	21.98	21.71
		RB Size=36, RB Offset=0	2	2	21.68	21.53	21.63
		RB Size=36, RB Offset=18	2	2	21.96	21.96	21.68
		RB Size=36, RB Offset=37	2	2	22.14	22.24	22.09
		RB Size=75, RB Offset=0	2	2	22.32	22.49	22.26
BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2580MHz	2535MHz	2610MHz
20M	QPSK	RB Size=1, RB Offset=0	0	0	22.37	22.88	22.47
		RB Size=1, RB Offset=49	0	0	22.52	22.54	22.43
		RB Size=1, RB Offset=99	0	0	22.44	22.43	22.30
		RB Size=50, RB Offset=0	1	1	22.17	22.11	22.28
		RB Size=50, RB Offset=24	1	1	22.21	21.93	22.06
		RB Size=50, RB Offset=49	1	1	21.94	21.92	21.60
		RB Size=100, RB Offset=0	1	1	21.89	21.87	22.18
	16QAM	RB Size=1, RB Offset=0	1	1	21.92	21.74	22.13
		RB Size=1, RB Offset=49	1	1	21.54	21.61	21.51
		RB Size=1, RB Offset=99	1	1	21.74	22.02	22.15
		RB Size=50, RB Offset=0	2	2	21.65	21.51	21.68
		RB Size=50, RB Offset=24	2	2	21.84	22.06	21.80
		RB Size=50, RB Offset=49	2	2	22.15	22.12	21.97
		RB Size=100, RB Offset=0	2	2	22.66	22.28	22.27

LTE Band 40Lower:

BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2307.5MHz	2310MHz	2312.5MHz
5M	QPSK	RB Size=1, RB Offset=0	0	0	22.29	22.57	22.55
		RB Size=1, RB Offset=13	0	0	22.58	22.39	22.48
		RB Size=1, RB Offset=24	0	0	22.45	22.29	22.33
		RB Size=15, RB Offset=0	1	1	21.96	22.08	21.93
		RB Size=15, RB Offset=10	1	1	21.97	21.79	21.87
		RB Size=25, RB Offset=0	1	1	21.51	22.05	21.85
	16QAM	RB Size=1, RB Offset=0	1	1	21.87	21.80	21.80
		RB Size=1, RB Offset=13	1	1	21.99	22.04	22.16
		RB Size=1, RB Offset=24	1	1	21.86	21.52	21.59
		RB Size=15, RB Offset=0	2	2	21.93	21.98	22.00
		RB Size=15, RB Offset=10	2	2	21.79	21.76	21.51
		RB Size=25, RB Offset=0	2	2	21.63	21.77	21.73
BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
						2310MHz	
10M	QPSK	RB Size=1, RB Offset=0	0	0	/	22.37	/
		RB Size=1, RB Offset=25	0	0	/	22.21	/
		RB Size=1, RB Offset=49	0	0	/	21.97	/
		RB Size=25, RB Offset=0	1	1	/	21.72	/
		RB Size=25, RB Offset=25	1	1	/	21.92	/
		RB Size=50, RB Offset=0	1	1	/	21.45	/
	16QAM	RB Size=1, RB Offset=0	1	1	/	21.61	/
		RB Size=1, RB Offset=25	1	1	/	21.52	/
		RB Size=1, RB Offset=49	1	1	/	21.45	/
		RB Size=25, RB Offset=0	2	2	/	21.80	/
		RB Size=25, RB Offset=25	2	2	/	21.27	/
		RB Size=50, RB Offset=0	2	2	/	21.75	/

LTE Band 40Upper:

BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2352.5MHz	2355MHz	2357.5MHz
5M	QPSK	RB Size=1, RB Offset=0	0	0	22.08	22.57	22.11
		RB Size=1, RB Offset=13	0	0	22.33	22.34	22.39
		RB Size=1, RB Offset=24	0	0	22.10	21.99	22.14
		RB Size=15, RB Offset=0	1	1	21.63	21.80	21.68
		RB Size=15, RB Offset=10	1	1	21.95	21.78	21.48
		RB Size=25, RB Offset=0	1	1	21.81	21.47	21.61
	16QAM	RB Size=1, RB Offset=0	1	1	21.62	21.68	21.86
		RB Size=1, RB Offset=13	1	1	21.97	21.97	21.61
		RB Size=1, RB Offset=24	1	1	21.40	21.27	21.61
		RB Size=15, RB Offset=0	2	2	21.59	21.73	21.76
		RB Size=15, RB Offset=10	2	2	21.57	21.41	21.42
		RB Size=25, RB Offset=0	2	2	21.53	21.79	21.69
BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
						2355MHz	
10M	QPSK	RB Size=1, RB Offset=0	0	0	/	22.24	/
		RB Size=1, RB Offset=25	0	0	/	21.97	/
		RB Size=1, RB Offset=49	0	0	/	21.90	/
		RB Size=25, RB Offset=0	1	1	/	21.91	/
		RB Size=25, RB Offset=25	1	1	/	21.95	/
		RB Size=50, RB Offset=0	1	1	/	21.57	/
	16QAM	RB Size=1, RB Offset=0	1	1	/	21.93	/
		RB Size=1, RB Offset=25	1	1	/	21.48	/
		RB Size=1, RB Offset=49	1	1	/	21.27	/
		RB Size=25, RB Offset=0	2	2	/	21.72	/
		RB Size=25, RB Offset=25	2	2	/	21.60	/
		RB Size=50, RB Offset=0	2	2	/	21.36	/

LTE Band 41:

BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2537.5MHz	2595MHz	2652.5MHz
5M	QPSK	RB Size=1, RB Offset=0	0	0	23.50	23.62	23.85
		RB Size=1, RB Offset=12	0	0	23.42	23.53	23.66
		RB Size=1, RB Offset=24	0	0	23.37	23.28	23.39
		RB Size=12, RB Offset=0	1	1	23.11	23.36	23.10
		RB Size=12, RB Offset=6	1	1	23.02	23.08	23.17
		RB Size=12, RB Offset=11	1	1	22.76	22.66	22.79
		RB Size=25, RB Offset=0	1	1	22.96	23.42	23.04
	16QAM	RB Size=1, RB Offset=0	1	1	23.23	23.31	23.18
		RB Size=1, RB Offset=12	1	1	22.81	22.88	22.50
		RB Size=1, RB Offset=24	1	1	22.87	23.08	22.92
		RB Size=12, RB Offset=0	2	2	23.00	22.47	22.82
		RB Size=12, RB Offset=6	2	2	22.78	22.70	23.14
		RB Size=12, RB Offset=11	2	2	23.02	22.67	23.10
		RB Size=25, RB Offset=0	2	2	23.28	22.93	23.33
BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2540MHz	2595MHz	2650MHz
10M	QPSK	RB Size=1, RB Offset=0	0	0	23.45	23.76	23.89
		RB Size=1, RB Offset=24	0	0	23.75	23.37	23.52
		RB Size=1, RB Offset=49	0	0	23.64	23.67	23.66
		RB Size=25, RB Offset=0	1	1	23.40	23.21	23.13
		RB Size=25, RB Offset=12	1	1	23.08	23.29	23.01
		RB Size=25, RB Offset=24	1	1	22.87	22.96	22.81
		RB Size=50, RB Offset=0	1	1	23.32	23.16	23.28
	16QAM	RB Size=1, RB Offset=0	1	1	23.28	22.94	23.22
		RB Size=1, RB Offset=24	1	1	22.78	22.96	22.68
		RB Size=1, RB Offset=49	1	1	23.08	22.91	23.21
		RB Size=25, RB Offset=0	2	2	22.83	22.92	22.87
		RB Size=25, RB Offset=12	2	2	22.78	22.99	22.66
		RB Size=25, RB Offset=24	2	2	23.02	23.39	22.73
		RB Size=50, RB Offset=0	2	2	23.44	23.66	23.26

BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2542.5MHz	2595MHz	2647.5MHz
15M	QPSK	RB Size=1, RB Offset=0	0	0	23.48	23.60	23.54
		RB Size=1, RB Offset=37	0	0	23.70	23.65	23.47
		RB Size=1, RB Offset=74	0	0	23.62	23.64	23.33
		RB Size=36, RB Offset=0	1	1	23.27	23.05	23.08
		RB Size=36, RB Offset=18	1	1	23.14	22.90	22.92
		RB Size=36, RB Offset=37	1	1	22.83	22.99	22.80
		RB Size=75, RB Offset=0	1	1	23.14	22.96	22.99
	16QAM	RB Size=1, RB Offset=0	1	1	23.22	23.10	23.12
		RB Size=1, RB Offset=37	1	1	22.76	22.67	22.67
		RB Size=1, RB Offset=74	1	1	23.12	22.89	23.33
		RB Size=36, RB Offset=0	2	2	22.79	22.92	22.94
		RB Size=36, RB Offset=18	2	2	22.73	22.87	22.91
		RB Size=36, RB Offset=37	2	2	23.02	23.11	23.26
		RB Size=75, RB Offset=0	2	2	23.51	23.33	23.35
BW	Modulation	Resource Block Size& Resource Block Offset	Target MP R	Meas M P R	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					2545MHz	2595MHz	2645MHz
20M	QPSK	RB Size=1, RB Offset=0	0	0	23.39	23.81	23.70
		RB Size=1, RB Offset=49	0	0	23.36	23.36	23.66
		RB Size=1, RB Offset=99	0	0	23.27	23.52	23.24
		RB Size=50, RB Offset=0	1	1	23.28	23.00	23.08
		RB Size=50, RB Offset=24	1	1	23.16	23.26	23.37
		RB Size=50, RB Offset=49	1	1	22.73	22.82	22.89
		RB Size=100, RB Offset=0	1	1	22.89	22.93	22.95
	16QAM	RB Size=1, RB Offset=0	1	1	23.19	23.18	22.83
		RB Size=1, RB Offset=49	1	1	22.75	22.72	22.90
		RB Size=1, RB Offset=99	1	1	23.16	23.05	22.97
		RB Size=50, RB Offset=0	2	2	22.85	22.66	22.84
		RB Size=50, RB Offset=24	2	2	22.89	22.76	23.12
		RB Size=50, RB Offset=49	2	2	23.14	22.84	23.28
		RB Size=100, RB Offset=0	2	2	23.28	22.85	23.72

Note:

1. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02.
2. The CMW500 Wideband Radio Communication tester is used for LTE output power measurements and SAR testing. Closed loop power control is used to keep the radio transmitters the max output power during the test.

Bluetooth:

Mode	Channel frequency (MHz)	RF Output Power (dBm)
BDR(GFSK)	2402	5.75
	2441	4.59
	2480	6.23
EDR($\pi/4$ -DQPSK)	2402	4.86
	2441	3.94
	2480	5.43
EDR(8-DPSK)	2402	4.92
	2441	3.95
	2480	5.58
Bluetooth LE_1M	2402	-2.52
	2440	-2.01
	2480	-1.50
Bluetooth LE_2M	2402	-2.04
	2440	-1.48
	2480	-1.39

WLAN 2.4G:

Mode	Channel frequency	Data Rate	RF Output Power(dBm)
802.11b	2412	1Mbps	15.00
	2442		15.08
	2472		15.27
802.11g	2412	6Mbps	15.27
	2442		15.56
	2472		15.57
802.11n HT20	2412	MCS0	15.18
	2442		15.39
	2472		15.30
802.11n HT40	2422	MCS0	14.55
	2442		14.87
	2462		14.88

WLAN 5G:

Mode	Channel frequency	Data Rate	RF Output Power(dBm)
802.11a	5180	6Mbps	11.48
	5200		11.34
	5240		11.38
	5745		12.19
	5785		11.93
	5825		11.86
802.11n HT20	5180	MCS0	11.45
	5200		11.41
	5240		11.28
	5745		12.16
	5785		11.80
	5825		11.43
802.11n HT40	5190	MCS0	10.89
	5230		10.69
	5755		11.66
	5795		11.39
802.11AC20	5180	MCS0	10.70
	5200		10.95
	5240		10.86
	5745		11.62
	5785		11.47
	5825		11.27
802.11AC40	5190	MCS0	10.79
	5230		11.01
	5755		11.47
	5795		11.31
802.11AC80	5210	MCS0	11.30
	5775		11.67

Antennas Location:



Bottom

Antenna Distance To Edge(mm)

- 1.The main antenna transmits GSM 850\ PCS 1900\ WCDMA Band 2\WCDMA Band 5\ Band 2\ LTE Band 5\
- 2.The aux antenna transmits LTE Band 7\ LTE Band 41\ LTE Band 40\LTE Band 38

Standalone SAR test exclusion considerations

Mode	Frequency (MHz)	P _{avg} (dBm)	P _{avg} (mW)	Distance (mm)	Calculated value	Threshold (1-g)	SAR Test Exclusion
WLAN 2.4G	2472	15.5	35.48	0	11.2	3.0	No
Bluetooth	2480	6.5	4.47	0	1.4	3.0	Yes

NOTE:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.
5. EUT photos are secret

Standalone SAR estimation:

Mode	Frequency (MHz)	Pavg (dBm)	Pavg (mW)	Distance (mm)	Estimated 1-g (W/kg)
Bluetooth Head	2480	6.5	4.47	0	0.19
Bluetooth Body	2480	6.5	4.47	10	0.09

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})/x}]$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

SAR test exclusion for the EUT edge considerations Result

Exclusion Result					
Mode	Back	Left	Right	Top	Bottom
Bluetooth	Exclusion*	Exclusion*	Exclusion*	Exclusion*	Exclusion*
WLAN 2.4G	Required	Required	Required	Required	Required
Aux Antenna	Required	Required	Required	Required	Required
WWAN Main Antenna	Required	Required	Required	Exclusion	Required

Note:

Required: The distance to Edge is less than 25mm, testing is required.

Exclusion*: SAR test exclusion evaluation has been done above.

Exclusion: The distance to Edge is more than 25 mm, testing is not required.

Corrected SAR Evaluation

62209-2 © IEC:2010

– 89 –

Annex F
(normative)**SAR correction for deviations of complex permittivity from targets****F.2 SAR correction formula**

From [13] and [14], a linear relationship was found between the percent change in SAR (denoted ΔSAR) and the percent change in the permittivity and conductivity from the target values in Table 1 (denoted $\Delta\epsilon_r$ and $\Delta\sigma$, respectively). This linear relationship agrees with the results of Kuster and Balzano [48] and Bit-Babik et al. [2]. The relationship is given by:

$$\Delta\text{SAR} = c_\epsilon \Delta\epsilon_r + c_\sigma \Delta\sigma \quad (\text{F.1})$$

where

$c_\epsilon = \partial(\Delta\text{SAR})/\partial(\Delta\epsilon_r)$ is the coefficients representing the sensitivity of SAR to permittivity where SAR is normalized to output power;

$c_\sigma = \partial(\Delta\text{SAR})/\partial(\Delta\sigma)$ is the coefficients representing the sensitivity of SAR to conductivity, where SAR is normalized to output power.

The values of c_ϵ and c_σ have a simple relationship with frequency that can be described using polynomial equations. For the 1 g averaged SAR c_ϵ and c_σ are given by

$$c_\epsilon = -7,854 \times 10^{-4} f^3 + 9,402 \times 10^{-3} f^2 - 2,742 \times 10^{-2} f - 0,202 \ 6 \quad (\text{F.2})$$

$$c_\sigma = 9,804 \times 10^{-3} f^3 - 8,661 \times 10^{-2} f^2 + 2,981 \times 10^{-2} f + 0,782 \ 9 \quad (\text{F.3})$$

where

f is the frequency in GHz.

For the 10 g averaged SAR, the variables c_ϵ and c_σ are given by:

$$c_\epsilon = 3,456 \times 10^{-3} f^3 - 3,531 \times 10^{-2} f^2 + 7,675 \times 10^{-2} f - 0,186 \ 0 \quad (\text{F.4})$$

$$c_\sigma = 4,479 \times 10^{-3} f^3 - 1,586 \times 10^{-2} f^2 - 0,197 \ 2 f + 0,771 \ 7 \quad (\text{F.5})$$

Test Date	Frequency (MHz)	C_{ϵ}	$\Delta\epsilon_r$	C_{δ}	$\Delta\delta$	ΔSAR
2021/05/10	750	-0.218	2.17	0.761	-1.46	-1.584
	824.2	-0.219	0.2	0.754	-1.89	-1.469
	826.4	-0.219	1.1	0.754	-0.78	-0.829
	829	-0.219	0.33	0.754	-0.44	-0.404
	836.5	-0.219	0.12	0.753	2.78	2.067
	836.6	-0.219	1.98	0.753	3.22	1.991
	844	-0.220	0.92	0.752	2.86	1.948
	846.6	-0.220	-0.1	0.752	2.97	2.255
	848.8	-0.220	-0.33	0.752	4.73	3.63
2021/05/12	1850.2	-0.226	-1.52	0.604	-1	-0.26
	1852.4	-0.226	-1.34	0.603	-1.29	-0.475
	1860	-0.226	0.13	0.602	-0.71	-0.457
	1880	-0.226	0.09	0.598	0.07	0.022
	1900	-0.226	0.02	0.594	0.43	0.251
	1907.6	-0.226	0.47	0.593	1.29	0.659
	1909.8	-0.226	0.52	0.592	1.86	0.984
2021/05/19	2300	-0.225	0.48	0.513	-0.72	-0.477
	2310	-0.225	0.94	0.510	-0.06	-0.242
	2355	-0.225	0.15	0.501	-2.75	-1.412
2021/05/13	2412	-0.225	-1.17	0.489	2.37	1.422
	2442	-0.225	-1.61	0.482	2.4	1.519
	2450	-0.225	-1.58	0.480	2.94	1.767
	2472	-0.225	-1.88	0.475	3.02	1.858
	2506	-0.225	-2.28	0.468	1.67	1.295
	2510	-0.225	-1.09	0.467	2.8	1.553
	2535	-0.224	-2.95	0.462	2.59	1.857
2021/05/11	2593	-0.224	-1.91	0.449	1.03	0.89
	2600	-0.224	-1.59	0.447	0.92	0.767
	2680	-0.224	-1.31	0.429	-2.89	-0.946

SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

SAR Test Data

Environmental Conditions

Temperature:	22.1-24.5 °C	22.1-23.9 °C	22.3-24.2 °C	22.1-23.2 °C	22.4-23.9 °C
Relative Humidity:	42-56%	42-58 %	40-55 %	41-59 %	39-58 %
ATM Pressure:	101.5 kPa	101.8 kPa	101.5 kPa	101.6 kPa	101.8 kPa
Test Date:	2021/05/10	2021/05/11	2021/05/12	2021/05/13	2021/05/19

Testing was performed by Afflict Gu.

Note:

1. According to **Notice 2016-DRS001**: Based on the IEEE 1528 and IEC 62209 requirements, the high, mid and low channels for the configuration with the highest SAR value must be tested regardless of the SAR value measured
2. According to **Notice 2012-DRS0529**, if the correction Δ SAR has a negative sign, **the measured SAR result should be corrected**, and has a positive sign, the measured SAR result shall not be corrected.

GSM 850 :

EUT Position	Frequency (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)			Plot
			Meas.	Rated		Meas.	Scaled	Corrected	
Head Left Cheek	824.2	GSM	/	/	/	/	/	/	/
	836.6	GSM	32.4	32.6	1.047	0.129	0.14	0.14	1#
	848.8	GSM	/	/	/	/	/	/	/
Head Left Tilt	824.2	GSM	/	/	/	/	/	/	/
	836.6	GSM	32.4	32.6	1.047	0.075	0.08	0.08	2#
	848.8	GSM	/	/	/	/	/	/	/
Head Right Cheek	824.2	GSM	/	/	/	/	/	/	/
	836.6	GSM	32.4	32.6	1.047	0.173	0.18	0.18	3#
	848.8	GSM	/	/	/	/	/	/	/
Head Right Tilt	824.2	GSM	/	/	/	/	/	/	/
	836.6	GSM	32.4	32.6	1.047	0.094	0.10	0.10	4#
	848.8	GSM	/	/	/	/	/	/	/
Body Worn Back (10mm)	824.2	GSM	/	/	/	/	/	/	/
	836.6	GSM	32.4	32.6	1.047	0.230	0.24	0.24	5#
	848.8	GSM	/	/	/	/	/	/	/
Body Back (10mm)	824.2	GPRS	/	/	/	/	/	/	/
	836.6	GPRS	27.84	28.5	1.164	0.295	0.34	0.34	6#
	848.8	GPRS	/	/	/	/	/	/	/
Body Left (10mm)	824.2	GPRS	/	/	/	/	/	/	/
	836.6	GPRS	27.84	28.5	1.164	0.030	0.03	0.03	7#
	848.8	GPRS	/	/	/	/	/	/	/
Body Right (10mm)	824.2	GPRS	/	/	/	/	/	/	/
	836.6	GPRS	27.84	28.5	1.164	0.028	0.03	0.03	8#
	848.8	GPRS	/	/	/	/	/	/	/
Body Bottom (10mm)	824.2	GPRS	/	/	/	/	/	/	/
	836.6	GPRS	27.84	28.5	1.164	0.201	0.23	0.23	9#
	848.8	GPRS	/	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is $> 0.5\text{ dB}$, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 1DL+4UL is the worst case.

PCS 1900 :

EUT Position	Frequency (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)			Plot
			Meas.	Rated		Meas.	Scaled	Corrected	
Head Left Cheek	1850.2	GSM	/	/	/	/	/	/	/
	1880	GSM	29.6	30.0	1.096	0.030	0.03	0.03	10#
	1909.8	GSM	/	/	/	/	/	/	/
Head Left Tilt	1850.2	GSM	/	/	/	/	/	/	/
	1880	GSM	29.6	30.0	1.096	0.016	0.02	0.02	11#
	1909.8	GSM	/	/	/	/	/	/	/
Head Right Cheek	1850.2	GSM	/	/	/	/	/	/	/
	1880	GSM	29.6	30.0	1.096	0.022	0.02	0.02	12#
	1909.8	GSM	/	/	/	/	/	/	/
Head Right Tilt	1850.2	GSM	/	/	/	/	/	/	/
	1880	GSM	29.6	30.0	1.096	0.017	0.02	0.02	13#
	1909.8	GSM	/	/	/	/	/	/	/
Body Worn Back (10mm)	1850.2	GSM	/	/	/	/	/	/	/
	1880	GSM	29.6	30.0	1.096	0.345	0.38	0.38	14#
	1909.8	GSM	/	/	/	/	/	/	/
Body Back (10mm)	1850.2	GPRS	/	/	/	/	/	/	/
	1880	GPRS	24.90	25.5	1.148	0.307	0.35	0.35	15#
	1909.8	GPRS	/	/	/	/	/	/	/
Body Left (10mm)	1850.2	GPRS	/	/	/	/	/	/	/
	1880	GPRS	24.90	25.5	1.148	0.060	0.07	0.07	16#
	1909.8	GPRS	/	/	/	/	/	/	/
Body Right (10mm)	1850.2	GPRS	/	/	/	/	/	/	/
	1880	GPRS	24.90	25.5	1.148	0.054	0.06	0.06	17#
	1909.8	GPRS	/	/	/	/	/	/	/
Body Bottom (10mm)	1850.2	GPRS	/	/	/	/	/	/	/
	1880	GPRS	24.90	25.5	1.148	0.683	0.78	0.78	18#
	1909.8	GPRS	/	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is $> 0.5\text{ dB}$, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 3DL+2UL is the worst case.

WCDMA Band 2 :

EUT Position	Frequency (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)			Plot
			Meas.	Rated		Meas.	Scaled	Corrected	
Head Left Cheek	1852.4	RMC	/	/	/	/	/	/	/
	1880	RMC	22.93	23.0	1.016	0.045	0.05	0.05	19#
	1907.6	RMC	/	/	/	/	/	/	/
Head Left Tilt	1852.4	RMC	/	/	/	/	/	/	/
	1880	RMC	22.93	23.0	1.016	0.031	0.03	0.03	20#
	1907.6	RMC	/	/	/	/	/	/	/
Head Right Cheek	1852.4	RMC	/	/	/	/	/	/	/
	1880	RMC	22.93	23.0	1.016	0.025	0.03	0.03	21#
	1907.6	RMC	/	/	/	/	/	/	/
Head Right Tilt	1852.4	RMC	/	/	/	/	/	/	/
	1880	RMC	22.93	23.0	1.016	0.026	0.03	0.03	22#
	1907.6	RMC	/	/	/	/	/	/	/
Body Back (10mm)	1852.4	RMC	/	/	/	/	/	/	/
	1880	RMC	22.93	23.0	1.016	0.222	0.23	0.23	23#
	1907.6	RMC	/	/	/	/	/	/	/
Body Left (10mm)	1852.4	RMC	/	/	/	/	/	/	/
	1880	RMC	22.93	23.0	1.016	0.055	0.06	0.06	24#
	1907.6	RMC	/	/	/	/	/	/	/
Body Right (10mm)	1852.4	RMC	/	/	/	/	/	/	/
	1880	RMC	22.93	23.0	1.016	0.043	0.04	0.04	25#
	1907.6	RMC	/	/	/	/	/	/	/
Body Bottom (10mm)	1852.4	RMC	/	/	/	/	/	/	/
	1880	RMC	22.93	23.0	1.016	0.527	0.54	0.54	26#
	1907.6	RMC	/	/	/	/	/	/	/

WCDMA Band 5 :

EUT Position	Frequency (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)			Plot
			Meas.	Rated		Meas.	Scaled	Corrected	
Head Left Cheek	826.4	RMC	/	/	/	/	/	/	/
	836.6	RMC	/	/	/	/	/	/	/
	846.6	RMC	22.80	23.0	1.047	0.116	0.12	0.12	27#
Head Left Tilt	826.4	RMC	/	/	/	/	/	/	/
	836.6	RMC	/	/	/	/	/	/	/
	846.6	RMC	22.80	23.0	1.047	0.071	0.07	0.07	28#
Head Right Cheek	826.4	RMC	/	/	/	/	/	/	/
	836.6	RMC	/	/	/	/	/	/	/
	846.6	RMC	22.80	23.0	1.047	0.137	0.14	0.14	29#
Head Right Tilt	826.4	RMC	/	/	/	/	/	/	/
	836.6	RMC	/	/	/	/	/	/	/
	846.6	RMC	22.80	23.0	1.047	0.070	0.07	0.07	30#
Body Back (10mm)	826.4	RMC	/	/	/	/	/	/	/
	836.6	RMC	/	/	/	/	/	/	/
	846.6	RMC	22.80	23.0	1.047	0.224	0.23	0.23	31#
Body Left (10mm)	826.4	RMC	/	/	/	/	/	/	/
	836.6	RMC	/	/	/	/	/	/	/
	846.6	RMC	22.80	23.0	1.047	0.101	0.11	0.11	32#
Body Right (10mm)	826.4	RMC	/	/	/	/	/	/	/
	836.6	RMC	/	/	/	/	/	/	/
	846.6	RMC	22.80	23.0	1.047	0.207	0.22	0.22	33#
Body Bottom (10mm)	826.4	RMC	/	/	/	/	/	/	/
	836.6	RMC	/	/	/	/	/	/	/
	846.6	RMC	22.80	23.0	1.047	0.138	0.14	0.14	34#

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. The EUT transmit and receive through the same antenna while testing SAR.
3. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model.
4. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/HSPA+ when the maximum average output of each RF channel is less than $\frac{1}{4}$ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is $< 75\%$ of SAR limit.
5. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

LTE Band 2 :

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)			Plot
				Meas.	Rated		Meas.	Scaled	Corrected	
Head Left Cheek	1860	20	1RB	/	/	/	/	/	/	/
	1880	20	1RB	22.81	23.5	1.172	0.041	0.05	0.05	35#
	1900	20	1RB	/	/	/	/	/	/	/
	1880	20	50%RB	21.90	23.5	1.445	0.035	0.05	0.05	36#
Head Left Tilt	1860	20	1RB	/	/	/	/	/	/	/
	1880	20	1RB	22.81	23.5	1.172	0.026	0.03	0.03	37#
	1900	20	1RB	/	/	/	/	/	/	/
	1880	20	50%RB	21.90	23.5	1.445	0.021	0.03	0.03	38#
Head Right Cheek	1860	20	1RB	/	/	/	/	/	/	/
	1880	20	1RB	22.81	23.5	1.172	0.023	0.03	0.03	39#
	1900	20	1RB	/	/	/	/	/	/	/
	1880	20	50%RB	21.90	23.5	1.445	0.020	0.03	0.03	40#
Head Right Tilt	1860	20	1RB	/	/	/	/	/	/	/
	1880	20	1RB	22.81	23.5	1.172	0.019	0.02	0.02	41#
	1900	20	1RB	/	/	/	/	/	/	/
	1880	20	50%RB	21.90	23.5	1.445	0.017	0.02	0.02	42#
Body Back (10mm)	1860	20	1RB	/	/	/	/	/	/	/
	1880	20	1RB	22.81	23.5	1.172	0.272	0.32	0.32	43#
	1900	20	1RB	/	/	/	/	/	/	/
	1880	20	50%RB	21.90	23.5	1.445	0.245	0.35	0.35	44#
Body Left (10mm)	1860	20	1RB	/	/	/	/	/	/	/
	1880	20	1RB	22.81	23.5	1.172	0.043	0.05	0.05	45#
	1900	20	1RB	/	/	/	/	/	/	/
	1880	20	50%RB	21.90	23.5	1.445	0.040	0.06	0.06	46#
Body Right (10mm)	1860	20	1RB	/	/	/	/	/	/	/
	1880	20	1RB	22.81	23.5	1.172	0.047	0.06	0.06	47#
	1900	20	1RB	/	/	/	/	/	/	/
	1880	20	50%RB	21.90	23.5	1.445	0.040	0.06	0.06	48#
Body Bottom (10mm)	1860	20	1RB	/	/	/	/	/	/	/
	1880	20	1RB	22.81	23.5	1.172	0.512	0.60	0.60	49#
	1900	20	1RB	/	/	/	/	/	/	/
	1880	20	50%RB	21.90	23.5	1.445	0.456	0.66	0.66	50#

LTE Band 5 :

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)			Plot
				Meas.	Rated		Meas.	Scaled	Corrected	
Head Left Cheek	829	10	1RB	/	/	/	/	/	/	/
	836.5	10	1RB	23.87	24.0	1.030	0.117	0.12	0.12	51#
	844	10	1RB	/	/	/	/	/	/	/
	836.5	10	50%RB	23.16	24.0	1.213	0.092	0.11	0.11	52#
Head Left Tilt	829	10	1RB	/	/	/	/	/	/	/
	836.5	10	1RB	23.87	24.0	1.030	0.066	0.07	0.07	53#
	844	10	1RB	/	/	/	/	/	/	/
	836.5	10	50%RB	23.16	24.0	1.213	0.051	0.06	0.06	54#
Head Right Cheek	829	10	1RB	/	/	/	/	/	/	/
	836.5	10	1RB	23.87	24.0	1.030	0.145	0.15	0.15	55#
	844	10	1RB	/	/	/	/	/	/	/
	844	10	50%RB	23.16	24.0	1.213	0.116	0.14	0.14	56#
Head Right Tilt	829	10	1RB	/	/	/	/	/	/	/
	836.5	10	1RB	23.87	24.0	1.030	0.067	0.07	0.07	57#
	844	10	1RB	/	/	/	/	/	/	/
	836.5	10	50%RB	23.16	24.0	1.213	0.052	0.06	0.06	58#
Body Back (10mm)	829	10	1RB	/	/	/	/	/	/	/
	836.5	10	1RB	23.87	24.0	1.030	0.083	0.09	0.09	59#
	844	10	1RB	/	/	/	/	/	/	/
	836.5	10	50%RB	23.16	24.0	1.213	0.067	0.08	0.08	60#
Body Left (10mm)	829	10	1RB	/	/	/	/	/	/	/
	836.5	10	1RB	23.87	24.0	1.030	0.041	0.04	0.04	61#
	844	10	1RB	/	/	/	/	/	/	/
	836.5	10	50%RB	23.16	24.0	1.213	0.033	0.04	0.04	62#
Body Right (10mm)	829	10	1RB	/	/	/	/	/	/	/
	836.5	10	1RB	23.87	24.0	1.030	0.085	0.09	0.09	63#
	844	10	1RB	/	/	/	/	/	/	/
	836.5	10	50%RB	23.16	24.0	1.213	0.069	0.08	0.08	64#
Body Bottom (10mm)	829	10	1RB	/	/	/	/	/	/	/
	836.5	10	1RB	23.87	24.0	1.030	0.059	0.06	0.06	65#
	844	10	1RB	/	/	/	/	/	/	/
	836.5	10	50%RB	23.16	24.0	1.213	0.045	0.05	0.05	66#

LTE Band 7 :

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)			Plot
				Meas.	Rated		Meas.	Scaled	Corrected	
Head Left Cheek	2510	20	1RB	/	/	/	/	/	/	/
	2535	20	1RB	23.76	24.0	1.057	0.278	0.29	0.29	67#
	2560	20	1RB	/	/	/	/	/	/	/
	2535	20	50%RB	22.93	24.0	1.279	0.256	0.33	0.33	68#
Head Left Tilt	2510	20	1RB	/	/	/	/	/	/	/
	2535	20	1RB	23.76	24.0	1.057	0.407	0.43	0.43	69#
	2560	20	1RB	/	/	/	/	/	/	/
	2535	20	50%RB	22.93	24.0	1.279	0.361	0.46	0.46	70#
Head Right Cheek	2510	20	1RB	/	/	/	/	/	/	/
	2535	20	1RB	23.76	24.0	1.057	0.730	0.77	0.77	71#
	2560	20	1RB	/	/	/	/	/	/	/
	2510	20	50%RB	23.20	24.0	1.202	0.482	0.58	0.58	72#
	2535	20	50%RB	22.93	24.0	1.279	0.688	0.88	0.88	73#
	2560	20	50%RB	22.86	24.0	1.300	0.552	0.72	0.72	74#
Head Right Tilt	2510	20	1RB	23.33	24.0	1.167	0.585	0.68	0.68	75#
	2535	20	1RB	23.76	24.0	1.057	0.894	0.94	0.94	76#
	2560	20	1RB	23.57	24.0	1.104	0.630	0.70	0.70	77#
	2510	20	50%RB	23.20	24.0	1.202	0.492	0.59	0.59	78#
	2535	20	50%RB	22.93	24.0	1.279	0.768	0.98	0.98	79#
	2560	20	50%RB	22.86	24.0	1.300	0.550	0.72	0.72	80#
	2535	20	100%RB	22.94	24.0	1.276	0.517	0.66	0.66	81#
Body Back (10mm)	2510	20	1RB	/	/	/	/	/	/	/
	2535	20	1RB	23.76	24.0	1.057	0.129	0.14	0.14	82#
	2560	20	1RB	/	/	/	/	/	/	/
	2535	20	50%RB	22.93	24.0	1.279	0.105	0.13	0.13	83#
Body Left (10mm)	2510	20	1RB	/	/	/	/	/	/	/
	2535	20	1RB	23.76	24.0	1.057	0.099	0.10	0.10	84#
	2560	20	1RB	/	/	/	/	/	/	/
	2535	20	50%RB	22.93	24.0	1.279	0.081	0.10	0.10	85#
Body Right (10mm)	2510	20	1RB	/	/	/	/	/	/	/
	2535	20	1RB	23.76	24.0	1.057	0.021	0.02	0.02	86#
	2560	20	1RB	/	/	/	/	/	/	/
	2535	20	50%RB	22.93	24.0	1.279	0.018	0.02	0.02	87#
Body Top (10mm)	2510	20	1RB	/	/	/	/	/	/	/
	2535	20	1RB	23.76	24.0	1.057	0.222	0.23	0.23	88#
	2560	20	1RB	/	/	/	/	/	/	/
	2535	20	50%RB	22.93	24.0	1.279	0.126	0.16	0.16	89#
Body Bottom (10mm)	2510	20	1RB	/	/	/	/	/	/	/
	2535	20	1RB	23.76	24.0	1.057	0.0097	0	0	/
	2560	20	1RB	/	/	/	/	/	/	/
	2535	20	50%RB	22.93	24.0	1.279	0.0091	0	0	/

LTE Band 40Lower :

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)			Plot
				Meas.	Rated		Meas.	Scaled	Corrected	
Head Left Cheek	/	20	1RB	/	/	/	/	/	/	/
	2310	20	1RB	22.37	23.0	1.156	0.061	0.07	0.07	90#
	/	20	1RB	/	/	/	/	/	/	/
	2310	20	50%RB	21.72	23.0	1.343	0.054	0.07	0.07	91#
Head Left Tilt	/	20	1RB	/	/	/	/	/	/	/
	2310	20	1RB	22.37	23.0	1.156	0.130	0.15	0.15	92#
	/	20	1RB	/	/	/	/	/	/	/
	2310	20	50%RB	21.72	23.0	1.343	0.123	0.17	0.17	93#
Head Right Cheek	/	20	1RB	/	/	/	/	/	/	/
	2310	20	1RB	22.37	23.0	1.156	0.252	0.29	0.29	94#
	/	20	1RB	/	/	/	/	/	/	/
	2310	20	50%RB	21.72	23.0	1.343	0.223	0.30	0.30	95#
Head Right Tilt	/	20	1RB	/	/	/	/	/	/	/
	2310	20	1RB	22.37	23.0	1.156	0.246	0.28	0.28	96#
	/	20	1RB	/	/	/	/	/	/	/
	2310	20	50%RB	21.72	23.0	1.343	0.220	0.30	0.30	97#
Body Back (10mm)	/	20	1RB	/	/	/	/	/	/	/
	2310	20	1RB	22.37	23.0	1.156	0.045	0.05	0.05	98#
	/	20	1RB	/	/	/	/	/	/	/
	2310	20	50%RB	21.72	23.0	1.343	0.042	0.06	0.06	99#
Body Left (10mm)	/	20	1RB	/	/	/	/	/	/	/
	2310	20	1RB	22.37	23.0	1.156	0.028	0.03	0.03	100#
	/	20	1RB	/	/	/	/	/	/	/
	2310	20	50%RB	21.72	23.0	1.343	0.026	0.03	0.03	101#
Body Right (10mm)	/	20	1RB	/	/	/	/	/	/	/
	2310	20	1RB	22.37	23.0	1.156	0.00753	0.01	0.01	102#
	/	20	1RB	/	/	/	/	/	/	/
	2310	20	50%RB	21.72	23.0	1.343	0.00495	0.01	0.01	103#
Body Top (10mm)	/	20	1RB	/	/	/	/	/	/	/
	2310	20	1RB	22.37	23.0	1.156	0.003	0.00	0.00	104#
	/	20	1RB	/	/	/	/	/	/	/
	2310	20	50%RB	21.72	23.0	1.343	0.003	0.00	0.00	105#
Body Bottom (10mm)	/	20	1RB	/	/	/	/	/	/	/
	2310	20	1RB	22.37	23.0	1.156	0.003	0.00	0.00	/
	/	20	1RB	/	/	/	/	/	/	/
	2310	20	50%RB	21.72	23.0	1.343	0.003	0.00	0.00	/

LTE Band 40Upper :

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)			Plot
				Meas.	Rated		Meas.	Scaled	Corrected	
Head Left Cheek	/	20	1RB	/	/	/	/	/	/	/
	2355	20	1RB	22.24	23.0	1.191	0.119	0.14	0.14	106#
	/	20	1RB	/	/	/	/	/	/	/
	2355	20	50%RB	21.91	23.0	1.285	0.100	0.13	0.13	107#
Head Left Tilt	/	20	1RB	/	/	/	/	/	/	/
	2355	20	1RB	22.24	23.0	1.191	0.141	0.17	0.17	108#
	/	20	1RB	/	/	/	/	/	/	/
	2355	20	50%RB	21.91	23.0	1.285	0.126	0.16	0.16	109#
Head Right Cheek	/	20	1RB	/	/	/	/	/	/	/
	2355	20	1RB	22.24	23.0	1.191	0.262	0.31	0.31	110#
	/	20	1RB	/	/	/	/	/	/	/
	2355	20	50%RB	21.91	23.0	1.285	0.233	0.30	0.30	111#
Head Right Tilt	/	20	1RB	/	/	/	/	/	/	/
	2355	20	1RB	22.24	23.0	1.191	0.280	0.33	0.33	112#
	/	20	1RB	/	/	/	/	/	/	/
	2355	20	50%RB	21.91	23.0	1.285	0.240	0.31	0.31	113#
Body Back (10mm)	/	20	1RB	/	/	/	/	/	/	/
	2355	20	1RB	22.24	23.0	1.191	0.045	0.05	0.05	114#
	/	20	1RB	/	/	/	/	/	/	/
	2355	20	50%RB	21.91	23.0	1.285	0.040	0.05	0.05	115#
Body Left (10mm)	/	20	1RB	/	/	/	/	/	/	/
	2355	20	1RB	22.24	23.0	1.191	0.044	0.05	0.05	116#
	/	20	1RB	/	/	/	/	/	/	/
	2355	20	50%RB	21.91	23.0	1.285	0.047	0.06	0.06	117#
Body Right (10mm)	/	20	1RB	/	/	/	/	/	/	/
	2355	20	1RB	22.24	23.0	1.191	0.009	0.01	0.01	118#
	/	20	1RB	/	/	/	/	/	/	/
	2355	20	50%RB	21.91	23.0	1.285	0.014	0.02	0.02	119#
Body Top (10mm)	/	20	1RB	/	/	/	/	/	/	/
	2355	20	1RB	22.24	23.0	1.191	0.0043	0.01	0.01	120#
	/	20	1RB	/	/	/	/	/	/	/
	2355	20	50%RB	21.91	23.0	1.285	0.0032	0.00	0.00	121#
Body Bottom (10mm)	/	20	1RB	/	/	/	/	/	/	/
	2355	20	1RB	22.24	23.0	1.191	0.001	0.00	0.00	/
	/	20	1RB	/	/	/	/	/	/	/
	2355	20	50%RB	21.91	23.0	1.285	0.001	0.00	0.00	/

LTE Band 41 :

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)			Plot
				Meas.	Rated		Meas.	Scaled	Corrected	
Head Left Cheek	2565	20	1RB	/	/	/	/	/	/	/
	2605	20	1RB	23.81	24.0	1.045	0.173	0.18	0.18	122#
	2655	20	1RB	/	/	/	/	/	/	/
	2605	20	50%RB	23.00	24.0	1.259	0.146	0.18	0.18	123#
Head Left Tilt	2565	20	1RB	/	/	/	/	/	/	/
	2605	20	1RB	23.81	24.0	1.045	0.220	0.23	0.23	124#
	2655	20	1RB	/	/	/	/	/	/	/
	2605	20	50%RB	23.00	24.0	1.259	0.188	0.24	0.24	125#
Head Right Cheek	2565	20	1RB	/	/	/	/	/	/	/
	2605	20	1RB	23.81	24.0	1.045	0.473	0.49	0.49	126#
	2655	20	1RB	/	/	/	/	/	/	/
	2605	20	50%RB	23.00	24.0	1.259	0.386	0.49	0.49	127#
Head Right Tilt	2565	20	1RB	/	/	/	/	/	/	/
	2605	20	1RB	23.81	24.0	1.045	0.493	0.52	0.52	128#
	2655	20	1RB	/	/	/	/	/	/	/
	2605	20	50%RB	23.00	24.0	1.259	0.421	0.53	0.53	129#
Body Back (10mm)	2565	20	1RB	/	/	/	/	/	/	/
	2605	20	1RB	23.81	24.0	1.045	0.108	0.11	0.11	130#
	2655	20	1RB	/	/	/	/	/	/	/
	2605	20	50%RB	23.00	24.0	1.259	0.091	0.11	0.11	131#
Body Left (10mm)	2565	20	1RB	/	/	/	/	/	/	/
	2605	20	1RB	23.81	24.0	1.045	0.045	0.05	0.05	132#
	2655	20	1RB	/	/	/	/	/	/	/
	2605	20	50%RB	23.00	24.0	1.259	0.034	0.04	0.04	133#
Body Right (10mm)	2565	20	1RB	/	/	/	/	/	/	/
	2605	20	1RB	23.81	24.0	1.045	0.015	0.02	0.02	134#
	2655	20	1RB	/	/	/	/	/	/	/
	2605	20	50%RB	23.00	24.0	1.259	0.014	0.02	0.02	135#
Body Top (10mm)	2565	20	1RB	/	/	/	/	/	/	/
	2605	20	1RB	23.81	24.0	1.045	0.120	0.13	0.13	136#
	2655	20	1RB	/	/	/	/	/	/	/
	2605	20	50%RB	23.00	24.0	1.259	0.097	0.12	0.12	137#
Body Bottom (10mm)	2565	20	1RB	/	/	/	/	/	/	/
	2605	20	1RB	23.81	24.0	1.045	0.120	0.13	0.13	138#
	2655	20	1RB	/	/	/	/	/	/	/
	2605	20	50%RB	23.00	24.0	1.259	0.097	0.12	0.12	139#

Note*: The LTE Operating Band 38 is a subset of band 41, and they are same in modulation type , therefore, they were considered as one frequency band during SAR measurement.

Note:

1. When the 1-g SAR is $\leq 0.8 \text{ W/Kg}$, testing for other channels are optional.
2. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02.
3. KDB941225D05-SAR for higher order modulation is required only when the highest maximum output power for the configuration in the higher order modulation is $> 0.5 \text{ dB}$ higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is $> 1.45 \text{ W/kg}$
4. KDB941225D05-For QPSK with 100% RB allocation, when the reported SAR measured for the Highest output power channel is $< 1.45 \text{ W/kg}$, tests for the remaining required test channels are optional.
5. KDB941225D05- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are $\leq 0.8 \text{ W/kg}$.
6. KDB941225D05- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offset the upper edge, middle and lower edge of each required test channel.
7. KDB941225D05- other channel bandwidths SAR test is required when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> 0.5 \text{ dB}$ higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is $> 1.45 \text{ W/kg}$.
8. Worst case SAR for 50% RB allocation is selected to be tested.
9. KDB 648474 D04-When the peak SAR located in regions that probe is unable to access, a flat phantom is used for SAR measurement.
10. For modes that peak SAR is too low to evaluate, a SAR value 0 W/kg is considered as their Scaled SAR

WLAN 2.4G:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Meas. SAR	Scaled SAR	Corrected SAR	Plot
Head Left Cheek	2412	802.11b	/	/	/	/	/	/	/
	2442	802.11b	/	/	/	/	/	/	/
	2472	802.11b	15.27	15.5	1.054	0.232	0.24	0.24	140#
Head Left Tilt	2412	802.11b	/	/	/	/	/	/	/
	2442	802.11b	/	/	/	/	/	/	/
	2472	802.11b	15.27	15.5	1.054	0.351	0.37	0.37	141#
Head Right Cheek	2412	802.11b	/	/	/	/	/	/	/
	2442	802.11b	/	/	/	/	/	/	/
	2472	802.11b	15.27	15.5	1.054	0.154	0.16	0.16	142#
Head Right Tilt	2412	802.11b	/	/	/	/	/	/	/
	2442	802.11b	/	/	/	/	/	/	/
	2472	802.11b	15.27	15.5	1.054	0.158	0.17	0.17	143#
Body Back (10mm)	2412	802.11b	/	/	/	/	/	/	/
	2442	802.11b	/	/	/	/	/	/	/
	2472	802.11b	15.27	15.5	1.054	0.053	0.06	0.06	144#
Body Left (10mm)	2412	802.11b	/	/	/	/	/	/	/
	2442	802.11b	/	/	/	/	/	/	/
	2472	802.11b	15.27	15.5	1.054	0.053	0.06	0.06	145#
Body Right (10mm)	2412	802.11b	/	/	/	/	/	/	/
	2442	802.11b	/	/	/	/	/	/	/
	2472	802.11b	15.27	15.5	1.054	0.046	0.05	0.05	146#
Body Top (10mm)	2412	802.11b	/	/	/	/	/	/	/
	2442	802.11b	/	/	/	/	/	/	/
	2472	802.11b	15.27	15.5	1.054	0.112	0.12	0.12	147#
Body Bottom (10mm)	2412	802.11b	/	/	/	/	/	/	/
	2442	802.11b	/	/	/	/	/	/	/
	2472	802.11b	15.27	15.5	1.054	0.00747	0	0	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2\text{ W/kg}$, OFDM SAR is not required.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11b/g/n mode is use for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.
5. For modes that peak SAR is too low to evaluate, a SAR value 0 W/kg is considered as their Scaled SAR.

SAR Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Note: The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The Highest Measured SAR Configuration in Each Frequency Band

Head

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
2450MHz (2400-2550MHz)	LTE Band 7	2535	Head Right Cheek	0.88	0.83	1.06
2450MHz (2400-2550MHz)	LTE Band 7	2535	Head Right Tilt	0.94	0.96	1.02

Body

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
/	/	/	/	/	/	/

Note:

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20 .
2. The measured SAR results **do not** have to be scaled to the maximum tune-up tolerance to determine if repeated measurements are required.
3. SAR measurement variability must be assessed for each frequency band, which is determined by the **SAR probe calibration point and tissue-equivalent medium** used for the device measurements..

SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

Simultaneous Transmission:

Description of Simultaneous Transmit Capabilities		
Transmitter Combination	Simultaneous?	Hotspot?
WWAN(GSM/WCDMA/LTE) + Bluetooth	√	×
WWAN(GSM/WCDMA/LTE) + WLAN	√	√

Simultaneous and Hotspot SAR test exclusion considerations:

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
GSM 850+Bluetooth	Head Left Cheek	0.14	0.19	0.330
	Head Left Tilt	0.08	0.19	0.270
	Head Right Cheek	0.18	0.19	0.370
	Head Right Tilt	0.10	0.19	0.290
	Body Worn Back	0.24	0.09	0.330
	Body Back	0.34	0.09	0.430
PCS1900 +Bluetooth	Head Left Cheek	0.03	0.19	0.220
	Head Left Tilt	0.02	0.19	0.210
	Head Right Cheek	0.02	0.19	0.210
	Head Right Tilt	0.02	0.19	0.210
	Body Worn Back	0.38	0.09	0.470
	Body Back	0.35	0.09	0.440
WCDMA Band 2+Bluetooth	Head Left Cheek	0.05	0.19	0.240
	Head Left Tilt	0.03	0.19	0.220
	Head Right Cheek	0.03	0.19	0.220
	Head Right Tilt	0.03	0.19	0.220
	Body Back	0.23	0.09	0.320
WCDMA Band 5+Bluetooth	Head Left Cheek	0.15	0.19	0.340
	Head Left Tilt	0.09	0.19	0.280
	Head Right Cheek	0.17	0.19	0.360
	Head Right Tilt	0.09	0.19	0.280
	Body Back	0.28	0.09	0.370

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
LTE Band 2+Bluetooth	Head Left Cheek	0.05	0.19	0.240
	Head Left Tilt	0.03	0.19	0.220
	Head Right Cheek	0.03	0.19	0.220
	Head Right Tilt	0.03	0.19	0.220
	Body Back	0.35	0.09	0.440
LTE Band 5+Bluetooth	Head Left Cheek	0.12	0.19	0.310
	Head Left Tilt	0.07	0.19	0.260
	Head Right Cheek	0.15	0.19	0.340
	Head Right Tilt	0.07	0.19	0.260
	Body Back	0.09	0.09	0.180
LTE Band 7+Bluetooth	Head Left Cheek	0.33	0.19	0.520
	Head Left Tilt	0.46	0.19	0.650
	Head Right Cheek	0.88	0.19	1.070
	Head Right Tilt	0.98	0.19	1.170
	Body Back	0.14	0.09	0.230
LTE Band 40Lower+Bluetooth	Head Left Cheek	0.07	0.19	0.260
	Head Left Tilt	0.17	0.19	0.360
	Head Right Cheek	0.30	0.19	0.490
	Head Right Tilt	0.30	0.19	0.490
	Body Back	0.06	0.09	0.150
LTE Band 40Upper+Bluetooth	Head Left Cheek	0.14	0.19	0.330
	Head Left Tilt	0.17	0.19	0.360
	Head Right Cheek	0.31	0.19	0.500
	Head Right Tilt	0.33	0.19	0.520
	Body Back	0.05	0.09	0.140
LTE Band 41&38+Bluetooth	Head Left Cheek	0.18	0.19	0.370
	Head Left Tilt	0.24	0.19	0.430
	Head Right Cheek	0.49	0.19	0.680
	Head Right Tilt	0.53	0.19	0.720
	Body Back	0.11	0.09	0.200

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
GSM 850+ WLAN(2.4G)	Head Left Cheek	0.14	0.24	0.380
	Head Left Tilt	0.08	0.37	0.450
	Head Right Cheek	0.18	0.16	0.340
	Head Right Tilt	0.10	0.17	0.270
	Body Worn Back	0.24	0.06	0.300
GPRS 850 + WLAN(2.4G) (Hotspot)	Body Back	0.34	0.06	0.400
	Body Left	0.03	0.06	0.090
	Body Right	0.03	0.05	0.080
	Body Top	/	0.12	0.120
	Body Bottom	0.23	/	0.230
PCS1900 + WLAN(2.4G)	Head Left Cheek	0.03	0.24	0.270
	Head Left Tilt	0.02	0.37	0.390
	Head Right Cheek	0.02	0.16	0.180
	Head Right Tilt	0.02	0.17	0.190
	Body Worn Back	0.38	0.06	0.440
GPRS 1900 + WLAN(2.4G) (Hotspot)	Body Back	0.35	0.06	0.410
	Body Left	0.07	0.06	0.130
	Body Right	0.06	0.05	0.110
	Body Top	/	0.12	0.120
	Body Bottom	0.78	/	0.780
WCDMA Band 2+ WLAN(2.4G)	Head Left Cheek	0.05	0.24	0.290
	Head Left Tilt	0.03	0.37	0.400
	Head Right Cheek	0.03	0.16	0.190
	Head Right Tilt	0.03	0.17	0.200
WCDMA Band 2+ WLAN(2.4G) (Hotspot)	Body Back	0.23	0.06	0.290
	Body Left	0.06	0.06	0.120
	Body Right	0.04	0.05	0.090
	Body Top	/	0.12	0.120
	Body Bottom	0.54	/	0.540
WCDMA Band 5+ WLAN(2.4G)	Head Left Cheek	0.15	0.24	0.390
	Head Left Tilt	0.09	0.37	0.460
	Head Right Cheek	0.17	0.16	0.330
	Head Right Tilt	0.09	0.17	0.260
WCDMA Band 5+ WLAN(2.4G) (Hotspot)	Body Back	0.28	0.06	0.340
	Body Left	0.13	0.06	0.190
	Body Right	0.26	0.05	0.310
	Body Top	/	0.12	0.120
	Body Bottom	0.17	/	0.170

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
LTE Band 2+ WLAN(2.4G)	Head Left Cheek	0.05	0.24	0.290
	Head Left Tilt	0.03	0.37	0.400
	Head Right Cheek	0.03	0.16	0.190
	Head Right Tilt	0.03	0.17	0.200
LTE Band 2+ WLAN(2.4G) (Hotspot)	Body Back	0.35	0.06	0.410
	Body Left	0.06	0.06	0.120
	Body Right	0.06	0.05	0.110
	Body Top	/	0.12	0.120
	Body Bottom	0.66	/	0.660
LTE Band 5+ WLAN(2.4G)	Head Left Cheek	0.12	0.24	0.360
	Head Left Tilt	0.07	0.37	0.440
	Head Right Cheek	0.15	0.16	0.310
	Head Right Tilt	0.07	0.17	0.240
LTE Band 5+ WLAN(2.4G) (Hotspot)	Body Back	0.09	0.06	0.150
	Body Left	0.04	0.06	0.100
	Body Right	0.09	0.05	0.140
	Body Top	/	0.12	0.120
	Body Bottom	0.06	/	0.060
LTE Band 7+ WLAN(2.4G)	Head Left Cheek	0.33	0.24	0.570
	Head Left Tilt	0.46	0.37	0.830
	Head Right Cheek	0.88	0.16	1.040
	Head Right Tilt	0.98	0.17	1.150
LTE Band 7+ WLAN(2.4G) (Hotspot)	Body Back	0.14	0.06	0.200
	Body Left	0.10	0.06	0.160
	Body Right	0.02	0.05	0.070
	Body Top	0.23	0.12	0.350
	Body Bottom	/	0.12	0.120
LTE Band 40Lowe+ WLAN(2.4G)	Head Left Cheek	0.07	0.24	0.310
	Head Left Tilt	0.17	0.37	0.540
	Head Right Cheek	0.30	0.16	0.460
	Head Right Tilt	0.30	0.17	0.470
LTE Band 40Lower+ WLAN(2.4G) (Hotspot)	Body Back	0.06	0.06	0.120
	Body Left	0.03	0.06	0.090
	Body Right	0.01	0.05	0.060
	Body Top	/	0.12	0.120
	Body Bottom	/	/	/

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
LTE Band 40Upper+ WLAN(2.4G)	Head Left Cheek	0.14	0.24	0.380
	Head Left Tilt	0.17	0.37	0.540
	Head Right Cheek	0.31	0.16	0.470
	Head Right Tilt	0.33	0.17	0.500
LTE Band 40Upperr+ WLAN(2.4G) (Hotspot)	Body Back	0.05	0.06	0.110
	Body Left	0.06	0.06	0.120
	Body Right	0.02	0.05	0.070
	Body Top	0.01	0.12	0.130
	Body Bottom	/	/	/
LTE Band 41&38+ WLAN(2.4G)	Head Left Cheek	0.18	0.24	0.420
	Head Left Tilt	0.24	0.37	0.610
	Head Right Cheek	0.49	0.16	0.650
	Head Right Tilt	0.53	0.17	0.700
LTE Band 41&38+ WLAN(2.4G) (Hotspot)	Body Back	0.11	0.06	0.170
	Body Left	0.05	0.06	0.110
	Body Right	0.02	0.05	0.070
	Body Top	0.13	0.12	0.250
	Body Bottom	0.13	/	0.130

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
GSM 850+ WLAN(5.2G)	Head Left Cheek	0.14	0.85	0.990
	Head Left Tilt	0.08	0.71	0.790
	Head Right Cheek	0.18	0.42	0.600
	Head Right Tilt	0.10	0.40	0.500
	Body Worn Back	0.24	0.53	0.770
GPRS 850 + WLAN(5.2G) (Hotspot)	Body Back	0.34	0.53	0.870
	Body Left	0.03	/	0.030
	Body Right	0.03	0.08	0.110
	Body Top	/	0.16	0.160
	Body Bottom	0.23	/	0.230
PCS1900 + WLAN(5.2G)	Head Left Cheek	0.03	0.85	0.880
	Head Left Tilt	0.02	0.71	0.730
	Head Right Cheek	0.02	0.42	0.440
	Head Right Tilt	0.02	0.40	0.420
	Body Worn Back	0.38	0.53	0.910
GPRS 1900 + WLAN(5.2G) (Hotspot)	Body Back	0.35	0.53	0.880
	Body Left	0.07	/	0.070
	Body Right	0.06	0.08	0.140
	Body Top	/	0.16	0.160
	Body Bottom	0.78	/	0.780
WCDMA Band 2+ WLAN(5.2G)	Head Left Cheek	0.05	0.85	0.900
	Head Left Tilt	0.03	0.71	0.740
	Head Right Cheek	0.03	0.42	0.450
	Head Right Tilt	0.03	0.40	0.430
WCDMA Band 2+ WLAN(5.2G) (Hotspot)	Body Back	0.23	0.53	0.760
	Body Left	0.06	/	0.060
	Body Right	0.04	0.08	0.120
	Body Top	/	0.16	0.160
	Body Bottom	0.54	/	0.540
WCDMA Band 5+ WLAN(5.2G)	Head Left Cheek	0.15	0.85	1.000
	Head Left Tilt	0.09	0.71	0.800
	Head Right Cheek	0.17	0.42	0.590
	Head Right Tilt	0.09	0.40	0.490
WCDMA Band 5+ WLAN(5.2G) (Hotspot)	Body Back	0.28	0.53	0.810
	Body Left	0.13	/	0.130
	Body Right	0.26	0.08	0.340
	Body Top	/	0.16	0.160
	Body Bottom	0.17	/	0.170

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
LTE Band 2+ WLAN(5.2G)	Head Left Cheek	0.05	0.85	0.900
	Head Left Tilt	0.03	0.71	0.740
	Head Right Cheek	0.03	0.42	0.450
	Head Right Tilt	0.03	0.40	0.430
LTE Band 2+ WLAN(5.2G) (Hotspot)	Body Back	0.35	0.53	0.880
	Body Left	0.06	/	0.060
	Body Right	0.06	0.08	0.140
	Body Top	/	0.16	0.160
	Body Bottom	0.66	/	0.660
LTE Band 5+ WLAN(5.2G)	Head Left Cheek	0.12	0.85	0.970
	Head Left Tilt	0.07	0.71	0.780
	Head Right Cheek	0.15	0.42	0.570
	Head Right Tilt	0.07	0.40	0.470
LTE Band 5+ WLAN(5.2G) (Hotspot)	Body Back	0.09	0.53	0.620
	Body Left	0.04	/	0.040
	Body Right	0.09	0.08	0.170
	Body Top	/	0.16	0.160
	Body Bottom	0.06	/	0.060
LTE Band 7+ WLAN(5.2G)	Head Left Cheek	0.33	0.85	1.180
	Head Left Tilt	0.46	0.71	1.170
	Head Right Cheek	0.88	0.42	1.300
	Head Right Tilt	0.98	0.40	1.380
LTE Band 7+ WLAN(5.2G) (Hotspot)	Body Back	0.14	0.53	0.670
	Body Left	0.10	/	0.100
	Body Right	0.02	0.08	0.100
	Body Top	0.23	0.16	0.390
	Body Bottom	/	/	/
LTE Band 40Lower+ WLAN(5.2G)	Head Left Cheek	0.07	0.85	0.920
	Head Left Tilt	0.17	0.71	0.880
	Head Right Cheek	0.30	0.42	0.720
	Head Right Tilt	0.30	0.40	0.700
LTE Band 40Lower+ WLAN(5.2G) (Hotspot)	Body Back	0.06	0.53	0.590
	Body Left	0.03	/	0.030
	Body Right	0.01	0.08	0.090
	Body Top	/	0.16	0.160
	Body Bottom	/	/	/

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
LTE Band 40Upper+ WLAN(5.2G)	Head Left Cheek	0.14	0.85	0.990
	Head Left Tilt	0.17	0.71	0.880
	Head Right Cheek	0.31	0.42	0.730
	Head Right Tilt	0.33	0.40	0.730
LTE Band 40Upper+ WLAN(5.2G) (Hotspot)	Body Back	0.05	0.53	0.580
	Body Left	0.06	/	0.060
	Body Right	0.02	0.08	0.100
	Body Top	0.01	0.16	0.170
	Body Bottom	/	/	/
LTE Band 41&38+ WLAN(5.2G)	Head Left Cheek	0.18	0.85	1.030
	Head Left Tilt	0.24	0.71	0.950
	Head Right Cheek	0.49	0.42	0.910
	Head Right Tilt	0.53	0.40	0.930
LTE Band 41&38+ WLAN(5.2G) (Hotspot)	Body Back	0.11	0.53	0.640
	Body Left	0.05	/	0.050
	Body Right	0.02	0.08	0.100
	Body Top	0.13	0.16	0.290
	Body Bottom	0.13	/	0.130

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
GSM 850+ WLAN(5.8G)	Head Left Cheek	0.14	0.68	0.820
	Head Left Tilt	0.08	0.57	0.650
	Head Right Cheek	0.18	0.48	0.660
	Head Right Tilt	0.10	0.49	0.590
	Body Worn Back	0.24	0.64	0.880
GPRS 850 + WLAN(5.8G) (Hotspot)	Body Back	0.34	0.64	0.980
	Body Left	0.03	/	0.030
	Body Right	0.03	0.13	0.160
	Body Top	/	0.35	0.350
	Body Bottom	0.23	/	0.230
PCS1900 + WLAN(5.8G)	Head Left Cheek	0.03	0.68	0.710
	Head Left Tilt	0.02	0.57	0.590
	Head Right Cheek	0.02	0.48	0.500
	Head Right Tilt	0.02	0.49	0.510
	Body Worn Back	0.38	0.64	1.020
GPRS 1900 + WLAN(5.8G) (Hotspot)	Body Back	0.35	0.64	0.990
	Body Left	0.07	/	0.070
	Body Right	0.06	0.13	0.190
	Body Top	/	0.35	0.350
	Body Bottom	0.78	/	0.780
WCDMA Band 2+ WLAN(5.8G)	Head Left Cheek	0.05	0.68	0.730
	Head Left Tilt	0.03	0.57	0.600
	Head Right Cheek	0.03	0.48	0.510
	Head Right Tilt	0.03	0.49	0.520
WCDMA Band 2+ WLAN(5.8G) (Hotspot)	Body Back	0.23	0.64	0.870
	Body Left	0.06	/	0.060
	Body Right	0.04	0.13	0.170
	Body Top	/	0.35	0.350
	Body Bottom	0.54	/	0.540
WCDMA Band 5+ WLAN(5.8G)	Head Left Cheek	0.15	0.68	0.830
	Head Left Tilt	0.09	0.57	0.660
	Head Right Cheek	0.17	0.48	0.650
	Head Right Tilt	0.09	0.49	0.580
WCDMA Band 5+ WLAN(5.8G) (Hotspot)	Body Back	0.28	0.64	0.920
	Body Left	0.13	/	0.130
	Body Right	0.26	0.13	0.390
	Body Top	/	0.35	0.350
	Body Bottom	0.17	/	0.170

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
LTE Band 2+ WLAN(5.8G)	Head Left Cheek	0.05	0.68	0.730
	Head Left Tilt	0.03	0.57	0.600
	Head Right Cheek	0.03	0.48	0.510
	Head Right Tilt	0.03	0.49	0.520
LTE Band 2+ WLAN(5.8G) (Hotspot)	Body Back	0.35	0.64	0.990
	Body Left	0.06	/	0.060
	Body Right	0.06	0.13	0.190
	Body Top	/	0.35	0.350
	Body Bottom	0.66	/	0.660
LTE Band 5+ WLAN(5.8G)	Head Left Cheek	0.12	0.68	0.800
	Head Left Tilt	0.07	0.57	0.640
	Head Right Cheek	0.15	0.48	0.630
	Head Right Tilt	0.07	0.49	0.560
LTE Band 5+ WLAN(5.8G) (Hotspot)	Body Back	0.09	0.64	0.730
	Body Left	0.04	/	0.040
	Body Right	0.09	0.13	0.220
	Body Top	/	0.35	0.350
	Body Bottom	0.06	/	0.060
LTE Band 7+ WLAN(5.8G)	Head Left Cheek	0.33	0.68	1.010
	Head Left Tilt	0.46	0.57	1.030
	Head Right Cheek	0.88	0.48	1.360
	Head Right Tilt	0.98	0.49	1.470
LTE Band 7+ WLAN(5.8G) (Hotspot)	Body Back	0.14	0.64	0.780
	Body Left	0.10	/	0.100
	Body Right	0.02	0.13	0.150
	Body Top	0.23	0.35	0.580
	Body Bottom	/	/	/
LTE Band 40Lower+ WLAN(5.8G)	Head Left Cheek	0.07	0.68	0.750
	Head Left Tilt	0.17	0.57	0.740
	Head Right Cheek	0.30	0.48	0.780
	Head Right Tilt	0.30	0.49	0.790
LTE Band 40Lower+ WLAN(5.8G) (Hotspot)	Body Back	0.06	0.64	0.700
	Body Left	0.03	/	0.030
	Body Right	0.01	0.13	0.140
	Body Top	/	0.35	0.350
	Body Bottom	/	/	/

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
LTE Band 40Upper+ WLAN(5.8G)	Head Left Cheek	0.14	0.68	0.820
	Head Left Tilt	0.17	0.57	0.740
	Head Right Cheek	0.31	0.48	0.790
	Head Right Tilt	0.33	0.49	0.820
LTE Band 40Upper+ WLAN(5.8G) (Hotspot)	Body Back	0.05	0.64	0.690
	Body Left	0.06	/	0.060
	Body Right	0.02	0.13	0.150
	Body Top	0.01	0.35	0.360
	Body Bottom	/	/	/
LTE Band 41&38+ WLAN(5.8G)	Head Left Cheek	0.18	0.68	0.860
	Head Left Tilt	0.24	0.57	0.810
	Head Right Cheek	0.49	0.48	0.970
	Head Right Tilt	0.53	0.49	1.020
LTE Band 41&38+ WLAN(5.8G) (Hotspot)	Body Back	0.11	0.64	0.750
	Body Left	0.05	/	0.050
	Body Right	0.02	0.13	0.150
	Body Top	0.13	0.35	0.480
	Body Bottom	0.13	/	0.130

Note:

1. Hotspot mode SAR is measured for all edges and surfaces of the device with a transmitting antenna located within 25 mm from that surface or edge; for the data modes, wireless technologies and frequency bands supporting hotspot mode.
2. Hotspot Mode is not feasible during voice calls.
3. Please Refer to the SAR Report SZ1210426-13944E-20.

Conclusion:

Sum of SAR: Σ SAR $\leq$ 1.6 W/kg therefore simultaneous transmission SAR with Volume Scans is **not required**.

SAR Plots

Please Refer to the Attachment.

APPENDIX A MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Source of uncertainty	Tolerance/ uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)
Measurement system							
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0	0	0.0	0.0
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Integration time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
RF ambient conditions–reflections	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Post-processing	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
Test sample related							
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Device holder uncertainty	6.3	N	1	1	1	6.3	6.3
Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
Phantom and set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Liquid conductivity target)	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2
Liquid conductivity meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity target)	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4
Liquid permittivity meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Combined standard uncertainty		RSS				12.2	12.0
Expanded uncertainty 95 % confidence interval)						24.3	23.9

Measurement uncertainty evaluation for IEC62209-2 SAR test

Source of uncertainty	Tolerance/uncertainty $\pm \%$	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty $\pm \%$, (1 g)	Standard uncertainty $\pm \%$, (10 g)
Measurement system							
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0	0	0.0	0.0
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Modulation Response	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Integration time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
RF ambient conditions–reflections	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Post-processing	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
Test sample related							
Device holder Uncertainty	6.3	N	1	1	1	6.3	6.3
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Power scaling	4.5	R	$\sqrt{3}$	1	1	2.6	2.6
Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
Phantom and set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Algorithm for correcting SAR for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.1	0.9
Liquid conductivity (meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity (meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Temp. unc. - Conductivity	1.7	R	$\sqrt{3}$	0.78	0.71	0.8	0.7
Temp. unc. - Permittivity	0.3	R	$\sqrt{3}$	0.23	0.26	0.0	0.0
Combined standard uncertainty		RSS				12.2	12.1
Expanded uncertainty 95 % confidence interval)						24.5	24.2

APPENDIX B EUT TEST POSITION PHOTOS

Please Refer to the Attachment.

APPENDIX C PROBE CALIBRATION CERTIFICATES

Please Refer to the Attachment.

APPENDIX D DIPOLE CALIBRATION CERTIFICATES

Please Refer to the Attachment.

******* END OF REPORT *******