

# TEST REPORT

Applicant Name : Shenzhen Youmi Intelligent Technology Co., Ltd.  
Address : 406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China  
Report Number : SZ1210909-53551E-RF-00A  
FCC ID: 2ATZ4-RP01X  
IC 26074-RP01X

## Test Standard (s)

FCC PART 15.247; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2; RSS-247, ISSUE 2, FEBRUARY 2017

## Sample Description

Product Type: RP01  
Model No.: RP01  
Multiple Model(s) No.: RP03, RP04  
Trade Mark: UMIDIGI  
Date Received: 2021/09/09  
Date of Test: 2021/09/26~2021/11/03  
Report Date: 2021/11/11

Test Result:	Pass*
--------------	-------

\* In the configuration tested, the EUT complied with the standards above.

## Prepared and Checked By:



Ting Lü  
EMC Engineer

## Approved By:



Candy Li  
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk ★.

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk \*\*. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY.....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EQUIPMENT MODIFICATIONS .....	7
EUT EXERCISE SOFTWARE .....	7
SUPPORT EQUIPMENT LIST AND DETAILS .....	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP .....	8
<b>SUMMARY OF TEST RESULTS.....</b>	<b>10</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>11</b>
<b>FCC §15.247 (I), §1.1307 (B) (1) &amp; §2.1093 – RF EXPOSURE .....</b>	<b>13</b>
APPLICABLE STANDARD .....	13
<b>RSS-102 – RF EXPOSURE.....</b>	<b>14</b>
APPLICABLE STANDARD .....	14
<b>§15.203 &amp; RSS-GEN §6.8 ANTENNA REQUIREMENT.....</b>	<b>15</b>
APPLICABLE STANDARD .....	15
ANTENNA CONNECTOR CONSTRUCTION .....	16
<b>§15.207 (A) &amp; RSS-GEN §8.8 AC LINE CONDUCTED EMISSIONS .....</b>	<b>17</b>
APPLICABLE STANDARD .....	17
EUT SETUP.....	18
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE .....	18
CORRECTED FACTOR & MARGIN CALCULATION .....	19
TEST DATA .....	19
<b>§15.205, §15.209, §15.247(D) &amp; RSS-GEN §8.10 &amp; RSS-247 §5.5 SPURIOUS EMISSIONS .....</b>	<b>22</b>
APPLICABLE STANDARD .....	22
EUT SETUP .....	22
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	23
TEST PROCEDURE .....	24
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	24
TEST DATA .....	24
<b>§15.247 (A)(2) &amp; RSS-GEN §6.7 RSS-247 §5.2 (A) 99% OCCUPIED BANDWIDTH &amp; 6 DB EMISSION BANDWIDTH.....</b>	<b>33</b>
APPLICABLE STANDARD .....	33
TEST PROCEDURE .....	33
TEST DATA .....	34
<b>§15.247(B)(3) &amp; RSS-247 §5.4(D) MAXIMUM CONDUCTED OUTPUT POWER .....</b>	<b>35</b>

APPLICABLE STANDARD .....	35
TEST PROCEDURE .....	35
TEST DATA .....	36
<b>§15.247(D) &amp; RSS-247 § 5.5 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>37</b>
APPLICABLE STANDARD .....	37
TEST PROCEDURE .....	37
TEST DATA .....	37
<b>§15.247(E) &amp; RSS-247 § 5.2 (B) POWER SPECTRAL DENSITY .....</b>	<b>38</b>
APPLICABLE STANDARD .....	38
TEST PROCEDURE .....	38
TEST DATA .....	39
<b>APPENDIX WI-FI.....</b>	<b>40</b>
APPENDIX A: DTS BANDWIDTH .....	40
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH .....	45
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER.....	50
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY .....	51
APPENDIX E: BAND EDGE MEASUREMENTS.....	56
APPENDIX F: DUTY CYCLE .....	59
<b>APPENDIX BLE.....</b>	<b>61</b>
APPENDIX A: DTS BANDWIDTH .....	61
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH .....	63
APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER.....	65
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY .....	66
APPENDIX E: BAND EDGE MEASUREMENTS.....	67
APPENDIX F: DUTY CYCLE .....	68

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Product	RP01
Tested Model	RP01
Multiple Models	RP03, RP04
Model Differences	Refer to the DoS letter
HVIN	G2189U-PT-V1.0, G2102U-MU-V1.0, H872_MB_V1
Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2472MHz
Maximum Conducted Peak Output Power	BLE: 4.23dBm Wi-Fi: 6.39dBm(802.11b), 13.92dBm(802.11g) 13.72dBm(802.11n-HT20), 13.05dBm(802.11n-HT40)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	1.8dBi (It is provided by the applicant)
Voltage Range	DC 3.87V from battery or DC 5V from adapter
Date of Test	2021-9-26 to 2021-11-03
Sample serial number	SZ1210909-53551E-RF-S1 for RF conducted SZ1210909-53551E-RF-S6 for CE&RE (Assigned by ATC)
Received date	2021-09-09
Sample/EUT Status	Good condition
Adapter information	Model: HJ-0502000W2-US Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 2.0A

### Objective

This report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules and RSS-GEN Issue 5, February 2021 Amendment 2 and RSS-247, Issue 2, February 2017 of the Innovation, Science and Economic Development Canada rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliant Testing of Unlicensed Wireless Devices and RSS-GEN Issue 5, February 2021 Amendment 2 and RSS-247, Issue 2, February 2017.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

## Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	5%	
RF Frequency	$0.082 \times 10^{-7}$	
RF output power, conducted	0.73dB	
Unwanted Emission, conducted	1.6dB	
AC Power Lines Conducted Emissions	2.72dB	
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature	1°C	
Humidity	6%	
Supply voltages	0.4%	

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20, EUT was tested with Channel 1, 7 and 13.

For 802.11n-HT40, EUT was tested with Channel 3, 7 and 11.

Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

## Equipment Modifications

No modification was made to the EUT tested.

## EUT Exercise Software

EUT testing in engineering mode.

The device was tested with the worst case was performed as below:

Mode	Date rate	Power Level		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	7	7	7
802.11g	6Mbps	12	12	12
802.11n-HT20	MCS0	12	12	12
802.11n-HT40	MCS0	10	10	10
BLE	1Mbps	Default	Default	Default

## Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Earphone	Unknown	Unknown

## External I/O Cable


Cable Description	Length (m)	From	To
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

## Block Diagram of Test Setup


For conducted emission:



For radiated emission: Below 1GHz



For radiated emission: Above 1GHz



## SUMMARY OF TEST RESULTS

FCC Rules	RSS Rules	Description of Test	Result
§15.247 (i), §2.1093	RSS-102	RF EXPOSURE	Compliant
§15.203	RSS-Gen §6.8	Antenna Requirement	Compliant
§15.207 (a)	RSS-Gen §8.8	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	RSS-GEN § 8.10 & RSS-247 §5.5	Spurious Emissions	Compliant
§15.247 (a)(2)	RSS- Gen §6.7 RSS-247 § 5.2 (a)	99% Occupied Bandwidth & 6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	RSS-247 § 5.4(d)	Maximum Conducted Output Power	Compliant
§15.247(d)	RSS-247 § 5.5	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	RSS-247 § 5.2 (b)	Power Spectral Density	Compliant

## TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	Test Receiver	ESPI3	100396	2020/12/24	2021/12/23
R & S	L.I.S.N.	ENV216	101314	2020/12/25	2021/12/24
Anritsu Corp	50ΩCoaxial Switch	MP59B	6200506474	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-2m	No.2	2020/12/25	2021/12/24
Conducted Emission Test Software: ES-K1 V1.71					
Radiated Emissions Test					
Rohde & Schwarz	Test Receiver	ESR	101817	2020/12/24	2021/12/23
Rohde & Schwarz	Spectrum Analyzer	FSV40	101495	2020/12/24	2021/12/23
SONOMA INSTRUMENT	Amplifier	310 N	186131	2020/12/25	2021/12/24
A.H. Systems, inc.	Preamplifier	PAM-0118P	531	2021/07/08	2022/07/07
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2020/12/25	2021/12/24
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2020/01/05	2023/01/04
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Unknown	RF Coaxial Cable	N-5m	No.3	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-5m	No.4	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.5	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.6	2020/12/25	2021/12/24
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2020/12/25	2021/12/24
Radiated Emission Test Software: EZ_EMCA V 1.1.4.2					
Radiated Emission Test Software: e3 19821G (V9)					

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2020/12/24	2021/12/23
Tonscend	RF Control Unit	JS0806-2	19G8060182	2021/07/06	2022/07/05

**\* Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**FCC §15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE****Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^{1/2}$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

**Measurement Result****For worst case:**

Mode	Frequency (MHz)	Max tune-up conducted power (dBm)	Max tune-up conducted power (mW)	Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2480	4.5	2.82	5	0.9	3.0	Yes
WIFI	2472	9.5	8.91	5	2.8	3.0	Yes

**Result: No SAR test is required**

## **RSS-102 – RF EXPOSURE**

### **Applicable Standard**

According to RSS-102, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

**Result:** Compliance.

Please refer to SAR Report Number: SZ1210909-53551E-20B.

## § 15.203 & RSS-Gen §6.8 ANTENNA REQUIREMENT

### Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

## Antenna Connector Construction

The EUT has an internal antenna arrangement which was permanently attached and the antenna gain is 1.8 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Type	Antenna Gain	Impedance
PIFA	1.8 dBi	50Ω

**Result: Compliant**

## § 15.207 (a) & RSS-GEN §8.8 AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC § 15.207 (a) & RSS-GEN §8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50  $\mu$ H / 50  $\Omega$  line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.


Table 4 - AC Power Lines Conducted Emission Limits		
Frequency range (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 <sup>1</sup>	56 to 46 <sup>1</sup>
0.5 – 5	56	46
5 – 30	60	50

**Note 1:** The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

- Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.
- Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

## EUT Setup



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 & RSS-247/RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

## Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


## Test Data

### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	65 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Amy Cao on 2021-09-26.*

*EUT operation mode: Transmitting (worst case is 802.11g mode, high channel)*

**AC 120V/60 Hz, Line****MEASUREMENT RESULT: "53551-6L\_fin"**


2021-9-26 11:08

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.230000	32.00	10.9	62	30.0	QP	L1	GND
0.750000	41.60	11.1	56	14.4	QP	L1	GND
0.880000	39.80	11.1	56	16.2	QP	L1	GND
2.380000	33.20	11.3	56	22.8	QP	L1	GND
12.150000	37.00	11.6	60	23.0	QP	L1	GND
20.150000	46.10	11.7	60	13.9	QP	L1	GND

**MEASUREMENT RESULT: "53551-6L\_fin2"**

2021-9-26 11:08

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.245000	22.20	10.9	52	29.8	AV	L1	GND
0.760000	29.90	11.1	46	16.1	AV	L1	GND
0.880000	27.50	11.1	46	18.5	AV	L1	GND
2.330000	22.60	11.3	46	23.4	AV	L1	GND
12.325000	24.70	11.6	50	25.3	AV	L1	GND
18.900000	32.20	11.7	50	17.8	AV	L1	GND

**AC 120V/60 Hz, Neutral****MEASUREMENT RESULT: "53551-6N\_fin"**

2021-9-26 11:06

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.355000	32.40	10.9	59	26.6	QP	N	GND
0.700000	46.70	11.1	56	9.3	QP	N	GND
0.900000	40.80	11.1	56	15.2	QP	N	GND
2.190000	38.50	11.3	56	17.5	QP	N	GND
12.175000	38.00	11.6	60	22.0	QP	N	GND
20.200000	43.20	11.7	60	16.8	QP	N	GND

**MEASUREMENT RESULT: "53551-6N\_fin2"**

2021-9-26 11:06

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.325000	30.50	10.9	50	19.5	AV	N	GND
0.700000	37.20	11.1	46	8.8	AV	N	GND
0.940000	30.60	11.1	46	15.4	AV	N	GND
2.210000	27.60	11.3	46	18.4	AV	N	GND
12.400000	26.10	11.6	50	23.9	AV	N	GND
19.350000	32.00	11.7	50	18.0	AV	N	GND

## §15.205, §15.209, §15.247(d) & RSS-GEN §8.10 & RSS-247 §5.5 SPURIOUS EMISSIONS

### Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


According to RSS-GEN § 8.10 & RSS-247 § 5.5


Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:(a) The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, Emergency Position Indicating Radio Beacons (EPIRB), Emergency Locator Transmitters (ELT), Personal Locator Beacons (PLB), and Maritime Survivor Locator Devices (MSLD).(b) Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.(c) Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### EUT Setup

Below 1 GHz:



**Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013 & RSS-Gen. The specification used was the FCC 15.209, and FCC 15.247 & RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz <sup>Note 1</sup>	/	Average
	1MHz	>1/T <sup>Note 2</sup>	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

## Test Data

### Environmental Conditions


Temperature:	23~25 °C
Relative Humidity:	48~50 %
ATM Pressure:	101.0 kPa

*The testing was performed by Caro Hu on 2021-09-28 for below 1GHz and Chao Mo on 2021-11-03 for above 1GHz.*

*EUT operation mode: Transmitting(Scan with X-AXIS, Y-AXIS, Z-AXIS, the worst case was recorded)*


**30 MHz~1 GHz:** (worst case is 802.11g mode, high channel)

Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	55.0274	40.11	-17.41	22.70	40.00	-17.30	QP			
2	98.8326	34.61	-18.49	16.12	43.50	-27.38	QP			
3	180.6488	46.09	-18.45	27.64	43.50	-15.86	QP			
4	207.8501	43.12	-17.49	25.63	43.50	-17.87	QP			
5	302.4812	42.55	-14.50	28.05	46.00	-17.95	QP			
6	706.6999	26.78	-6.86	19.92	46.00	-26.08	QP			

Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	31.0706	45.78	-13.88	31.90	40.00	-8.10	QP			
2	54.0711	46.21	-17.61	28.60	40.00	-11.40	QP			
3	98.8326	37.11	-18.49	18.62	43.50	-24.88	QP			
4	216.0240	37.64	-17.19	20.45	46.00	-25.55	QP			
5	289.0021	35.98	-14.94	21.04	46.00	-24.96	QP			
6	462.3455	28.14	-10.68	17.46	46.00	-28.54	QP			

**1 GHz-25 GHz:****For Wi-Fi**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)					
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
<b>802.11b Mode</b>														
Low Channel (2412 MHz)														
2310	68.28	PK	160	1.6	H	-6.84	61.44	74	-12.56					
2310	54.12	Ave.	160	1.6	H	-6.84	47.28	54	-6.72					
2310	66.56	PK	99	1.1	V	-6.84	59.72	74	-14.28					
2310	53.15	Ave.	99	1.1	V	-6.84	46.31	54	-7.69					
2390	69.13	PK	38	1.8	H	-6.44	62.69	74	-11.31					
2390	54.26	Ave.	38	1.8	H	-6.44	47.82	54	-6.18					
2390	67.63	PK	137	2.1	V	-6.44	61.19	74	-12.81					
2390	53.51	Ave.	137	2.1	V	-6.44	47.07	54	-6.93					
4824	52.53	PK	203	1.9	H	2.87	55.40	74	-18.60					
4824	46.95	Ave.	203	1.9	H	2.87	49.82	54	-4.18					
4824	49.97	PK	150	1.6	V	2.87	52.84	74	-21.16					
Middle Channel (2442MHz)														
4884	53.87	PK	345	1	H	3.04	56.91	74	-17.09					
4884	47.95	Ave.	345	1	H	3.04	50.99	54	-3.01					
4884	50.83	PK	140	1.4	H	3.04	53.87	74	-20.13					
High Channel (2472 MHz)														
2483.5	68.23	PK	265	1.5	H	-5.96	62.27	74	-11.73					
2483.5	53.75	Ave.	265	1.5	H	-5.96	47.79	54	-6.21					
2483.5	66.71	PK	338	2	V	-5.96	60.75	74	-13.25					
2483.5	52.93	Ave.	338	2	V	-5.96	46.97	54	-7.03					
2500	67.43	PK	291	1.3	H	-5.88	61.55	74	-12.45					
2500	53.17	Ave.	291	1.3	H	-5.88	47.29	54	-6.71					
2500	65.55	PK	202	1.4	V	-5.88	59.67	74	-14.33					
2500	51.72	Ave.	202	1.4	V	-5.88	45.84	54	-8.16					
4944	54.06	PK	44	2.3	H	3.29	57.35	74	-16.65					
4944	47.65	Ave.	44	2.3	H	3.29	50.94	54	-3.06					
4944	50.69	PK	236	2.2	V	3.29	53.98	74	-20.02					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)					
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
<b>802.11g Mode</b>														
Low Channel (2412 MHz)														
2310	69.13	PK	332	1.6	H	-6.84	62.29	74	-11.71					
2310	54.76	Ave.	332	1.6	H	-6.84	47.92	54	-6.08					
2310	66.58	PK	91	2.2	V	-6.84	59.74	74	-14.26					
2310	52.17	Ave.	91	2.2	V	-6.84	45.33	54	-8.67					
2390	68.59	PK	225	1.7	H	-6.44	62.15	74	-11.85					
2390	54.27	Ave.	225	1.7	H	-6.44	47.83	54	-6.17					
2390	66.88	PK	110	1.7	V	-6.44	60.44	74	-13.56					
2390	52.52	Ave.	110	1.7	V	-6.44	46.08	54	-7.92					
4824	59.03	PK	8	2.1	H	2.87	61.90	74	-12.10					
4824	43.45	Ave.	8	2.1	H	2.87	46.32	54	-7.68					
4824	55.80	PK	30	1.7	V	2.87	58.67	74	-15.33					
4824	40.92	Ave.	30	1.7	V	2.87	43.79	54	-10.21					
Middle Channel (2442 MHz)														
4884	59.59	PK	356	1.2	H	3.04	62.63	74	-11.37					
4884	43.88	Ave.	356	1.2	H	3.04	46.92	54	-7.08					
4884	56.34	PK	355	1.8	V	3.04	59.38	74	-14.62					
4884	40.95	Ave.	355	1.8	V	3.04	43.99	54	-10.01					
High Channel (2472 MHz)														
2483.5	73.53	PK	259	2.5	H	-5.96	67.57	74	-6.43					
2483.5	56.48	Ave.	259	2.5	H	-5.96	50.52	54	-3.48					
2483.5	72.70	PK	100	1.1	V	-5.96	66.74	74	-7.26					
2483.5	55.67	Ave.	100	1.1	V	-5.96	49.71	54	-4.29					
2500	67.30	PK	290	1.8	H	-5.88	61.42	74	-12.58					
2500	52.87	Ave.	290	1.8	H	-5.88	46.99	54	-7.01					
2500	65.67	PK	288	2.2	V	-5.88	59.79	74	-14.21					
2500	52.05	Ave.	288	2.2	V	-5.88	46.17	54	-7.83					
4944	59.86	PK	156	1.1	H	3.29	63.15	74	-10.85					
4944	44.45	Ave.	156	1.1	H	3.29	47.74	54	-6.26					
4944	55.84	PK	242	1.2	V	3.29	59.13	74	-14.87					
4944	40.50	Ave.	242	1.2	V	3.29	43.79	54	-10.21					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)					
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
<b>802.11n20 Mode</b>														
Low Channel (2412 MHz)														
2310	68.23	PK	225	2.5	H	-6.84	61.39	74	-12.61					
2310	54.37	Ave.	225	2.5	H	-6.84	47.53	54	-6.47					
2310	66.62	PK	111	2.3	V	-6.84	59.78	74	-14.22					
2310	52.66	Ave.	111	2.3	V	-6.84	45.82	54	-8.18					
2390	68.96	PK	276	1.6	H	-6.44	62.52	74	-11.48					
2390	54.43	Ave.	276	1.6	H	-6.44	47.99	54	-6.01					
2390	67.27	PK	257	2.1	V	-6.44	60.83	74	-13.17					
2390	52.63	Ave.	257	2.1	V	-6.44	46.19	54	-7.81					
4824	57.68	PK	251	2.1	H	2.87	60.55	74	-13.45					
4824	42.17	Ave.	251	2.1	H	2.87	45.04	54	-8.96					
4824	55.91	PK	80	1.9	V	2.87	58.78	74	-15.22					
4824	40.75	Ave.	80	1.9	V	2.87	43.62	54	-10.38					
Middle Channel (2442MHz)														
4884	58.15	PK	95	1.4	H	3.04	61.19	74	-12.81					
4884	43.47	Ave.	95	1.4	H	3.04	46.51	54	-7.49					
4884	56.15	PK	264	2.2	V	3.04	59.19	74	-14.81					
4884	41.33	Ave.	264	2.2	V	3.04	44.37	54	-9.63					
High Channel (2472 MHz)														
2483.5	73.53	PK	49	2.2	H	-5.96	67.57	74	-6.43					
2483.5	56.48	Ave.	49	2.2	H	-5.96	50.52	54	-3.48					
2483.5	72.34	PK	78	2.1	V	-5.96	66.38	74	-7.62					
2483.5	55.37	Ave.	78	2.1	V	-5.96	49.41	54	-4.59					
2500	71.19	PK	252	1.3	H	-5.88	65.31	74	-8.69					
2500	56.24	Ave.	252	1.3	H	-5.88	50.36	54	-3.64					
2500	70.52	PK	166	1.9	V	-5.88	64.64	74	-9.36					
2500	55.30	Ave.	166	1.9	V	-5.88	49.42	54	-4.58					
4944	58.31	PK	38	1.5	H	3.29	61.60	74	-12.40					
4944	43.68	Ave.	38	1.5	H	3.29	46.97	54	-7.03					
4944	55.42	PK	2	1.8	V	3.29	58.71	74	-15.29					
4944	40.40	Ave.	2	1.8	V	3.29	43.69	54	-10.31					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)					
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)									
<b>802.11n40 Mode</b>														
Low Channel (2422 MHz)														
2310	73.86	PK	87	2.1	H	-6.84	67.02	74	-6.98					
2310	57.44	Ave.	87	2.1	H	-6.84	50.6	54	-3.40					
2310	73.01	PK	37	1.4	V	-6.84	66.17	74	-7.83					
2310	56.59	Ave.	37	1.4	V	-6.84	49.75	54	-4.25					
2390	69.66	PK	213	1.4	H	-6.44	63.22	74	-10.78					
2390	55.14	Ave.	213	1.4	H	-6.44	48.7	54	-5.30					
2390	68.08	PK	29	2.3	V	-6.44	61.64	74	-12.36					
2390	53.63	Ave.	29	2.3	V	-6.44	47.19	54	-6.81					
4844	55.22	PK	127	1.4	H	2.92	58.14	74	-15.86					
4844	43.75	Ave.	127	1.4	H	2.92	46.67	54	-7.33					
4844	52.82	PK	161	1.4	V	2.92	55.74	74	-18.26					
4844	41.06	Ave.	161	1.4	V	2.92	43.98	54	-10.02					
Middle Channel (2442MHz)														
4884	55.96	PK	35	1.7	H	3.04	59.00	74	-15.00					
4884	44.84	Ave.	35	1.7	H	3.04	47.88	54	-6.12					
4884	52.83	PK	60	1.8	V	3.04	55.87	74	-18.13					
4884	41.09	Ave.	60	1.8	V	3.04	44.13	54	-9.87					
High Channel (2462 MHz)														
2483.5	70.20	PK	296	1.1	H	-5.96	64.24	74	-9.76					
2483.5	56.44	Ave.	296	1.1	H	-5.96	50.48	54	-3.52					
2483.5	68.73	PK	243	1.1	V	-5.96	62.77	74	-11.23					
2483.5	54.70	Ave.	243	1.1	V	-5.96	48.74	54	-5.26					
2500	67.38	PK	188	1.6	H	-5.88	61.50	74	-12.50					
2500	53.20	Ave.	188	1.6	H	-5.88	47.32	54	-6.68					
2500	65.50	PK	241	2.2	V	-5.88	59.62	74	-14.38					
2500	52.07	Ave.	241	2.2	V	-5.88	46.19	54	-7.81					
4924	56.34	PK	25	2.5	H	3.17	59.51	74	-14.49					
4924	44.96	Ave.	25	2.5	H	3.17	48.13	54	-5.87					
4924	52.97	PK	267	1.3	V	3.17	56.14	74	-17.86					
4924	41.55	Ave.	267	1.3	V	3.17	44.72	54	-9.28					

**BLE:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2310	68.59	PK	215	1.6	H	-6.84	61.75	74	-12.25
2310	54.36	Ave.	215	1.6	H	-6.84	47.52	54	-6.48
2310	67.46	PK	219	1.5	V	-6.84	60.62	74	-13.38
2310	53.63	Ave.	219	1.5	V	-6.84	46.79	54	-7.21
2390	68.17	PK	316	1.4	H	-6.44	61.73	74	-12.27
2390	54.17	Ave.	316	1.4	H	-6.44	47.73	54	-6.27
2390	67.48	PK	295	2.4	V	-6.44	61.04	74	-12.96
2390	53.61	Ave.	295	2.4	V	-6.44	47.17	54	-6.83
4804	52.83	PK	73	2.2	H	2.81	55.64	74	-18.36
4804	47.07	Ave.	73	2.2	H	2.81	49.88	54	-4.12
4804	52.50	PK	359	1.7	V	2.81	55.31	74	-18.69
4804	46.36	Ave.	359	1.7	V	2.81	49.17	54	-4.83
Middle Channel (2440 MHz)									
4880	52.99	PK	299	1.8	H	3.04	56.03	74	-17.97
4880	47.68	Ave.	299	1.8	H	3.04	50.72	54	-3.28
4880	52.71	PK	256	1.6	V	3.04	55.75	74	-18.25
4880	46.45	Ave.	256	1.6	V	3.04	49.49	54	-4.51
High Channel (2480 MHz)									
2483.5	67.84	PK	48	1.3	H	-5.96	61.88	74	-12.12
2483.5	53.81	Ave.	48	1.3	H	-5.96	47.85	54	-6.15
2483.5	66.80	PK	246	1.5	V	-5.96	60.84	74	-13.16
2483.5	52.73	Ave.	246	1.5	V	-5.96	46.77	54	-7.23
2500	67.40	PK	182	2.3	H	-5.88	61.52	74	-12.48
2500	53.43	Ave.	182	2.3	H	-5.88	47.55	54	-6.45
2500	65.95	PK	195	1	V	-5.88	60.07	74	-13.93
2500	52.00	Ave.	195	1	V	-5.88	46.12	54	-7.88
4960	54.73	PK	65	1.8	H	3.29	58.02	74	-15.98
4960	49.66	Ave.	65	1.8	H	3.29	52.95	54	-1.05
4960	53.14	PK	1	1.5	V	3.29	56.43	74	-17.57
4960	47.38	Ave.	1	1.5	V	3.29	50.67	54	-3.33

**Note:**

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Corrected. Amplitude - Limit

The other spurious emission which is 20dB to the limit was not recorded.


1-18 GHz:



## Pre-scan for BLE High Channel

Horizontal



Vertical



**18 -25GHz:****Pre-scan for BLE High Channel****Horizontal****Vertical**

## **§15.247 (a)(2) & RSS-Gen §6.7 RSS-247 § 5.2 (a) 99% OCCUPIED BANDWIDTH & 6 dB EMISSION BANDWIDTH**

### **Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “6 dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 6 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.


The following conditions shall be observed for measuring the occupied bandwidth and 6 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 6 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 6 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed

in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



## Test Data

### Environmental Conditions

<b>Temperature:</b>	27 °C
<b>Relative Humidity:</b>	57 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Paul liu on 2021-10-26 and 2021-10-27.*

*EUT operation mode: Transmitting*

Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.

## §15.247(b)(3) & RSS-247 § 5.4(d) MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



## Test Data

### Environmental Conditions

Temperature:	27 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

*The testing was performed by Paul liu on 2021-10-26 and 2021-10-27.*

*EUT operation mode: Transmitting*

Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.


## § 15.247(d) & RSS-247 § 5.5 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VSWR of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



### Test Data

#### Environmental Conditions

Temperature:	27 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

The testing was performed by Paul liu on 2021-10-26 and 2021-10-27.

EUT operation mode: Transmitting

Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.

## §15.247(e) & RSS-247 §5.2 (b) POWER SPECTRAL DENSITY


### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



## Test Data

### Environmental Conditions

Temperature:	27 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

*The testing was performed by Paul liu on 2021-10-26 and 2021-10-27.*

*EUT operation mode: Transmitting*


Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.




## APPENDIX Wi-Fi



### Appendix A: DTS Bandwidth Test Result



Test Mode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	7.680	0.5	PASS
		2442	7.200	0.5	PASS
		2472	7.200	0.5	PASS
11G	Ant1	2412	16.400	0.5	PASS
		2442	16.440	0.5	PASS
		2472	16.440	0.5	PASS
11N20SISO	Ant1	2412	17.680	0.5	PASS
		2442	17.680	0.5	PASS
		2472	17.680	0.5	PASS
11N40SISO	Ant1	2422	36.000	0.5	PASS
		2442	36.240	0.5	PASS
		2462	36.240	0.5	PASS


### Test Graphs












## Appendix B: Occupied Channel Bandwidth Test Result



Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	14.066	---	PASS
		2442	14.306	---	PASS
		2472	14.306	---	PASS
11G	Ant1	2412	17.343	---	PASS
		2442	17.263	---	PASS
		2472	17.263	---	PASS
11N20SISO	Ant1	2412	18.142	---	PASS
		2442	18.142	---	PASS
		2472	18.102	---	PASS
11N40SISO	Ant1	2422	36.683	---	PASS
		2442	36.923	---	PASS
		2462	36.523	---	PASS


## Test Graphs











## Appendix C: Maximum conducted output power Test Result

Peak:

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	5.90	≤30	PASS
		2442	5.40	≤30	PASS
		2472	6.39	≤30	PASS
11G	Ant1	2412	13.61	≤30	PASS
		2442	13.42	≤30	PASS
		2472	13.92	≤30	PASS
11N20SISO	Ant1	2412	13.39	≤30	PASS
		2442	13.72	≤30	PASS
		2472	13.27	≤30	PASS
11N40SISO	Ant1	2422	12.68	≤30	PASS
		2442	13.05	≤30	PASS
		2462	12.81	≤30	PASS

Av:


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	3.67	≤30	PASS
		2442	3.21	≤30	PASS
		2472	4.52	≤30	PASS
11G	Ant1	2412	8.76	≤30	PASS
		2442	8.68	≤30	PASS
		2472	9.20	≤30	PASS
11N20SISO	Ant1	2412	7.92	≤30	PASS
		2442	8.59	≤30	PASS
		2472	8.03	≤30	PASS
11N40SISO	Ant1	2422	8.34	≤30	PASS
		2442	9.08	≤30	PASS
		2462	8.31	≤30	PASS




Note: the maximum antenna gain is 1.8dBi, the maximum EIRP=13.92dBm+1.8dBi=15.72dBm<36dBm, so it's compliance with ISED/C EIRP limit.




## Appendix D: Maximum power spectral density Test Result




Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-18.14	≤8	PASS
		2442	-18.65	≤8	PASS
		2472	-17.94	≤8	PASS
11G	Ant1	2412	-16.73	≤8	PASS
		2442	-16.74	≤8	PASS
		2472	-15.66	≤8	PASS
11N20SISO	Ant1	2412	-16.59	≤8	PASS
		2442	-15.98	≤8	PASS
		2472	-16.67	≤8	PASS
11N40SISO	Ant1	2422	-18.19	≤8	PASS
		2442	-17.57	≤8	PASS
		2462	-18.43	≤8	PASS


## Test Graphs














## Appendix E: Band edge measurements

### Test Graphs









## Appendix F: Duty Cycle

### Test Result

Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2442	30.00	30.00	100.00
11G	Ant1	2442	30.00	30.00	100.00
11N20SISO	Ant1	2442	30.00	30.00	100.00
11N40SISO	Ant1	2442	30.00	30.00	100.00

### Test Graphs







## APPENDIX BLE

### Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.708	0.5	PASS
		2440	0.700	0.5	PASS
		2480	0.692	0.5	PASS

### Test Graphs







## Appendix B: Occupied Channel Bandwidth Test Result

Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.035	---	PASS
		2440	1.035	---	PASS
		2480	1.035	---	PASS

### Test Graphs





**Appendix C: Maximum conducted Peak output power  
Test Result**


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	3.92	≤30	PASS
		2440	3.84	≤30	PASS
		2480	4.23	≤30	PASS

Note: the maximum antenna gain is 1.8dBi, the maximum EIRP=4.23dBm+1.8dBi=6.03dBm<36dBm, so it's compliance with ISEDC EIRP limit.

## Appendix D: Maximum power spectral density Test Result


Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-11.48	≤8	PASS
		2440	-12.08	≤8	PASS
		2480	-11.64	≤8	PASS

### Test Graphs



## Appendix E: Band edge measurements

### Test Graphs




## Appendix F: Duty Cycle

### Test Result

Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
BLE_1M	Ant1	2440	0.38	0.62	61.29

### Test Graphs



\*\*\*\*\* END OF REPORT \*\*\*\*\*