

# FCC REPORT

**Applicant:** Shenzhen Youmi Intelligent Technology Co., Ltd.

**Address of Applicant:** 406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China.

## Equipment Under Test (EUT)

**Product Name:** Smart phone

**Model No.:** A3S

**Trade mark:** UMIDIGI

**FCC ID:** 2ATZ4A3S

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart B

**Date of sample receipt:** 30 Apr., 2020

**Date of Test:** 05 Jun., to 12 Jun., 2020

**Date of report issued:** 15 Jun., 2020

**Test Result:** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang

Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

**2 Version**

Version No.	Date	Description
00	15 Jun., 2020	Original

**Tested by:****Test Engineer****Date:** 15 Jun., 2020**Reviewed by:****Project Engineer****Date:** 15 Jun., 2020

### 3 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 VERSION.....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>3</b>
<b>4 TEST SUMMARY.....</b>	<b>4</b>
<b>5 GENERAL INFORMATION .....</b>	<b>5</b>
5.1 CLIENT INFORMATION .....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY.....	5
5.5 DESCRIPTION OF SUPPORT UNITS .....	6
5.6 RELATED SUBMITTAL(S) / GRANT (s).....	6
5.7 DESCRIPTION OF CABLE USED .....	6
5.8 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD .....	6
5.9 LABORATORY FACILITY.....	6
5.10 LABORATORY LOCATION.....	6
5.11 TEST INSTRUMENTS LIST.....	7
<b>6 TEST RESULTS AND MEASUREMENT DATA .....</b>	<b>8</b>
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION .....	11
<b>7 TEST SETUP PHOTO.....</b>	<b>17</b>
<b>8 EUT CONSTRUCTIONAL DETAILS.....</b>	<b>18</b>

## 4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass
<b>Remark:</b>		
1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: The EUT not applicable of the test item.		
Test Method:	ANSI C63.4:2014	

## 5 General Information

### 5.1 Client Information

Applicant:	Shenzhen Youmi Intelligent Technology Co., Ltd.
Address:	406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China.
Manufacturer:	Shenzhen Youmi Intelligent Technology Co., Ltd.
Address:	406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China.

### 5.2 General Description of E.U.T.

Product Name:	Smart phone
Model No.:	A3S
Power supply:	Rechargeable Li-Polymer Battery DC3.85V-3950mAh
AC adapter:	Model: HJ-0501000B2-US Input: AC100-240V, 50/60Hz, 0.15A Output: DC 5.0V, 1000mA
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

### 5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
FM mode	Keep the EUT in FM receiver mode
GPS mode	Keep the EUT in GPS receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

### 5.4 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.16 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.20 dB (k=2)

## 5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX7070	2J8XSZ2	DoC
DELL	MONITOR	SE2018HR	3M7QPY2	DoC
DELL	KEYBOARD	KB216d	N/A	DoC
DELL	MOUSE	MS116t1	N/A	DoC
HP	Printer	HP LaserJet P1007	VNFP409729	DoC

## 5.6 Related Submittal(s) / Grant (s)

This is an original grant, no related submittals and grants.

## 5.7 Description of Cable Used

Cable Type	Description	Length	From	To
Detached USB Cable	Shielding	1.0m	EUT	PC/Adapter

## 5.8 Additions to, deviations, or exclusions from the method

No

## 5.9 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

## 5.10 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,

Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: [info@ccis-cb.com](mailto:info@ccis-cb.com), Website: <http://www.ccis-cb.com>


## 5.11 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-07-2020	03-06-2021
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2019	11-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2020	03-06-2021
Pre-amplifier	CD	PAP-1G18	11804	03-07-2020	03-06-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-05-2020	03-04-2021
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2019	11-17-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-05-2020	03-04-2021
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2020	03-06-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2020	03-06-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2020	03-06-2021

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-05-2020	03-04-2021
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-05-2020	03-04-2021
LISN	CHASE	MN2050D	1447	03-05-2020	03-04-2021
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2017	07-20-2020
Cable	HP	10503A	N/A	03-05-2020	03-04-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		


## 6 Test results and Measurement Data

### 6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107		
Test Frequency Range:	150kHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)		Limit (dB $\mu$ V)
			Quasi-peak
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	0.5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	 <p>Remark:    E.U.T: Equipment Under Test    LISN: Line Impedance Stabilization Network    Test table height=0.8m</p>		
Test procedure	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). They provide a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4(latest version) on conducted measurement.</li> </ol>		
Test Instruments:	Refer to section 5.11 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		

## Measurement data:

Product name:	Smart phone	Product model:	A3S
Test by:	Carey	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%




Freq MHz	Read Level dBuV	LISN Factor dB	Cable Loss dB	Level dBuV	Limit Line dBuV	Over Limit dB	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.222	32.71	-0.58	10.76	42.70	62.74	-20.04 QP
2	0.222	20.85	-0.58	10.76	30.84	52.74	-21.90 Average
3	0.286	24.80	-0.55	10.74	34.74	60.63	-25.89 QP
4	0.365	23.98	-0.50	10.73	34.42	58.61	-24.19 QP
5	0.365	17.63	-0.50	10.73	28.07	48.61	-20.54 Average
6	0.435	26.69	-0.46	10.73	37.09	57.15	-20.06 QP
7	0.435	20.22	-0.46	10.73	30.62	47.15	-16.53 Average
8	0.510	28.12	-0.44	10.76	38.09	56.00	-17.91 QP
9	0.582	26.69	-0.48	10.76	36.60	56.00	-19.40 QP
10	0.582	19.13	-0.48	10.76	29.04	46.00	-16.96 Average
11	0.871	16.00	-0.59	10.83	26.37	46.00	-19.63 Average
12	1.016	15.99	-0.62	10.87	26.68	46.00	-19.32 Average

## Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.

<b>Product name:</b>	Smart phone	<b>Product model:</b>	A3S
<b>Test by:</b>	Carey	<b>Test mode:</b>	PC mode
<b>Test frequency:</b>	150 kHz ~ 30 MHz	<b>Phase:</b>	Neutral
<b>Test voltage:</b>	AC 120 V/60 Hz	<b>Environment:</b>	Temp: 22.5°C Huni: 55%





Trace: 1

Freq MHz	Read Level dBuV	LISN Factor	Cable Loss dB	Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.214	35.05	-0.67	10.76	45.14	63.05	-17.91 QP
2	0.214	22.41	-0.67	10.76	32.50	53.05	-20.55 Average
3	0.289	32.25	-0.67	10.74	42.33	60.54	-18.21 QP
4	0.289	23.41	-0.67	10.74	33.49	50.54	-17.05 Average
5	0.361	19.71	-0.64	10.73	29.77	48.69	-18.92 Average
6	0.437	30.03	-0.64	10.74	40.11	57.11	-17.00 QP
7	0.510	18.86	-0.65	10.76	29.00	46.00	-17.00 Average
8	0.582	27.98	-0.65	10.76	38.12	56.00	-17.88 QP
9	0.727	17.51	-0.64	10.78	27.69	46.00	-18.31 Average
10	0.731	28.32	-0.64	10.78	38.50	56.00	-17.50 QP
11	0.948	27.75	-0.67	10.85	38.00	56.00	-18.00 QP
12	0.948	15.62	-0.67	10.85	25.87	46.00	-20.13 Average

**Notes:**

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

## 6.2 Radiated Emission


Test Requirement:	FCC Part 15 B Section 15.109													
Test Frequency Range:	30MHz to 6000MHz													
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)													
Receiver setup:	Frequency	Detector	RBW	VBW	Remark									
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value									
	Above 1GHz	Peak	1MHz	3MHz	Peak Value									
Limit:	RMS	1MHz	3MHz	Average	Value									
	Frequency	Limit (dBuV/m @3m)		Remark										
	30MHz-88MHz	40.0		Quasi-peak Value										
	88MHz-216MHz	43.5		Quasi-peak Value										
	216MHz-960MHz	46.0		Quasi-peak Value										
	960MHz-1GHz	54.0		Quasi-peak Value										
Test setup:	Above 1GHz													
	Below 1GHz													
														
														
Test Procedure:	<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> </ol>													

	<ol style="list-style-type: none"><li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li><li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li><li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li></ol>
Test Instruments:	Refer to section 5.11 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	All of the observed value above 6GHz were the noise floor , which were not recorded

## Measurement Data:

Below 1GHz:

Product Name:	Smart phone	Product Model:	A3S
Test By:	Carey	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq MHz	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamplifier Factor	Limit Level dBuV/m	Line Limit dBuV/m	Over Limit dB	Remark
	MHz	dBuV	dB/m	dB	dB				
1	65.573	56.13	9.84	1.41	0.00	29.75	37.63	40.00	-2.37 QP
2	191.745	47.14	17.55	2.81	0.00	28.89	38.61	43.50	-4.89 QP
3	197.893	47.02	18.09	2.86	0.00	28.84	39.13	43.50	-4.37 QP
4	294.114	40.59	18.68	2.92	0.00	28.46	33.73	46.00	-12.27 QP
5	480.528	44.59	19.33	3.46	0.00	28.92	38.46	46.00	-7.54 QP
6	962.162	41.48	22.88	4.27	0.00	27.65	40.98	54.00	-13.02 QP

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

<b>Product Name:</b>	Smart phone	<b>Product Model:</b>	A3S
<b>Test By:</b>	Carey	<b>Test mode:</b>	PC mode
<b>Test Frequency:</b>	30 MHz ~ 1 GHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	AC 120/60Hz	<b>Environment:</b>	Temp: 24°C Huni: 57%



Freq MHz	Read	Antenna Level	Cable Loss	Aux Factor	Preamp Factor	Limit Line	Over Limit	Remark
	Freq MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 65.803	49.62	9.85	1.41	0.00	29.75	31.13	40.00	-8.87 QP
2 179.386	48.60	16.89	2.73	0.00	28.98	39.24	43.50	-4.26 QP
3 199.286	47.19	18.23	2.86	0.00	28.83	39.45	43.50	-4.05 QP
4 295.147	45.09	18.68	2.93	0.00	28.46	38.24	46.00	-7.76 QP
5 480.528	49.44	19.33	3.46	0.00	28.92	43.31	46.00	-2.69 QP
6 962.162	43.42	22.88	4.27	0.00	27.65	42.92	54.00	-11.08 QP


## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## Above 1GHz:

<b>Product Name:</b>	Smart phone			<b>Product Model:</b>	A3S																																																																																		
<b>Test By:</b>	Carey			<b>Test mode:</b>	PC mode																																																																																		
<b>Test Frequency:</b>	1 GHz ~ 6 GHz			<b>Polarization:</b>	Vertical																																																																																		
<b>Test Voltage:</b>	AC 120/60Hz			<b>Environment:</b>	Temp: 24°C Huni: 57%																																																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Freq MHz</th> <th colspan="2">Read</th> <th colspan="2">Antenna</th> <th colspan="2">Cable</th> <th colspan="2">Aux</th> <th>Preamp</th> <th rowspan="2">Limit Level dBuV/m</th> <th rowspan="2">Line Limit dBuV/m</th> <th rowspan="2">Over Limit dB</th> <th rowspan="2">Remark</th> </tr> <tr> <th>Level dBuV</th> <th>Antenna Factor</th> <th>Loss dB</th> <th>Factor</th> <th>Factor</th> <th>dB</th> <th>dBuV/m</th> </tr> </thead> <tbody> <tr> <td>1 3895.981</td> <td>47.77</td> <td>29.19</td> <td>6.10</td> <td>2.20</td> <td>41.80</td> <td>43.46</td> <td>74.00</td> <td>-30.54</td> <td>Peak</td> </tr> <tr> <td>2 3895.981</td> <td>40.91</td> <td>29.19</td> <td>6.10</td> <td>2.20</td> <td>41.80</td> <td>36.60</td> <td>54.00</td> <td>-17.40</td> <td>Average</td> </tr> <tr> <td>3 4719.315</td> <td>47.59</td> <td>30.61</td> <td>6.84</td> <td>2.42</td> <td>41.94</td> <td>45.52</td> <td>74.00</td> <td>-28.48</td> <td>Peak</td> </tr> <tr> <td>4 4719.315</td> <td>42.13</td> <td>30.61</td> <td>6.84</td> <td>2.42</td> <td>41.94</td> <td>40.06</td> <td>54.00</td> <td>-13.94</td> <td>Average</td> </tr> <tr> <td>5 5525.306</td> <td>47.19</td> <td>32.31</td> <td>7.23</td> <td>2.66</td> <td>41.82</td> <td>47.57</td> <td>74.00</td> <td>-26.43</td> <td>Peak</td> </tr> <tr> <td>6 5525.306</td> <td>40.91</td> <td>32.31</td> <td>7.23</td> <td>2.66</td> <td>41.82</td> <td>41.29</td> <td>54.00</td> <td>-12.71</td> <td>Average</td> </tr> </tbody> </table>							Freq MHz	Read		Antenna		Cable		Aux		Preamp	Limit Level dBuV/m	Line Limit dBuV/m	Over Limit dB	Remark	Level dBuV	Antenna Factor	Loss dB	Factor	Factor	dB	dBuV/m	1 3895.981	47.77	29.19	6.10	2.20	41.80	43.46	74.00	-30.54	Peak	2 3895.981	40.91	29.19	6.10	2.20	41.80	36.60	54.00	-17.40	Average	3 4719.315	47.59	30.61	6.84	2.42	41.94	45.52	74.00	-28.48	Peak	4 4719.315	42.13	30.61	6.84	2.42	41.94	40.06	54.00	-13.94	Average	5 5525.306	47.19	32.31	7.23	2.66	41.82	47.57	74.00	-26.43	Peak	6 5525.306	40.91	32.31	7.23	2.66	41.82	41.29	54.00	-12.71	Average
Freq MHz	Read		Antenna		Cable			Aux		Preamp	Limit Level dBuV/m	Line Limit dBuV/m	Over Limit dB	Remark																																																																									
	Level dBuV	Antenna Factor	Loss dB	Factor	Factor	dB	dBuV/m																																																																																
1 3895.981	47.77	29.19	6.10	2.20	41.80	43.46	74.00	-30.54	Peak																																																																														
2 3895.981	40.91	29.19	6.10	2.20	41.80	36.60	54.00	-17.40	Average																																																																														
3 4719.315	47.59	30.61	6.84	2.42	41.94	45.52	74.00	-28.48	Peak																																																																														
4 4719.315	42.13	30.61	6.84	2.42	41.94	40.06	54.00	-13.94	Average																																																																														
5 5525.306	47.19	32.31	7.23	2.66	41.82	47.57	74.00	-26.43	Peak																																																																														
6 5525.306	40.91	32.31	7.23	2.66	41.82	41.29	54.00	-12.71	Average																																																																														
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.</li> <li>The emission levels of other frequencies are very lower than the limit and not show in test report.</li> </ol>																																																																																							

<b>Product Name:</b>	Smart phone	<b>Product Model:</b>	A3S
<b>Test By:</b>	Carey	<b>Test mode:</b>	PC mode
<b>Test Frequency:</b>	1 GHz ~ 6 GHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	AC 120/60Hz	<b>Environment:</b>	Temp: 24°C Huni: 57%



Freq	Read	Antenna	Cable	Aux	Preamp	Limit	Over	Over	Remark
	Freq	Level	Factor	Loss	Factor				
MHz	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	4067.171	47.11	29.40	6.20	2.22	41.81	43.12	74.00	-30.88 Peak
2	4067.171	40.24	29.40	6.20	2.22	41.81	36.25	54.00	-17.75 Average
3	4778.879	46.83	30.72	6.81	2.43	41.85	44.94	74.00	-29.06 Peak
4	4778.879	40.74	30.72	6.81	2.43	41.85	38.85	54.00	-15.15 Average
5	5799.177	47.62	32.42	7.89	2.75	42.02	48.66	74.00	-25.34 Peak
6	5799.177	40.86	32.42	7.89	2.75	42.02	41.90	54.00	-12.10 Average

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.