

FCC RF Exposure

EUT Description: SMART EYEWEAR

Model No.: TCW01-A1, TCW01-A2, TCW01-C, TCW01-D, TCW01-B1, TCW01-B2

FCC ID: 2AU3D-TCW01A1

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max power of channel, including tune - up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

$$\text{Result} = P/D \cdot \sqrt{F}$$

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

2.4G

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit	SAR Test Exclusion
EDR	-3.299	-4 ± 1	-3 / 0.5	5	0.15748	3.0	Pass
BLE	-3.259	-4 ± 1	-3 / 0.5	5	0.15748	3.0	Pass

Note:
PK Output power= conducted power.
Conducted power see the test report **HK2009242789-1E/2E**, antenna gain=-0dB

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.15748 which is ≤ 3 , RF Exposure testing is not required.

Note: Exclusion Thresholds Results=[*(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)*] • [$\sqrt{f(\text{GHz})}$]

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm