

FCC ID: 2AU4M-VS800S

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

Antenna Type: Chip Antenna

Antenna Gain: 4.99dBi

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
BLE(1M)	2.40	-2.22	0.600	-2±1	-1.0	0.794	<5	0.24622	3.00	YES
	2.44	-2.95	0.507	-2±1	-1.0	0.794	<5	0.24816	3.00	YES
	2.48	-3.37	0.460	-3±1	-2.0	0.631	<5	0.19873	3.00	YES
BLE(2M)	2.40	-2.19	0.604	-2±1	-1.0	0.794	<5	0.24622	3.00	YES
	2.44	-2.93	0.509	-2±1	-1.0	0.794	<5	0.24816	3.00	YES
	2.48	-3.35	0.462	-3±1	-2.0	0.631	<5	0.19873	3.00	YES

Conclusion:

For the max result : $0.24816 \leq 3.0$ for 1-g SAR, No SAR is required.

Signature:



Date: 2024-12-11

NAME AND TITLE (Please print or type): Alex /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.