

Test Report

Report No. : MTi250506005-0402E2

Date of Issue : 2025-06-04

Applicant : Tennrich International Corp.

Product : 3 DEVICE WIRELESS CHARGING STAND



Model(s) : WCP309

FCC ID : 2AU4P-WCP309

Shenzhen Microtest Co., Ltd.

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	5
1.3	Description of support units	7
2	Measurement uncertainty	7
3	Test facilities and accreditations	8
3.1	Test laboratory	8
4	List of test equipment	9
5	Test result	10
5.2	Test setup	11
5.3	Test Procedures	11
5.4	Information of test equipment	12
5.5	Test results	13
	Photographs of the Test Setup	15
	Photographs of the EUT	16

Test Result Certification		
Applicant	Tennrich International Corp.	
Applicant Address	1-3, Alley 5, Lane 305, Sec 1, Shin Nan Road, Lu Chu District, Taoyuan City, Taiwan 338	
Manufacturer	Shenzhen GPO Tech CO.,LTD	
Manufacturer Address	708, Building 3, South Taiyun Chuanggu, Tangwei Community, Fenghuang Street, Guangming District, , Shenzhen	
Factory	Seosin Electronics Vina Co.,Ltd	
Factory Address	Chau Son Industrial Park, Le Chan Road, Le Hong Phong Ward, Phu ly City, Ha Nam Province, Vietnam	
Product description		
Product name	3 DEVICE WIRELESS CHARGING STAND	
Trademark	Energizer	
Model name	WCP309	
Series Model(s)	N/A	
Standards	47 CFR PART 1, § 1.1310 47 CFR PART 2.1091	
Test method	KDB 680106 D01 Wireless Power Transfer v04	
Testing Information		
Date of test	2025-05-13 to 2025-05-16	
Test Result	Pass	
Prepared by:	Yanice.Xie	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

1 General Description

1.1 Description of the EUT

Product name:	3 DEVICE WIRELESS CHARGING STAND
Model name:	WCP309
Series Model:	N/A
Model difference:	N/A
Electrical rating:	Rated Input: USB-C 5V/3A,9V/2A,12V/2.5A Mobile Phone Output:15W/10W/7.5W/5W Earbuds Output:3W(Max.) Watch Output: 3W(Max.)
Accessories:	Cable: USB-C to USB-C 1m
Test sample(s) number:	MTi250506005-04-R001
RF specification:	
Operation frequency:	Coil 1:115-205kHz Coil 2:115-205kHz Coil 3:115-205kHz Coil 4:300-350kHz
Modulation type:	ASK
Antenna type:	Coil

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode1	Wireless output(Coil 1:5W)+Earbud(3W)+Watch(3W)
Mode2	Wireless output(Coil 1:7.5W)+Earbud(3W)+Watch(3W)
Mode3	Wireless output(Coil 1:10W)+Earbud(3W)+Watch(3W)
Mode4	Wireless output(Coil 1:5W)+Earbud(3W)
Mode5	Wireless output(Coil 1:7.5W)+Earbud(3W)
Mode6	Wireless output(Coil 1:10W)+Earbud(3W)
Mode7	Wireless output(Coil 1:5W)+Watch(3W)
Mode8	Wireless output(Coil 1:7.5W)+Watch(3W)
Mode9	Wireless output(Coil 1:10W)+Watch(3W)
Mode10	Wireless output(Coil 1:15W)+Watch(3W)
Mode11	Wireless output Earbud(3W)+Watch(3W)
Mode12	Wireless output(Coil 1:5W)
Mode13	Wireless output(Coil 1:7.5W)
Mode14	Wireless output(Coil 1:10W)
Mode15	Wireless output(Coil 1:15W)
Mode16	Wireless Watch(3W)
Mode17	Wireless Earbud(3W)
Mode18	Wireless output(Coil 1:5W)+Earbud(3W)+Watch(3W)
Mode19	Wireless output(Coil 1:7.5W)+Earbud(3W)+Watch(3W)
Mode20	Wireless output(Coil 1:10W)+Earbud(3W)+Watch(3W)
Mode21	Wireless output(Coil 2:5W)+Earbud(3W)
Mode22	Wireless output(Coil 2:7.5W)+Earbud(3W)
Mode23	Wireless output(Coil 2:10W)+Earbud(3W)
Mode24	Wireless output(Coil 2:5W)+Watch(3W)
Mode25	Wireless output(Coil 2:7.5W)+Watch(3W)
Mode26	Wireless output(Coil 2:10W)+Watch(3W)
Mode27	Wireless output(Coil 2:15W)+Watch(3W)
Mode28	Wireless output(Coil 2:5W)
Mode29	Wireless output(Coil 2:7.5W)
Mode30	Wireless output(Coil 2:10W)
Mode31	Wireless output(Coil 2:15W)
Mode32	Standby

TEST REPORT

Report No.: MTi250506005-0402E2

Note: The maximum combined output power of the EUT is phone 10W+watch 3W+earbus 3W at the same time.

1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
Lenovo USB-C adapter	C65B	1SGX21B35621Z13F1D4W	Lenovo
Moible Phone	iPhone 8	/	Apple
Moible Phone	Find X3	/	OPPO
Moible Phone	S9+	/	YBZ
Air Pods	MQD83CH/A	/	Apple
iWatch	Apple Watch SE	FH7PP6BAG91J6	Apple
Support cable list			
Description	Length (m)	From	To
/	/	/	/

2 Measurement uncertainty

Parameter	Expanded Uncertainty
Magnetic field measurements(3kHz~10MHz)	$\pm 14.8\%$
Electric field measurements(3kHz~10MHz)	$\pm 17.5\%$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 Test facilities and accreditations**3.1 Test laboratory**

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E143	Near-field Electric and Magnetic Field Sensor System	SPEAG	MAGPy-8H3 D+ED3	3101	2024/3/12	2027/3/11

No.	Equipment	Manufacturer	Model	Software version:	Cal. date	Cal. Due
MTI-E016S	MPE test software	SPEAG	MAGPY 2.6	2.6	/	/

5 Test result

5.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)


Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30

f = frequency in MHz

* = Plane-wave equivalent power density

Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

5.2 Test setup**5.3 Test Procedures**

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with these devices considered to meet the § 2.1091-Mobile conditions ("generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and [the nearest person]").
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

5.4 Information of test equipment

Test equipment: MAGPy-8H3D+ED3	
Diameter	60mm
8 isotropic H-field sensors	Concentric loops of 1cm ² arranged at the corner of a cube of 22mm side length
1 isotropic E-field sensor	Orthogonal dipole/monopole (arm length: 50mm)
Measurement center	18.5mm from the probe tip
Dimensions	110*635*35mm (MAGPy-8H3D+E3D V2 & MAGPy-DAS V2)
	
Test probe, without the casing	

5.5 Test results

Test condition 1: Mode 3 operating mode with client device (1 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	2.12	614	0.35%	0.14	1.63	8.59%
Left	1.63			0.07		
Right	1.48			0.08		
Front	1.29			0.05		
Rear	1.51			0.09		
Bottom	1.97			0.06		

Test condition 2: Mode 3 operating mode with client device (50 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Z axis	1.70	614	0.28%	0.11	1.63	6.87%
Left	1.30			0.06		
Right	1.18			0.06		
Front	1.03			0.04		
Rear	1.21			0.07		
Bottom	1.58			0.05		

Test condition 3: Mode 3 operating mode with client device (99 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	1.38	614	0.22%	0.09	1.63	5.58%
Left	1.06			0.05		
Right	0.96			0.05		
Front	0.84			0.03		

TEST REPORT

Report No.: MTi250506005-0402E2

Rear	0.98			0.06	
Bottom	1.28			0.04	

Photographs of the Test Setup

See the Appendix - Test Setup Photos.

Photographs of the EUT

See the Appendix - EUT Photos.

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****