



Shenzhen CTL Testing Technology Co., Ltd.  
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

# TEST REPORT

## FCC Part 27

Report Reference No. ....: **CTL1909098011-WF04**

Compiled by:  
( position+printed name+signature)

Happy Guo  
(File administrators)

*Happy Guo*

Tested by:  
( position+printed name+signature)

Nice Nong  
(Test Engineer)

*Nice Nong*

Approved by:  
( position+printed name+signature)

Ivan Xie  
(Manager)

*Ivan Xie*

Product Name.....: Master Roam GLocal Pocket Wifi T6

Model/Type reference .....: T6

List Model(s).....: N/A

Trade Mark.....: Master Roam

FCC ID.....: 2AU4T-T6

Applicant's name .....: **Shanghai TUGE Data Technologies Co., Ltd.**

Address of applicant .....: Building C, No.888, Huanhu West 2<sup>nd</sup> Road, Nanhui New Town,  
Pudong New District, Shanghai, China.

Test Firm .....: **Shenzhen CTL Testing Technology Co., Ltd.**

Address of Test Firm .....: Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road,  
Nanshan District, Shenzhen, China 518055

Test specification.....:

Standard.....: **FCC CFR Title 47 Part 2, Part 27**  
**EIA/TIA 603-D: 2010**  
**KDB 971168 D01**

TRF Originator .....: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF .....: Dated 2011-01

Date of receipt of test item.....: Sep. 30, 2019

Date of sampling.....: Sep. 30, 2019

Date of Test Date.....: Sep. 30, 2019-Nov. 07, 2019

Data of Issue.....: Nov. 08, 2019

Result.....: Pass

**Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

# TEST REPORT

|                                             |                                |
|---------------------------------------------|--------------------------------|
| <b>Test Report No. :</b> CTL1909098011-WF04 | Nov. 08, 2019<br>Date of issue |
|---------------------------------------------|--------------------------------|

Equipment under Test : Master Roam GLobal Pocket Wifi T6

Model /Type : T6

Listed Models : N/A

**Applicant** : Shanghai TUGE Data Technologies Co., Ltd.

**Address** : Building C, No.888, Huanhu West 2<sup>nd</sup> Road, Nanhui  
New Town, Pudong New District, Shanghai, China

**Manufacturer** : Hui Zhou fortuneship technology Company  
Limited

**Address** : NO.86, Hechang 7th West Road, Zhong Kai Hi-tech  
Development District, Huizhou City, Guangdong  
Province, P.R.China (Phase II plant)

|                    |               |
|--------------------|---------------|
| <b>Test result</b> | <b>Pass *</b> |
|--------------------|---------------|

\*In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

[illegible]

## Table of Contents

## Page

|                                                                      |                  |
|----------------------------------------------------------------------|------------------|
| <b>1. SUMMARY.....</b>                                               | <b>5</b>         |
| 1.1. TEST STANDARDS.....                                             | 5                |
| 1.2. TEST DESCRIPTION.....                                           | 5                |
| 1.3. TEST FACILITY .....                                             | 6                |
| 1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....                   | 6                |
| <b>2. GENERAL INFORMATION.....</b>                                   | <b>7</b>         |
| 2.1. ENVIRONMENTAL CONDITIONS .....                                  | 7                |
| 2.2. GENERAL DESCRIPTION OF EUT .....                                | 7                |
| 2.3. DESCRIPTION OF TEST MODES .....                                 | 7                |
| 2.4. EQUIPMENTS USED DURING THE TEST .....                           | 7                |
| 2.5. RELATED SUBMITTAL(S) / GRANT (S).....                           | 8                |
| 2.6. MODIFICATIONS.....                                              | 8                |
| <b>3. TEST CONDITIONS AND RESULTS .....</b>                          | <b>9</b>         |
| 3.1. OUTPUT POWER .....                                              | 9                |
| 3.2. PEAK-TO-AVERAGE RATIO (PAR).....                                | 13               |
| 3.3. OCCUPIED BANDWIDTH AND EMISSION BANDWIDTH.....                  | 14               |
| 3.4. BAND EDGE COMPLIANCE .....                                      | 15               |
| 3.5. SPURIOUS EMISSION.....                                          | 16               |
| 3.6. FREQUENCY STABILITY UNDER TEMPERATURE & VOLTAGE VARIATIONS..... | 22               |
| <b>4. TEST SETUP PHOTOS OF THE EUT .....</b>                         | <b>24</b>        |
| <b>5. PHOTOS OF THE EUT .....</b>                                    | <b>错误！未定义书签。</b> |

## 1. SUMMARY

### 1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 27](#) : MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES

[TIA/EIA 603 D June 2010](#):Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[FCC Part 2](#): FREQUENCY ALLOCA-TIONS AND RADIO TREATY MAT-TERS; GENERAL RULES AND REG-ULATIONS

[KDB971168 D01: v02r02](#) MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS

[ANSI C63.10: 2013](#): American National Standard for Testing Unlicensed Wireless Devices

[ANSI C63.4: 2014](#): –American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz  
Range of 9 kHz to 40GHz

### 1.2. Test Description

| Test Item                              | Section in CFR 47               | Result |
|----------------------------------------|---------------------------------|--------|
| RF Output Power                        | Part 2.1046<br>Part 27.50(d)(4) | Pass   |
| Peak-to-Average Ratio                  | Part 27.50(d)(4)                | Pass   |
| 99% & -26 dB Occupied Bandwidth        | Part 2.1049<br>Part 27.53(h)    | Pass   |
| Spurious Emissions at Antenna Terminal | Part 2.1051<br>Part 27.53(h)    | Pass   |
| Field Strength of Spurious Radiation   | Part 2.1053<br>Part 27.53(h)    | Pass   |
| Out of band emission, Band Edge        | Part 2.1051<br>Part 27.53(h)    | Pass   |
| Frequency stability                    | Part 2.1055<br>Part 27.54       | Pass   |

### 1.3. Test Facility

#### 1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

#### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

##### CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

##### A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

##### IC Registration No.: 9518B

##### CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9518B on Jan. 22, 2019.

##### FCC-Registration No.: 399832

##### Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

### 1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

| Test                  | Range      | Measurement Uncertainty | Notes |
|-----------------------|------------|-------------------------|-------|
| Radiated Emission     | 30~1000MHz | 4.10dB                  | (1)   |
| Radiated Emission     | Above 1GHz | 4.32dB                  | (1)   |
| Conducted Disturbance | 0.15~30MHz | 3.20dB                  | (1)   |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2. GENERAL INFORMATION

### 2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

|                     |         |
|---------------------|---------|
| Normal Temperature: | 25°C    |
| Relative Humidity:  | 55 %    |
| Air Pressure:       | 101 kPa |

### 2.2. General Description of EUT

|                       |                                                    |
|-----------------------|----------------------------------------------------|
| Product Name:         | Master Roam GLocal Pocket Wifi T6                  |
| Model/Type reference: | T6                                                 |
| Power supply:         | DC 3.8V from battery                               |
| Hardware version:     | ET612-MB-V0.2                                      |
| Software version:     | Android 7.0                                        |
| <b>LTE</b>            |                                                    |
| Operation Band:       | FDD-LTE: Band 2/4/5/7/12/17<br>TDD-LTE: Band 38/41 |
| Modulation Type:      | QPSK, 16QAM                                        |
| Release Version:      | Release 9                                          |
| Category:             | Cat 4                                              |
| Antenna type:         | FPC antenna                                        |
| Antenna gain:         | 3dBi                                               |

Note: For more details, please refer to the user's manual of the EUT.

Note1: This report only reports band 4.

### 2.3. Description of Test Modes

The EUT has been tested under typical operating condition. The CMW500 used to control the EUT staying in continuous transmitting and receiving mode for testing. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.

### 2.4. Equipments Used during the Test

| Test Equipment    | Manufacturer         | Model No.          | Serial No. | Calibration Date | Calibration Due Date |
|-------------------|----------------------|--------------------|------------|------------------|----------------------|
| Bilog Antenna     | Sunol Sciences Corp. | JB1                | A061713    | 2019/05/20       | 2020/05/19           |
| Bilog Antenna     | Sunol Sciences Corp. | JB1                | A061714    | 2019/05/20       | 2020/05/19           |
| EMI Test Receiver | R&S                  | ESCI               | 103710     | 2019/05/20       | 2020/05/19           |
| Spectrum Analyzer | Agilent              | E4407B             | MY41440676 | 2019/05/20       | 2020/05/19           |
| Spectrum Analyzer | Agilent              | N9020              | US46220290 | 2019/05/20       | 2020/05/19           |
| Spectrum Analyzer | Keysight             | N9020A             | MY53420874 | 2019/05/20       | 2020/05/19           |
| Controller        | EM Electronics       | Controller EM 1000 | N/A        | 2019/05/20       | 2020/05/19           |

|                                     |                      |                        |            |            |            |
|-------------------------------------|----------------------|------------------------|------------|------------|------------|
| Horn Antenna                        | Sunol Sciences Corp. | DRH-118                | A062013    | 2019/05/20 | 2020/05/19 |
| Horn Antenna                        | Sunol Sciences Corp. | DRH-118                | A062014    | 2019/05/20 | 2020/05/19 |
| Active Loop Antenna                 | SCHWARZBEC K         | FMZB1519               | 1519-037   | 2019/05/20 | 2020/05/19 |
| Amplifier                           | Agilent              | 8349B                  | 3008A02306 | 2019/05/20 | 2020/05/19 |
| Amplifier                           | Agilent              | 8447D                  | 2944A10176 | 2019/05/20 | 2020/05/19 |
| Temperature/Humidity Meter          | Gangxing             | CTH-608                | 02         | 2019/05/20 | 2020/05/19 |
| Wideband Radio Communication Tester | R&S                  | CMW500                 | 101814     | 2019/05/20 | 2020/05/19 |
| High-Pass Filter                    | K&L                  | 9SH10-2700/X1 2750-O/O | N/A        | 2019/05/20 | 2020/05/19 |
| High-Pass Filter                    | K&L                  | 41H10-1375/U1 2750-O/O | N/A        | 2019/05/20 | 2020/05/19 |
| RF Cable                            | HUBER+SUHNER         | RG214                  | N/A        | 2019/05/20 | 2020/05/19 |
| Climate Chamber                     | ESPEC                | EL-10KA                | A20120523  | 2019/05/20 | 2020/05/19 |
| Power Sensor                        | Agilent              | U2021XA                | MY5365004  | 2019/05/20 | 2020/05/19 |
| Power Meter                         | Agilent              | U2531A                 | TW53323507 | 2019/05/20 | 2020/05/19 |
| SIGNAL GENERATOR                    | Agilent              | E4421B                 | US40051744 | 2019/05/20 | 2020/05/19 |
| Directional Coupler                 | Agilent              | 87300B                 | 3116A03638 | 2019/05/20 | 2020/05/19 |

The calibration interval was one year

## 2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with of the Part 27 Rules.

## 2.6. Modifications

No modifications were implemented to meet testing criteria.



### 3. TEST CONDITIONS AND RESULTS


#### 3.1. Output Power

##### LIMIT


According to §27.50 (d) (4): Fixed, mobile, and portable (hand- held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

##### TEST CONFIGURATION

Conducted Power Measurement



Radiated Power Measurement:



##### TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

##### **Conducted Power Measurement:**

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- EUT Communicate with CMW500 then selects a channel for testing.
- Add a correction factor to the display of spectrum, and then test.

##### **Radiated Power Measurement:**

- The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- The output of the test antenna shall be connected to the measuring receiver.

- d) The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h) The maximum signal level detected by the measuring receiver shall be noted.
- i) The transmitter shall be replaced by a substitution antenna.
- j) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k) The substitution antenna shall be connected to a calibrated signal generator.
- l) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q) Test site anechoic chamber refer to ANSI C63.4.

**TEST RESULTS****Conducted Measurement:** See Appendix A.**Radiated Measurement:***Remark:*

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case for each Channel Bandwidth of LTE FDD Band 4.
2.  $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + P_{Ag}(dB) + G_a(dBi)$

*LTE FDD Band 4\_Channel Bandwidth 1.4MHz\_QPSK*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1710.7          | -20.77                 | 2.75                 | 8.98                            | 35.70                | 21.16      | 30.00       | 8.84        | V            |
| 1732.5          | -19.70                 | 2.81                 | 9.15                            | 35.70                | 22.34      | 30.00       | 7.66        | V            |
| 1754.3          | -20.75                 | 2.85                 | 9.47                            | 35.70                | 21.57      | 30.00       | 8.43        | V            |

*LTE FDD Band 4\_Channel Bandwidth 3MHz\_QPSK*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1711.5          | -19.85                 | 2.75                 | 8.98                            | 35.70                | 22.08      | 30.00       | 7.92        | V            |
| 1732.5          | -19.68                 | 2.81                 | 9.15                            | 35.70                | 22.36      | 30.00       | 7.64        | V            |
| 1753.5          | -20.59                 | 2.85                 | 9.47                            | 35.70                | 21.73      | 30.00       | 8.27        | V            |

*LTE FDD Band 4\_Channel Bandwidth 5MHz\_QPSK*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1712.5          | -19.77                 | 2.75                 | 8.98                            | 35.70                | 22.16      | 30.00       | 7.84        | V            |
| 1732.5          | -19.66                 | 2.81                 | 9.15                            | 35.70                | 22.38      | 30.00       | 7.62        | V            |
| 1752.5          | -20.05                 | 2.85                 | 9.47                            | 35.70                | 22.27      | 30.00       | 7.73        | V            |

*LTE FDD Band 4\_Channel Bandwidth 10MHz\_QPSK*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1715.0          | -20.30                 | 2.75                 | 8.98                            | 35.70                | 21.63      | 30.00       | 8.37        | V            |
| 1732.5          | -19.66                 | 2.81                 | 9.15                            | 35.70                | 22.38      | 30.00       | 7.62        | V            |
| 1750.0          | -19.78                 | 2.85                 | 9.47                            | 35.70                | 22.54      | 30.00       | 7.46        | V            |

*LTE FDD Band 4\_Channel Bandwidth 15MHz\_QPSK*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1717.5          | -20.87                 | 2.75                 | 8.98                            | 35.70                | 21.06      | 30.00       | 8.94        | V            |
| 1732.5          | -19.70                 | 2.81                 | 9.15                            | 35.70                | 22.34      | 30.00       | 7.66        | V            |
| 1747.5          | -19.71                 | 2.85                 | 9.47                            | 35.70                | 22.61      | 30.00       | 7.39        | V            |

*LTE FDD Band 4\_Channel Bandwidth 20MHz\_QPSK*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1720.0          | -20.36                 | 2.75                 | 8.98                            | 35.70                | 21.57      | 30.00       | 8.43        | V            |
| 1732.5          | -19.41                 | 2.81                 | 9.15                            | 35.70                | 22.63      | 30.00       | 7.37        | V            |
| 1745.0          | -20.13                 | 2.85                 | 9.47                            | 35.70                | 22.19      | 30.00       | 7.81        | V            |

*LTE FDD Band 4\_Channel Bandwidth 1.4MHz\_16QAM*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1710.7          | -20.62                 | 2.75                 | 8.98                            | 35.70                | 21.31      | 30.00       | 8.69        | V            |
| 1732.5          | -20.87                 | 2.81                 | 9.15                            | 35.70                | 21.17      | 30.00       | 8.83        | V            |
| 1754.3          | -20.96                 | 2.85                 | 9.47                            | 35.70                | 21.36      | 30.00       | 8.64        | V            |

*LTE FDD Band 4\_Channel Bandwidth 3MHz\_16QAM*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1711.5          | -20.42                 | 2.75                 | 8.98                            | 35.70                | 21.51      | 30.00       | 8.49        | V            |
| 1732.5          | -20.61                 | 2.81                 | 9.15                            | 35.70                | 21.43      | 30.00       | 8.57        | V            |
| 1753.5          | -22.03                 | 2.85                 | 9.47                            | 35.70                | 20.29      | 30.00       | 9.71        | V            |

*LTE FDD Band 4\_Channel Bandwidth 5MHz\_16QAM*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1712.5          | -20.79                 | 2.75                 | 8.98                            | 35.70                | 21.14      | 30.00       | 8.86        | V            |
| 1732.5          | -20.77                 | 2.81                 | 9.15                            | 35.70                | 21.27      | 30.00       | 8.73        | V            |
| 1752.5          | -21.56                 | 2.85                 | 9.47                            | 35.70                | 20.76      | 30.00       | 9.24        | V            |

*LTE FDD Band 4\_Channel Bandwidth 10MHz\_16QAM*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1715.0          | -21.36                 | 2.75                 | 8.98                            | 35.70                | 20.57      | 30.00       | 9.43        | V            |
| 1732.5          | -20.88                 | 2.81                 | 9.15                            | 35.70                | 21.16      | 30.00       | 8.84        | V            |
| 1750.0          | -20.91                 | 2.85                 | 9.47                            | 35.70                | 21.41      | 30.00       | 8.59        | V            |

*LTE FDD Band 4\_Channel Bandwidth 15MHz\_16QAM*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1717.5          | -20.69                 | 2.75                 | 8.98                            | 35.70                | 21.24      | 30.00       | 8.76        | V            |
| 1732.5          | -21.17                 | 2.81                 | 9.15                            | 35.70                | 20.87      | 30.00       | 9.13        | V            |
| 1747.5          | -20.96                 | 2.85                 | 9.47                            | 35.70                | 21.36      | 30.00       | 8.64        | V            |

*LTE FDD Band 4\_Channel Bandwidth 20MHz\_16QAM*


| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | G <sub>a</sub> Antenna Gain(dB) | P <sub>Ag</sub> (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|---------------------------------|----------------------|------------|-------------|-------------|--------------|
| 1720.0          | -20.30                 | 2.75                 | 8.98                            | 35.70                | 21.63      | 30.00       | 8.37        | V            |
| 1732.5          | -20.45                 | 2.81                 | 9.15                            | 35.70                | 21.59      | 30.00       | 8.41        | V            |
| 1745.0          | -20.39                 | 2.85                 | 9.47                            | 35.70                | 21.93      | 30.00       | 8.07        | V            |

### 3.2. Peak-to-Average Ratio (PAR)

#### LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
2. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
3. Set the number of counts to a value that stabilizes the measured CCDF curve;
4. Set the measurement interval as follows:
  - 1). for continuous transmissions, set to 1 ms,
  - 2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
5. Record the maximum PAPR level associated with a probability of 0.1%.

#### TEST RESULTS


See Appendix B.

### 3.3. Occupied Bandwidth and Emission Bandwidth

#### LIMIT

N/A

#### TEST CONFIGURATION



#### TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at low, middle and high channel in each band. The -26dBc Emission bandwidth was also measured and recorded.

Set RBW was set to about 1% of emission BW, VBW $\geq$ 3 times RBW.

-26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

#### TEST RESULTS


See Appendix C.

### 3.4. Band Edge compliance

#### LIMIT

According to §27.53 (h): For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB.

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest and highest channels for each band and different modulation.
5. Measure Band edge using RMS (Average) detector by spectrum

#### TEST RESULTS

See Appendix D.


### 3.5. Spurious Emission

#### LIMIT


According to §27.53 (h): For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB.

#### TEST CONFIGURATION

Conducted Spurious Measurement:



Radiated Spurious Measurement:



#### TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

##### **Conducted Spurious Measurement:**

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- EUT Communicate with CMW500 then selects a channel for testing.
- Add a correction factor to the display of spectrum, and then test.
- The resolution bandwidth of the spectrum analyzer was set sufficient scans were taken to show the out of band Emission if any up to 10th harmonic.



**Radiated Spurious Measurement:**

- a. The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c. The output of the test antenna shall be connected to the measuring receiver.
- d. The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h. The maximum signal level detected by the measuring receiver shall be noted.
- i. The transmitter shall be replaced by a substitution antenna.
- j. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k. The substitution antenna shall be connected to a calibrated signal generator.
- l. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for Part 22 and 1MHz for Part 24. The frequency range was checked up to 10th harmonic.
- r. Test site anechoic chamber refer to ANSI C63.

**TEST RESULTS**

**Conducted Measurement:** See Appendix E.

**Radiated Measurement:***Remark:*

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case for each Channel Bandwidth of LTE FDD Band 4 @ QPSK
2.  $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + G_a(dBi)$
3. We were not recorded other points as values lower than limits.
4.  $Margin = Limit - EIRP$

*LTE FDD Band 4\_Channel Bandwidth 1.4MHz\_QPSK\_Low Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|-----------------|-------------|-------------|--------------|
| 3421.4          | -40.65                 | 4.02                 | 3.00         | 12.50                           | -32.17          | -13.00      | 19.17       | H            |
| 5132.1          | -44.54                 | 5.11                 | 3.00         | 13.38                           | -36.27          | -13.00      | 23.27       | H            |
| 3421.4          | -39.64                 | 4.02                 | 3.00         | 12.50                           | -31.16          | -13.00      | 18.16       | V            |
| 5132.1          | -43.35                 | 5.11                 | 3.00         | 13.38                           | -35.08          | -13.00      | 22.08       | V            |

*LTE FDD Band 4\_Channel Bandwidth 1.4MHz\_QPSK\_Middle Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3465.0          | -39.59                 | 4.02                 | 3.00         | 12.45                           | -31.16     | -13.00      | 18.16       | H            |
| 5197.5          | -45.51                 | 5.11                 | 3.00         | 13.38                           | -37.24     | -13.00      | 24.24       | H            |
| 3465.0          | -38.96                 | 4.02                 | 3.00         | 12.45                           | -30.53     | -13.00      | 17.53       | V            |
| 5197.5          | -44.42                 | 5.11                 | 3.00         | 13.38                           | -36.15     | -13.00      | 23.15       | V            |

*LTE FDD Band 4\_Channel Bandwidth 1.4MHz\_QPSK\_High Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3508.6          | -40.40                 | 4.02                 | 3.00         | 12.21                           | -32.21     | -13.00      | 19.21       | H            |
| 5262.9          | -44.62                 | 5.11                 | 3.00         | 13.26                           | -36.47     | -13.00      | 23.47       | H            |
| 3508.6          | -39.75                 | 4.02                 | 3.00         | 12.21                           | -31.56     | -13.00      | 18.56       | V            |
| 5262.9          | -43.51                 | 5.11                 | 3.00         | 13.26                           | -35.36     | -13.00      | 22.36       | V            |

*LTE FDD Band 4\_Channel Bandwidth 3MHz\_QPSK\_Low Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|-----------------|-------------|-------------|--------------|
| 3423.0          | -40.52                 | 4.02                 | 3.00         | 12.50                           | -32.04          | -13.00      | 19.04       | H            |
| 5134.5          | -44.48                 | 5.11                 | 3.00         | 13.38                           | -36.21          | -13.00      | 23.21       | H            |
| 3423.0          | -39.83                 | 4.02                 | 3.00         | 12.50                           | -31.35          | -13.00      | 18.35       | V            |
| 5134.5          | -43.78                 | 5.11                 | 3.00         | 13.38                           | -35.51          | -13.00      | 22.51       | V            |

*LTE FDD Band 4\_Channel Bandwidth 3MHz\_QPSK\_Middle Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3465.0          | -40.86                 | 4.02                 | 3.00         | 12.45                           | -32.43     | -13.00      | 19.43       | H            |
| 5197.5          | -44.78                 | 5.11                 | 3.00         | 13.38                           | -36.51     | -13.00      | 23.51       | H            |
| 3465.0          | -40.08                 | 4.02                 | 3.00         | 12.45                           | -31.65     | -13.00      | 18.65       | V            |
| 5197.5          | -43.41                 | 5.11                 | 3.00         | 13.38                           | -35.14     | -13.00      | 22.14       | V            |

*LTE FDD Band 4\_Channel Bandwidth 3MHz\_QPSK\_High Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3507.0          | -40.44                 | 4.02                 | 3.00         | 12.21                           | -32.25     | -13.00      | 19.25       | H            |
| 5260.5          | -44.91                 | 5.11                 | 3.00         | 13.26                           | -36.76     | -13.00      | 23.76       | H            |
| 3507.0          | -39.62                 | 4.02                 | 3.00         | 12.21                           | -31.43     | -13.00      | 18.43       | V            |
| 5260.5          | -43.62                 | 5.11                 | 3.00         | 13.26                           | -35.47     | -13.00      | 22.47       | V            |

*LTE FDD Band 4\_Channel Bandwidth 5MHz\_QPSK\_Low Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|-----------------|-------------|-------------|--------------|
| 3425.0          | -41.33                 | 4.02                 | 3.00         | 12.50                           | -32.85          | -13.00      | 19.85       | H            |
| 5137.5          | -44.81                 | 5.11                 | 3.00         | 13.38                           | -36.54          | -13.00      | 23.54       | H            |
| 3425.0          | -39.83                 | 4.02                 | 3.00         | 12.50                           | -31.35          | -13.00      | 18.35       | V            |
| 5137.5          | -43.40                 | 5.11                 | 3.00         | 13.38                           | -35.13          | -13.00      | 22.13       | V            |

*LTE FDD Band 4\_Channel Bandwidth 5MHz\_QPSK\_Middle Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3465.0          | -40.91                 | 4.02                 | 3.00         | 12.45                           | -32.48     | -13.00      | 19.48       | H            |
| 5197.5          | -44.83                 | 5.11                 | 3.00         | 13.38                           | -36.56     | -13.00      | 23.56       | H            |
| 3465.0          | -40.14                 | 4.02                 | 3.00         | 12.45                           | -31.71     | -13.00      | 18.71       | V            |
| 5197.5          | -43.42                 | 5.11                 | 3.00         | 13.38                           | -35.15     | -13.00      | 22.15       | V            |

*LTE FDD Band 4\_Channel Bandwidth 5MHz\_QPSK\_High Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3505.0          | -40.54                 | 4.02                 | 3.00         | 12.21                           | -32.35     | -13.00      | 19.35       | H            |
| 5257.5          | -44.76                 | 5.11                 | 3.00         | 13.26                           | -36.61     | -13.00      | 23.61       | H            |
| 3505.0          | -39.66                 | 4.02                 | 3.00         | 12.21                           | -31.47     | -13.00      | 18.47       | V            |
| 5257.5          | -44.01                 | 5.11                 | 3.00         | 13.26                           | -35.86     | -13.00      | 22.86       | V            |

*LTE FDD Band 4\_Channel Bandwidth 10MHz\_QPSK\_Low Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|-----------------|-------------|-------------|--------------|
| 3430.0          | -39.64                 | 4.02                 | 3.00         | 12.50                           | -31.16          | -13.00      | 18.16       | H            |
| 5145.0          | -45.35                 | 5.11                 | 3.00         | 13.38                           | -37.08          | -13.00      | 24.08       | H            |
| 3430.0          | -38.60                 | 4.02                 | 3.00         | 12.50                           | -30.12          | -13.00      | 17.12       | V            |
| 5145.0          | -44.78                 | 5.11                 | 3.00         | 13.38                           | -36.51          | -13.00      | 23.51       | V            |

*LTE FDD Band 4\_Channel Bandwidth 10MHz\_QPSK\_Middle Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3465.0          | -40.86                 | 4.02                 | 3.00         | 12.45                           | -32.43     | -13.00      | 19.43       | H            |
| 5197.5          | -46.41                 | 5.11                 | 3.00         | 13.38                           | -38.14     | -13.00      | 25.14       | H            |
| 3465.0          | -39.22                 | 4.02                 | 3.00         | 12.45                           | -30.79     | -13.00      | 17.79       | V            |
| 5197.5          | -44.79                 | 5.11                 | 3.00         | 13.38                           | -36.52     | -13.00      | 23.52       | V            |

*LTE FDD Band 4\_Channel Bandwidth 10MHz\_QPSK\_High Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3500.0          | -40.47                 | 4.02                 | 3.00         | 12.21                           | -32.28     | -13.00      | 19.28       | H            |
| 5250.0          | -44.69                 | 5.11                 | 3.00         | 13.26                           | -36.54     | -13.00      | 23.54       | H            |
| 3500.0          | -40.02                 | 4.02                 | 3.00         | 12.21                           | -31.83     | -13.00      | 18.83       | V            |
| 5250.0          | -43.66                 | 5.11                 | 3.00         | 13.26                           | -35.51     | -13.00      | 22.51       | V            |

*LTE FDD Band 4\_Channel Bandwidth 15MHz\_QPSK\_Low Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|-----------------|-------------|-------------|--------------|
| 3435.0          | -40.01                 | 4.02                 | 3.00         | 12.50                           | -31.53          | -13.00      | 18.53       | H            |
| 5152.5          | -45.42                 | 5.11                 | 3.00         | 13.38                           | -37.15          | -13.00      | 24.15       | H            |
| 3435.0          | -38.90                 | 4.02                 | 3.00         | 12.50                           | -30.42          | -13.00      | 17.42       | V            |
| 5152.5          | -43.46                 | 5.11                 | 3.00         | 13.38                           | -35.19          | -13.00      | 22.19       | V            |

*LTE FDD Band 4\_Channel Bandwidth 15MHz\_QPSK\_Middle Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3465.0          | -40.69                 | 4.02                 | 3.00         | 12.45                           | -32.26     | -13.00      | 19.26       | H            |
| 5197.5          | -44.42                 | 5.11                 | 3.00         | 13.38                           | -36.15     | -13.00      | 23.15       | H            |
| 3465.0          | -40.05                 | 4.02                 | 3.00         | 12.45                           | -31.62     | -13.00      | 18.62       | V            |
| 5197.5          | -43.66                 | 5.11                 | 3.00         | 13.38                           | -35.39     | -13.00      | 22.39       | V            |

*LTE FDD Band 4\_Channel Bandwidth 15MHz\_QPSK\_High Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3495.0          | -40.55                 | 4.02                 | 3.00         | 12.21                           | -32.36     | -13.00      | 19.36       | H            |
| 5242.5          | -44.24                 | 5.11                 | 3.00         | 13.26                           | -36.09     | -13.00      | 23.09       | H            |
| 3495.0          | -40.08                 | 4.02                 | 3.00         | 12.21                           | -31.89     | -13.00      | 18.89       | V            |
| 5242.5          | -43.41                 | 5.11                 | 3.00         | 13.26                           | -35.26     | -13.00      | 22.26       | V            |

*LTE FDD Band 4\_Channel Bandwidth 20MHz\_QPSK\_Low Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|-----------------|-------------|-------------|--------------|
| 3440.0          | -40.74                 | 4.02                 | 3.00         | 12.50                           | -32.26          | -13.00      | 19.26       | H            |
| 5160.0          | -44.72                 | 5.11                 | 3.00         | 13.38                           | -36.45          | -13.00      | 23.45       | H            |
| 3440.0          | -40.31                 | 4.02                 | 3.00         | 12.50                           | -31.83          | -13.00      | 18.83       | V            |
| 5160.0          | -43.69                 | 5.11                 | 3.00         | 13.38                           | -35.42          | -13.00      | 22.42       | V            |

*LTE FDD Band 4\_Channel Bandwidth 20MHz\_QPSK\_Middle Channel*

| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Distance (m) | G <sub>a</sub> Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|--------------|---------------------------------|------------|-------------|-------------|--------------|
| 3465.0          | -40.96                 | 4.02                 | 3.00         | 12.45                           | -32.53     | -13.00      | 19.53       | H            |
| 5197.5          | -44.65                 | 5.11                 | 3.00         | 13.38                           | -36.38     | -13.00      | 23.38       | H            |
| 3465.0          | -40.16                 | 4.02                 | 3.00         | 12.45                           | -31.73     | -13.00      | 18.73       | V            |
| 5197.5          | -43.36                 | 5.11                 | 3.00         | 13.38                           | -35.09     | -13.00      | 22.09       | V            |

*LTE FDD Band 4\_Channel Bandwidth 20MHz\_QPSK\_High Channel*


| Frequency<br>(MHz) | P <sub>Mea</sub><br>(dBm) | P <sub>cl</sub><br>(dB) | Distance<br>(m) | G <sub>a</sub><br>Antenna<br>Gain(dB) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) | Polarization |
|--------------------|---------------------------|-------------------------|-----------------|---------------------------------------|---------------|----------------|----------------|--------------|
| 3490.0             | -40.87                    | 4.02                    | 3.00            | 12.21                                 | -32.68        | -13.00         | 19.68          | H            |
| 5235.0             | -44.28                    | 5.11                    | 3.00            | 13.26                                 | -36.13        | -13.00         | 23.13          | H            |
| 3490.0             | -39.48                    | 4.02                    | 3.00            | 12.21                                 | -31.29        | -13.00         | 18.29          | V            |
| 5235.0             | -42.80                    | 5.11                    | 3.00            | 13.26                                 | -34.65        | -13.00         | 21.65          | V            |

### 3.6. Frequency Stability under Temperature & Voltage Variations

#### LIMIT

According to §27.54, §2.1055 requirement, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation and should not exceed 2.5ppm.

#### TEST CONFIGURATION



#### TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

##### **Frequency Stability under Temperature Variations:**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 4, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

##### **Frequency Stability under Voltage Variations:**

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ( $\pm 15\%$ ) and endpoint, record the maximum frequency change.

**TEST RESULTS**

Remark:

1. We tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case.

LTE Band 4, 1.4MHz bandwidth (worst case of all bandwidths)

***Frequency Error vs Voltage***

| Voltage<br>(V) | Frequency error (Hz) |       | Frequency error (ppm) |          | Limit<br>(ppm) |
|----------------|----------------------|-------|-----------------------|----------|----------------|
|                | QPSK                 | 16QAM | QPSK                  | 16QAM    |                |
| 3.23           | -6.85                | -8.03 | -0.00396              | -0.00464 | ±2.50          |
| 3.80           | -0.33                | 1.81  | -0.00018              | 0.00105  | ±2.50          |
| 4.37           | 4.53                 | -3.31 | 0.00262               | -0.00192 | ±2.50          |

***Frequency Error vs Temperature***

| Temperature<br>(°C) | Frequency error (Hz) |       | Frequency error (ppm) |          | Limit<br>(ppm) |
|---------------------|----------------------|-------|-----------------------|----------|----------------|
|                     | QPSK                 | 16QAM | QPSK                  | 16QAM    |                |
| -30°                | 4.94                 | 2.55  | 0.00286               | 0.00148  | ±2.50          |
| -20°                | 9.96                 | 2.93  | 0.00575               | 0.00169  | ±2.50          |
| -10°                | -1.50                | 9.21  | -0.00087              | 0.00531  | ±2.50          |
| 0°                  | 9.97                 | 0.42  | 0.00576               | 0.00023  | ±2.50          |
| 10°                 | 6.96                 | 0.27  | 0.00402               | 0.00016  | ±2.50          |
| 20°                 | 3.81                 | 3.53  | 0.00220               | 0.00204  | ±2.50          |
| 30°                 | -5.93                | 4.22  | -0.00341              | 0.00243  | ±2.50          |
| 40°                 | -8.06                | -8.18 | -0.00466              | -0.00473 | ±2.50          |
| 50°                 | 1.42                 | -5.75 | 0.00081               | -0.00332 | ±2.50          |



#### 4. Test Setup Photos of the EUT





## 5. External and Internal Photos of the EUT

Reference to the test report No. CTL1909098011-WF01

\*\*\*\*\* End of Report \*\*\*\*\*