





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com



Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



LTE FDD Band 4-10MHz Channel Bandwidth  
Low Channel


QPSK

16QAM



30MHz~1GHz

30MHz~1GHz



1GHz~5GHz


1GHz~5GHz




5GHz~12GHz

5GHz~12GHz






LTE FDD Band 4-10MHz Channel Bandwidth  
Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



5GHz~12GHz

5GHz~12GHz



12GHz~26.5GHz

12GHz~26.5GHz


1RB#0

1RB#0

LTE FDD Band 4-10MHz Channel Bandwidth  
High Channel

QPSK

16QAM



30MHz~1GHz


30MHz~1GHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






LTE FDD Band 4-15MHz Channel Bandwidth  
Low Channel


## QPSK




## 16QAM




## 30MHz~1GHz




## 30MHz~1GHz



## 1GHz~5GHz





## 1GHz~5GHz



## 5GHz~12GHz

## 5GHz~12GHz




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






LTE FDD Band 4-20MHz Channel Bandwidth  
Low Channel

## QPSK




## 16QAM



## 30MHz~1GHz



## 30MHz~1GHz



## 1GHz~5GHz




## 1GHz~5GHz



## 5GHz~12GHz


## 5GHz~12GHz



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

**Radiated Measurement:****Remark:**

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case for each Channel Bandwidth of LTE FDD Band 4.
2.  $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + G_a(dBi)$
3. We were not recorded other points as values lower than limits.
4.  $Margin = Limit - EIRP$

LTE FDD Band 4 Channel Bandwidth 1.4MHz QPSK Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3421.4          | -43.08     | 4.02     | 3.00     | 12.5                | -34.6           | -13.00      | 21.6        | H            |
| 5132.1          | -48.23     | 5.11     | 3.00     | 13.38               | -39.96          | -13.00      | 26.96       | H            |
| 3421.4          | -51.18     | 4.02     | 3.00     | 12.5                | -42.7           | -13.00      | 29.7        | V            |
| 5132.1          | -49.49     | 5.11     | 3.00     | 13.38               | -41.22          | -13.00      | 28.22       | V            |

LTE FDD Band 4 Channel Bandwidth 1.4MHz QPSK Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -44.01     | 4.02     | 3.00     | 12.45               | -35.58     | -13.00      | 22.58       | H            |
| 5197.5          | -47.75     | 5.11     | 3.00     | 13.38               | -39.48     | -13.00      | 26.48       | H            |
| 3465.0          | -49.15     | 4.02     | 3.00     | 12.45               | -40.72     | -13.00      | 27.72       | V            |
| 5197.5          | -47.65     | 5.11     | 3.00     | 13.38               | -39.38     | -13.00      | 26.38       | V            |

LTE FDD Band 4 Channel Bandwidth 1.4MHz QPSK High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3508.6          | -43.37     | 4.02     | 3.00     | 12.21               | -35.18     | -13.00      | 22.18       | H            |
| 5262.9          | -46.69     | 5.11     | 3.00     | 13.26               | -38.54     | -13.00      | 25.54       | H            |
| 3508.6          | -48.27     | 4.02     | 3.00     | 12.21               | -40.08     | -13.00      | 27.08       | V            |
| 5262.9          | -47.82     | 5.11     | 3.00     | 13.26               | -39.67     | -13.00      | 26.67       | V            |

LTE FDD Band 4 Channel Bandwidth 3MHz QPSK Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3423.0          | -45.32     | 4.02     | 3.00     | 12.5                | -36.84          | -13.00      | 23.84       | H            |
| 5134.5          | -47.9      | 5.11     | 3.00     | 13.38               | -39.63          | -13.00      | 26.63       | H            |
| 3423.0          | -49.92     | 4.02     | 3.00     | 12.5                | -41.44          | -13.00      | 28.44       | V            |
| 5134.5          | -47.79     | 5.11     | 3.00     | 13.38               | -39.52          | -13.00      | 26.52       | V            |

LTE FDD Band 4 Channel Bandwidth 3MHz QPSK Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -44.57     | 4.02     | 3.00     | 12.45               | -36.14     | -13.00      | 23.14       | H            |
| 5197.5          | -47.12     | 5.11     | 3.00     | 13.38               | -38.85     | -13.00      | 25.85       | H            |
| 3465.0          | -49.66     | 4.02     | 3.00     | 12.45               | -41.23     | -13.00      | 28.23       | V            |
| 5197.5          | -47.81     | 5.11     | 3.00     | 13.38               | -39.54     | -13.00      | 26.54       | V            |



LTE FDD Band 4\_Channel Bandwidth 3MHz\_QPSK\_High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3507.0          | -43.34     | 4.02     | 3.00     | 12.21               | -35.15     | -13.00      | 22.15       | H            |
| 5260.5          | -47.27     | 5.11     | 3.00     | 13.26               | -39.12     | -13.00      | 26.12       | H            |
| 3507.0          | -48.44     | 4.02     | 3.00     | 12.21               | -40.25     | -13.00      | 27.25       | V            |
| 5260.5          | -48.37     | 5.11     | 3.00     | 13.26               | -40.22     | -13.00      | 27.22       | V            |

LTE FDD Band 4\_Channel Bandwidth 5MHz\_QPSK\_Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3425.0          | -42.83     | 4.02     | 3.00     | 12.5                | -34.35          | -13.00      | 21.35       | H            |
| 5137.5          | -48.29     | 5.11     | 3.00     | 13.38               | -40.02          | -13.00      | 27.02       | H            |
| 3425.0          | -51.59     | 4.02     | 3.00     | 12.5                | -43.11          | -13.00      | 30.11       | V            |
| 5137.5          | -48.37     | 5.11     | 3.00     | 13.38               | -40.1           | -13.00      | 27.1        | V            |

LTE FDD Band 4\_Channel Bandwidth 5MHz\_QPSK\_Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -44.15     | 4.02     | 3.00     | 12.45               | -35.72     | -13.00      | 22.72       | H            |
| 5197.5          | -47.58     | 5.11     | 3.00     | 13.38               | -39.31     | -13.00      | 26.31       | H            |
| 3465.0          | -49.74     | 4.02     | 3.00     | 12.45               | -41.31     | -13.00      | 28.31       | V            |
| 5197.5          | -47.36     | 5.11     | 3.00     | 13.38               | -39.09     | -13.00      | 26.09       | V            |

LTE FDD Band 4\_Channel Bandwidth 5MHz\_QPSK\_High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3505.0          | -42.82     | 4.02     | 3.00     | 12.21               | -34.63     | -13.00      | 21.63       | H            |
| 5257.5          | -47.25     | 5.11     | 3.00     | 13.26               | -39.1      | -13.00      | 26.1        | H            |
| 3505.0          | -48.29     | 4.02     | 3.00     | 12.21               | -40.1      | -13.00      | 27.1        | V            |
| 5257.5          | -48.1      | 5.11     | 3.00     | 13.26               | -39.95     | -13.00      | 26.95       | V            |

LTE FDD Band 4\_Channel Bandwidth 10MHz\_QPSK\_Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3430.0          | -43.4      | 4.02     | 3.00     | 12.5                | -34.92          | -13.00      | 21.92       | H            |
| 5145.0          | -48.23     | 5.11     | 3.00     | 13.38               | -39.96          | -13.00      | 26.96       | H            |
| 3430.0          | -51.16     | 4.02     | 3.00     | 12.5                | -42.68          | -13.00      | 29.68       | V            |
| 5145.0          | -48.77     | 5.11     | 3.00     | 13.38               | -40.5           | -13.00      | 27.5        | V            |

LTE FDD Band 4\_Channel Bandwidth 10MHz\_QPSK\_Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -44.09     | 4.02     | 3.00     | 12.45               | -35.66     | -13.00      | 22.66       | H            |
| 5197.5          | -47.53     | 5.11     | 3.00     | 13.38               | -39.26     | -13.00      | 26.26       | H            |
| 3465.0          | -49.3      | 4.02     | 3.00     | 12.45               | -40.87     | -13.00      | 27.87       | V            |
| 5197.5          | -47.68     | 5.11     | 3.00     | 13.38               | -39.41     | -13.00      | 26.41       | V            |





LTE FDD Band 4 Channel Bandwidth 10MHz\_QPSK\_High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3500.0          | -43.3      | 4.02     | 3.00     | 12.21               | -35.11     | -13.00      | 22.11       | H            |
| 5250.0          | -46.99     | 5.11     | 3.00     | 13.26               | -38.84     | -13.00      | 25.84       | H            |
| 3500.0          | -49.11     | 4.02     | 3.00     | 12.21               | -40.92     | -13.00      | 27.92       | V            |
| 5250.0          | -48.47     | 5.11     | 3.00     | 13.26               | -40.32     | -13.00      | 27.32       | V            |

LTE FDD Band 4 Channel Bandwidth 15MHz\_QPSK\_Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3435.0          | -43.2      | 4.02     | 3.00     | 12.5                | -34.72          | -13.00      | 21.72       | H            |
| 5152.5          | -48.34     | 5.11     | 3.00     | 13.38               | -40.07          | -13.00      | 27.07       | H            |
| 3435.0          | -50.97     | 4.02     | 3.00     | 12.5                | -42.49          | -13.00      | 29.49       | V            |
| 5152.5          | -49.53     | 5.11     | 3.00     | 13.38               | -41.26          | -13.00      | 28.26       | V            |

LTE FDD Band 4 Channel Bandwidth 15MHz\_QPSK\_Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -44.2      | 4.02     | 3.00     | 12.45               | -35.77     | -13.00      | 22.77       | H            |
| 5197.5          | -47.09     | 5.11     | 3.00     | 13.38               | -38.82     | -13.00      | 25.82       | H            |
| 3465.0          | -49.87     | 4.02     | 3.00     | 12.45               | -41.44     | -13.00      | 28.44       | V            |
| 5197.5          | -48.03     | 5.11     | 3.00     | 13.38               | -39.76     | -13.00      | 26.76       | V            |

LTE FDD Band 4 Channel Bandwidth 15MHz\_QPSK\_High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3495.0          | -43.27     | 4.02     | 3.00     | 12.21               | -35.08     | -13.00      | 22.08       | H            |
| 5242.5          | -46.7      | 5.11     | 3.00     | 13.26               | -38.55     | -13.00      | 25.55       | H            |
| 3495.0          | -48.61     | 4.02     | 3.00     | 12.21               | -40.42     | -13.00      | 27.42       | V            |
| 5242.5          | -47.94     | 5.11     | 3.00     | 13.26               | -39.79     | -13.00      | 26.79       | V            |

LTE FDD Band 4 Channel Bandwidth 20MHz\_QPSK\_Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3440.0          | -45.51     | 4.02     | 3.00     | 12.5                | -37.03          | -13.00      | 24.03       | H            |
| 5160.0          | -50.41     | 5.11     | 3.00     | 13.38               | -42.14          | -13.00      | 29.14       | H            |
| 3440.0          | -48.85     | 4.02     | 3.00     | 12.5                | -40.37          | -13.00      | 27.37       | V            |
| 5160.0          | -47.8      | 5.11     | 3.00     | 13.38               | -39.53          | -13.00      | 26.53       | V            |

LTE FDD Band 4 Channel Bandwidth 20MHz\_QPSK\_Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -43.76     | 4.02     | 3.00     | 12.45               | -35.33     | -13.00      | 22.33       | H            |
| 5197.5          | -47.67     | 5.11     | 3.00     | 13.38               | -39.4      | -13.00      | 26.4        | H            |
| 3465.0          | -49.98     | 4.02     | 3.00     | 12.45               | -41.55     | -13.00      | 28.55       | V            |
| 5197.5          | -47.25     | 5.11     | 3.00     | 13.38               | -38.98     | -13.00      | 25.98       | V            |



LTE FDD Band 4 Channel Bandwidth 20MHz\_QPSK\_High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3490.0          | -42.83     | 4.02     | 3.00     | 12.21               | -34.64     | -13.00      | 21.64       | H            |
| 5235.0          | -46.76     | 5.11     | 3.00     | 13.26               | -38.61     | -13.00      | 25.61       | H            |
| 3490.0          | -48.62     | 4.02     | 3.00     | 12.21               | -40.43     | -13.00      | 27.43       | V            |
| 5235.0          | -48.15     | 5.11     | 3.00     | 13.26               | -40        | -13.00      | 27          | V            |

LTE FDD Band 4 Channel Bandwidth 1.4MHz\_16QAM\_Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3421.4          | -44.69     | 4.02     | 3.00     | 12.5                | -36.21          | -13.00      | 23.21       | H            |
| 5132.1          | -47.95     | 5.11     | 3.00     | 13.38               | -39.68          | -13.00      | 26.68       | H            |
| 3421.4          | -50.87     | 4.02     | 3.00     | 12.5                | -42.39          | -13.00      | 29.39       | V            |
| 5132.1          | -47.38     | 5.11     | 3.00     | 13.38               | -39.11          | -13.00      | 26.11       | V            |

LTE FDD Band 4 Channel Bandwidth 1.4MHz\_16QAM\_Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -44.11     | 4.02     | 3.00     | 12.45               | -35.68     | -13.00      | 22.68       | H            |
| 5197.5          | -47.91     | 5.11     | 3.00     | 13.38               | -39.64     | -13.00      | 26.64       | H            |
| 3465.0          | -49.6      | 4.02     | 3.00     | 12.45               | -41.17     | -13.00      | 28.17       | V            |
| 5197.5          | -47.15     | 5.11     | 3.00     | 13.38               | -38.88     | -13.00      | 25.88       | V            |

LTE FDD Band 4 Channel Bandwidth 1.4MHz\_16QAM\_High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3508.6          | -42.69     | 4.02     | 3.00     | 12.21               | -34.5      | -13.00      | 21.5        | H            |
| 5262.9          | -47.07     | 5.11     | 3.00     | 13.26               | -38.92     | -13.00      | 25.92       | H            |
| 3508.6          | -49.15     | 4.02     | 3.00     | 12.21               | -40.96     | -13.00      | 27.96       | V            |
| 5262.9          | -48        | 5.11     | 3.00     | 13.26               | -39.85     | -13.00      | 26.85       | V            |

LTE FDD Band 4 Channel Bandwidth 3MHz\_16QAM\_Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3423.0          | -43.25     | 4.02     | 3.00     | 12.5                | -34.77          | -13.00      | 21.77       | H            |
| 5134.5          | -48.85     | 5.11     | 3.00     | 13.38               | -40.58          | -13.00      | 27.58       | H            |
| 3423.0          | -51.42     | 4.02     | 3.00     | 12.5                | -42.94          | -13.00      | 29.94       | V            |
| 5134.5          | -49.85     | 5.11     | 3.00     | 13.38               | -41.58          | -13.00      | 28.58       | V            |

LTE FDD Band 4 Channel Bandwidth 3MHz\_16QAM\_Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -43.72     | 4.02     | 3.00     | 12.45               | -35.29     | -13.00      | 22.29       | H            |
| 5197.5          | -47.61     | 5.11     | 3.00     | 13.38               | -39.34     | -13.00      | 26.34       | H            |
| 3465.0          | -49.8      | 4.02     | 3.00     | 12.45               | -41.37     | -13.00      | 28.37       | V            |
| 5197.5          | -47.41     | 5.11     | 3.00     | 13.38               | -39.14     | -13.00      | 26.14       | V            |



LTE FDD Band 4 Channel Bandwidth 3MHz\_16QAM\_High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3507.0          | -42.65     | 4.02     | 3.00     | 12.21               | -34.46     | -13.00      | 21.46       | H            |
| 5260.5          | -47.06     | 5.11     | 3.00     | 13.26               | -38.91     | -13.00      | 25.91       | H            |
| 3507.0          | -48.88     | 4.02     | 3.00     | 12.21               | -40.69     | -13.00      | 27.69       | V            |
| 5260.5          | -48.03     | 5.11     | 3.00     | 13.26               | -39.88     | -13.00      | 26.88       | V            |

LTE FDD Band 4 Channel Bandwidth 5MHz\_16QAM\_Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3425.0          | -44.29     | 4.02     | 3.00     | 12.5                | -35.81          | -13.00      | 22.81       | H            |
| 5137.5          | -50.33     | 5.11     | 3.00     | 13.38               | -42.06          | -13.00      | 29.06       | H            |
| 3425.0          | -49.42     | 4.02     | 3.00     | 12.5                | -40.94          | -13.00      | 27.94       | V            |
| 5137.5          | -48.17     | 5.11     | 3.00     | 13.38               | -39.9           | -13.00      | 26.9        | V            |

LTE FDD Band 4 Channel Bandwidth 5MHz\_16QAM\_Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -43.66     | 4.02     | 3.00     | 12.45               | -35.23     | -13.00      | 22.23       | H            |
| 5197.5          | -47.45     | 5.11     | 3.00     | 13.38               | -39.18     | -13.00      | 26.18       | H            |
| 3465.0          | -49.35     | 4.02     | 3.00     | 12.45               | -40.92     | -13.00      | 27.92       | V            |
| 5197.5          | -47.65     | 5.11     | 3.00     | 13.38               | -39.38     | -13.00      | 26.38       | V            |

LTE FDD Band 4 Channel Bandwidth 5MHz\_16QAM\_High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3505.0          | -42.68     | 4.02     | 3.00     | 12.21               | -34.49     | -13.00      | 21.49       | H            |
| 5257.5          | -47.25     | 5.11     | 3.00     | 13.26               | -39.1      | -13.00      | 26.1        | H            |
| 3505.0          | -48.52     | 4.02     | 3.00     | 12.21               | -40.33     | -13.00      | 27.33       | V            |
| 5257.5          | -47.83     | 5.11     | 3.00     | 13.26               | -39.68     | -13.00      | 26.68       | V            |

LTE FDD Band 4 Channel Bandwidth 10MHz\_16QAM\_Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3430.0          | -45.57     | 4.02     | 3.00     | 12.5                | -37.09          | -13.00      | 24.09       | H            |
| 5145.0          | -47.88     | 5.11     | 3.00     | 13.38               | -39.61          | -13.00      | 26.61       | H            |
| 3430.0          | -49.08     | 4.02     | 3.00     | 12.5                | -40.6           | -13.00      | 27.6        | V            |
| 5145.0          | -47.14     | 5.11     | 3.00     | 13.38               | -38.87          | -13.00      | 25.87       | V            |

LTE FDD Band 4 Channel Bandwidth 10MHz\_16QAM\_Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -44.44     | 4.02     | 3.00     | 12.45               | -36.01     | -13.00      | 23.01       | H            |
| 5197.5          | -47.65     | 5.11     | 3.00     | 13.38               | -39.38     | -13.00      | 26.38       | H            |
| 3465.0          | -49.69     | 4.02     | 3.00     | 12.45               | -41.26     | -13.00      | 28.26       | V            |
| 5197.5          | -48.02     | 5.11     | 3.00     | 13.38               | -39.75     | -13.00      | 26.75       | V            |





LTE FDD Band 4 Channel Bandwidth 10MHz\_16QAM\_High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3500.0          | -42.6      | 4.02     | 3.00     | 12.21               | -34.41     | -13.00      | 21.41       | H            |
| 5250.0          | -46.92     | 5.11     | 3.00     | 13.26               | -38.77     | -13.00      | 25.77       | H            |
| 3500.0          | -49.21     | 4.02     | 3.00     | 12.21               | -41.02     | -13.00      | 28.02       | V            |
| 5250.0          | -47.95     | 5.11     | 3.00     | 13.26               | -39.8      | -13.00      | 26.8        | V            |

LTE FDD Band 4 Channel Bandwidth 15MHz\_16QAM\_Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3435.0          | -44.2      | 4.02     | 3.00     | 12.5                | -35.72          | -13.00      | 22.72       | H            |
| 5152.5          | -47.72     | 5.11     | 3.00     | 13.38               | -39.45          | -13.00      | 26.45       | H            |
| 3435.0          | -49.08     | 4.02     | 3.00     | 12.5                | -40.6           | -13.00      | 27.6        | V            |
| 5152.5          | -47.43     | 5.11     | 3.00     | 13.38               | -39.16          | -13.00      | 26.16       | V            |

LTE FDD Band 4 Channel Bandwidth 15MHz\_16QAM\_Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -44.11     | 4.02     | 3.00     | 12.45               | -35.68     | -13.00      | 22.68       | H            |
| 5197.5          | -47.1      | 5.11     | 3.00     | 13.38               | -38.83     | -13.00      | 25.83       | H            |
| 3465.0          | -49.76     | 4.02     | 3.00     | 12.45               | -41.33     | -13.00      | 28.33       | V            |
| 5197.5          | -47.59     | 5.11     | 3.00     | 13.38               | -39.32     | -13.00      | 26.32       | V            |

LTE FDD Band 4 Channel Bandwidth 15MHz\_16QAM\_High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3495.0          | -42.9      | 4.02     | 3.00     | 12.21               | -34.71     | -13.00      | 21.71       | H            |
| 5242.5          | -47.09     | 5.11     | 3.00     | 13.26               | -38.94     | -13.00      | 25.94       | H            |
| 3495.0          | -48.53     | 4.02     | 3.00     | 12.21               | -40.34     | -13.00      | 27.34       | V            |
| 5242.5          | -48.29     | 5.11     | 3.00     | 13.26               | -40.14     | -13.00      | 27.14       | V            |

LTE FDD Band 4 Channel Bandwidth 20MHz\_16QAM\_Low Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|-----------------|-------------|-------------|--------------|
| 3440.0          | -44.55     | 4.02     | 3.00     | 12.5                | -36.07          | -13.00      | 23.07       | H            |
| 5160.0          | -48.08     | 5.11     | 3.00     | 13.38               | -39.81          | -13.00      | 26.81       | H            |
| 3440.0          | -49.27     | 4.02     | 3.00     | 12.5                | -40.79          | -13.00      | 27.79       | V            |
| 5160.0          | -47.07     | 5.11     | 3.00     | 13.38               | -38.8           | -13.00      | 25.8        | V            |

LTE FDD Band 4 Channel Bandwidth 20MHz\_16QAM\_Middle Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3465.0          | -43.72     | 4.02     | 3.00     | 12.45               | -35.29     | -13.00      | 22.29       | H            |
| 5197.5          | -47.54     | 5.11     | 3.00     | 13.38               | -39.27     | -13.00      | 26.27       | H            |
| 3465.0          | -49.76     | 4.02     | 3.00     | 12.45               | -41.33     | -13.00      | 28.33       | V            |
| 5197.5          | -47.92     | 5.11     | 3.00     | 13.38               | -39.65     | -13.00      | 26.65       | V            |



## LTE FDD Band 4 Channel Bandwidth 20MHz 16QAM High Channel

| Frequency (MHz) | PMea (dBm) | Pcl (dB) | Diatance | Ga Antenna Gain(dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------|----------|----------|---------------------|------------|-------------|-------------|--------------|
| 3490.0          | -43.37     | 4.02     | 3.00     | 12.21               | -35.18     | -13.00      | 22.18       | H            |
| 5235.0          | -46.96     | 5.11     | 3.00     | 13.26               | -38.81     | -13.00      | 25.81       | H            |
| 3490.0          | -48.62     | 4.02     | 3.00     | 12.21               | -40.43     | -13.00      | 27.43       | V            |
| 5235.0          | -48.56     | 5.11     | 3.00     | 13.26               | -40.41     | -13.00      | 27.41       | V            |




### 3.6 Frequency Stability Under Temperature & Voltage Variations

#### LIMIT

According to §27.54, §2.1055 requirement, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation and should not exceed 2.5ppm.

#### TEST CONFIGURATION



#### TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D.

##### **Frequency Stability Under Temperature Variations:**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 4, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

##### **Frequency Stability Under Voltage Variations:**

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ( $\pm 15\%$ ) and endpoint, record the maximum frequency change.



**TEST RESULTS**

Remark:

1. We tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case.

LTE Band 4, 1.4MHz bandwidth, QPSK (worst case of all bandwidths).


| LTE FDD Band 4 |                  |                     |                      |         |
|----------------|------------------|---------------------|----------------------|---------|
| DC Power(V)    | Temperature (°C) | Frequency error(Hz) | Frequency error(ppm) | Verdict |
| 4.5            | 20               | 26.99               | 0.015777             | PASS    |
| 5.0            | 20               | 12.82               | 0.007494             | PASS    |
| 5.5            | 20               | 22.34               | 0.013059             | PASS    |
| 5.0            | -30              | 37.44               | 0.021886             | PASS    |
| 5.0            | -20              | 28.61               | 0.016724             | PASS    |
| 5.0            | -10              | 27.24               | 0.015923             | PASS    |
| 5.0            | 0                | 36.51               | 0.021342             | PASS    |
| 5.0            | 10               | 27.68               | 0.016181             | PASS    |
| 5.0            | 20               | -42.31              | -0.024421            | PASS    |
| 5.0            | 30               | -24.36              | -0.014061            | PASS    |
| 5.0            | 40               | -35.16              | -0.020294            | PASS    |
| 5.0            | 50               | -31.20              | -0.018009            | PASS    |

LTE Band 4, 1.4MHz bandwidth , 16QAM (worst case of all bandwidths)

| LTE FDD Band 4 |                  |                     |                      |         |
|----------------|------------------|---------------------|----------------------|---------|
| DC Power(V)    | Temperature (°C) | Frequency error(Hz) | Frequency error(ppm) | Verdict |
| 4.5            | 20               | 11.19               | 0.006541             | PASS    |
| 5.0            | 20               | 3.86                | 0.002256             | PASS    |
| 5.5            | 20               | 18.58               | 0.010861             | PASS    |
| 5.0            | -30              | 8.87                | 0.005185             | PASS    |
| 5.0            | -20              | 20.48               | 0.011972             | PASS    |
| 5.0            | -10              | -13.62              | -0.007962            | PASS    |
| 5.0            | 0                | 32.62               | 0.019068             | PASS    |
| 5.0            | 10               | 39.41               | 0.023037             | PASS    |
| 5.0            | 20               | -31.50              | -0.018182            | PASS    |
| 5.0            | 30               | -22.24              | -0.012837            | PASS    |
| 5.0            | 40               | -52.69              | -0.030413            | PASS    |
| 5.0            | 50               | -25.78              | -0.014880            | PASS    |



#### 4 TEST SETUP PHOTOS OF THE EUT





## **5 PHOTOS OF THE EUT**

Reference to the report: ANNEX A of external photos and ANNEX B of internal photos.

.....End of Report.....