

FCC Test Report

FCC ID: 2AU5L-M5502B

Product: 4G Smart Phone

Trade Mark: CloudMosa

Model Number: Puffin OS Phone Founder's Edition
M5502B

Family Model: N/A

Report No.: STR191022002007E

Prepared for

CloudMosa, Inc.

20863 Stevens Creek Blvd. Suite 560, Cupertino, CA 95014

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen P.R. China
Tel.: +86-755-6115 6588
Fax.: +86-755-6115 6599
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name: CloudMosa, Inc.

Address: 20863 Stevens Creek Blvd. Suite 560, Cupertino, CA 95014

Manufacturer's Name: VPLUS COMMUNICATION INTELLIGENT CO.,LTD.

Address: 4/F, Building G ,Huachuangda Central Business Building,Junction of Xinghua 1st Road and Ban'an Avenue, Bao'an District,Shenzhen, China

Product description

Product name: 4G Smart Phone

Model and/or type reference : Puffin OS Phone Founder's Edition M5502B

Family Model: N/A

FCC Part15B

Standards: ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test:

Date (s) of performance of tests: Oct. 26, 2019 ~ Nov. 13, 2019

Date of Issue: Nov. 14, 2019

Test Result: **Pass**

Testing Engineer : Allen Liu
(Allen Liu)

Technical Manager : Jason Chen
(Jason Chen)

Authorized Signatory : Sam Chen
(Sam Chen)

Table of Contents	Page
1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST SETUP	8
2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	9
2.4 MEASUREMENT INSTRUMENTS LIST	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION	11
3.1.2 TEST PROCEDURE	12
3.1.3 TEST SETUP	12
3.1.4 EUT OPERATING CONDITIONS	12
3.1.5 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	17
3.2.2 TEST PROCEDURE	17
3.2.3 TEST SETUP	18
3.2.4 TEST RESULTS	19
3.2.5 TEST RESULTS	21

1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B ANSI C63.4: 2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

FCC Registration Number:463705; IC Registration Number:9270A-1

CNAS Registration Number:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95 %**.

Test Item	Measurement Frequency Range	K	U(dB)
AC Mains Conducted Emission	0.009kHz ~ 0.15MHz	2	2.66
AC Mains Conducted Emission	0.15MHz ~ 30MHz	2	2.80
Telecom Conducted Emission (Cat 3)	0.15MHz ~ 30MHz	2	2.40
Telecom Conducted Emission (Cat 5)	0.15MHz ~ 30MHz	2	2.58
Radiated Emission	30MHz ~ 1000MHz	2	2.64
Radiated Emission	1000MHz ~ 6000MHz	2	5.10
Radiated Emission	6000MHz ~ 18000MHz	2	2.52
Power Clamp	30MHz ~ 300MHz	2	2.20

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	4G Smart Phone				
Trade Mark	CloudMosa				
Model Name	Puffin OS Phone Founder's Edition M5502B				
Family Model	N/A				
Model Difference	N/A				
Product Description	<p>The EUT is a 4G Smart Phone.</p> <table border="1"><tr><td>Connecting I/O port:</td><td>Micro USB, Earphone</td></tr><tr><td>Operation Frequency:</td><td>2.568GHz</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>	Connecting I/O port:	Micro USB, Earphone	Operation Frequency:	2.568GHz
Connecting I/O port:	Micro USB, Earphone				
Operation Frequency:	2.568GHz				
Power Source	DC 3.8V from Battery or DC 5V from USB Port.				
Adapter	Model: HJ-0501000E1-US Input: 100-240V~50/60Hz 0.2A Output: 5V ---1000mA				
Battery	DC 3.8V/2600mAh				
HW Version	E62A-MB-V1.0				
SW Version	E62_M5502B_V02				

2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	USB Data Transmission
Mode 2	TF card Playing
Mode 3	REC
Mode 4	FM


For Conducted Test	
Final Test Mode	Description
Mode 1	USB Data Transmission
Mode 2	TF card Playing
Mode 3	REC
Mode 4	FM

For Radiated Test	
Final Test Mode	Description
Mode 1	USB Data Transmission
Mode 2	TF card Playing
Mode 3	REC
Mode 4	FM

Note: Final Test Mode: Through Pre-scan, find the mode 1 is the worst case.

Only the worst case mode is recorded in the report.

2.2 DESCRIPTION OF TEST SETUP



2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
AE-1	PC	DELL	FT4Y23X	N/A	Peripherals
AE-2	KB	DELL	SK-8185	N/A	Peripherals
AE-3	Mouse	DELL	MS111-P	N/A	Peripherals
AE-4	Monitor	SHARP	LCD-32MS46A	N/A	Peripherals
AE-5	Printer	Canon	L11121E	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable	NO	NO	1.0m	
C-2	KB Cable	NO	NO	1.2m	
C-3	Mouse Cable	NO	NO	1.2m	
C-4	HDMI Cable	YES	YES	1.0m	
C-5	USB Cable	NO	NO	1.2m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".

2.4 MEASUREMENT INSTRUMENTS LIST

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2019.05.13	2020.05.12	1 year
2	Test Receiver	R&S	ESPI	101318	2019.05.13	2020.05.12	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2019.04.15	2020.04.14	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2019.05.13	2020.05.12	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2019.05.13	2020.05.12	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2019.04.15	2020.04.14	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2019.05.13	2020.05.12	1 year
8	Amplifier	EMC	EMC051835 SE	980246	2019.08.06	2020.08.05	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2019.05.13	2020.05.12	1 year
10	Power Meter	DARE	RPR3006W	15I00041SN084	2019.08.06	2020.08.05	1 year
11	Power Sensor	R&S	URPuffin OS Phone Founder's Edition M5502B-Z4	0395.1619.05	2019.05.13	2020.05.12	1 year
12	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
13	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
14	High Test Cable(1G-40G Hz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2019.05.13	2020.05.12	1 year
2	LISN	R&S	ENV216	101313	2019.04.15	2020.04.14	1 year
3	LISN	SCHWARZ BECK	NNLK 8129	8129245	2019.05.13	2020.05.12	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2019.05.13	2020.05.12	1 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2017.04.21	2020.04.20	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMH) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.


3.1.5 TEST RESULTS

EUT:	4G Smart Phone	Model Name. :	Puffin OS Phone Founder's Edition M5502B
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2019-11-08
Test Mode:	Mode 1	Phase :	L
Test Voltage:	DC 5V from PC AC120V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.1660	41.95	9.76	51.71	65.15	-13.44	QP
0.1660	31.60	9.76	41.36	55.15	-13.79	AVG
0.2139	35.83	9.76	45.59	63.05	-17.46	QP
0.2139	25.60	9.76	35.36	53.05	-17.69	AVG
0.4979	36.06	9.74	45.80	56.03	-10.23	QP
0.4979	25.70	9.74	35.44	46.03	-10.59	AVG
0.8860	23.48	9.74	33.22	56.00	-22.78	QP
0.8860	13.62	9.74	23.36	46.00	-22.64	AVG
2.7659	23.95	9.82	33.77	56.00	-22.23	QP
2.7659	13.76	9.82	23.58	46.00	-22.42	AVG
13.7896	28.26	10.08	38.34	60.00	-21.66	QP
13.7896	18.36	10.08	28.44	50.00	-21.56	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	4G Smart Phone	Model Name. :	Puffin OS Phone Founder's Edition M5502B
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2019-11-08
Test Mode:	Mode 1	Phase :	N
Test Voltage:	DC 5V from PC AC120V/60Hz		

Frequency (MHz)	Reading Level (dB μ V)	Correct Factor (dB)	Measure-ment (dB μ V)	Limits (dB μ V)	Margin (dB)	Remark
0.1539	42.97	9.74	52.71	65.78	-13.07	QP
0.1539	32.28	9.74	42.02	55.78	-13.76	AVG
0.1819	39.91	9.73	49.64	64.39	-14.75	QP
0.1819	29.63	9.73	39.36	54.39	-15.03	AVG
0.2340	34.19	9.74	43.93	62.30	-18.37	QP
0.2340	23.51	9.74	33.25	52.30	-19.05	AVG
0.4979	35.76	9.75	45.51	56.03	-10.52	QP
0.4979	25.40	9.75	35.15	46.03	-10.88	AVG
3.5099	23.30	9.90	33.20	56.00	-22.80	QP
3.5099	13.12	9.90	23.02	46.00	-22.98	AVG
14.1059	27.03	10.09	37.12	60.00	-22.88	QP
14.1059	19.06	10.09	29.15	50.00	-20.85	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	4G Smart Phone	Model Name.:	Puffin OS Phone Founder's Edition M5502B
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2019-11-08
Test Mode:	Mode 1	Phase :	L
Test Voltage:	DC 5V from PC AC240V/60Hz		

Frequency (MHz)	Reading Level (dB μ V)	Correct Factor (dB)	Measure-ment (dB μ V)	Limits (dB μ V)	Margin (dB)	Remark
0.1660	44.95	9.76	54.71	65.15	-10.44	QP
0.1660	25.49	9.76	35.25	55.15	-19.90	AVG
0.4979	38.56	9.74	48.30	56.03	-7.73	QP
0.4979	30.55	9.74	40.29	46.03	-5.74	AVG
0.8860	25.98	9.74	35.72	56.00	-20.28	QP
0.8860	15.62	9.74	25.36	46.00	-20.64	AVG
1.3460	27.20	9.75	36.95	56.00	-19.05	QP
1.3460	18.61	9.75	28.36	46.00	-17.64	AVG
2.0139	27.42	9.78	37.20	56.00	-18.80	QP
2.0139	18.67	9.78	28.45	46.00	-17.55	AVG
13.7896	30.76	10.08	40.84	60.00	-19.16	QP
13.7896	20.69	10.08	30.77	50.00	-19.23	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	4G Smart Phone	Model Name. :	Puffin OS Phone Founder's Edition M5502B
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2019-11-08
Test Mode:	Mode 1	Phase :	N
Test Voltage:	DC 5V from PC AC240V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.1547	45.31	9.74	55.05	65.74	-10.69	QP
0.1547	35.36	9.74	45.10	55.74	-10.64	AVG
0.1900	42.97	9.73	52.70	64.03	-11.33	QP
0.1900	32.63	9.73	42.36	54.03	-11.67	AVG
0.2620	35.61	9.74	45.35	61.36	-16.01	QP
0.2620	25.92	9.74	35.66	51.36	-15.70	AVG
0.4979	38.76	9.75	48.51	56.03	-7.52	QP
0.4979	30.83	9.75	40.58	46.03	-5.45	AVG
1.4899	23.95	9.77	33.72	56.00	-22.28	QP
1.4899	16.25	9.77	26.02	46.00	-19.98	AVG
13.9419	30.80	10.09	40.89	60.00	-19.11	QP
13.9419	21.16	10.09	31.25	50.00	-18.75	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:

- (1) The limit for radiated test was performed according to as following:
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

3.2.2 TEST PROCEDURE

Test Arrangement for Radiated Emissions up to 1 GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

Test Arrangement for Radiated Emissions above 1 GHz.

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.


Note: For the hand-held device, the EUT should be measured for all 3 axes and only the worst case is recorded in the report

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Avg	1 MHz	10 Hz

3.2.3 TEST SETUP

For Radiated Emission 30~1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



3.2.4 TEST RESULTS


TEST RESULTS (30~1000 MHz)

EUT:	4G Smart Phone	Model Name:	Puffin OS Phone Founder's Edition M5502B
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2019-11-08
Test Mode :	Mode 1	Polarization :	Horizontal
Test Power :	DC 5V from PC AC120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	166.0680	26.93	10.51	37.44	43.50	-6.06	QP
H	224.5192	28.30	10.72	39.02	46.00	-6.98	QP
H	239.1473	28.75	11.45	40.20	46.00	-5.80	QP
H	314.3765	25.80	14.89	40.69	46.00	-5.31	QP
H	719.1992	15.70	24.01	39.71	46.00	-6.29	QP
H	827.4932	16.44	25.34	41.78	46.00	-4.22	QP

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.




EUT:	4G Smart Phone	Model Name :	Puffin OS Phone Founder's Edition M5502B
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2019-11-08
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	DC 5V from PC AC120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	166.0680	27.76	10.51	38.27	43.50	-5.23	QP
V	180.0165	27.71	9.68	37.39	43.50	-6.11	QP
V	226.0994	29.54	10.73	40.27	46.00	-5.73	QP
V	239.9874	28.93	11.55	40.48	46.00	-5.52	QP
V	324.4561	24.42	15.07	39.49	46.00	-6.51	QP
V	706.6998	16.93	23.23	40.16	46.00	-5.84	QP

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.



3.2.5 TEST RESULTS

EUT:	4G Smart Phone	Model Name :	Puffin OS Phone Founder's Edition M5502B
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2019-11-08
Test Mode :	Mode 1		
Test Power :	DC 5V from PC AC120V/60Hz		

All the modulation modes have been tested, and the worst result was report as below:

Polar (H/V)	Frequency	Reading	Correct	Result	Limit	Over Limit	Remar k
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/ m)	(dB)	
V	2105.00	38.52	6.20	44.72	74.00	-29.28	peak
V	2105.00	25.82	6.20	32.02	54.00	-21.98	AVG
V	2912.50	38.53	6.01	44.54	74.00	-29.46	peak
V	2912.50	28.14	6.01	34.15	54.00	-19.85	AVG
V	4187.50	38.60	11.16	49.76	74.00	-24.24	peak
V	4187.50	26.17	11.16	37.33	54.00	-16.67	AVG
V	4825.00	36.48	13.46	49.94	74.00	-24.06	peak
V	4825.00	23.23	13.46	36.69	54.00	-17.31	AVG
V	6567.50	34.82	15.57	50.39	74.00	-23.61	peak
V	6567.50	24.55	15.57	40.12	54.00	-13.88	AVG
V	8480.00	34.55	18.46	53.01	74.00	-20.99	peak
V	8480.00	22.86	18.46	41.32	54.00	-12.68	AVG
H	2105.00	38.08	6.20	44.28	74.00	-29.72	peak
H	2105.00	24.05	6.20	30.25	54.00	-23.75	AVG
H	3805.00	37.40	9.85	47.25	74.00	-26.75	peak
H	3805.00	21.17	9.85	31.02	54.00	-22.98	AVG
H	4230.00	38.08	11.33	49.41	74.00	-24.59	peak
H	4230.00	21.93	11.33	33.26	54.00	-20.74	AVG
H	4825.00	36.12	13.46	49.58	74.00	-24.42	peak
H	4825.00	21.66	13.46	35.12	54.00	-18.88	AVG
H	6567.50	34.77	15.57	50.34	74.00	-23.66	peak
H	6567.50	24.44	15.57	40.01	54.00	-13.99	AVG
H	8097.50	34.21	18.09	52.30	74.00	-21.70	peak
H	8097.50	21.45	18.09	39.54	54.00	-14.46	AVG

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

Note: Only the worst results data points are reported in the report.

When PK value is lower than the Average value limit, average don't record.