



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

RSS-GEN, ISSUE 5, MARCH 2019 AMENDMENT 1

RSS-247, ISSUE 2, FEBRUARY 2017

TEST REPORT

For

**Shenzhen Aukey Smart Information Technology
Co.,Ltd.**

Building P03, South China city Electronics Trading Center, Longgang District, Shenzhen,
Guangdong, 518111, China.

**FCC ID:2AU5S-EPK06NC
IC:25698-EPK06NC**

Report Type: Original Report	Product Name: True Wireless ANC Earbuds
Report Number: RDG200508005-00A	
Report Date: 2020-06-09	
Reviewed By:	Ivan Cao Assistant Manager 
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
DECLARATIONS.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §15.247 (i) & §1.1310 & §2.1093- RF Exposure	8
APPLICABLE STANDARD	8
RSS-102 § 2.5.1 EXEMPTION LIMITS FOR ROUTINE EVALUATION – SAR EVALUATION	9
APPLICABLE STANDARD	9
FCC §15.203, RSS-GEN CLAUSE 6.8 - ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.209, §15.205 & §15.247(d) , RSS-247 CLAUSE 5.5,RSS -GEN CLAUSE 8.10 - SPURIOUS EMISSIONS.....	11
APPLICABLE STANDARD	11
EUT SETUP.....	11
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	12
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST DATA	13
FCC §15.247(a) (1), RSS-247 CLAUSE 5.1 b) - CHANNEL SEPARATION TEST	19
APPLICABLE STANDARD	19
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST PROCEDURE	19
TEST DATA	19
FCC §15.247(a) (1), RSS-247 CLUASE 5.1&RSS-GEN CLAUSE 6.7 –BANDWIDTH TESTING.....	25
APPLICABLE STANDARD	25
TEST PROCEDURE	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST DATA	26
FCC §15.247(a) (1) (iii), RSS-247 CLAUSE 5.1 d) - QUANTITY OF HOPPING CHANNEL TEST	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37

TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA	37
FCC §15.247(a) (1) (iii), RSS-247 CLAUSE 5.1 d) - TIME OF OCCUPANCY (DWELL TIME).....	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST EQUIPMENT LIST AND DETAILS.....	40
TEST DATA	40
FCC §15.247(b) (1), RSS-247 CLAUSE 5.4 b) - PEAK OUTPUT POWER MEASUREMENT	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST EQUIPMENT LIST AND DETAILS.....	46
TEST DATA	46
FCC §15.247(d), RSS-247 CLAUSE 5.5 - BAND EDGES TESTING	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST EQUIPMENT LIST AND DETAILS.....	49
TEST DATA	49

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	True Wireless ANC Earbuds
EUT Model:	EP-K06NC
Operation Frequency:	2402-2480MHz
Maximum Peak Output Power (Conducted):	0.86 dBm
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Rated Input Voltage:	DC 3.7V from Battery or Charged by charger
Serial Number:	RDG200508005-RF-S1
EUT Received Date:	2020.05.12
EUT Received Status:	Good

Note: the left Earbuds and right Earbuds are identical, only left unit was tested.

Objective

This report is prepared on behalf of **Shenzhen Aukey Smart Information Technology Co.,Ltd.** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules, RSS-247, Issue 2, February 2017 of the Innovation, Science and Economic Development Canada, RSS-Gen, Issue 5, March 2019 Amendment 1 of the Innovation, Science and Economic Development Canada.

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules, RSS-247, Issue 2, February 2017, RSS-Gen, Issue 5, March 2019 Amendment 1 of the Innovation, Science and Economic Development Canada.

Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID:2AU5S-EPK06NC
RSS-247 submissions with IC:25698-EPK06NC

Test Methodology

All measurements detailed in this test report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices", RSS-247, Issue 2, February 2017 of the Innovation, Science and Economic Development Canada, RSS-Gen Issue 5, March 2019 Amendment 1 of the Innovation, Science and Economic Development Canada.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier : CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “△”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

The software " BQB.exe"was used for testing and the maximum power was configured as below:


Test Software Version	BQB.exe		
Test Frequency	2402MHz	2441MHz	2480MHz
GFSK	4	4	4
$\pi/4$ -DQPSK	4	4	4
8DPSK	4	4	4

Equipment Modifications

No modification was made to the EUT.

Block Diagram of Test Setup

Radiated Emissions:



SUMMARY OF TEST RESULTS

Rules	Description of Test	Result
§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
RSS-102 Clause 2.5.1	Exemption Limit For Routine Evaluation-SAR Evaluation	Compliance
FCC§15.203; RSS-GEN Clause 6.8	Antenna Requirement	Compliance
FCC§15.207 (a); RSS-Gen Clause 8.8	Conducted Emissions	Not Applicable
FCC§15.205, §15.209, §15.247(d); RSS-247 Clause 5.5, RSS-Gen Clause 8.10	Spurious Emissions	Compliance
FCC§15.247 (a)(1); RSS-247 Clause 5.1 b) RSS-Gen Clause 6.7	Bandwidth Test	Compliance
FCC§15.247(a)(1); RSS-247 Clause 5.1 b)	Channel Separation Test	Compliance
FCC§15.247(a)(1)(iii); RSS-247 Clause 5.1 d)	Time of Occupancy (Dwell Time)	Compliance
FCC§15.247(a)(1)(iii); RSS-247 Clause 5.1 d)	Quantity of hopping channel Test	Compliance
FCC§15.247(b)(1); RSS-247 Clause 5.4 b)	Peak Output Power Measurement	Compliance
FCC§15.247(d); RSS-247 Clause 5.5	Band Edges	Compliance

Not Applicable: the device was powered by battery when operating.

FCC §15.247 (i) & §1.1310 & §2.1093- RF Exposure

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is 1.0 dBm (1.26 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 1.26/5 \cdot (\sqrt{2.480}) = 0.4 < 3.0$

Result: Compliance. The stand-alone SAR evaluation is not necessary.

RSS-102 § 2.5.1 EXEMPTION LIMITS FOR ROUTINE EVALUATION – SAR EVALUATION

Applicable Standard

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5.

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance⁴⁵

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤ 5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤ 300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥ 50 mm
≤ 300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

Measurement Result:

The max tune-up conducted power is 1.0 dBm, Antenna Gain: 1.3 dBi, EIRP=2.13 dBm(1.63mW)

The exemption power(P) limits for routine evaluation in 2402-2480MHz is:

$$(2480-2450)/(3500-2450)=(P-4)/(2-4)$$

$$\Rightarrow P=3.94 \text{ mW}@2480 \text{ MHz}$$

$$> 1.63\text{mW}$$

So the stand-alone SAR evaluation can be exempted.

FCC §15.203, RSS-GEN CLAUSE 6.8 - ANTENNA REQUIREMENT**Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

According to RSS-Gen §6.8, The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has one internal FPC antenna arrangement, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
FPC	50	1.3 dBi/2.4~2.5GHz

Result: Compliance.


FCC §15.209, §15.205 & §15.247(d) , RSS-247 CLAUSE 5.5, RSS -GEN CLAUSE 8.10 - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205; RSS-247 Clause 5.5, RSS-GEN Clause 8.10

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 3 meters chamber test site A, above 1GHz tests were performed in the 3 meters chamber test site B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits and the RSS-247 Clause 5.5, RSS-GEN Clause 8.10 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

According to FCC public notice: DA-00-705, during the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
R&S	EMI Test Receiver	ESR3	102453	2019-09-12	2020-09-12
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2020-05-06	2021-05-06
HP	Amplifier	8447D	2727A05902	2019-09-05	2020-09-05
Radiation Above 1GHz					
Agilent	Spectrum Analyzer	E4440A	SG43360054	2020-05-09	2021-05-09
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2017-12-06	2020-12-05
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2019-09-05	2020-09-05
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	2019-09-05	2020-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2019-06-27	2020-06-27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2019-06-16	2020-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2019-06-16	2020-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	24.1 °C	24°C
Relative Humidity:	51%	51 %
ATM Pressure:	100.3 kPa	100.6 kPa
Tester:	Leo Long	Jalon Liu
Test Date:	2020-05-30	2020-05-31

Test Mode: Transmitting

1) 30MHz-1GHz(GFSK High channel was the worst)**Horizontal:**80.0 dB μ V/m

No.	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1	30.0000	25.77	peak	1.72	27.49	40.00	12.51
2	121.1800	27.26	peak	-4.68	22.58	43.50	20.92
3	311.3000	26.46	peak	-3.56	22.90	46.00	23.10
4	494.6300	28.18	peak	-0.28	27.90	46.00	18.10
5	641.1000	26.88	peak	2.25	29.13	46.00	16.87
6	710.9400	28.09	peak	3.16	31.25	46.00	14.75




Vertical:

No.	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1	30.9700	27.08	peak	0.91	27.99	40.00	12.01
2	128.9400	26.49	peak	-4.79	21.70	43.50	21.80
3	372.4100	27.47	peak	-2.74	24.73	46.00	21.27
4	473.2900	27.59	peak	-0.40	27.19	46.00	18.81
5	646.9200	28.54	peak	2.16	30.70	46.00	15.30
6	795.3300	28.53	peak	4.28	32.81	46.00	13.19

2) 1GHz-25GHz BDR Mode (GFSK) was the worst:




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2390.00	26.34	PK	V	28.08	1.80	0.00	56.22	74.00	17.78
2390.00	13.34	AV	V	28.08	1.80	0.00	43.22	54.00	10.78
4804.00	39.06	PK	V	32.91	3.17	25.60	49.54	74.00	24.46
4804.00	25.57	AV	V	32.91	3.17	25.60	36.05	54.00	17.95
7206.00	36.26	PK	V	35.74	4.82	25.60	51.22	74.00	22.78
7206.00	22.78	AV	V	35.74	4.82	25.60	37.74	54.00	16.26
Middle Channel: 2441 MHz									
4882.00	39.21	PK	V	33.06	3.27	25.66	49.88	74.00	24.12
4882.00	25.28	AV	V	33.06	3.27	25.66	35.95	54.00	18.05
7323.00	35.60	PK	V	36.04	4.62	25.73	50.53	74.00	23.47
7323.00	22.61	AV	V	36.04	4.62	25.73	37.54	54.00	16.46
High Channel: 2480 MHz									
2483.50	26.91	PK	V	28.27	1.84	0.00	57.02	74.00	16.98
2483.50	13.83	AV	V	28.27	1.84	0.00	43.94	54.00	10.06
4960.00	39.98	PK	V	33.22	3.23	25.63	50.80	74.00	23.20
4960.00	26.12	AV	V	33.22	3.23	25.63	36.94	54.00	17.06
7440.00	35.95	PK	V	36.34	4.41	25.85	50.85	74.00	23.15
7440.00	22.60	AV	V	36.34	4.41	25.85	37.50	54.00	16.50

Worst plots (GFSK Middle channel)
Horizontal



Vertical

Fundamental
Test with Band
Rejection Filter



FCC §15.247(a) (1), RSS-247 CLAUSE 5.1 b) - CHANNEL SEPARATION TEST**Applicable Standard**

According to FCC §15.247(a) (1), RSS-247 Clause 5.1 b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2019-09-19	2020-09-19
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data**Environmental Conditions**

Temperature:	28.1°C
Relative Humidity:	66%
ATM Pressure:	100.9Pa
Tester:	Chris Mo
Test Date:	2020-06-04


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
<i>BDR</i> (<i>GFSK</i>)	Low	2402	1.002	0.63
	Middle	2441	0.996	0.63
	High	2480	1.002	0.59
EDR ($\pi/4$ -DQPSK)	Low	2402	1.002	0.96
	Middle	2441	1.002	0.94
	High	2480	1.002	0.95
EDR (8-DPSK)	Low	2402	1.002	0.96
	Middle	2441	1.002	0.96
	High	2480	0.996	0.96

BDR Mode (GFSK):




Date: 4.JUN.2020 16:40:22

Middle Channel



Date: 4.JUN.2020 16:38:29


High Channel



Date: 4.JUN.2020 16:36:52


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 4.JUN.2020 15:48:42

Middle Channel



Date: 4.JUN.2020 15:46:38


High Channel



Date: 4.JUN.2020 15:44:49


EDR Mode (8DPSK):

Low Channel




Date: 4.JUN.2020 15:51:14

Middle Channel



Date: 4.JUN.2020 15:53:14

High Channel



Date: 4.JUN.2020 15:55:11

FCC §15.247(a) (1), RSS-247 CLAUSE 5.1&RSS-GEN CLAUSE 6.7 – BANDWIDTH TESTING

Applicable Standard

According to FCC §15.247(a) (1):

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to RSS-247 Clause 5.1 b):

- b) FHSs shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

According to RSS-Gen Clause 6.7:

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.

- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.
5. Use the OBW test function test the 99% Occupied bandwidth.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2019-09-19	2020-09-19
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.1°C
Relative Humidity:	66%
ATM Pressure:	100.9Pa
Tester:	Chris Mo
Test Date:	2020-06-04


Test Result: Compliance.
Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.940	0.848
	Middle	2441	0.944	0.852
	High	2480	0.884	0.852
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	1.434	1.350
	Middle	2441	1.404	1.344
	High	2480	1.422	1.344
EDR Mode (8DPSK)	Low	2402	1.440	1.344
	Middle	2441	1.446	1.350
	High	2480	1.440	1.350


20 dB Bandwidth BDR Mode (GFSK):

Low Channel




Date: 4.JUN.2020 16:39:02

Middle Channel




Date: 4.JUN.2020 16:37:25


High Channel



Date: 4.JUN.2020 16:35:35


*EDR Mode ($\pi/4$ -DQPSK):***Low Channel**

Date: 4.JUN.2020 17:37:37

Middle Channel

Date: 4.JUN.2020 17:38:56


High Channel



Date: 4.JUN.2020 17:41:40


EDR Mode (8DPSK):

Low Channel




Date: 4.JUN.2020 17:46:06

Middle Channel



Date: 4.JUN.2020 17:45:04


High Channel



Date: 4.JUN.2020 17:42:55


99% dB Bandwidth
BDR Mode (GFSK):

Low Channel




Date: 4.JUN.2020 16:39:21

Middle Channel



Date: 4.JUN.2020 16:37:41


High Channel



Date: 4.JUN.2020 16:35:48


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 4.JUN.2020 17:35:46

Middle Channel



Date: 4.JUN.2020 17:39:26


High Channel



Date: 4.JUN.2020 17:40:11


EDR Mode (8DPSK):

Low Channel




Date: 4.JUN.2020 17:47:12

Middle Channel



Date: 4.JUN.2020 17:44:10

High Channel



Date: 4.JUN.2020 17:43:29

FCC §15.247(a) (1) (iii), RSS-247 CLAUSE 5.1 d) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

According to FCC §15.247(a) (1) (iii), RSS-247 Clause 5.1 d)

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2019-09-19	2020-09-19
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	28.1°C
Relative Humidity:	66%
ATM Pressure:	100.9Pa
Tester:	Chris Mo
Test Date:	2020-06-04

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting


Test mode	Frequency Range (MHz)	Number of Hopping Channel	Limit
GFSK	2400-2483.5	79	≥ 15
$\pi/4$ -DQPSK	2400-2483.5	79	≥ 15
8DPSK	2400-2483.5	79	≥ 15

BDR Mode (GFSK)

Date: 4.JUN.2020 16:47:15

EDR Mode ($\pi/4$ -DQPSK)

Date: 4.JUN.2020 17:17:06

EDR Mode (8DPSK)

Date: 4.JUN.2020 17:32:51

FCC §15.247(a) (1) (iii), RSS-247 CLAUSE 5.1 d) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

According to FCC §15.247(a) (1) (iii), RSS-247 Clause 5.1 d):

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2019-09-19	2020-09-19
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	28.1°C
Relative Humidity:	66%
ATM Pressure:	100.9Pa
Tester:	Chris Mo
Test Date:	2020-06-04


Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Mode	Packet type	Channel	Frequency (MHz)	Pulse width (ms)	Result (s)	Limit (s)
GFSK	DH1	Middle	2441	0.394	0.126	0.4
	DH3	Middle	2441	1.513	0.242	
	DH5	Middle	2441	2.923	0.312	
$\pi/4$ -DQPSK	2DH1	Middle	2441	0.406	0.130	
	2DH3	Middle	2441	1.668	0.267	
	2DH5	Middle	2441	2.928	0.312	
8DPSK	3DH1	Middle	2441	0.406	0.130	
	3DH3	Middle	2441	1.682	0.269	
	3DH5	Middle	2441	2.928	0.312	


Note:
DH1:Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s
DH3:Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s
DH5:Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s

*BDR Mode (GFSK):***DH1: Middle Channel**


Date: 4.JUN.2020 16:51:01

DH3: Middle Channel


Date: 4.JUN.2020 16:52:50

DH5: Middle Channel

Date: 4.JUN.2020 16:53:43


*EDR Mode ($\pi/4$ -DQPSK):***2DH1: Middle Channel**

Date: 4.JUN.2020 17:06:26

2DH3: Middle Channel

Date: 4.JUN.2020 17:18:58


2DH5: Middle Channel



Date: 4.JUN.2020 17:20:48


EDR Mode (8DPSK):

Low Channel




Date: 4.JUN.2020 17:24:33

Middle Channel



Date: 4.JUN.2020 17:23:12

High Channel



Date: 4.JUN.2020 17:21:36

FCC §15.247(b) (1), RSS-247 CLAUSE 5.4 b) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

According to RSS-247 Clause 5.4 b)

- b) For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
E-Microwave	Blocking Control	EMDCB-00036	0E01201048	Each Time	/
Agilent	USB Wideband Power Sensor	U2021XA	MY5425009	2020-05-09	2021-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.1°C
Relative Humidity:	66%
ATM Pressure:	100.9Pa
Tester:	Chris Mo
Test Date:	2020-06-04

Test Result: Compliance.

Test Mode: Transmitting

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	2402	0.19	21
	2441	0.86	21
	2480	-0.05	21
EDR Mode ($\pi/4$ -DQPSK)	2402	-1.46	21
	2441	-0.78	21
	2480	-1.39	21
EDR Mode (8DPSK)	2402	-1.15	21
	2441	-0.48	21
	2480	-1.12	21

Note: The data above was tested in conducted mode and the antenna gain is 1.3 dBi, so it meets the EIRP limit for ISSED.

FCC §15.247(d), RSS-247 CLAUSE 5.5 - BAND EDGES TESTING

Applicable Standard

According to FCC §15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to RSS-247 Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2019-09-19	2020-09-19
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

Temperature:	28.1°C
Relative Humidity:	66%
ATM Pressure:	100.9Pa
Tester:	Chris Mo
Test Date:	2020-06-04

Test Result: Compliance


Single mode:
BDR Mode (GFSK):

Band Edge, Left Side




Date: 4.JUN.2020 16:39:49


Band Edge, Right Side




Date: 4.JUN.2020 16:36:19

*EDR Mode ($\pi/4$ -DQPSK):***Band Edge, Left Side**


Date: 4.JUN.2020 15:48:03

Band Edge, Right Side


Date: 4.JUN.2020 15:44:11

*EDR Mode (8DPSK):***Band Edge, Left Side**


Date: 4.JUN.2020 15:50:07

Band Edge, Right Side

Date: 4.JUN.2020 15:54:31

*Hopping mode:**BDR Mode (GFSK):***Band Edge, Left Side**


Date: 4.JUN.2020 16:48:42

Band Edge, Right Side

Date: 4.JUN.2020 16:49:41


EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side



Date: 4.JUN.2020 17:09:01


Band Edge, Right Side



Date: 4.JUN.2020 17:11:17


EDR Mode (8DPSK):

Band Edge, Left Side



Date: 4.JUN.2020 17:26:59

Band Edge, Right Side



Date: 4.JUN.2020 17:28:19

***** END OF REPORT *****