

**Prüfbericht - Nr.:**  
Test Report No.:

**ReferenceTest Report No:**  
**ULR-TC568819300000076F**

**Seite 1 von 2**  
Page 1 of 2

# 1 RF Exposure Report

## 1.1 RF Exposure Measurement

The limit for Maximum Permissible Exposure (MPE) specified in FCC Part 1 Subpart I 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

## 1.2 RF Exposure Limit

According to FCC Part 1 Subpart I 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

**Table 1: Limits for Maximum Permissible Exposure (MPE)**

| Frequency Range<br>(MHz)                              | Electric Field<br>Strength (V/m) | Magnetic Field<br>Strength (A/m) | Power Density<br>(mW/cm <sup>2</sup> ) |
|-------------------------------------------------------|----------------------------------|----------------------------------|----------------------------------------|
| Limits for Occupational / controlled Exposures        |                                  |                                  |                                        |
| 300 - 1500                                            | --                               | --                               | F/300                                  |
| 1500 – 100000                                         | --                               | --                               | 5.0                                    |
| Limits for General population / Uncontrolled Exposure |                                  |                                  |                                        |
| 300 - 1500                                            | --                               | --                               | F/1500                                 |
| 1500 – 100000                                         | --                               | --                               | 1.0                                    |

F= Frequency in MHz

**Prüfbericht - Nr.:**

Test Report No.:

**ReferenceTest Report No:**

**ULR-TC568819300000076F**

Seite 2 von 2

Page 2 of 2

**1.2.1 Friss Formula**

Friss Transmission Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

**1.2.2 EUT Operation condition**

EUT was enabled to transmit and receive at lowest, middle and highest channels.

**1.2.3 Classification**

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.

Protocol: Bluetooth Low energy

Data Rate: 1 Mbps

Antenna Gain: +2 dBi = 1.5848 (linear gain)

**Table 2: Test Results for Maximum Permissible Exposure**

| Antenna Gain (dBi) | Channel (MHz) | Maximum Pout (dBm) | Output Power to Antenna (mW) | Power Density (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) |
|--------------------|---------------|--------------------|------------------------------|-------------------------------------|-----------------------------|
| 2                  | 2440          | 7.45               | 6.97                         | 0.00219789                          | 1                           |

**\*\*\*END OF TEST REPORT\*\*\***