

APPLICATION FOR CERTIFICATION  
On Behalf of  
GoodWe Technologies Co., Ltd.  
Smart Dongle

Model No. : WiFi/LAN Kit-20  
Brand : GOODWE  
FCC ID : 2AU7J-WIFILANKIT20

Prepared for

**GoodWe Technologies Co., Ltd.**  
No.90 Zijin Rd., New District, Suzhou, 215011, China

Prepared by

**Audix Technology (Wujiang) Co., Ltd. EMC Dept.**  
No. 1289 Jiangxing East Road, the Eastern Part of Wujiang Economic Development Zone  
Jiangsu China 215200

Tel : +86-512-63403993  
Fax : +86-512-63403339

Report Number : ACWE-F2308009  
Date of Test : May 10, 2024  
Date of Report : May 31, 2024

## TABLE OF CONTENTS

| <u>Description</u>                                     | <u>Page</u> |
|--|-------------|
| TEST REPORT CERTIFICATION .....                        | 4           |
| <b>1. DESCRIPTION OF VERSION</b> .....                 | <b>3</b>    |
| <b>2. GENERAL INFORMATION.....</b>                     | <b>5</b>    |
| 2.1. Description of Device (EUT).....                  | 5           |
| 2.2. Antenna Information.....                          | 5           |
| 2.3. EUT Specification Assessed in Current Report..... | 5           |
| 2.4. Description of Test Facility .....                | 6           |
| 2.5. Measurement Uncertainty.....                      | 6           |
| <b>3. SUMMARY OF STADARDS AND RESULTS.....</b>         | <b>7</b>    |
| 3.1. Specification Limits.....                         | 7           |
| 3.2. MPE Calculator Method .....                       | 7           |
| 3.3. Calculated Result .....                           | 8           |

## TEST REPORT CERTIFICATION

Applicant : GoodWe Technologies Co., Ltd.  
 Manufacturer : GoodWe Technologies Co., Ltd.  
 EUT Description : Smart Dongle  
 FCC ID : 2AU7J-WIFILANKIT20  
 (A) Model No. : WiFi/LAN Kit-20  
 (B) Brand : GOODWE  
 (C) Test Voltage : DC 5V

The measurement results are contained in this test report and Audix Technology (Wujiang) Co., Ltd. EMC Dept. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this test report shows that the EUT to be technically compliant with the FCC limits.

This test report applies to above tested sample only. This test report shall not be reproduced in part without written approval of Audix Technology (Wujiang) Co., Ltd. EMC Dept.

Date of Test: May 10, 2024

Date of Report: May 31, 2024

Prepared by :

Emma Hu  
(Emma Hu/Assistant Administrator)

Approved & Authorized Signer :

K.M Tong  
(K.M Tong/Assistant Manager)



## 1. DESCRIPTION OF VERSION

| Edition No. | Date of Rev. | Summary          | Report No.    |
|-------------|--------------|------------------|---------------|
| 0           | May 31, 2024 | Original Report. | ACWE-F2308009 |

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

Description : Smart Dongle  
 Model No. : WiFi/LAN Kit-20  
 FCC ID : 2AU7J-WIFILANKIT20  
 Brand : GOODWE  
 Applicant : GoodWe Technologies Co., Ltd.  
                   No.90 Zijin Rd., New District, Suzhou, 215011, China  
 Manufacturer : GoodWe Technologies Co., Ltd.  
                   No.90 Zijin Rd., New District, Suzhou, 215011, China  
 I/O Ports : LAN port\*1  
                   USB port\*1  
 Date of Receipt of Sample : Aug.01, 2023

### 2.2. Antenna Information

| Type        | Frequency (MHz) | Gain(dBi) |
|-------------|-----------------|-----------|
| PCB Antenna | 2400-2500       | 3.76      |

### 2.3. EUT Specification Assessed in Current Report

| Mode         | Fundamental Range (MHz) | Channel Number | Modulation                      |
|--------------|-------------------------|----------------|---------------------------------|
| 802.11b      | 2412-2462               | 11             | DSSS<br>(DBPSK/DQPSK/CCK)       |
| 802.11g      | 2412-2462               | 11             | OFDM<br>(BPSK/QPSK/16QAM/64QAM) |
| 802.11n-HT20 |                         |                |                                 |
| BLE-1M       | 2402-2480               | 40             | GFSK                            |

Remark: The information of test software, fixture and antenna gain is provided by customer.

## 2.4. Description of Test Facility

|                 |   |   |
|-----------------|---|---|
| Name of Firm    | : | <b>Audix Technology (Wujiang) Co., Ltd. EMC Dept.</b>   |
| Site Location   | : | No. 1289 Jiangxing East Road, the Eastern Part of Wujiang Economic Development Zone<br>Jiangsu China 215200   |
| Test Facilities | : | <b>RF Fully Chamber</b>   |
| NVLAP Lab Code  | : | 200786-0<br>Valid until on Sep.30, 2024<br>(NVLAP is a signatory member of ILAC MRA)<br>Remark: This report shall not be imply endorsement, certification or approval by NVLAP, NIST, or any agency of the U.S. Federal Government. |

## 2.5. Measurement Uncertainty

| Test Item       | Uncertainty                      |
|-----------------|----------------------------------|
| RF Output Power | y(dBm) $\pm$ U=y(dBm) $\pm$ 0.73 |

Remark: Uncertainty =  $k u_c(y)$

The standards listed in this report only require the uncertainty to be listed, and the measurement uncertainty is not required to be calculated in the measurement results. Therefore, the conformity judgment results are in accordance with the quality document TMC-205, and the test results in this report meet the requirements of the standards listed in this report.

### 3. SUMMARY OF STADARDS AND RESULTS

#### 3.1. Specification Limits

According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Limits for Maximum Permissible Exposure

| Frequency Range (MHz)   | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Average Time (Minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits For Occupational / Control Exposures (f = frequency)           |                               |                               |                                     |                        |
| 30-300  | 61.4                          | 0.163                         | 1.0                                 | 6                      |
| 300-1500  | ...                           | ...                           | f/300                               | 6                      |
| 1500-100,000  | ...                           | ...                           | 5.0                                 | 6                      |
| (B) Limits For General Population / Uncontrolled Exposure (f = frequency) |                               |                               |                                     |                        |
| 30-300  | 27.5                          | 0.073                         | 0.2                                 | 30                     |
| 300-1500  | ...                           | ...                           | f/1500                              | 30                     |
| 1500-100,000  | ...                           | ...                           | 1.0                                 | 30                     |

NOTE: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

#### 3.2. MPE Calculator Method

$$S = PG/(4 \pi R^2)$$

$$R = [PG/(4 \pi S)]^{0.5}$$

where: S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW) (the measured power value see Report: F12124 Section 6.6)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

## 3.3. Calculated Result

## WIFI 2.4GHz MPE

|   |   |
|---|---|
| Based on safety distance (r)=             | 20cm  |
| Highest Power Output (P)=                 | 16.04dBm = 40.18mW  |
| Antenna Gain (G)=                         | 3.76dBi =2.38Numerical  |
| MPE (S) = (P*G) / (4*π*r <sup>2</sup> ) = | = (40.18*2.38)/(4*π*20 <sup>2</sup> )=0.019mW/cm <sup>2</sup> |
| Conclusion: PASS                          |   |

-----The End-----