

FCC TEST REPORT

Product Name: Tablet

Trade Mark:  VaxCare or

Model No.: VaxHub2

Report Number: 200628012RFM-2

Test Standards: FCC 47 CFR Part 22
FCC 47 CFR Part 24
FCC 47 CFR Part 27

FCC ID: 2AU8DVAXHUB2

Test Result: PASS

Date of Issue: August 14, 2020

Prepared for:

VaxCare Corporation

3113 Lawton Road, Suite 250 Orlando, FL 32803

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China

TEL: +86-755-2823 0888

FAX: +86-755-2823 0886

Prepared by: _____
Henry Lu
Team Leader

Reviewed by: _____
Kevin Liang
Assistant Manager

Approved by: _____
Billy Li
Technical Director

Date: _____
August 14, 2020

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC4G-V1.0

Version

Version No.	Date	Description
V1.0	August 14, 2020	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC4G-V1.0

CONTENTS

1. GENERAL INFORMATION	5
1.1 CLIENT INFORMATION	5
1.2 EUT INFORMATION	5
1.2.1 GENERAL DESCRIPTION OF EUT	5
1.2.2 DESCRIPTION OF ACCESSORIES	5
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	6
1.4 DESCRIPTION OF SUPPORT UNITS	9
1.5 TEST LOCATION	9
1.6 TEST FACILITY	9
1.7 DEVIATION FROM STANDARDS	10
1.8 ABNORMALITIES FROM STANDARD CONDITIONS	10
1.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	10
1.10 MEASUREMENT UNCERTAINTY	10
2. TEST SUMMARY	11
3. EQUIPMENT LIST	13
4. TEST CONFIGURATION	14
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	14
4.2 TEST SETUP	15
4.2.1 FOR RADIATED EMISSIONS TEST SETUP	15
4.2.2 FOR CONDUCTED RF TEST SETUP	16
4.3 TEST CHANNELS	17
4.4 SYSTEM TEST CONFIGURATION	19
4.5 PRE-SCAN	20
4.5.1 LTE BAND 2	20
4.5.2 LTE BAND 4	21
4.5.3 LTE BAND 5	23
4.5.4 LTE BAND 12	24
4.5.5 LTE BAND 17	25
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	28
5.1 REFERENCE DOCUMENTS FOR TESTING	28
5.2 ERP OR EIRP	28
5.2.1 LTE BAND 2	29
5.2.2 LTE BAND 4	30
5.2.3 LTE BAND 5	31
5.2.4 LTE BAND 12	31
5.2.5 LTE BAND 17	32
5.3 CONDUCTED OUTPUT POWER	33
5.4 PEAK-TO-AVERAGE RATIO	34
5.4.1 LTE BAND 2	34
5.4.2 LTE BAND 4	38
5.4.3 LTE BAND 5	42
5.4.4 LTE BAND 12	46
5.4.5 LTE BAND 17	50
5.5 99%&26dB BANDWIDTH	54
5.5.1 LTE BAND 2	54
5.5.2 LTE BAND 4	64
5.5.3 LTE BAND 5	74
5.5.4 LTE BAND 12	81
5.5.5 LTE BAND 17	88
5.6 BAND EDGE AT ANTENNA TERMINALS	92
5.6.1 LTE BAND 2	93
5.6.2 LTE BAND 4	111
5.6.3 LTE BAND 5	129

5.6.4	LTE BAND 12	141
5.6.5	LTE BAND 17	153
5.7	SPURIOUS EMISSIONS AT ANTENNA TERMINALS	159
5.7.1	LTE BAND 2	160
5.7.2	LTE BAND 4	169
5.7.3	LTE BAND 5	178
5.7.4	LTE BAND 12	184
5.7.5	LTE BAND 17	190
5.8	FIELD STRENGTH OF SPURIOUS RADIATION.....	193
5.8.1	LTE BAND 2	194
5.8.2	LTE BAND 4	195
5.8.3	LTE BAND 5	196
5.8.4	LTE BAND 12	197
5.8.5	LTE BAND 17	198
5.9	FREQUENCY STABILITY	200
5.9.1	LTE BAND 2	200
5.9.2	LTE BAND 4	201
5.9.3	LTE BAND 5	201
5.9.4	LTE BAND 12	202
5.9.5	LTE BAND 17	202
APPENDIX 1 PHOTOS OF TEST SETUP		203
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS.....		203

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	VaxCare Corporation
Address of Applicant:	3113 Lawton Road, Suite 250 Orlando, FL 32803
Manufacturer:	VaxCare Corporation
Address of Manufacturer:	3113 Lawton Road, Suite 250 Orlando, FL 32803

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Tablet		
Model No.:	VaxHub2		
Trade Mark:	 VaxCare or		
DUT Stage:	Identical Prototype		
EUT Supports Function:	UTRA Bands:	Band II/ Band IV/ Band V	
	E-UTRA Bands:	FDD Band 2/ Band 4/ Band 5/ Band 12/ Band 17	
	2.4 GHz ISM Band:	IEEE 802.11b/g/n	
		Bluetooth V4.1	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac
Sample Received Date:	July 1, 2020		
Sample Tested Date:	July 1, 2020 to July 29, 2020		

1.2.2 Description of Accessories

Adapter	
Model No.:	Vaxhub2
Input:	120 V~60 Hz 0.6A
Output:	12V $\Rightarrow$ 2.0A
AC Cable:	0.50 Meter, Unshielded without ferrite
Manufacturer:	Ten Pao Electronics(Huizhou)Co.,Ltd

Battery	
Model No.:	BPVaxHub2
Battery Type:	Lithium-ion Rechargeable Battery
Rated Voltage:	7.4 Vdc
Limited Charge Voltage:	8.4 Vdc
Rated Capacity:	2600 mAh
Manufacturer:	Henan Great Power Energy Co.,Ltd

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Support Networks:	LTE	
Type of Modulation:	LTE Band 2/4/5/12/17	QPSK,16QAM,64QAM
Antenna Type:	PIFA Antenna	
Antenna Gain:	LTE Band 2:	1.2 dBi
	LTE Band 4:	0.4 dBi
	LTE Band 5:	-0.4dBi
	LTE Band 12:	-1.0 dBi
	LTE Band 17:	-1.0 dBi
Normal Test Voltage:	7.4 Vdc	
Extreme Test Voltage:	7.2 to 8.4Vdc	
Extreme Test Temperature:	-30 °C to +55 °C	

Summary of Results:								
Bands	BW	Modulation	Frequency Range	Max RF Output Power (dBm)		EIRP	99% BW	Emission Designator
	(MHz)		(MHz)	Conducted (Average)	ERP/EIRP (Average)	(W)	(MHz)	
2	1.4	QPSK	1850.7-1909.3	24.52	25.72	0.37325	1.1045	1M10G7D
		16QAM		23.87	25.07	0.32137	1.0970	1M10W7D
		64QAM		23.86	25.06	0.32063	1.0952	1M10W7D
	3	QPSK	1851.5-1908.5	24.45	25.74	0.37497	2.6950	2M70G7D
		16QAM		23.93	25.17	0.32885	2.6884	2M69W7D
		64QAM		23.80	25.00	0.31623	2.6830	2M68W7D
	5	QPSK	1852.5-1907.5	24.54	25.65	0.36728	4.5315	4M53G7D
		16QAM		23.97	25.17	0.32885	4.5553	4M55W7D
		64QAM		23.80	25.00	0.31623	4.5416	4M54W7D
	10	QPSK	1855.0-1905.0	24.59	25.79	0.37931	9.0280	9M03G7D
		16QAM		23.87	25.07	0.32137	9.0156	9M02W7D
		64QAM		23.82	25.02	0.31769	9.0019	9M00W7D
	15	QPSK	1857.5-1902.5	24.49	25.69	0.37068	13.535	13M5G7D
		16QAM		23.89	25.09	0.32285	13.536	13M5W7D
		64QAM		23.86	25.06	0.32063	13.536	13M5W7D
	20	QPSK	1860.0-1900.0	24.61	25.81	0.38107	18.029	18M0G7D
		16QAM		24.00	25.20	0.33113	18.060	18M1W7D
		64QAM		23.89	25.09	0.32285	18.023	18M0W7D

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC4G-V1.0

Summary of Results:								
Bands	BW	Modulation	Frequency Range	Max RF Output Power (dBm)		EIRP	99% BW	Emission Designator
	(MHz)		(MHz)	Conducted (Average)	ERP/EIRP (Average)	(W)	(MHz)	
4	1.4	QPSK	1710.7-1754.3	24.35	24.75	0.29854	1.1065	1M11G7D
		16QAM		23.69	24.09	0.25645	1.1033	1M10W7D
		64QAM		23.50	23.90	0.24547	1.0995	1M10W7D
	3	QPSK	1711.5-1753.5	24.30	24.70	0.29512	2.6905	2M69G7D
		16QAM		23.61	24.01	0.25177	2.6914	2M69W7D
		64QAM		23.48	23.88	0.24434	2.6848	2M68W7D
	5	QPSK	1712.5-1752.5	24.35	24.75	0.29854	4.5523	4M55G7D
		16QAM		23.51	23.91	0.24604	4.5484	4M55W7D
		64QAM		23.44	23.84	0.24210	4.5510	4M55W7D
	10	QPSK	1715-1750	24.31	24.71	0.29580	9.0461	9M05G7D
		16QAM		23.52	23.92	0.24660	9.0245	9M02W7D
		64QAM		23.50	23.90	0.24547	9.0166	9M02W7D
	15	QPSK	1717.5-1747.5	24.30	24.70	0.29512	13.576	13M6G7D
		16QAM		23.68	24.08	0.25586	13.529	13M5W7D
		64QAM		23.53	23.90	0.24547	13.530	13M5W7D
	20	QPSK	1720-1745	24.41	24.81	0.30269	18.039	18M0G7D
		16QAM		23.70	24.10	0.25704	18.055	18M1W7D
		64QAM		23.62	24.02	0.25235	18.052	18M1W7D
5	1.4	QPSK	824.7-848.3	24.68	24.54	0.28445	1.1065	1M11G7D
		16QAM		23.86	24.14	0.25942	1.1000	1M10W7D
		64QAM		23.88	24.68	0.29376	1.0993	1M10W7D
	3	QPSK	825.5-847.5	24.43	24.43	0.27733	2.6958	2M70G7D
		16QAM		23.95	24.38	0.27416	2.6881	2M69W7D
		64QAM		23.84	24.42	0.27669	2.6858	2M69W7D
	5	QPSK	826.5-846.5	24.52	24.50	0.28184	4.5428	4M54G7D
		16QAM		23.90	24.44	0.27797	4.5500	4M55W7D
		64QAM		23.86	24.52	0.28314	4.5410	4M54W7D
	10	QPSK	829-844	24.62	24.58	0.28708	9.0398	9M04G7D
		16QAM		23.98	24.53	0.28379	9.0312	9M03W7D
		64QAM		23.93	24.62	0.28973	9.0407	9M04W7D

Summary of Results:								
Bands	BW	Modulation	Frequency Range	Max RF Output Power (dBm)		EIRP	99% BW	Emission Designator
	(MHz)		(MHz)	Conducted (Average)	ERP/EIRP (Average)	(W)	(MHz)	
12	1.4	QPSK	699.7-715.3	24.05	24.01	0.25177	1.1015	1M10G7D
		16QAM		23.58	24.05	0.25410	1.0975	1M09W7D
		64QAM		23.40	23.95	0.24831	1.0994	1M09W7D
	3	QPSK	700.5-714.5	24.04	23.93	0.24717	2.6962	2M70G7D
		16QAM		23.57	24.04	0.25351	2.6897	2M69W7D
		64QAM		23.33	23.90	0.24547	2.6858	2M69W7D
	5	QPSK	701.5-713.5	24.11	23.92	0.24660	4.5482	4M55G7D
		16QAM		23.46	24.11	0.25763	4.5522	4M55W7D
		64QAM		23.28	24.04	0.25351	4.5415	4M54W7D
	10	QPSK	704-711	24.14	24.11	0.25763	9.0426	9M04G7D
		16QAM		23.62	24.14	0.25942	9.0402	9M04W7D
		64QAM		23.42	24.08	0.25586	9.0100	9M01W7D
17	5	QPSK	706.5-713.5	24.08	24.08	0.25586	4.5434	4M54G7D
		16QAM		23.55	23.95	0.24831	4.5600	4M56W7D
		64QAM		23.49	24.05	0.25410	4.5274	4M53W7D
	10	QPSK	709-711	24.13	24.11	0.25763	9.0346	9M03G7D
		16QAM		23.62	24.11	0.25763	9.0217	9M02W7D
		64QAM		23.53	24.13	0.25882	9.0148	9M01W7D

1.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
-	-	-	-	-

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.30 Meter	UnionTrust

1.5 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.6 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.7 DEVIATION FROM STANDARDS

None.

1.8 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.10 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.2 dB
2	Conducted emission 150KHz-30MHz	±2.7 dB
3	Radiated spurious emissions 30MHz-1GHz	± 4.9 dB
4	Radiated spurious emissions 1GHz-18GHz	± 4.8 dB
5	Radiated spurious emissions 18GHz-40GHz	± 5.1 dB
6	Occupied Bandwidth	± 1.86 %
7	DC Supply Voltages	± 0.68 %
8	Temperature	± 0.62 °C
9	Humidity	± 3.9 %
10	Conducted spurious emissions	± 2.7 dB
11	DC Supply Voltages	± 0.68 %
12	AC Supply Voltages	± 1.2 %
13	Radio Frequency	± 6.5 x 10 ⁻⁸
14	RF Power, Conducted	± 0.9 dB

2. TEST SUMMARY

FCC 47 CFR Part 24 Test Cases (Band 2)			
Test Item	Test Requirement	Test Method	Result
Equivalent Isotropic Radiated Power (EIRP)	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 24.232(c)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Conducted Output Power	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 24.232(c)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Peak-to-average ratio	FCC 47 CFR Part 24.232(d)	KDB 971168 D01v03r01	PASS
99%&26dB Bandwidth	FCC 47 CFR Part 2.1049(h) & FCC 47 CFR Part 24.238(b)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Band Edge at antenna terminals	FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 24.238(a)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Spurious emissions at antenna terminals	FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 24.238(a)(b)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Field strength of spurious radiation	FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 24.238(a)(b)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Frequency stability	FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 24.235	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS

FCC 47 CFR Part 27 Test Cases (LTE Band 4)			
Test Item	Test Requirement	Test Method	Result
Equivalent Isotropic Radiated Power (EIRP)	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 27.50(d)(4)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Conducted Output Power	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 27.50(d)(4)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Peak-to-average ratio	FCC 47 CFR Part 27.50(d)(5)	KDB 971168 D01v03r01	PASS
99%&26dB Bandwidth	FCC 47 CFR Part 2.1049(h) & FCC 47 CFR Part 27.53(h)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Band Edge at antenna terminals	FCC 47 CFR Part 27.53(h)(1)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Spurious emissions at antenna terminals	FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 27.53(h)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Field strength of spurious radiation	FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 27.53(h)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Frequency stability	FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 27.54	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS

FCC 47 CFR Part 22 Test Cases (Band 5)			
Test Item	Test Requirement	Test Method	Result
Effective Radiated Power (ERP)	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 22.913(a)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Conducted Output Power	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 22.913(a)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Peak-to-average ratio	FCC 47 CFR Part 22.913(a)	KDB 971168 D01v03r01	PASS
99%&26dB Bandwidth	FCC 47 CFR Part 2.1049(h)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Band Edge at antenna terminals	FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 22.917(a)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Spurious emissions at antenna terminals	FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 22.917(a)(b)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Field strength of spurious radiation	FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 22.917(a)(b)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Frequency stability	FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 22.355	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS

FCC 47 CFR Part 27 Test Cases (LTE Band 12&17)			
Test Item	Test Requirement	Test Method	Result
Effective Radiated Power (ERP)	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 27.50(c)(10)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Conducted Output Power	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 27.50(c)(10)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Peak-to-average ratio	FCC 47 CFR Part 27.50(d)(5)	KDB 971168 D01v03r01	PASS
99%&26dB Bandwidth	FCC 47 CFR Part 2.1049(h) FCC 47 CFR Part 27.53(g)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Band Edge at antenna terminals	FCC 47 CFR Part 27.53(g)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Spurious emissions at antenna terminals	FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 27.53(g)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Field strength of spurious radiation	FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 27.53(g)	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS
Frequency stability	FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 27.54	ANSI C63.26-2015 & KDB 971168 D01v03r01	PASS

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 03, 2018	Dec. 03, 2021
☒	Receiver	R&S	ESIB26	100114	Nov. 24, 2019	Nov. 23, 2020
☐	Loop Antenna	ETS-LINDGREN	6502	00202525	Nov. 24, 2019	Nov. 23, 2020
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Nov. 16, 2019	Nov. 15, 2020
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	Nov. 16, 2019	Nov. 15, 2020
☒	Preamplifier	HP	8447F	2805A02960	Nov. 16, 2019	Nov. 15, 2020
☐	Broadband Antenna (Pre-amplifier)	ETS-LINDGREN	3142E-PA	00201891	Nov. 24, 2019	Nov. 23, 2020
☐	6dB Attenuator	Talent	RA6A5-N-18	18103002	Nov. 24, 2019	Nov. 23, 2020
☒	Horn Antenna	ETS-LINDGREN	3117	00164202	Nov. 24, 2019	Nov. 23, 2020
☒	Pre-amplifier	ETS-LINDGREN	118385	00201874	Nov. 16, 2019	Nov. 15, 2020
☐	Horn Antenna	ETS-LINDGREN	3116C	00200180	Jun. 19, 2020	Jun. 18, 2021
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Nov. 16, 2019	Nov. 15, 2020
☒	Wideband Radio Communication Tester	R&S	CMW500	119583	Jul. 31, 2019	Jul. 31, 2020
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

RF Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Nov. 24, 2019	Nov. 23, 2020
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Nov. 24, 2019	Nov. 23, 2020
☒	Wideband Radio Communication Tester	R&S	CMW500	119583	Jul. 31, 2019	Jul. 31, 2020
☒	DC Source	KIKUSUI	PWR400L	LK003024	Sep. 09, 2019	Sep. 08, 2020
☐	Temp & Humidity chamber	Espec	GL(U)04K A(W)	16921H201P3	Sep. 09, 2019	Sep. 08, 2020
☒	Temp & Humidity chamber	Votisch	VT4002	58566133290020	May 11, 2020	May 10, 2021

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING


Test Environment	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
TN/VN	+15 to +35	7.4	20 to 75
TL/VL	-30	7.2	20 to 75
TH/VL	+55	7.2	20 to 75
TL/VH	-30	8.4	20 to 75
TH/VH	+55	8.4	20 to 75

Remark:


- 1) The EUT just work in such extreme temperature of -30 °C to +55 °C and the extreme voltage of 7.2 V to 8.4 V, so here the EUT is tested in the temperature of -30 °C to +55 °C and the voltage of 7.2 V to 8.4 V.
- 2) VN: Normal Voltage; TN: Normal Temperature;
TL: Low Extreme Test Temperature; TH: High Extreme Test Temperature;
VL: Low Extreme Test Voltage; VH: High Extreme Test Voltage.

4.2 TEST SETUP

4.2.1 For Radiated Emissions test setup



4.2.2 For Conducted RF test setup



4.3 TEST CHANNELS

Band	Test Frequency ID	Bandwidth (MHz)	Number [UL]	Frequency of Uplink (MHz)
LTE Band 2 TX: 1850-1910MHz	Low Range	1.4	18607	1850.7
		3	18615	1851.5
		5	18625	1852.5
		10	18650	1855
		15	18675	1857.5
		20	18700	1860
	Middle Range	1.4/3/5/10/15/20	18900	1880
	High Range	1.4	19193	1909.3
		3	19185	1908.5
		5	19175	1907.5
		10	19150	1905
		15	19125	1902.5
		20	19100	1900
LTE Band 4 TX: 1710-1755MHz	Low Range	1.4	19957	1710.7
		3	19965	1711.5
		5	19975	1712.5
		10	20000	1715
		15	20025	1717.5
		20	20050	1720
	Middle Range	1.4/3/5/10/ 15/20	20175	1732.5
	High Range	1.4	20393	1754.3
		3	20385	1753.5
		5	20375	1752.5
		10	20350	1750
		15	20325	1747.5
		20	20300	1745
LTE band 5 TX: 824-849MHz	Low Range	1.4	20407	824.7
		3	20415	825.5
		5	20425	826.5
		10	20450	829
	Middle Range	1.4/3/5/10	20525	836.5
	High Range	1.4	20643	848.3
		3	20635	847.5
		5	20625	846.5
		10	20600	844
LTE Band 12 TX: 699-716MHz	Low Range	1.4	23017	699.7
		3	23025	700.5
		5	23035	701.5
		10	23060	704
	Middle Range	1.4/3/5/10	23095	707.5
	High Range	1.4	23173	715.3
		3	23165	714.5
		5	23155	713.5

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC4G-V1.0

		10	23130	711
LTE Band 17 TX: 704-716MHz	Low Range	5	23755	706.5
		10	23780	709
	Middle Range	5/10	23790	710
	High Range	5	23825	713.5
		10	23800	711



4.4 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 7.4V battery. Only the worst case data were recorded in this test report.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, X/Y/Z axis, and antenna ports.

The worst case was found when positioned as the table below.

Band	Mode	Antenna Port	Worst-case axis positioning
LTE Band 2	1TX	Chain 0	Y axis
LTE Band 4	1TX	Chain 0	Y axis
LTE Band 5	1TX	Chain 0	Y axis
LTE Band 12	1TX	Chain 0	Y axis
LTE Band 17	1TX	Chain 0	Y axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.5 PRE-SCAN

Pre-scan under all rate at lowest middle and highest channel, find the transmitter power as below.

4.5.1 LTE Band 2

LTE Band 2 Maximum Average Power (dBm)										
Modulation	RB		Test Channel			RB		Test Channel		
	Size	Offset	Low	Mid	High	Size	Offset	Low	Mid	High
Channel Bandwidth: 1.4 MHz						Channel Bandwidth: 3 MHz				
QPSK	1	0	24.40	24.24	24.08	1	0	24.26	24.14	24.00
	1	2	24.49	24.52	24.45	1	7	24.43	24.45	24.40
	1	5	24.24	23.97	24.12	1	14	24.08	23.98	23.99
	3	0	24.36	24.27	24.30	8	0	23.26	23.26	23.40
	3	1	24.39	24.25	24.35	8	3	23.35	23.40	23.29
	3	3	24.23	24.23	24.14	8	7	23.11	23.33	23.28
	6	0	23.24	23.34	23.34	15	0	23.23	23.20	23.29
16QAM	1	0	23.56	23.61	23.55	1	0	23.57	23.61	23.39
	1	2	23.84	23.87	23.78	1	7	23.76	23.93	23.76
	1	5	23.58	23.61	23.36	1	14	23.49	23.63	23.47
	3	0	23.32	23.19	23.42	8	0	22.21	22.30	22.41
	3	1	23.43	23.34	23.35	8	3	22.39	22.41	22.32
	3	3	23.23	23.33	23.30	8	7	22.29	22.35	22.30
	6	0	22.25	22.41	22.24	15	0	22.38	22.24	22.34
64QAM	1	0	23.45	23.72	23.35	1	0	23.36	23.62	23.46
	1	2	23.70	23.86	23.79	1	7	23.71	23.69	23.80
	1	5	23.51	23.61	23.51	1	14	23.48	23.54	23.44
	3	0	23.32	23.35	23.34	8	0	22.33	22.34	22.32
	3	1	23.39	23.29	23.27	8	3	22.34	22.23	22.20
	3	3	23.33	23.27	23.29	8	7	22.18	22.31	22.32
	6	0	22.18	22.17	22.24	15	0	22.33	22.13	22.29
Channel Bandwidth: 5 MHz						Channel Bandwidth: 10 MHz				
QPSK	1	0	24.41	24.16	24.07	1	0	24.35	24.18	24.12
	1	12	24.54	24.35	24.45	1	24	24.59	24.38	24.41
	1	24	24.19	23.97	24.08	1	49	24.15	24.13	24.06
	12	0	23.19	23.22	23.41	25	0	23.34	23.19	23.33
	12	6	23.42	23.33	23.25	25	12	23.36	23.33	23.28
	12	13	23.28	23.27	23.17	25	25	23.17	23.24	23.22
	25	0	23.33	23.24	23.28	50	0	23.28	23.33	23.34
16QAM	1	0	23.50	23.54	23.40	1	0	23.45	23.63	23.57
	1	12	23.66	23.97	23.84	1	24	23.67	23.82	23.87
	1	24	23.51	23.47	23.50	1	49	23.49	23.46	23.47
	12	0	22.31	22.34	22.32	25	0	22.19	22.35	22.48
	12	6	22.31	22.39	22.44	25	12	22.40	22.43	22.28
	12	13	22.32	22.24	22.30	25	25	22.25	22.37	22.19
	25	0	22.35	22.29	22.36	50	0	22.21	22.31	22.36
64QAM	1	0	23.44	23.74	23.34	1	0	23.37	23.70	23.33
	1	12	23.66	23.80	23.76	1	24	23.73	23.82	23.81
	1	24	23.57	23.51	23.46	1	49	23.49	23.57	23.35
	12	0	22.20	22.35	22.42	25	0	22.28	22.37	22.44
	12	6	22.40	22.24	22.34	25	12	22.35	22.34	22.22
	12	13	22.28	22.40	22.21	25	25	22.14	22.34	22.25
	25	0	22.31	22.14	22.29	50	0	22.20	22.18	22.32

LTE Band 2 Maximum Average Power (dBm)										
Modulation	RB		Test Channel			RB		Test Channel		
	Size	Offset	Low	Mid	High	Size	Offset	Low	Mid	High
Channel Bandwidth: 15 MHz						Channel Bandwidth: 20 MHz				
QPSK	1	0	24.34	24.23	24.07	1	0	24.42	24.29	24.19
	1	37	24.41	24.49	24.40	1	50	24.61	24.53	24.51
	1	74	24.26	24.13	24.05	1	99	24.27	24.15	24.18
	37	0	23.31	23.34	23.30	50	0	23.39	23.38	23.46
	37	19	23.34	23.35	23.35	50	25	23.45	23.42	23.40
	37	39	23.16	23.32	23.19	50	50	23.31	23.39	23.31
	75	0	23.20	23.32	23.23	100	0	23.39	23.36	23.35
16QAM	1	0	23.43	23.62	23.52	1	0	23.58	23.73	23.57
	1	37	23.83	23.89	23.87	1	50	23.85	24.00	23.91
	1	74	23.63	23.51	23.42	1	99	23.68	23.64	23.54
	37	0	22.27	22.32	22.46	50	0	22.37	22.39	22.52
	37	19	22.27	22.41	22.32	50	25	22.46	22.47	22.45
	37	39	22.31	22.41	22.28	50	50	22.34	22.44	22.34
	75	0	22.20	22.23	22.34	100	0	22.40	22.42	22.41
64QAM	1	0	23.46	23.75	23.48	1	0	23.54	23.75	23.53
	1	37	23.76	23.86	23.83	1	50	23.85	23.89	23.87
	1	74	23.50	23.58	23.50	1	99	23.65	23.64	23.54
	37	0	22.20	22.38	22.49	50	0	22.34	22.39	22.51
	37	19	22.39	22.25	22.25	50	25	22.43	22.34	22.35
	37	39	22.24	22.39	22.29	50	50	22.34	22.43	22.34
	75	0	22.29	22.16	22.38	100	0	22.33	22.25	22.42

4.5.2 LTE Band 4

LTE Band 4 Maximum Average Power (dBm)										
Modulation	RB		Test Channel			RB		Test Channel		
	Size	Offset	Low	Mid	High	Size	Offset	Low	Mid	High
Channel Bandwidth: 1.4 MHz						Channel Bandwidth: 3 MHz				
QPSK	1	0	24.06	23.92	23.96	1	0	23.92	23.82	23.88
	1	2	24.10	24.31	24.35	1	7	24.04	24.24	24.30
	1	5	24.01	23.97	23.99	1	14	23.85	23.98	23.86
	3	0	24.05	23.97	23.83	8	0	22.95	22.96	22.93
	3	1	24.04	23.93	24.05	8	3	23.00	23.08	22.99
	3	3	23.95	23.95	23.91	8	7	22.83	23.05	23.05
	6	0	22.91	23.07	23.04	15	0	22.90	22.93	22.99
16QAM	1	0	23.26	23.23	23.14	1	0	23.27	23.23	22.98
	1	2	23.69	23.40	23.28	1	7	23.61	23.46	23.26
	1	5	23.37	23.22	23.15	1	14	23.28	23.24	23.26
	3	0	23.08	22.95	22.87	8	0	21.97	22.06	21.86
	3	1	23.14	23.00	22.96	8	3	22.10	22.07	21.93
	3	3	23.03	23.00	23.08	8	7	22.09	22.02	22.08
	6	0	22.00	22.12	21.89	15	0	22.13	21.95	21.99
64QAM	1	0	23.15	23.29	22.89	1	0	23.06	23.19	23.00
	1	2	23.47	23.50	23.27	1	7	23.48	23.33	23.28
	1	5	23.29	23.20	23.30	1	14	23.26	23.13	23.23
	3	0	23.09	22.11	21.75	8	0	22.10	22.10	21.73
	3	1	23.13	22.07	21.95	8	3	22.08	22.01	21.88
	3	3	23.07	21.95	22.07	8	7	21.92	21.99	22.10
	6	0	22.00	22.05	21.84	15	0	22.15	22.01	21.89

LTE Band 4 Maximum Average Power (dBm)										
Modulation	RB		Test Channel			RB		Test Channel		
	Size	Offset	Low	Mid	High	Size	Offset	Low	Mid	High
Channel Bandwidth: 5 MHz						Channel Bandwidth: 10 MHz				
QPSK	1	0	24.07	23.84	23.95	1	0	24.01	23.86	24.00
	1	12	24.15	24.14	24.35	1	24	24.20	24.17	24.31
	1	24	23.96	23.97	23.95	1	49	23.92	24.13	23.93
	12	0	22.88	22.92	22.94	25	0	23.03	22.89	22.86
	12	6	23.07	23.01	22.95	25	12	23.01	23.01	22.98
	12	13	23.00	22.99	22.94	25	25	22.89	22.96	22.99
	25	0	23.00	22.97	22.98	50	0	22.95	23.06	23.04
16QAM	1	0	23.20	23.16	22.99	1	0	23.15	23.25	23.16
	1	12	23.51	23.50	23.34	1	24	23.52	23.35	23.37
	1	24	23.30	23.08	23.29	1	49	23.28	23.07	23.26
	12	0	22.07	22.10	21.77	25	0	21.95	22.11	21.93
	12	6	22.02	22.05	22.05	25	12	22.11	22.09	21.89
	12	13	22.12	21.91	22.08	25	25	22.05	22.04	21.97
	25	0	22.10	22.00	22.01	50	0	21.96	22.02	22.01
64QAM	1	0	23.14	23.31	22.88	1	0	23.07	23.27	22.87
	1	12	23.43	23.44	23.24	1	24	23.50	23.46	23.29
	1	24	23.35	23.10	23.25	1	49	23.27	23.16	23.14
	12	0	21.97	22.11	21.83	25	0	22.05	22.13	21.85
	12	6	22.14	22.02	22.02	25	12	22.09	22.12	21.90
	12	13	22.02	22.08	21.99	25	25	21.88	22.02	22.03
	25	0	22.13	22.02	21.89	50	0	22.02	22.06	21.92
Channel Bandwidth: 15 MHz						Channel Bandwidth: 20 MHz				
QPSK	1	0	24.00	23.91	23.95	1	0	24.08	23.97	24.07
	1	37	24.02	24.28	24.30	1	50	24.22	24.32	24.41
	1	74	24.03	24.13	23.92	1	99	24.04	24.15	24.05
	37	0	23.00	23.04	22.83	50	0	23.08	23.08	22.99
	37	19	22.99	23.03	23.05	50	25	23.10	23.10	23.10
	37	39	22.88	23.04	22.96	50	50	23.03	23.11	23.08
	75	0	22.87	23.05	22.93	100	0	23.06	23.09	23.05
16QAM	1	0	23.13	23.24	23.11	1	0	23.28	23.35	23.16
	1	37	23.68	23.42	23.37	1	50	23.70	23.53	23.41
	1	74	23.42	23.12	23.21	1	99	23.47	23.25	23.33
	37	0	22.03	22.08	21.91	50	0	22.13	22.15	21.97
	37	19	21.98	22.07	21.93	50	25	22.17	22.13	22.06
	37	39	22.11	22.08	22.06	50	50	22.14	22.11	22.12
	75	0	21.95	21.94	21.99	100	0	22.15	22.13	22.06
64QAM	1	0	23.16	23.32	23.02	1	0	23.24	23.32	23.07
	1	37	23.53	23.50	23.31	1	50	23.62	23.53	23.35
	1	74	23.28	23.17	23.29	1	99	23.43	23.23	23.33
	37	0	21.97	22.14	21.90	50	0	22.11	22.15	21.92
	37	19	22.13	22.03	21.93	50	25	22.17	22.12	22.03
	37	39	21.98	22.07	22.07	50	50	22.08	22.11	22.12
	75	0	22.11	22.04	21.98	100	0	22.15	22.13	22.02

4.5.3 LTE Band 5

LTE Band 5 Maximum Average Power (dBm)										
Modulation	RB		Test Channel			RB		Test Channel		
	Size	Offset	Low	Mid	High	Size	Offset	Low	Mid	High
Channel Bandwidth: 1.4 MHz						Channel Bandwidth: 3 MHz				
QPSK	1	0	24.25	24.36	24.26	1	0	24.32	24.38	24.35
	1	2	24.56	24.36	24.52	1	7	24.43	24.38	24.42
	1	5	24.32	24.38	24.38	1	14	24.41	24.32	24.36
	3	0	24.27	24.41	24.51	8	0	23.35	23.27	23.49
	3	1	24.54	24.28	24.35	8	3	23.51	23.17	23.45
	3	3	24.54	24.14	24.68	8	7	23.46	23.15	23.52
	6	0	23.48	23.23	23.57	15	0	23.43	23.24	23.51
16QAM	1	0	23.54	23.77	23.29	1	0	23.38	23.65	23.25
	1	2	23.55	23.78	23.43	1	7	23.65	23.95	23.61
	1	5	23.50	23.86	23.26	1	14	23.53	23.87	23.29
	3	0	23.47	23.38	23.54	8	0	22.35	22.35	22.63
	3	1	23.50	23.26	23.49	8	3	22.43	22.25	22.44
	3	3	23.53	23.28	23.59	8	7	22.50	22.33	22.61
	6	0	22.42	22.27	22.53	15	0	22.49	22.30	22.65
64QAM	1	0	23.45	23.72	23.20	1	0	23.47	23.69	23.24
	1	2	23.58	23.88	23.10	1	7	23.60	23.84	23.16
	1	5	23.39	23.66	23.37	1	14	23.47	23.75	23.36
	3	0	23.35	23.42	23.06	8	0	22.35	22.23	22.21
	3	1	23.46	23.08	23.64	8	3	22.53	22.06	22.55
	3	3	23.44	23.22	23.68	8	7	22.38	22.16	22.68
	6	0	22.43	22.20	22.19	15	0	22.41	22.17	22.37
Channel Bandwidth: 5 MHz						Channel Bandwidth: 10 MHz				
QPSK	1	0	24.22	24.26	24.43	1	0	24.40	24.41	24.43
	1	12	24.50	24.44	24.52	1	24	24.58	24.53	24.62
	1	24	24.39	24.37	24.44	1	49	24.43	24.42	24.49
	12	0	23.41	23.36	23.42	25	0	23.44	23.41	23.59
	12	6	23.44	23.31	23.39	25	12	23.60	23.35	23.55
	12	13	23.52	23.23	23.54	25	25	23.58	23.31	23.68
	25	0	23.33	23.25	23.62	50	0	23.53	23.37	23.64
16QAM	1	0	23.48	23.71	23.22	1	0	23.55	23.85	23.41
	1	12	23.66	23.81	23.60	1	24	23.71	23.98	23.62
	1	24	23.51	23.90	23.37	1	49	23.54	23.96	23.44
	12	0	22.43	22.36	22.60	25	0	22.53	22.44	22.69
	12	6	22.53	22.19	22.55	25	12	22.58	22.38	22.64
	12	13	22.56	22.23	22.66	25	25	22.60	22.34	22.74
	25	0	22.32	22.31	22.66	50	0	22.51	22.38	22.69
64QAM	1	0	23.40	23.80	23.19	1	0	23.54	23.81	23.32
	1	12	23.51	23.86	23.18	1	24	23.65	23.93	23.24
	1	24	23.48	23.68	23.24	1	49	23.53	23.84	23.44
	12	0	22.43	22.33	22.20	25	0	22.46	22.43	22.22
	12	6	22.48	22.06	22.45	25	12	22.54	22.18	22.64
	12	13	22.46	22.29	22.57	25	25	22.52	22.34	22.73
	25	0	22.46	22.25	22.22	50	0	22.48	22.32	22.39

4.5.4 LTE Band 12

LTE Band 12 Maximum Average Power (dBm)										
Modulation	RB		Test Channel			RB		Test Channel		
	Size	Offset	Low	Mid	High	Size	Offset	Low	Mid	High
Channel Bandwidth: 1.4 MHz						Channel Bandwidth: 3 MHz				
QPSK	1	0	23.87	23.81	23.69	1	0	23.79	23.86	23.83
	1	2	24.01	24.05	23.95	1	7	23.93	24.04	23.90
	1	5	23.73	23.92	23.93	1	14	23.89	23.86	23.79
	3	0	23.89	23.89	23.91	8	0	23.01	22.91	22.82
	3	1	23.99	24.03	23.82	8	3	22.98	22.87	22.90
	3	3	23.97	24.04	23.81	8	7	22.90	23.04	22.80
	6	0	22.89	22.91	22.79	15	0	22.96	22.96	22.89
16QAM	1	0	22.91	22.76	23.43	1	0	22.98	22.89	23.45
	1	2	23.14	23.00	23.58	1	7	23.14	23.04	23.57
	1	5	23.07	22.89	23.39	1	14	23.04	22.83	23.49
	3	0	22.93	22.91	22.90	8	0	21.96	21.98	21.82
	3	1	23.05	22.92	22.86	8	3	21.96	22.06	21.79
	3	3	22.86	23.10	22.82	8	7	21.86	22.12	21.96
	6	0	22.03	22.04	21.84	15	0	22.04	21.91	21.85
64QAM	1	0	22.86	22.63	23.24	1	0	22.77	22.71	23.20
	1	2	22.96	22.87	23.40	1	7	23.01	23.00	23.33
	1	5	23.00	22.77	23.21	1	14	23.02	22.91	23.12
	3	0	23.00	22.87	22.85	8	0	21.95	21.88	21.80
	3	1	22.93	22.94	22.71	8	3	21.91	21.94	21.72
	3	3	22.95	22.94	22.85	8	7	21.84	22.01	21.73
	6	0	21.82	21.87	21.68	15	0	21.98	21.98	21.54
Channel Bandwidth: 5 MHz						Channel Bandwidth: 10 MHz				
QPSK	1	0	23.80	23.68	23.67	1	0	23.88	23.87	23.87
	1	12	23.92	24.11	24.04	1	24	24.11	24.14	24.08
	1	24	23.92	23.79	23.77	1	49	23.93	23.94	23.94
	12	0	23.07	22.98	22.78	25	0	23.08	22.99	22.95
	12	6	22.97	22.96	22.82	25	12	23.05	23.04	22.91
	12	13	22.87	23.06	22.93	25	25	23.03	23.06	22.97
	25	0	22.97	22.90	22.85	50	0	23.06	23.01	22.93
16QAM	1	0	22.88	22.86	23.31	1	0	23.01	22.94	23.46
	1	12	23.15	23.07	23.46	1	24	23.27	23.09	23.62
	1	24	22.98	22.88	23.31	1	49	23.12	22.98	23.51
	12	0	22.02	22.00	21.97	25	0	22.09	22.07	21.99
	12	6	21.94	22.03	21.96	25	12	22.07	22.08	21.97
	12	13	21.93	22.05	21.81	25	25	22.04	22.13	21.98
	25	0	22.01	21.96	21.80	50	0	22.06	22.05	21.96
64QAM	1	0	22.85	22.77	23.28	1	0	22.89	22.78	23.32
	1	12	23.06	23.03	23.24	1	24	23.14	23.04	23.42
	1	24	22.96	22.75	23.23	1	49	23.11	22.92	23.31
	12	0	21.94	21.93	21.91	25	0	22.04	22.01	21.92
	12	6	21.95	21.93	21.73	25	12	22.03	22.08	21.78
	12	13	21.95	21.97	21.87	25	25	21.97	22.03	21.88
	25	0	21.91	21.95	21.60	50	0	22.02	22.05	21.69

4.5.5 LTE Band 17

LTE Band 17 Maximum Average Power (dBm)										
Modulation	RB		Test Channel			RB		Test Channel		
	Size	Offset	Low	Mid	High	Size	Offset	Low	Mid	High
Channel Bandwidth: 5 MHz						Channel Bandwidth: 10 MHz				
QPSK	1	0	23.66	23.88	23.77	1	0	23.82	23.91	23.93
	1	12	24.08	23.95	24.05	1	24	24.11	24.11	24.13
	1	24	23.73	23.77	23.88	1	49	23.89	23.93	23.99
	12	0	22.81	22.79	22.90	25	0	23.01	22.93	22.92
	12	6	22.89	22.92	22.80	25	12	22.95	22.98	22.94
	12	13	22.90	22.75	22.75	25	25	22.92	22.91	22.92
16QAM	25	0	22.76	22.88	22.92	50	0	22.93	22.95	22.95
	1	0	23.40	22.90	22.80	1	0	23.44	23.07	22.94
	1	12	23.55	23.23	23.12	1	24	23.62	23.27	23.22
	1	24	23.25	22.93	22.79	1	49	23.44	23.11	22.99
	12	0	21.90	21.86	21.98	25	0	22.02	21.96	22.00
	12	6	21.89	21.94	21.88	25	12	21.94	21.96	21.92
64QAM	12	13	21.92	21.84	21.85	25	25	21.99	21.89	21.98
	25	0	21.89	21.76	21.98	50	0	21.95	21.91	21.99
	1	0	23.26	22.88	22.87	1	0	23.43	23.05	22.92
	1	12	23.49	23.00	23.07	1	24	23.53	23.11	23.21
	1	24	23.32	23.10	22.89	1	49	23.43	23.11	22.93
	12	0	21.87	21.26	21.82	25	0	22.01	21.38	21.87
	12	6	21.71	21.56	21.84	25	12	21.78	21.56	21.87
	12	13	21.48	21.58	21.90	25	25	21.67	21.76	21.94
	25	0	21.88	21.40	21.78	50	0	21.93	21.51	21.92

Pre-scan all bandwidth and RB, find worse case mode are chosen to the report, the LTE worse case mode applicability and tested channel detail as below:

Item	Band	Bandwidth(MHz)						Modulation			RB			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
ERP/EIRP	2	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☐	☐	☑	☑	☑
	4	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☐	☐	☑	☑	☑
	5	☑	☑	☑	☑	--	--	☑	☑	☑	☑	☐	☐	☑	☑	☑
	12	☑	☑	☑	☑	-	-	☑	☑	☑	☑	☐	☐	☑	☑	☑
	17	-	-	☑	☑	-	-	☑	☑	☑	☑	☐	☐	☑	☑	☑
Conducted output power	2	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑
	4	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑
	7	-	-	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑	☑
	12	☑	☑	☑	☑	-	-	☑	☑	☑	☑	☑	☑	☑	☑	☑
	17	-	-	☑	☑	-	-	☑	☑	☑	☑	☑	☑	☑	☑	☑
Item	Band	Bandwidth(MHz)						Modulation			RB			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
99%&26dB Bandwidth	2	☑	☑	☑	☑	☑	☑	☑	☑	☑	☐	☐	☑	☑	☑	☑
	4	☑	☑	☑	☑	☑	☑	☑	☑	☑	☐	☐	☑	☑	☑	☑
	5	☑	☑	☑	☑	--	--	☑	☑	☑	☐	☐	☑	☑	☑	☑
	12	☑	☑	☑	☑	-	-	☑	☑	☑	☐	☐	☑	☑	☑	☑
	17	-	-	☑	☑	-	-	☑	☑	☑	☐	☐	☑	☑	☑	☑
peak-to-average ratio	2	☐	☐	☐	☐	☐	☑	☑	☑	☑	☑	☐	☑	☑	☐	☑
	4	☐	☐	☐	☐	☐	☑	☑	☑	☑	☑	☐	☑	☑	☐	☑
	5	☐	☐	☐	☑	--	--	☑	☑	☑	☑	☐	☑	☑	☐	☑
	12	☐	☐	☐	☑	-	-	☑	☑	☑	☑	☐	☑	☑	☐	☑
	17	☐	☐	☐	☑	☐	☐	☑	☑	☑	☑	☐	☑	☑	☐	☑

Item	Band	Bandwidth(MHz)						Modulation			RB			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Band Edge at antenna terminals	2	☒	☒	☒	☒	☒	☒	☒	☒	☒	☒	☐	☒	☒	☐	☒
	4	☒	☒	☒	☒	☒	☒	☒	☒	☒	☒	☐	☒	☒	☐	☒
	5	☒	☒	☒	☒	--	--	☒	☒	☒	☒	☐	☒	☒	☐	☒
	12	☒	☒	☒	☒	-	-	☒	☒	☒	☒	☐	☒	☒	☐	☒
	17	-	-	☒	☒	-	-	☒	☒	☒	☒	☐	☒	☒	☐	☒
Spurious emissions at antenna terminals	2	☒	☒	☒	☒	☒	☒	☒	☒	☒	☒	☐	☐	☒	☒	☒
	4	☒	☒	☒	☒	☒	☒	☒	☒	☒	☒	☐	☐	☒	☒	☒
	5	☒	☒	☒	☒	--	--	☒	☒	☒	☒	☐	☐	☒	☒	☒
	12	☒	☒	☒	☒	-	-	☒	☒	☒	☒	☐	☐	☒	☒	☒
	17	-	-	☒	☒	-	-	☒	☒	☒	☒	☐	☐	☒	☒	☒
Item	Band	Bandwidth(MHz)						Modulation			RB			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Field strength of spurious radiation	2	☐	☐	☐	☐	☐	☒	☒	☐	☐	☒	☐	☐	☒	☒	☒
	4	☐	☐	☐	☐	☐	☒	☒	☐	☐	☒	☐	☐	☒	☒	☒
	5	☐	☐	☐	☒	--	--	☒	☐	☐	☒	☐	☐	☒	☒	☒
	12	☐	☐	☐	☒	-	-	☒	☐	☐	☒	☐	☐	☒	☒	☒
	17	☐	☐	☐	☒	☐	☐	☒	☐	☐	☒	☐	☐	☒	☒	☒
Frequency stability	2	☐	☐	☐	☐	☐	☒	☒	☐	☐	☐	☐	☒	☐	☒	☐
	4	☐	☐	☐	☐	☐	☒	☒	☐	☐	☐	☐	☒	☐	☒	☐
	5	☐	☐	☐	☒	--	--	☒	☐	☐	☐	☐	☒	☐	☒	☐
	12	☐	☐	☐	☒	-	-	☒	☐	☐	☐	☐	☒	☐	☒	☐
	17	☐	☐	☐	☒	☐	☐	☒	☐	☐	☐	☐	☒	☐	☒	☐
Remark: The mark " ☒ " means is chosen for testing; The mark " ☐ " means is not chosen for testing; The mark "-" means is not supported bandwidth																

5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 22	Public Mobile Services
3	FCC 47 CFR Part 27	Miscellaneous Wireless Communications Services
4	FCC 47 CFR Part 24	Personal Communications Services
5	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
6	KDB 971168 D01	KDB 971168 D01 Power Meas License Digital Systems v03r01

5.2 ERP OR EIRP

Test Requirement: FCC 47 CFR Part 2.1046(a)
LTE Band 2: FCC 47 CFR Part 24.232(c)
LTE Band 4: FCC 47 CFR Part 27.50(d)(4)
LTE Band 5: FCC 47 CFR Part 22.913(a)
LTE Band 12 & Band 17: FCC 47 CFR Part 27.50(c)(10)

Test Method: KDB 971168 D01v03r01 Section 5.6 & ANSI C63.26-2015

Limit:

FCC 47 CFR Part 22.913(a):

The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

FCC 47 CFR Part 24.232(c):

Mobile and portable stations are limited to 2 watts EIRP.

FCC 47 CFR Part 27.50(d)(4):

Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

FCC 47 CFR Part 27.50(c)(10):

Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

1. Power is given in terms of effective radiated power (ERP).
2. Applicants in the Los Angeles, CA, area who demonstrate a need to serve both the downtown and fringe areas will be permitted to utilize an ERP of 1 kw at the following mountaintop sites: Santiago Park, Sierra Peak, Mount Lukens, and Mount Wilson.
3. Stations with antennas below 305 m (1,000 ft) (AAT) will be restricted to a maximum power of 1 kw (ERP).
4. Licensees in San Diego, CA, will be permitted to utilize an ERP of 500 watts at the following mountaintop sites: Palomar, Otay, Woodson and Miguel.

Test Procedure:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_{\text{T}} - L_{\text{C}}$$

where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas}, typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

- 1) L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

Test Setup: Refer to section 4.2.1 for details.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC4G-V1.0

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Pass

Test Data: See table below

5.2.1 LTE Band 2

LTE Band 2 Maximum EIRP (dBm)					
Channel	QPSK; RB:1	16QAM; RB:1	64QAM; RB:1	Limit (dBm)	Result
Channel Bandwidth: 1.4MHz					
Lowest	25.69	25.04	24.90	33.01	Pass
Middle	25.72	25.07	25.06	33.01	Pass
Highest	25.65	24.98	24.99	33.01	Pass
Channel Bandwidth: 3MHz					
Lowest	25.63	24.96	24.91	33.01	Pass
Middle	25.65	25.13	24.89	33.01	Pass
Highest	25.60	24.96	25.00	33.01	Pass
Channel Bandwidth: 5MHz					
Lowest	25.74	24.86	24.86	33.01	Pass
Middle	25.55	25.17	25.00	33.01	Pass
Highest	25.65	25.04	24.96	33.01	Pass
Channel Bandwidth: 10MHz					
Lowest	25.79	24.87	24.93	33.01	Pass
Middle	25.58	25.02	25.02	33.01	Pass
Highest	25.61	25.07	25.01	33.01	Pass
Channel Bandwidth: 15MHz					
Lowest	25.61	25.03	24.96	33.01	Pass
Middle	25.69	25.09	25.06	33.01	Pass
Highest	25.60	25.07	25.03	33.01	Pass
Channel Bandwidth: 20MHz					
Lowest	25.81	25.05	25.05	33.01	Pass
Middle	25.73	25.20	25.09	33.01	Pass
Highest	25.71	25.11	25.07	33.01	Pass

5.2.2 LTE Band 4

LTE Band 4 Maximum EIRP (dBm)					
Channel	QPSK; RB:1	16QAM; RB:1	64QAM; RB:1	Limit (dBm)	Result
Channel Bandwidth: 1.4MHz					
Lowest	24.50	24.09	23.87	30.00	Pass
Middle	24.71	23.80	23.90	30.00	Pass
Highest	24.75	23.68	23.67	30.00	Pass
Channel Bandwidth: 3MHz					
Lowest	24.44	24.01	23.88	30.00	Pass
Middle	24.64	23.86	23.73	30.00	Pass
Highest	24.70	23.66	23.68	30.00	Pass
Channel Bandwidth: 5MHz					
Lowest	24.55	23.91	23.83	30.00	Pass
Middle	24.54	23.90	23.84	30.00	Pass
Highest	24.75	23.74	23.64	30.00	Pass
Channel Bandwidth: 10MHz					
Lowest	24.60	23.92	23.90	30.00	Pass
Middle	24.57	23.75	23.86	30.00	Pass
Highest	24.71	23.77	23.69	30.00	Pass
Channel Bandwidth: 15MHz					
Lowest	24.42	24.08	23.93	30.00	Pass
Middle	24.68	23.82	23.90	30.00	Pass
Highest	24.70	23.77	23.71	30.00	Pass
Channel Bandwidth: 20MHz					
Lowest	24.62	24.10	24.02	30.00	Pass
Middle	24.72	23.93	23.93	30.00	Pass
Highest	24.81	23.81	23.75	30.00	Pass

5.2.3 LTE Band 5

LTE Band 5 Maximum ERP (dBm)					
Channel	QPSK; RB:1	16QAM; RB:1	64QAM; RB:1	Limit (dBm)	Result
Channel Bandwidth: 1.4MHz					
Lowest	24.54	24.14	24.68	38.45	Pass
Middle	23.50	23.86	23.26	38.45	Pass
Highest	23.58	23.88	23.10	38.45	Pass
Channel Bandwidth: 3MHz					
Lowest	24.43	24.38	24.42	38.45	Pass
Middle	23.65	23.95	23.61	38.45	Pass
Highest	23.60	23.84	23.16	38.45	Pass
Channel Bandwidth: 5MHz					
Lowest	24.50	24.44	24.52	38.45	Pass
Middle	23.51	23.90	23.37	38.45	Pass
Highest	23.51	23.86	23.18	38.45	Pass
Channel Bandwidth: 10MHz					
Lowest	24.58	24.53	24.62	38.45	Pass
Middle	23.71	23.98	23.62	38.45	Pass
Highest	23.65	23.93	23.24	38.45	Pass

5.2.4 LTE Band 12

LTE Band 12 Maximum ERP (dBm)					
Channel	QPSK; RB:1	16QAM; RB:1	64QAM; RB:1	Limit (dBm)	Result
Channel Bandwidth: 1.4MHz					
Lowest	24.01	24.05	23.95	34.77	Pass
Middle	23.14	23.00	23.58	34.77	Pass
Highest	22.96	22.87	23.40	34.77	Pass
Channel Bandwidth: 3MHz					
Lowest	23.93	24.04	23.90	34.77	Pass
Middle	23.14	23.04	23.57	34.77	Pass
Highest	23.01	23.00	23.33	34.77	Pass
Channel Bandwidth: 5MHz					
Lowest	23.92	24.11	24.04	34.77	Pass
Middle	23.15	23.07	23.46	34.77	Pass
Highest	22.85	22.77	23.28	34.77	Pass
Channel Bandwidth: 10MHz					
Lowest	24.11	24.14	24.08	34.77	Pass
Middle	23.27	23.09	23.62	34.77	Pass
Highest	23.14	23.04	23.42	34.77	Pass

5.2.5 LTE Band 17

LTE Band 17 Maximum ERP (dBm)					
Channel	QPSK; RB:1	16QAM; RB:1	64QAM; RB:1	Limit (dBm)	Result
Channel Bandwidth: 5MHz					
Lowest	24.08	23.95	24.05	34.77	Pass
Middle	23.55	23.23	23.12	34.77	Pass
Highest	23.49	23.00	23.07	34.77	Pass
Channel Bandwidth: 10MHz					
Lowest	24.11	24.11	24.13	34.77	Pass
Middle	23.62	23.27	23.22	34.77	Pass
Highest	23.53	23.11	23.21	34.77	Pass

5.3 CONDUCTED OUTPUT POWER

FCC 47 CFR Part 2.1046(a)

Test Requirement: **LTE Band 2:** FCC 47 CFR Part 24.232(c)
LTE Band 4: FCC 47 CFR Part 27.50(d)(4)
LTE Band 5: FCC 47 CFR Part 22.913(a)
LTE Band 12 & Band 17 : FCC 47 CFR Part 27.50(c)(10)

Test Method: KDB 971168 D01v03r01 & ANSI C63.26-2015

Limit:

FCC 47 CFR Part 22.913(a):

The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

FCC 47 CFR Part 24.232(c):

Mobile and portable stations are limited to 2 watts EIRP.

FCC 47 CFR Part 27.50(d)(4):

Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

FCC 47 CFR Part 27.50(c)(10):

Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

1. Power is given in terms of effective radiated power (ERP).
2. Applicants in the Los Angeles, CA, area who demonstrate a need to serve both the downtown and fringe areas will be permitted to utilize an ERP of 1 kw at the following mountaintop sites: Santiago Park, Sierra Peak, Mount Lukens, and Mount Wilson.
3. Stations with antennas below 305 m (1,000 ft) (AAT) will be restricted to a maximum power of 1 kw (ERP).
4. Licensees in San Diego, CA, will be permitted to utilize an ERP of 500 watts at the following mountaintop sites: Palomar, Otay, Woodson and Miguel.

Test Procedure:

The EUT was set up for the maximum power with LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.2.2 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Pass

Test Data: [The full result refer to section 4.5 for details.](#)

5.4 PEAK-TO-AVERAGE RATIO

Test Requirement: LTE Band 2: FCC 47 CFR Part 24.232(d)
 LTE Band 4: FCC 47 CFR Part 27.50(d)(5)
 LTE Band 5: FCC 47 CFR Part 22.913(a)
 LTE Band 12 & Band 17: FCC 47 CFR Part 27.50(d)(5)

Test Method: KDB 971168 D01v03r01 Section 5.7

Limit: In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB

Test Procedure:

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer.

- Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth
- Set the number of counts to a value that stabilizes the measured CCDF curve
- Record the maximum PAPR level associated with a probability of 0.1 %

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.2.2 for details.

Instruments Used: Refer to section 3 for details


Test Mode: Link mode


Test Results: Pass

Test Data: See table below

5.4.1 LTE Band 2

LTE Band 2 Peak-to-average ratio (dB)						
Channel	RB Configuration	Channel Bandwidth: 20 MHz			Limit (dB)	Result
		QPSK	16QAM	64QAM		
Lowest	1 RB	2.98	3.89	4.12	13	Pass
	Full RB	5.01	5.79	5.76	13	Pass
Middle	1 RB	4.76	5.57	5.29	13	Pass
	Full RB	5.35	6.14	6.07	13	Pass
Highest	1 RB	4.12	5.12	4.95	13	Pass
	Full RB	5.24	6.03	6.03	13	Pass








5.4.2 LTE Band 4

LTE Band 4 Peak-to-average ratio (dB)						
Channel	RB Configuration	Channel Bandwidth: 20 MHz			Limit (dB)	Result
		QPSK	16QAM	64QAM		
Lowest	1 RB	3.25	4.04	3.95	13	Pass
	Full RB	5.02	5.84	5.81	13	Pass
Middle	1 RB	4.14	5.03	5.05	13	Pass
	Full RB	4.75	5.52	5.48	13	Pass
Highest	1 RB	2.97	4.09	4.06	13	Pass
	Full RB	4.73	5.49	5.44	13	Pass







5.4.3 LTE Band 5

LTE Band 5 Peak-to-average ratio (dB)						
Channel	RB Configuration	Channel Bandwidth: 10 MHz			Limit (dB)	Result
		QPSK	16QAM	64QAM		
Lowest	1 RB	4.60	5.29	5.64	13	Pass
	Full RB	5.41	6.22	6.22	13	Pass
Middle	1 RB	4.70	5.52	5.28	13	Pass
	Full RB	5.16	5.94	5.96	13	Pass
Highest	1 RB	4.69	5.71	5.55	13	Pass
	Full RB	5.56	6.34	6.31	13	Pass

