



FCC TEST REPORT

FCC ID: 2AU8F-SW1073

Product : Remote Control
Model Name : SW1073
Brand : N/A
Report No. : PTC25070700101E-FC01

Prepared for

DONGGUAN SMALL WORLD NOVELTY CO., LTD.

7th Floor, C building, Zhongdingtongxun Industry park, Jinxiaotang, Fenggang, Dongguan,
Guangdong, China

Prepared by

Precise Testing & Certification Co., Ltd

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China



Report No.: PTC25070700101E-FC01

1.TEST RESULT CERTIFICATION

Applicant's name : DONGGUAN SMALL WORLD NOVELTY CO., LTD.

Address : 7th Floor, C building, Zhongdingtongxun Industry park, Jinxiaotang, Fenggang, Dongguan,Guangdong, China

Manufacture's name : DONGGUAN SMALL WORLD NOVELTY CO., LTD.

Address : 7th Floor, C building, Zhongdingtongxun Industry park, Jinxiaotang, Fenggang, Dongguan,Guangdong, China

Product : Remote Control

Model : SW1073

Standards : FCC CFR47 Part 15 Section 15.231

Test procedure : ANSI C63.10:2013

Test Date : July 08, 2025 to July 23, 2025

Date of Issue : July 23, 2025

Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF E.U.T.	5
2.2 TEST MODE	6
2.3 TEST SITE	6
3 EQUIPMENT DURING TEST	7
3.1 EQUIPMENTS LIST	7
3.2 MEASUREMENT UNCERTAINTY	9
3.3 DESCRIPTION OF SUPPORT UNITS	9
4 CONDUCTED EMISSION	10
4.1 E.U.T. OPERATION	10
4.2 EUT SETUP	10
4.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	11
4.4 MEASUREMENT PROCEDURE	11
4.5 CONDUCTED EMISSION LIMIT	11
4.6 MEASUREMENT DESCRIPTION	11
4.7 CONDUCTED EMISSION TEST RESULT	11
5 PERIODIC OPERATION	14
5.1 TEST SETUP	14
6 RADIATED SPURIOUS EMISSIONS	17
6.1 EUT OPERATION	18
6.2 TEST SETUP	19
6.3 SPECTRUM ANALYZER SETUP	20
6.4 TEST PROCEDURE	21
6.5 SUMMARY OF TEST RESULTS	22
7 20DB BANDWIDTH MEASUREMENT	26
7.1 TEST PROCEDURE	26
7.2 TEST SETUP	26
7.3 TEST RESULT	26
8 ANTENNA REQUIREMENT	27
9 TEST SETUP	28
10 EUT PHOTOS	30



1 Test Summary

Test Items	Test Requirement	Result
Conducted Emissions	15.207	PASS
Transmission Cease Time	15.231(a)	PASS
Radiated Emission	15.209 15.205(a)	PASS
Periodic Operation	15.35(c)	PASS
Outside of Band Emission	15.231(b) 15.205 15.209	PASS
20dB Bandwidth	15.215(c)	PASS
Antenna Requirement	15.203	PASS
Remark: N/A: Not Applicable		



2 General Information

2.1 General Description of E.U.T.

Product	:	Remote Control
Model	:	SW1073
Specification	:	SRD
Operating frequency	:	433.92MHz
Modulation	:	ASK
Number of Channel	:	1 channel
Antenna installation	:	PCB Antenna
Antenna Gain	:	0 dBi
Power supply	:	Li-ion Battery: 3.7V
Hardware Version	:	V1.0
Software Version	:	V1.0



2.2 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Modulation	Test mode	Low channel	Middle channel	High channel
ASK	continuously Transmitting	433.92MHz	\	\

2.3 Test Site

Precise Testing & Certification Co., Ltd

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A

FCC Designation Number: CN1219



3 Equipment During Test

3.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Last Calibration	Calibration Interval
MXG Signal Analyzer	Agilent	N9020A	SER MY5111038	10Hz-26.5GHz	Aug.15, 2024	1 Year
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Aug.15, 2024	1 Year
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Aug.15, 2024	1 Year
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Aug.15, 2024	1 Year
DC power Supply	Agilent	E3642A	MY52420017	0-8V,5A/0-20 ,2.5A	Aug.15, 2024	1 Year
Humidity Chamber	AISRY	ASR-HW2-1000	20230926003	-40°C-150°C	Feb.23 ,2025	1year
Test S/W	Tonscend	JS1120-3	/	/	/	/

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Last Calibration	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESPI7	101671	9KHz-7GHz	Aug.15, 2024	1 Year
Loop Antenna	Schwarzbeck	FMZB 1519	192	9 KHz -30MHz	Nov.28, 2024	1 Year
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Sep.10, 2024	1 Year
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	9KHz-1GHz	Mar.21, 2025	1 Year
Cable	IMRO	AK-9515E(9m)	Cable-L	9KHz-3GHz	Aug.15, 2024	1 Year
Spectrum Analyzer	Rohde&Schwarz	FSV40	6625-01-588-5515	9KHz-40GHz	Aug.15, 2024	1 Year



Report No.: PTC25070700101E-FC01

Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1246	1GHz-18GHz	Dec.12, 2024	1 Year
Power Amplifier	ZHINAN	ZN3380C	15002	1GHz-26.5GHz	Aug.15, 2024	1 Year
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-1066	15GHz-40GHz	Jul. 24, 2024	1 Year
Amplifier	SCHWARZBECK	BBV 9721	9721-205	18GHz-40GHz	Jul. 25, 2024	1 Year
Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	Aug.15, 2024	1 Year
RF Cable	R&S	R204	R21X	1GHz-40GHz	Aug.15, 2024	1 Year
Test S/W	Tonscend	TS+	/	/	/	/

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Date	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESC13	101417	9KHz-3GHz	Aug.15, 2024	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	102453	9KHz-300MHz	Oct.30, 2024	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz-300MHz	Oct.30, 2024	1 Year
Limiter	R&S	ESH3-Z2	0357.8810.54-102808-NB	0Hz-30MHz	Aug.15, 2024	1 Year
RF Switch	DIAMOND ANTENNA	CX-210	/	0.09MHz-6GHz	Mar. 21,2025	1 Year
Test S/W	Tonscend	JS32-CE	/	/	/	/



3.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^\circ\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(9kHz~30MHz)	$\pm 3.15\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$

3.3 Description of Support Units

Equipment	Model No.	Series No.
Adapter	Model: PS65B050Y3000S	N/A

4 Conducted Emission

Test Requirement:	: FCC CFR 47 Part 15 Section 15.207
Test Method	: ANSI C63.10: 2013
Test Result	: PASS
Frequency Range	: 150kHz to 30MHz
Class/Severity	: Class B


4.1 E.U.T. Operation

Operating Environment :


Temperature	: 23.9 °C
Humidity	: 51.4 % RH
Atmospheric Pressure	: 101.21kPa

4.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



4.3 Test SET-UP (Block Diagram of Configuration)



4.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

4.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


4.7 Conducted Emission Test Result

PASS.

Conducted emission at both 120V & 240V is assessed, and emission at 120V represents the worst case. All the modulation modes were tested the data of the worst mode (ASK) are recorded in the following pages and the others modulation methods do not exceed the limits.



Line -120V/60Hz:




Final Data List

NO.	Freq. [MHz]	QP Reading	Factor [dB]	QP Value	QP Limit	QP Margin	AV Reading	AV Value	AV Limit	AV Margin	Verdict
1	0.204	28.97	9.81	38.78	63.45	24.67	19.13	28.94	53.45	24.51	PASS
2	0.245	28.44	9.81	38.25	61.94	23.69	18.62	28.43	51.94	23.51	PASS
3	0.371	27.67	9.81	37.48	58.49	21.01	16.69	26.50	48.49	21.99	PASS
4	0.501	27.53	9.81	37.34	56.00	18.66	17.44	27.25	46.00	18.75	PASS
5	0.861	26.45	9.82	36.27	56.00	19.73	17.38	27.20	46.00	18.80	PASS
6	1.154	27.53	9.83	37.36	56.00	18.64	17.15	26.98	46.00	19.02	PASS



Neutral -120V/60Hz:



Final Data List

NO.	Freq. [MHz]	QP Reading	Factor [dB]	QP Value	QP Limit	QP Margin	AV Reading	AV Value	AV Limit	AV Margin	Verdict
1	0.465	31.33	9.81	41.14	56.60	15.46	20.40	30.21	46.60	16.39	PASS
2	0.614	28.01	9.81	37.82	56.00	18.18	18.22	28.03	46.00	17.97	PASS
3	0.870	28.90	9.82	38.72	56.00	17.28	16.64	26.46	46.00	19.54	PASS
4	1.275	28.84	9.83	38.67	56.00	17.33	17.38	27.21	46.00	18.79	PASS
5	1.653	26.42	9.82	36.24	56.00	19.76	14.62	24.44	46.00	21.56	PASS
6	2.877	23.82	9.82	33.64	56.00	22.36	13.22	23.04	46.00	22.96	PASS




5 Periodic Operation

The duty cycle was determined by the following equation:

To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion

5.1 Test Setup



Duty Cycle(%)=Total On interval in a complete pulse train/ Length of a complete pulse train * %

Duty Cycle Correction Factor (dB)=20 * Log₁₀(Duty Cycle(%))

Total transmission time(ms)	0.79*10+0.31*15=12.55
Length of a complete transmission period(ms)	31.52
Duty Cycle(%)	39.82
Duty Cycle Correction Factor(dB)	-8.00


Refer to the duty cycle plot (as below), This device meets the FCC requirement.

Length of a complete pulse train:

Remark: FCC part15.35(c) required that a complete pulse train is more than 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.



Tp




Pulse 1






Pulse 2



FCC Part15.231 (a) (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

(2)A transmitter activated automatically shall cease transmission within 5 seconds after activation.





6 Radiated Spurious Emissions

Test Requirement: : FCC CFR47 Part 15 Section 15.231 & 15.209 & 15.205
 Test Method: : ANSI C63.10:2013
 Test Result: : PASS
 Measurement Distance: : 3m
 Limit: : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

In addition to the provisions of § 15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	1,250 to 3,750	125 to 375
174-260	3,750	375
260-470	3,750 to 12,500	375 to 1250
Above 470	12,500	1,250

Note: Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, $\mu\text{V/m}$ at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in S 15.209, whichever limit permits a higher field strength.



Report No.: PTC25070700101E-FC01

6.1 EUT Operation


Operating Environment :

Temperature:	:	23.5 °C
Humidity:	:	51.1 % RH
Atmospheric Pressure:	:	101.2kPa
EUT Operation :	:	Refer to section 3.3


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

Below 30MHz

IF Bandwidth	10kHz
Resolution Bandwidth	10kHz
Video Bandwidth	10kHz

30MHz ~ 1GHz

Detector	: PK
Resolution Bandwidth	: 100kHz
Video Bandwidth	: 300kHz
Detector	: QP
Resolution Bandwidth	: 120kHz
Video Bandwidth	: 300kHz

Above 1GHz

Detector	: PK
Resolution Bandwidth	: 1MHz
Video Bandwidth	: 3MHz
Detector	: AV
Resolution Bandwidth	: 1MHz
Video Bandwidth	: 10Hz



6.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m or 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.
8. The test above 1GHz must be use the fully anechoic room, and the test below 1GHz use the half anechoic room



6.5 Summary of Test Results

Test Frequency: Below 30MHz

The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test Frequency: 30MHz ~ 5GHz

All applicable test modes have been tested with TX mode(433.92MHz)

Test Result of Fundamental Emission:

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Peak Value (dBμV/m)	PDCF	Average value (dBuV/m)	Average Limit (dBμV/m)	Margin Limit (dB)	Polarization
433.92	95.46	12.32	83.14	-8.0	75.14	80.8	5.66	H
433.92	94.43	12.32	82.11	-8.0	74.11	80.8	6.69	V


Note: PDCF is the abbreviation of duty cycle factor, $DCF = 20 \log(\text{Duty cycle})$.



Test Result of Spurious Emissions:

Blow 1GHz:

Antenna Polarization: Horizontal




Final Data List[QP]

NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	36.31	25.42	-11.56	13.86	40.00	26.14	Horizontal	PASS
2	54.74	26.59	-10.87	15.72	40.00	24.28	Horizontal	PASS
3	143.01	27.48	-9.93	17.55	43.50	25.95	Horizontal	PASS
4	317.85	27.19	-8.28	18.91	46.00	27.09	Horizontal	PASS
5	662.93	27.81	-0.13	27.68	46.00	18.32	Horizontal	PASS
6	867.84	35.22	3.57	38.79	46.00	7.21	Horizontal	PASS

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor



Antenna Polarization: Vertical



Final Data List[QP]

NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	46.73	26.69	-10.96	15.73	40.00	24.27	Vertical	PASS
2	70.98	29.63	-13.24	16.39	40.00	23.61	Vertical	PASS
3	108.09	28.18	-12.05	16.13	43.50	27.37	Vertical	PASS
4	165.07	27.03	-9.47	17.56	43.50	25.94	Vertical	PASS
5	318.82	28.49	-8.28	20.21	46.00	25.79	Vertical	PASS
6	868.08	36.18	3.53	39.71	46.00	6.29	Vertical	PASS

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor



Above 1GHz:

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	PDCF	Level [dBμ V/m]	Limit [dBμ V/m]	Margin [dB]	Result	Polarity	Detector
1	1301.76	52.18	-11.6	/	40.58	74	33.42	PASS	H	PK
2	1735.68	55.45	-7.98	/	47.47	74	26.53	PASS	H	PK
3	2169.60	53.15	-6.99	/	46.16	74	27.84	PASS	H	PK
4	2603.52	55.55	-4.31	/	51.24	74	22.76	PASS	H	PK
5	3037.44	51.05	-3.5	/	47.55	74	26.45	PASS	H	PK
6	3471.36	51.91	-0.38	/	51.53	74	22.47	PASS	H	PK
7	1301.76	57.39	-11.6	/	45.79	74	28.21	PASS	V	PK
8	1735.68	55.17	-7.98	/	47.19	74	26.81	PASS	V	PK
9	2169.60	54.67	-6.99	/	47.68	74	26.32	PASS	V	PK
10	2603.52	51.77	-4.07	/	47.7	74	26.3	PASS	V	PK
11	3037.44	49.91	-1.91	/	48	74	26	PASS	V	PK
12	3471.36	48.82	1.25	/	50.07	74	23.93	PASS	V	PK

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	PDCF	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Detector
1	1301.76	52.09	-11.6	-8.00	32.49	54	21.51	PASS	H	AV
2	1735.68	55.25	-7.98	-8.00	39.27	54	14.73	PASS	H	AV
3	2169.60	52.87	-6.99	-8.00	37.88	54	16.12	PASS	H	AV
4	2603.52	55.65	-4.31	-8.00	43.34	54	10.66	PASS	H	AV
5	3037.44	51.3	-3.5	-8.00	39.80	54	14.2	PASS	H	AV
6	3471.36	51.36	-0.38	-8.00	42.98	54	11.02	PASS	H	AV
7	1301.76	57.94	-11.6	-8.00	38.34	54	15.66	PASS	V	AV
8	1735.68	55.29	-7.98	-8.00	39.31	54	14.69	PASS	V	AV
9	2169.60	54.86	-6.99	-8.00	39.87	54	14.13	PASS	V	AV
10	2603.52	51.51	-4.07	-8.00	39.44	54	14.56	PASS	V	AV
11	3037.44	49.84	-1.91	-8.00	39.93	54	14.07	PASS	V	AV
12	3471.36	49.84	1.25	-8.00	43.09	54	10.91	PASS	V	AV

Remark:

1.The field strength is calculated by adding the Antenna Factor, Cable Factor and Preamplifier.

The formula is as follows is as follows:

Final Test Level =Receiver Reading +Correct Factor




7 20dB Bandwidth Measurement

Test Requirement	: FCC Part15.231(c)
Test Method	: FCC Part15.231(c)
Test Mode	: Refer to section 3.3
Limit	: The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency.

7.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 1% to 5% of the OBW, VBW = three times the RBW,


7.2 Test Setup



7.3 Test Result

Test Frequency (MHz)	20dB Bandwidth (kHz)	Limit (kHz)	Result
433.92	12.49	1084.80	pass

Test plots





Report No.: PTC25070700101E-FC01

8 Antenna Requirement


According to the FCC part15.203, a transmitter can only be sold or operated with antennas with which it was approved. This product has an PCB Antenna which meet the requirement of this section.

9 Test Setup

Conducted Emissions



Radiated Spurious Emissions
From 30MHz-1000MHz




Above 1GHz






10 EUT Photos




















*******THE END REPORT*******