

FCC RF Test Report

APPLICANT : Shanghai Smawave Technology Co. ,Ltd
EQUIPMENT : LTE Module
BRAND NAME : smawave
MODEL NAME : MG401
FCC ID : 2AU8H-MG401
STANDARD : 47 CFR Part 2, 90(R)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Nov. 30, 2018 and completely tested on May 16, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test	5
1.4 Maximum ERP Power, Frequency Tolerance, and Emission Designator	6
1.5 Testing Site	6
1.6 Applied Standards	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Test Mode	7
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration and system	8
2.4 Measurement Results Explanation Example	9
3 CONDUCTED TEST ITEMS	10
3.1 Measuring Instruments	10
3.2 Conducted Output Power and ERP	11
3.3 Peak-to-Average Ratio	12
3.4 Occupied Bandwidth	13
3.5 Conducted Band Edge Measurement	14
3.6 Emission Mask	15
3.7 Conducted Spurious Emission Measurement	16
3.8 Frequency Stability Measurement	17
4 RADIATED TEST ITEMS	18
4.1 Measuring Instruments	18
4.2 Test Setup	18
4.3 Test Result of Radiated Test	18
4.4 Radiated Spurious Emission Measurement	19
5 LIST OF MEASURING EQUIPMENT	20
6 UNCERTAINTY OF EVALUATION	21
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG033107B	Rev. 01	Initial issue of report	May 22, 2020

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	PASS	-
	§90.542 (a)(7)	Effective Radiated Power	ERP < 3Watt	PASS	-
3.3	-	Peak-to-Average Ratio	Reporting only	-	-
3.4	§2.1049	Occupied Bandwidth	Reporting only	PASS	-
3.5	§2.1053 §90.543 (e)(2)(3)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.6	§2.1051 §90.210(n)	Emission Mask	Mask B	PASS	-
3.7	§2.1053 §90.543 (e)(3)	Conducted Spurious Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.8	§2.1055 §90.539 (e)	Frequency Stability Temperature & Voltage	< ±1.25 ppm	PASS	-
4.4	§2.1053 §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 13.00 dB at 1586.000 MHz

1 General Description

1.1 Applicant

Shanghai Smawave Technology Co. ,Ltd

3/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China

1.2 Manufacturer

Shanghai Smawave Technology Co. ,Ltd

3/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	LTE Module
Brand Name	smawave
Model Name	MG401
FCC ID	2AU8H-MG401
Tx Frequency	LTE Band 14: 790.5 MHz ~ 795.5 MHz
Rx Frequency	LTE Band 14: 760.5 MHz ~ 765.5 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	24.52 dBm
Antenna Type / Gain	PCB Antenna with gain 0.50dBi
Type of Modulation	QPSK / 16QAM
IMEI Code	Conducted: 860524031915919 Radiation: 860524031915752
HW Version	V1.2
SW Version	CAT4_GS_BYPASS_0.3.3.2_V1.4
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. This is a change FCC ID report, the change has no influence on the test results, all the test results are leveraged from original report FG8N3015C.

1.4 Maximum ERP Power, Frequency Tolerance, and Emission Designator

LTE Band 14		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum Conducted Power(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum Conducted Power(W)
5	790.5~795.5	4M51G7D	-	0.2831	4M52W7D	-	0.2489
10	793	8M99G7D	0.0044	0.2679	8M95W7D	-	0.2360

1.5 Testing Site

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-KS 03CH06-KS	CN1257	314309

1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, Part 90(R)
- ANSI C63.26-2015
- KDB 971168 D01 Power Meas License Digital Systems v03r01
- KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	14	-	-	V		-	-	V	V		V	V	V	V	V	V
	14	-	-		V	-	-	V	V		V	V	V		V	
Peak-to-Average Ratio	14	-	-		V	-	-	V	V		V		V		V	
26dB and 99% Bandwidth	14	-	-	V		-	-	V	V				V	V	V	V
	14	-	-		V	-	-	V	V				V		V	
Conducted Band Edge	14	-	-	V		-	-	V	V		V		V	V		V
	14	-	-		V	-	-	V	V		V		V		V	
Emission Mask	14	-	-	V		-	-	V	V		V		V	V	V	V
	14	-	-		V	-	-	V	V		V		V		V	
Conducted Spurious Emission	14	-	-	V		-	-	V	V		V			V	V	V
	14	-	-		V	-	-	V	V		V				V	
Frequency Stability	14	-	-		V	-	-	V					V		V	
E.R.P	14	-	-	V		-	-	V	V		V			V	V	V
	14	-	-		V	-	-	V	V		V				V	
Radiated Spurious Emission	14	-	-		V	-	-	V			V				V	
		-	-	V		-	-	V			V			V	V	V
Note	- The mark “v” means that this configuration is chosen for testing - The mark “-” means that this bandwidth is not supported. - The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
3.	Adapter	N/A	ASSA651-1-120100	N/A	N/A	N/A
4.	WWAN Antenna	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 4.3 dB.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 4.3 \text{ (dB)}\end{aligned}$$


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power and ERP

3.2.1 Description of the Conducted Output Power Measurement and ERP

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of portable station transmitters must not exceed 3 Watts.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.5 Conducted Band Edge Measurement

3.5.1 Description of Conducted Band Edge Measurement

For operations in the 758-768 MHz and the 788-798 MHz bands

- (1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations.
- (2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.
- (3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10 \log(P)]$ (dB)
 $= [30 + 10 \log(P)]$ (dBm) - $[43 + 10 \log(P)]$ (dB) = -13dBm.

3.6 Emission Mask

3.6.1 Description of Emission Mask

<Emission Mask B>.


For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
- (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
- (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log (P)$ dB.

3.6.2 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The power of the modulated signal was measured on a spectrum analyzer using an RMS and 10 second sweep time in order to maximize the level.
3. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.6.3 Test Setup



3.7 Conducted Spurious Emission Measurement

3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and base station via power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's, for under 1GHz RBW = 100kHz, VBW = 300kHz and for above 1GHz RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= P(W)- $[43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 1.25 ppm of the center frequency.

3.8.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
11. $\text{ERP (dBm)} = \text{EIRP} - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$= P(W) - [43 + 10\log(P)] \text{ (dB)}$

$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$

$= -13\text{dBm}.$

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2018	May 04, 2019~ May 15, 2019	Aug. 06, 2019	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Nov. 19, 2018	May 04, 2019~ May 15, 2019	Nov. 18, 2019	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471084	10Hz~44GHz	Jun. 25, 2018	May 16, 2019	Jun. 24, 2019	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Dec. 28, 2018	May 16, 2019	Dec. 27, 2019	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 20, 2018	May 16, 2019	Oct. 19, 2019	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	May 16, 2019	Jan. 04, 2020	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug. 06, 2018	May 16, 2019	Aug. 05, 2019	Radiation (03CH06-KS)
Amplifier	MITEQ	TTA1840-35-HG	2014749	18~40GHz	Jan. 14, 2019	May 16, 2019	Jan. 13, 2020	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Apr. 17, 2019	May 16, 2019	Apr. 16, 2020	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 15, 2019	May 16, 2019	Apr. 14, 2020	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	May 16, 2019	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	May 16, 2019	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	May 16, 2019	NCR	Radiation (03CH06-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.1dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.1dB
---	-------

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 14 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.48	24.44	23.91
5	1	12		24.39	23.82	22.98
5	1	24		24.26	23.02	23.68
5	12	0		23.65	23.44	22.48
5	12	7		23.82	22.94	22.27
5	12	13		23.63	22.88	22.67
5	25	0		24.52	23.20	22.49
5	1	0	16-QAM	23.96	23.90	23.21
5	1	12		23.79	22.95	22.26
5	1	24		23.59	22.31	22.99
5	12	0		22.77	22.47	21.50
5	12	7		22.77	21.88	21.31
5	12	13		22.65	21.85	21.55
5	25	0		23.52	22.23	21.55



LTE Band 14 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK		24.28	
10	1	25			23.69	
10	1	49			23.34	
10	25	0			24.16	
10	25	12			22.93	
10	25	25			22.19	
10	50	0			23.43	
10	1	0	16-QAM		23.73	
10	1	25			23.04	
10	1	49			22.61	
10	25	0			23.22	
10	25	12			22.01	
10	25	25			21.18	
10	50	0			22.39	

ERP

LTE Band 14 ($G_T - L_C = 0.50$ dBi) QPSK						
Bandwidth	5M			10M		
Channel	23305	23330	23355		23330	
	(Low)	(Mid)	(High)		(Mid)	
Frequency	790.5	793	795.5		793	
(MHz)						
Conducted Power (dBm)	24.52	23.20	22.49		24.28	
Conducted Power (Watts)	0.2831	0.2089	0.1774		0.2679	
ERP(dBm)	22.87	21.55	20.84		22.63	
ERP(Watts)	0.1936	0.1429	0.1213		0.1832	

LTE Band 14 ($G_T - L_C = 0.50$ dBi) 16QAM						
Bandwidth	5M			10M		
Channel	23305	23330	23355		23330	
	(Low)	(Mid)	(High)		(Mid)	
Frequency	790.5	793	795.5		793	
(MHz)						
Conducted Power (dBm)	23.96	23.90	23.21		23.73	
Conducted Power (Watts)	0.2489	0.2455	0.2094		0.2360	
ERP(dBm)	22.31	22.25	21.56		22.08	
ERP(Watts)	0.1702	0.1679	0.1432		0.1614	



Peak-to-Average Ratio

Mode	LTE Band 14 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH					PASS
Middle CH	5.83	5.86	6.61	6.52	
Highest CH					

LTE Band 14 / 10MHz / QPSK

Middle Channel/ 1RB



Date: 4 MAY 2019 16:09:45


Middle Channel / Full RB



Date: 4 MAY 2019 16:11:32


LTE Band 14 / 10MHz / 16QAM

Middle Channel/ 1RB



Date: 4 MAY 2019 16:10:38

Middle Channel / Full RB



Date: 4 MAY 2019 16:11:55




26dB Bandwidth

Mode	LTE Band 14 : 26dB BW(MHz)											
BW	5MHz		10MHz									
Mod.	QPSK	16QAM	QPSK	16QAM								
Lowest CH	5.036	5.065										
Middle CH	5.094	5.137	9.957	9.841								
Highest CH	5.007	5.065										


LTE Band 14

Lowest Channel / 5MHz / QPSK




Date: 4 MAY 2019 15:21:09

Lowest Channel / 5MHz / 16QAM




Date: 4 MAY 2019 15:22:35

Middle Channel / 5MHz / QPSK




Date: 4 MAY 2019 15:17:24

Middle Channel / 5MHz / 16QAM




Date: 4 MAY 2019 15:18:30

Highest Channel / 5MHz / QPSK



Date: 4 MAY 2019 15:25:01


Highest Channel / 5MHz / 16QAM



Date: 4 MAY 2019 15:24:31


LTE Band 14

Middle Channel / 10MHz / QPSK



Date: 4 MAY 2019 15:15:55

Middle Channel / 10MHz / 16QAM




Date: 4 MAY 2019 15:15:27

**Occupied Bandwidth**

Mode	LTE Band 14 : 99%OBW(MHz)											
BW	5MHz		10MHz									
Mod.	QPSK	16QAM	QPSK	16QAM								
Lowest CH	4.50	4.50										
Middle CH	4.51	4.52	8.99	8.95								
Highest CH	4.50	4.49										


LTE Band 14

Lowest Channel / 5MHz / QPSK




Date: 4 MAY 2019 15:05:24

Lowest Channel / 5MHz / 16QAM




Date: 4 MAY 2019 15:05:45

Middle Channel / 5MHz / QPSK




Date: 4 MAY 2019 15:07:49

Middle Channel / 5MHz / 16QAM



Date: 4 MAY 2019 15:07:24

Highest Channel / 5MHz / QPSK



Date: 4 MAY 2019 15:02:59

Highest Channel / 5MHz / 16QAM




Date: 4 MAY 2019 15:03:59




LTE Band 14

Middle Channel / 10MHz / QPSK



Date: 4 MAY 2019 15:09:12

Middle Channel / 10MHz / 16QAM




Date: 4 MAY 2019 15:09:47



Conducted Band Edge

LTE Band 14 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 4 MAY 2019 15:31:34

Highest Band Edge / 1 RB




Date: 4 MAY 2019 15:40:12

Lowest Band Edge / Full RB



Date: 4 MAY 2019 15:35:28

Highest Band Edge / Full RB



Date: 4 MAY 2019 15:38:05



LTE Band 14 / 5MHz / 16QAM

Lowest Band Edge /1 RB




Date: 4 MAY 2019 15:33:24

Highest Band Edge / 1 RB




Date: 4 MAY 2019 15:41:03

Lowest Band Edge / Full RB



Date: 4 MAY 2019 15:36:25


Highest Band Edge / Full RB



Date: 4 MAY 2019 15:38:39

LTE Band 14 / 10MHz / QPSK

Lowest Band Edge / 1 RB




Date: 4.MAY.2019 15:44:31

Highest Band Edge / 1 RB



Date: 4.MAY.2019 15:46:25

Band Edge / Full RB



Date: 4.MAY.2019 15:48:45



LTE Band 14 / 10MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 4.MAY.2019 15:45:07

Highest Band Edge / 1 RB



Date: 4.MAY.2019 15:47:23


Band Edge / Full RB



Date: 4.MAY.2019 15:49:31




Conducted Spurious Emission






LTE Band 14 / 5MHz

Highest Channel / QPSK



Date: 4 MAY 2019 16:02:08


Highest Channel / 16QAM



Date: 4 MAY 2019 16:02:52


LTE Band 14 / 10MHz

Middle Channel / QPSK



Date: 4 MAY 2019 15:54:21

Middle Channel / 16QAM




Date: 4 MAY 2019 15:55:40

Emission Mask


LTE Band 14/ 5M(1RB0)

Lowest Channel / 5MHz / QPSK




Date: 15 MAY 2019 22:25:42

Lowest Channel / 5MHz / 16QAM




Date: 15 MAY 2019 22:28:41

Middle Channel / 5MHz / QPSK




Date: 15 MAY 2019 22:28:58

Middle Channel / 5MHz / 16QAM




Date: 15 MAY 2019 22:28:44

Highest Channel / 5MHz / QPSK



Date: 15 MAY 2019 22:21:27


Highest Channel / 5MHz / 16QAM



Date: 15 MAY 2019 22:28:28


LTE Band 14/ 5M(1RBmax)

Lowest Channel / 5MHz / QPSK




Date: 15 MAY 2019 22:36:34

Lowest Channel / 5MHz / 16QAM




Date: 15 MAY 2019 22:37:33

Middle Channel / 5MHz / QPSK




Date: 15 MAY 2019 22:32:28

Middle Channel / 5MHz / 16QAM




Date: 15 MAY 2019 22:31:19

Highest Channel / 5MHz / QPSK




Date: 15 MAY 2019 22:39:42


Highest Channel / 5MHz / 16QAM




Date: 15 MAY 2019 22:40:39

LTE Band 14/ 5M(fullRB0)
Lowest Channel / 5MHz / QPSK



Date: 15 MAY 2019 22:56:38

Lowest Channel / 5MHz / 16QAM



Date: 15 MAY 2019 22:57:35

Middle Channel / 5MHz / QPSK



Date: 15 MAY 2019 22:49:16

Middle Channel / 5MHz / 16QAM



Date: 15 MAY 2019 22:50:10

Highest Channel / 5MHz / QPSK



Date: 15 MAY 2019 22:44:21

Highest Channel / 5MHz / 16QAM



Date: 15 MAY 2019 22:46:32

LTE Band 14/ 10MHz
Middle Channel / 1RB0 / QPSK



Date: 15 MAY 2019 23:11:07

Middle Channel / 1RB0 / 16QAM



Date: 15 MAY 2019 23:12:23

Middle Channel / 1RBmax / QPSK



Date: 15 MAY 2019 23:14:54

Middle Channel / 1RBmax / 16QAM


Date: 15 MAY 2019 23:16:09

Middle Channel / fullRB0 / QPSK


Date: 15 MAY 2019 23:18:44

Middle Channel / fullRB0 / 16QAM


Date: 15 MAY 2019 23:20:11

Frequency Stability

Test Conditions		LTE Band 14 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0044	PASS
40	Normal Voltage	0.0035	
30	Normal Voltage	0.0005	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0026	
0	Normal Voltage	0.0040	
-10	Normal Voltage	0.0011	
-20	Normal Voltage	0.0044	
-30	Normal Voltage	0.0006	
20	Maximum Voltage	0.0037	
20	Normal Voltage	0.0006	
20	Battery End Point	0.0026	

Note:

1. Normal Voltage =3.3V. ; Battery End Point (BEP) =3V. ; Maximum Voltage =3.6V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.

Appendix B. Test Results of Radiated Test

Field Strength of Spurious Radiated

LTE Band 14 / 5MHz / QPSK / RB Size 1 Offset 0								
Bandwidth	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1576	-53.30	-40	-13.30	-55.01	2.23	6.09	H
	2365.02	-67.80	-13	-54.80	-68.33	2.83	5.51	H
	3153	-57.89	-13	-44.89	-59.83	3.21	7.30	H
	1576	-60.85	-40	-20.85	-62.56	2.23	6.09	V
	2365.02	-67.25	-13	-54.25	-67.78	2.83	5.51	V
	3153	-61.83	-13	-48.83	-63.77	3.21	7.30	V
Middle	1582	-59.09	-40	-19.09	-60.80	2.23	6.09	H
	2372.52	-66.47	-13	-53.47	-67.00	2.83	5.51	H
	3162	-63.36	-13	-50.36	-65.30	3.21	7.30	H
	1582	-55.64	-40	-15.64	-57.35	2.23	6.09	V
	2372	-66.16	-13	-53.16	-66.69	2.83	5.51	V
	3162	-60.31	-13	-47.31	-62.25	3.21	7.30	V
Highest	1586	-53.00	-40	-13.00	-54.71	2.23	6.09	H
	2380	-64.75	-13	-51.75	-65.28	2.83	5.51	H
	3174	-58.23	-13	-45.23	-60.17	3.21	7.30	H
	1586	-60.25	-40	-20.25	-61.96	2.23	6.09	V
	2484	-65.51	-13	-52.51	-66.04	2.83	5.51	V
	3174	-61.22	-13	-48.22	-63.16	3.21	7.30	V
Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Test Result					PASS			

LTE Band 14 / 10MHz / QPSK / RB Size 1 Offset 0								
Bandwidth	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1578	-53.78	-40	-13.78	-55.49	2.23	6.09	H
	2365.77	-67.79	-13	-54.79	-68.32	2.83	5.51	H
	3153	-58.67	-13	-45.67	-60.61	3.21	7.30	H
	1578	-61.56	-40	-21.56	-63.27	2.23	6.09	V
	2366	-67.73	-13	-54.73	-68.26	2.83	5.51	V
	3153	-61.52	-13	-48.52	-63.46	3.21	7.30	V
Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Test Result					PASS			