

RF EXPOSURE EVULATION

1.1 Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength	Magnetic field Strength	Power density	Averaging time
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			<u>1.0</u>	30

F = frequency in MHz

* = Plane-wave equivalent power density

1.2 MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Power density at the specific separation:

$S = PG/(4R^2 \pi)$ $S = (4.05 * 0.32) / (4 * 5^2 * \pi)$ $S = 0.42 \text{ mW/cm}^2$	Where, S = Maximum power density (mW/cm²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20 cm = limit for MPE)
--	--

1.3 MAXIMUM PERMISSIBLE EXPOSURE Prediction

- Calculated under the worst-case conditions of each mode.

(Measured power 6.1 dBm ± 0.5dB)

3-1. 2.4 GHz Zigbee Mode

Max Peak output Power at antenna input terminal	6.07	dBm
Max Peak output Power at antenna input terminal	4.05	mW
Prediction distance	5	cm
Prediction frequency	2,480	MHz
Antenna Gain(typical)	-4.91	dBi
Antenna Gain(numeric)	0.32	-
Power density at prediction frequency(S)	0.42	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.21	mW/cm ²

SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance ≤ 50 mm = **Used**

$[(\text{max.power of channel, including tune-up torelance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f}(\text{GHz})]$

$= [4.05 / 5] * [\sqrt{2.480}] = 1.07 \leq 7.5$, for 1g SAR

Thus, SAR for this device is not required.