

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Lockdown Wireless Hygrometer
Model Name	1116792, S5007B
FCC ID	2AU981116792

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.}$

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

According to the follow transmitter output power (P_t) formula:

$$P_t = (E \times d)^2 / (30 \times g_t)$$

P_t =transmitter output power in watts

g_t =numeric gain of the transmitting antenna (unitless)

E =electric field strength in V/m

d =measurement distance in meters (m)

$$P_t=0.00191 \text{ mW}$$

The result for RF exposure evaluation

$$\text{SAR} = (0.00191 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{0.433922(\text{GHz})}] = 2.516 \times 10^{-4} < 3.0 \text{ for 1-g SAR}$$

4. CONCLUSION

The SAR evaluation is not required.