


Manual of Calling Transmitter



CT06 Calling Transmitter

1. Wireless coding: 1527
2. Operating voltage: DC12V ;
3. Operating current: 15±3mA;
4. Range: 500m (open aera);
5. Operating frequency: 433.67MHz;
6. Used as calling button or emergency button, waterproof;
7. Size: ø60*H22mm
8. Color options: White/Red, White/Blue; Black/Red, Black/Blue

Instructions for use:

Press the call button.

This button will send a calling signal to the receiver when you press the button. Then the waiter will know who needs to service by the receiver. It wildly used in restaurants, coffee shops, health care center and so on.

Warning:

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) this device may not cause harmful interference, and

(2) this device must accept any interference received, including interference that may cause undesired operation.

This device and its antenna(s) must not be co-located or operating in conjunction with any other antenna or transmitter.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception,

which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-- Reorient or relocate the receiving antenna.

-- Increase the separation between the equipment and receiver.

-- Connect the equipment into an outlet on a circuit different

from that to which the receiver is connected.

-- Consult the dealer or an experienced radio/TV technician for help. The device has been evaluated to meet general RF exposure requirement.

The device can be used in portable exposure condition without restriction

FCC ID: 2AUASWL-CT06