

# ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

**Test Report No.** : OT-198-RWD-024

**AGR No.** : A194A-422R

**Applicant** : Cufit Inc.

**Address** : 705, HumanTeco, 57, Achasan17gil, Seongdong-gu, Seoul 04799, Republic of Korea

**Manufacturer** : InfosTechnology

**Address** : 2F Gubo bldg, 133 Nonhyun-ro, Seocho-gu, Seoul, 137-890, Korea

**Type of Equipment** : OPENRIDER R1

**FCC ID.** : 2AUADR1-200-GE

**Model Name** : R1-200-GE

**Multiple Model Name** : N/A

**Serial number** : N/A

**Total page of Report** : 8 pages (including this page)

**Date of Incoming** : January 23, 2019

**Date of issue** : August 08, 2019

## SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:

Yu-Seog Sim / Assistant Manager  
ONETECH Corp.



Approved by:

Jae-Ho Lee / Chief Engineer  
ONETECH Corp.



## CONTENTS

	PAGE
<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION.....</b>	<b>5</b>
<b>2.1 PRODUCT DESCRIPTION.....</b>	<b>5</b>
<b>3. EUT MODIFICATIONS.....</b>	<b>6</b>
<b>4. RF EXPOSURE EVALUATION .....</b>	<b>7</b>
<b>4.1 STANDARD APPLICABLE .....</b>	<b>7</b>
<b>4.2 EUT DESCRIPTION.....</b>	<b>7</b>
<b>4.3 CALCULATED MPE SAFE DISTANCE.....</b>	<b>8</b>

### Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-198-RWD-024	August 08, 2019	Initial Issue	All

## 1. VERIFICATION OF COMPLIANCE

Applicant : Cufit Inc.  
Address : 705, HumanTeco, 57, Achasan17gil, Seongdong-gu, Seoul 04799, Republic of Korea  
Contact Person : Haeng-ro Choi/Senior Manager  
Telephone No. : +82-10-6316-0364  
FCC ID : 2AUADR1-200-GE  
Brand Name : OPENRIDER  
Model Name : R1-200-GE  
Serial Number : N/A  
Date : August 08, 2019

EQUIPMENT CLASS	DTS – DIGITAL TRANSMISSION SYSTEM
E.U.T. DESCRIPTION	OPENRIDER R1
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT	Certification
AUTHORIZATION REQUESTED	
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. GENERAL INFORMATION

### 2.1 Product Description

The Cufit Inc., Model R1-200-GE (referred to as the EUT in this report) is a OPENRIDER R1. Product specification information described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	OPENRIDER R1	
OPERATING FREQUENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz
	ANT+	2 402 MHz ~ 2 480 MHz
	NFC	860 ~960 MHz (Rx Only)
RF OUTPUT POWER	Bluetooth LE	0.57 dBm
	ANT+	-1.18 dBm
NUMBER OF CHANNEL	Bluetooth LE	40 Channels
	ANT+	79 Channels
MODULATION TYPE	Bluetooth LE	GFSK
	ANT+	
	NFC	DSB-ASK, SSB-ASK, or PR-ASK
ANTENNA TYPE	Bluetooth LE	MULTILAYER CERAMIC ANTENNA
	ANT+	
	NFC	Combination of loop and dipole(Blade antenna) Antenna
ANTENNA GAIN	2.12 dBi	
LIST OF EACH OSC. OR CRYSTAL. FREQ.(FREQ.>=1 MHz)	16 MHz, 32.768 kHz	
RATED SUPPLY VOLTAGE	DC 3.0 V	

Note: Bluetooth and ANT+ do not operate simultaneously.

**2.2 Alternative type(s)/model(s); also covered by this test report.**

- None

**3. EUT MODIFICATIONS**

- None

## 4. RF Exposure Evaluation

### 4.1 Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is

$[(\text{Max. Power of channel, including tune-up tolerance, mW}) / (\text{Min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] < 3$

### 4.2 EUT Description

Kind of EUT	OPENRIDER R1
Operating Frequency Band	<input type="checkbox"/> Wireless Microphone: 494.000 MHz ~ 501.000 MHz <input type="checkbox"/> and 498.200 MHz ~ 505.200 MHz <input type="checkbox"/> WLAN: 2 412 MHz ~ 2 462 MHz <input type="checkbox"/> WLAN: 5 180 MHz ~ 5 240 MHz <input type="checkbox"/> WLAN: 5 745 MHz ~ 5 825 MHz <input type="checkbox"/> Bluetooth: 2 402 MHz ~ 2 480 MHz <input checked="" type="checkbox"/> Bluetooth BLE: 2 402 MHz ~ 2 480 MHz
MAX. RF OUTPUT POWER	0.57 dBm
Antenna Gain	2.12 dBi
Exposure Evaluation Applied	<input type="checkbox"/> MPE <input type="checkbox"/> SAR <input checked="" type="checkbox"/> SAR Test Exclusion Evaluation

Note : It was calculated as SAR Test Exclusion Evaluation because it can be installed on the bicycle panel in the manual.

#### 4.3 Calculated MPE Safe Distance

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is  
[(Max. Power of channel, including tune-up tolerance, mW)/(Min. test separation distance, mm)] X [  $\sqrt{f(\text{GHz})}$  ] < 3  
= (1.07/5) X  $\sqrt{2.402} = 0.40$

Conclusion: The SAR test exclusion threshold is less than 3, so the device meets the RF Exposure Requirement and excluded SAR Test.

	Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
BLE (GFSK)	2.402	0.57 ± 0.5	1.07	1.28	5	0.40



Tested by: Ha-Ram Lee / Assistant Manager