

Maximum Permissible Exposure Evaluation

FCC ID: 2AUAG-S80-A3-AZH

1. Client Information

Applicant	:	Shenzhen United Innovation Auto-control Systems Co.,Ltd
Address	:	16/F Block A, Bank of China Buildings, CaiTian Road, FuTian District, Shenzhen, China
Manufacturer	:	Shenzhen United Innovation Auto-control Systems Co.,Ltd
Address	:	16/F Block A, Bank of China Buildings, CaiTian Road, FuTian District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Temperature and humidity sensor	
Models No.	:	S80-A3-AZH	
Model Difference	:	N/A	
Product Description	:	Operation Frequency:	Zigbee: 2405MHz~2480MHz
	:	Max Output Power:	Zigbee: -11.869dBm
	:	Antenna Gain:	1.5dBi PCB Antenna
Power Supply	:	Input: DC 3V by battery CR2450.	
Software Version	:	V3.0	
Hardware Version	:	Z-RH-T	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

MPE Calculations for Zigbee

1. Antenna Gain:

Zigbee: 1.5dBi PCB Antenna

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
Zigbee	-11.869	-12±1	-11	1.5	20	0.00002

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For Zigbee:2405-2480 MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as $0.00002\text{mW} / \text{cm}^2 < \text{limit } 1\text{mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----