



Choose Scandinavian trust

RADIO TEST REPORT

Report ID

REP021484

Project ID

PRJ0046803

Type of assessment:

MPE Calculation report

Manufacturer:

Ingeniarts Technologies Inc

Product Marketing Name (PMN):

UGOWORK HMI V2

Hardware Version Identification Number (HVIN):

UGOWORK HMI V2

FCC identifier:

FCC ID: 2AUBT-UGOWORKHMI2

ISED certification number:

IC: 25380-UGOWORKHMI2

Specification:

- ◆ FCC 47 CFR Part 1 Subpart I, §1.1307, §1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ FCC KDB 447498 D01 General RF Exposure Guidance v06
- ◆ ISED Canada RSS-102 Issue 5 Amendment 1 (February 2021)

RSS-102 Annex B - Declaration of RF Exposure Compliance

ATTESTATION: I attest that the information provided in Annex A is correct; that the Technical Brief was prepared and the information contained therein is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed; and that the device meets the SAR and/or RF field strength limits of RSS-102.

Date of issue: December 22, 2023

Hossein Zamani Zardehsavari, EMC/RF Specialiste

Prepared by



Signature

Nemko Canada Inc., a testing laboratory, is accredited by ANSI National Accreditation Board (ANAB).
The tests included in this report are within the scope of this accreditation.

The ANAB symbol is an official symbol of the ANSI National Accreditation Board, used under licence.

ANAB File Number: AT-3195 (Ottawa/Almonte); AT-3193 (Pointe-Claire); AT-3194 (Cambridge)



Lab locations

| Company name | Nemko Canada Inc. | | | |
|----------------------|---|--|---|---|
| Facilities | <i>Ottawa site:</i> 303 River Road Ottawa, Ontario Canada K1V 1H2 | <i>Montréal site:</i> 292 Labrosse Avenue Pointe-Claire, Québec Canada H9R 5L8 | <i>Cambridge site:</i> 1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2 | <i>Almonte site:</i> 1500 Peter Robinson Road West Carleton, Ontario Canada K0A 1L0 |
| | Tel: +1 613 737 9680 Fax: +1 613 737 9691 | Tel: +1 514 694 2684 Fax: +1 514 694 3528 | Tel: +1 519 650 4811 | Tel: +1 613 256-9117 |
| Test site identifier | Organization | Ottawa/Almonte | Montreal | Cambridge |
| | FCC: ISED: | CA2040 2040A-4 | CA2041 2040G-5 | CA0101 24676 |
| Website | www.nemko.com | | | |

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

Table of Contents

| | |
|--|----------|
| Table of Contents | 3 |
| Section 1 Evaluation summary | 4 |
| 1.1 MPE calculation for standalone transmission | 4 |

Section 1 Evaluation summary

1.1 MPE calculation for standalone transmission

1.1.1 References, definitions and limits

FCC §2.1091(d)

- (2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

Table 1.1-1: Table 1 to §1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|---|----------------------------------|----------------------------------|--|-----------------------------|
| (i) Limits for Occupational/Controlled Exposure | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | ≤6 |
| 3.0–30 | 1842 / f | 4.89 / f | *(900 / f ²) | <6 |
| 30–300 | 61.4 | 0.163 | 1.0 | <6 |
| 300–1500 | | | f / 300 | <6 |
| 1500–100000 | | | 5 | <6 |
| (ii) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | <30 |
| 1.34–30 | 824 / f | 2.19 / f | *(180 / f ²) | <30 |
| 30–300 | 27.5 | 0.073 | 0.2 | <30 |
| 300–1500 | | | f / 1500 | <30 |
| 1500–100000 | | | 1.0 | <30 |

Notes: f = frequency in MHz. * = Plane-wave equivalent power density.

RSS-102, Section 4

For the purpose of this standard, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6:

Table 1.1-2: Table 4 to RSS-102—RF Field Strength Limits

| Frequency range (MHz) | Electric field strength (V/m rms) | Magnetic field strength (A/m rms) | Power density (W/m ²) | Reference Period (minutes) |
|--|--------------------------------------|--------------------------------------|--------------------------------------|-------------------------------|
| Limits for Controlled Environment | | | | |
| 10–20 | 61.4 | 0.163 | 10 | 6 |
| 20–48 | 129.8 / f ^{0.25} | 0.3444 / f ^{0.25} | 44.72 / f ^{0.5} | 6 |
| 48–100 | 49.33 | 0.1309 | 6.455 | 6 |
| 100–6000 | 15.60 f ^{0.25} | 0.04138 f ^{0.25} | 0.6455 f ^{0.5} | 6 |
| 6000–15000 | 137 | 0.364 | 50 | 6 |
| Limits for Uncontrolled Environment | | | | |
| 10–20 | 27.46 | 0.0728 | 2 | 6 |
| 20–48 | 58.07 / f ^{0.25} | 0.1540 / f ^{0.25} | 8.944 / f ^{0.5} | 6 |
| 48–300 | 22.06 | 0.05852 | 1.291 | 6 |
| 300–6000 | 3.142 f ^{0.3417} | 0.008335 f ^{0.3417} | 0.02619 f ^{0.6834} | 6 |
| 6000–15000 | 61.4 | 0.163 | 10 | 6 |

Notes: f = frequency in MHz.

References, definitions and limits, continued

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm² or W/m²)

P = power input to the antenna (mW or W)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm or m)

1.1.2 EUT technical information

| | |
|--------------------------------|-----------------------|
| Prediction frequency | 2437 MHz |
| Antenna type | Internal antenna |
| Antenna gain | 1.9 dBi |
| Number of antennas | 1 |
| Maximum transmitter power | 20.98 dBm (conducted) |
| Prediction distance (declared) | 20 cm |

1.1.3 MPE calculation

| | | |
|---|-----------------------------|-----------------------------|
| Fundamental transmit (prediction) frequency: | 2437 MHz | |
| Maximum measured conducted peak output power: | 20.98 dBm | |
| Cable and/or jumper loss: | 0 dB | |
| Maximum peak power at antenna input terminal: | 20.98 dBm | |
| Duty cycle: | 100 % | |
| Maximum calculated average power at antenna input terminal: | 125.3141175 mW | |
| Single Antenna gain (typical): | 1.9 dBi | |
| Number of antennae: | 1 | |
| Total system gain: | 1.9 dBi | |
| FCC limit: | | ISED limit: |
| MPE limit for <u>uncontrolled</u> exposure at prediction frequency: | 1.000000 mW/cm ² | 0.540397 mW/cm ² |
| | 10.000000 W/m ² | 5.403965 W/m ² |
| MPE limit for <u>controlled</u> exposure at prediction frequency: | 5.000000 mW/cm ² | 3.186574 mW/cm ² |
| | 50.000000 W/m ² | 31.865740 W/m ² |
| Minimum calculated prediction distance for compliance: | 20 cm | 20 cm |
| Typical (declared) distance: | 20 cm | 20 cm |
| Average power density at prediction frequency: | 0.038613 mW/cm ² | 0.038613 mW/cm ² |
| | 0.386127 W/m ² | 0.386127 W/m ² |
| Margin of Compliance for <u>uncontrolled</u> environment: | 14.13 dB | 11.46 dB |
| with Maximum premitted antenna gain: | 16.03 dBi | 13.36 dBi |
| Margin of Compliance for <u>controlled</u> environment: | 21.12 dB | 19.17 dB |
| with Maximum permitted antenna gain: | 44.00 dBi | 42.05 dBi |

1.1.4 Verdict

The calculation is below the limit; therefore, the product is passing the RF Exposure requirements for the declared distance.

End of the test report