



Maximum Permissible Exposure Evaluation

FCC ID:2AUDF-CG286&IC:29207-CG628

Report No.	:	TBR-C-202505-0155-9
Applicant	:	Shenzhen ADDX Innovation Technology co., LTD.
Equipment Under Test (EUT)		
EUT Name	:	Smart Battery Camera
Model No.	:	CG6
HVIN	:	CG628
Series Model No.	:	CG3A,SRS300,X82,X83,X84,CG6S,CG6F,CG6X,CG6H,CG6D,CG6K,CG6E,CG6C,BC01,BCam-02, HB911,CRS300,CG6T,CG6L
Brand Name	:	N/A
Sample ID	:	HC-C-202505-0155-01-01
Receipt Date	:	2025-05-29
Test Date	:	2025-05-29 to 2025-06-16
Issue Date	:	2025-06-16
Standards	:	FCC Part 2.1091 RSS-102 Issue 6 December 15, 2023
Test Method	:	KDB 447498 D01 General RF Exposure Guidance v06
Conclusions	:	PASS
		In the configuration tested, the EUT complied with the standards specified above.
Test By	:	<i>Lily.zhang</i> Lily.zhang
Reviewed By	:	<i>Henry.huang</i> Henry.huang
Approved By	:	<i>Ivan.Su</i> Ivan.Su

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

CONTENTS

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT.....	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
2. MEASUREMENT UNCERTAINTY	5
3. TEST FACILITY.....	6
4. METHOD OF MEASUREMENT FOR FCC.....	7
5. METHOD OF MEASUREMENT FOR IC.....	9
5.1. Applicable Standard	9
5.2. Evaluation Method and Limit.....	9
5.3. Calculation Formula.....	10
5.4. Evaluation Results	11



Revision History



1. General Information about EUT

1.1 Client Information

Applicant	:	Shenzhen ADDX Innovation Technology co., LTD.
Address	:	NO.2013, Building 9B-3. Shenzhen Bay, Technology and Ecological Park, Nanshan District, shenzhen, China
Manufacturer	:	Shenzhen ADDX Innovation Technology co., LTD.
Address	:	NO.2013, Building 9B-3. Shenzhen Bay, Technology and Ecological Park, Nanshan District, shenzhen, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Smart Battery Camera
Models No.	:	CG6,CG3A,SRS300,X82,X83,X84,CG6S,CG6F,CG6X,CG6H,CG6D,CG6K,CG6E,CG6C,BC01,BCam-02,HB911,CRS300,CG6T,CG6L
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is model name.
Product Description	Operation Frequency:	BLE: 2402MHz~2480MHz 2.4G Wi-Fi: 2412MHz~2462MHz
	Modulation Type:	BLE: GFSK, Pi/4-DQPSK, 8DPSK 802.11b: DSSS (DQPSK, DBPSK, CCK) 802.11g: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11n: OFDM (QPSK, BPSK, 16QAM, 64QAM)
	Antenna Gain:	BLE: 0.5dBi PCB Antenna 2.4G WIFI: -2.48 dBi Steel sheet Antenna
Power Rating	:	USB Input:5V DC 3.7V 5200mAh Rechargeable Li-ion battery (XL18650-2600-2P) DC 3.6V 5000mAh Rechargeable Li-ion battery (INR18650) (Battery differences are mainly based on the applicant and model and capacity differences, only the worst mode is assessed (XL18650-2600-2P))
Software Version	:	1.12.10
Hardware Version	:	CG628_C01_V2

Remark: The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.



2. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.50 dB ± 3.10 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.50 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB
RF Power-Conducted	Level Accuracy: Above 1000MHz	± 0.95 dB
Power Spectral Density-Conducted	Level Accuracy: Above 1000MHz	± 3 dB
Occupied Bandwidth	Level Accuracy: 30MHz to 1000 MHz Above 1000MHz	$\pm 3.8\%$
Unwanted Emission-Conducted	Level Accuracy: 30MHz to 1000 MHz Above 1000MHz	± 2.72 dB
Temperature	/	$\pm 0.6^\circ\text{C}$
Humidity	/	$\pm 4\%$
Supply voltages	/	$\pm 2\%$
Time	/	$\pm 4\%$



3. Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F., Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.



4. Method of Measurement for FCC

4.1 EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

$$\sum \text{ of MPE ratios} \leq 1.0$$



4.3 Test Result:

Test Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	Max. ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
Bluetooth	2.625	2±1	3	0.5	20	0.00045
2.4G b	17	17±1	18	-2.48	20	0.00709
2.4G g	15.36	15±1	16	-2.48	20	0.00447
2.4G n20	15.16	15±1	16	-2.48	20	0.00447

4.4 Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For: 2402~2480MHz&2412~2462MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as $0.00709 \text{ mW/cm}^2 < \text{limit } 1 \text{ mW/cm}^2$.

4.5 Summary simultaneous transmission results

Bluetooth and WiFi support Synchronization transmitter

Maximum MPE ratio Bluetooth	Maximum MPE ratio WiFi	Σ MPE ratios	Limit	Results
0.00045	0.00709	0.00754	1	PASS

So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091 (b). The RF Exposure Information page from the manual is included here for reference.



5. Method Of Measurement for IC

5.1. Applicable Standard

[Radio Standards Specification 102](#), Radio Frequency (RF) Exposure Compliance of Radio communication Apparatus (All Frequency Bands), sets out the requirements and measurement techniques used to evaluate radio frequency (RF) exposure compliance of radio communication apparatus designed to be used within the vicinity of the human body.

[ANSI C95.1–1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

5.2. Evaluation Method and Limit

According to RSS-102 Issue 6 5.3.2. Table 7, RF field strength and power density limits for devices used by the general public (uncontrolled environment)

Frequency range (MHz)	Electric field (V _{RMS} /m)	Magnetic field (A _{RMS} /m)	Power density (W/m ²)	Reference period (minutes)
10-20	27.46	0.0728	2	6
20-48	58.07 / $f^{0.25}$	0.1540 / $f^{0.25}$	8.944 / $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 × 10 ⁻⁴ $f^{0.5}$	6.67 × 10 ⁻⁵ f	616000/ $f^{1.2}$

Note: f is frequency in MHz.

Frequency Band	f (MHz)	Limit of Power Density (W/m ²)
Bluetooth	2402	5.35
2.4G WLAN	2412	5.37

Note: Limit=0.02619 $f^{0.6834}$ (where f is in MHz).

The f in the limit is the frequency of the lowest Channel.



5.3. Calculation Formula

Prediction of power density at the distance of the applicable MPE limit:

S=PG/4πR²=Power density(in appropriate units, e.g W/m²)

P=power input to antenna (in appropriate units, e.g W)

G=power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R=distance to the center of radiation of the antenna(in appropriate units, e.g m)

Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

Σ of MPE ratios ≤ 1.0



5.4. Evaluation Results

Test Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	Max. ANT Gain (dBi) [G]	Distance (m) [R]	Power Density (W/m ²) [S]
Bluetooth	2.625	2±1	3	0.5	0.2	0.0045
2.4G b	17	17±1	18	-2.48	0.2	0.0709
2.4G g	15.36	15±1	16	-2.48	0.2	0.0447
2.4G n20	15.16	15±1	16	-2.48	0.2	0.0447

Summary simultaneous transmission results

Bluetooth and WiFi support Synchronization transmitter

Maximum MPE ratio Bluetooth	Maximum MPE ratio WiFi	Σ MPE ratios	Limit	Results
0.0045	0.0709	0.0754	1	PASS

Remark:

1. Output power including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF THE REPORT-----

