

Above 1GHz

Temperature:	24.6℃	Relative Humidity:	48%					
Test Voltage:	DC 3.6V							
Test Mode:	BLE(1Mbps) Mode TX 2402 MHz							
Remark:	Only worse case is reported.							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10817.500	46.08	-0.97	45.11	74.00	-28.89	peak	P
2 *	14923.000	41.43	4.02	45.45	74.00	-28.55	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12653.500	42.31	0.73	43.04	74.00	-30.96	peak	P
2 *	14795.500	40.57	3.94	44.51	74.00	-29.49	peak	P
Remark:								
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)								
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)								
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)								
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.								
5. No report for the emission which below the prescribed limit.								
6. The peak value < average limit, So only show the peak value.								



Temperature:	24.6℃		Relative Humidity:		48%																												
Test Voltage:	DC 3.6V																																
Test Mode:	BLE(1Mbps) Mode TX 2440 MHz																																
Remark:	Only worse case is reported.																																
Horizontal																																	
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBuV)</td><td>Factor (dB/m)</td><td>Level (dBuV/m)</td><td>Limit (dBuV/m)</td><td>Margin (dB)</td><td>Detector</td><td>P/F</td></tr><tr><td>1 *</td><td>9364.000</td><td>46.32</td><td>-0.59</td><td>45.73</td><td>74.00</td><td>-28.27</td><td>peak</td><td>P</td></tr><tr><td>2</td><td>12704.500</td><td>41.79</td><td>0.86</td><td>42.65</td><td>74.00</td><td>-31.35</td><td>peak</td><td>P</td></tr></table>							No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	9364.000	46.32	-0.59	45.73	74.00	-28.27	peak	P	2	12704.500	41.79	0.86	42.65	74.00	-31.35	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																									
1 *	9364.000	46.32	-0.59	45.73	74.00	-28.27	peak	P																									
2	12704.500	41.79	0.86	42.65	74.00	-31.35	peak	P																									
Vertical																																	
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBuV)</td><td>Factor (dB/m)</td><td>Level (dBuV/m)</td><td>Limit (dBuV/m)</td><td>Margin (dB)</td><td>Detector</td><td>P/F</td></tr><tr><td>1 *</td><td>9440.500</td><td>45.09</td><td>0.16</td><td>45.25</td><td>74.00</td><td>-28.75</td><td>peak</td><td>P</td></tr><tr><td>2</td><td>14821.000</td><td>39.96</td><td>4.01</td><td>43.97</td><td>74.00</td><td>-30.03</td><td>peak</td><td>P</td></tr></table>							No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	9440.500	45.09	0.16	45.25	74.00	-28.75	peak	P	2	14821.000	39.96	4.01	43.97	74.00	-30.03	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																									
1 *	9440.500	45.09	0.16	45.25	74.00	-28.75	peak	P																									
2	14821.000	39.96	4.01	43.97	74.00	-30.03	peak	P																									
Remark:																																	
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)																																	
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)																																	
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)																																	
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.																																	
5. No report for the emission which below the prescribed limit.																																	
6. The peak value < average limit, So only show the peak value.																																	



Temperature:	24.6℃	Relative Humidity:	48%																											
Test Voltage:	DC 3.6V																													
Test Mode:	BLE(1Mbps) Mode TX 2480 MHz																													
Remark:	Only worse case is reported.																													
Horizontal																														
<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr><tr><td>1 *</td><td>9491.500</td><td>44.95</td><td>0.44</td><td>45.39</td><td>74.00</td><td>-28.61</td><td>peak</td><td>P</td></tr><tr><td>2</td><td>14872.000</td><td>40.27</td><td>4.11</td><td>44.38</td><td>74.00</td><td>-29.62</td><td>peak</td><td>P</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	9491.500	44.95	0.44	45.39	74.00	-28.61	peak	P	2	14872.000	40.27	4.11	44.38	74.00	-29.62	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	9491.500	44.95	0.44	45.39	74.00	-28.61	peak	P																						
2	14872.000	40.27	4.11	44.38	74.00	-29.62	peak	P																						
Vertical																														
<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr><tr><td>1</td><td>10282.000</td><td>45.27</td><td>-1.37</td><td>43.90</td><td>74.00</td><td>-30.10</td><td>peak</td><td>P</td></tr><tr><td>2 *</td><td>14770.000</td><td>40.66</td><td>3.73</td><td>44.39</td><td>74.00</td><td>-29.61</td><td>peak</td><td>P</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	10282.000	45.27	-1.37	43.90	74.00	-30.10	peak	P	2 *	14770.000	40.66	3.73	44.39	74.00	-29.61	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	10282.000	45.27	-1.37	43.90	74.00	-30.10	peak	P																						
2 *	14770.000	40.66	3.73	44.39	74.00	-29.61	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value < average limit, So only show the peak value.																														

-----END OF THE REPORT-----

