

PRODUCT SPECIFICATION

Customer: Shenzhen Itian Technology Co., LTD

Customer part number: 131.010

Jin Zanliao No.: J30-000101-001

K C P/N: _____

Product model: 21.3*42*0.08*80P*11TS*13MM

D E S E :__(S21-Qi2-MPP coil-8.1uH-wire length 13mm)

Date: July 25,2024

Version: A.0

(Stamp of acceptance by the customer) ACCEPTANCE STAMP

Version

1. Product external version	fiction PREPARED BY	merchandiser MERCHANDISER	Project audit ENGINEER CHECKED BY	ratify APPROVED BY
	Yan Huilin			

Address: No.2 Xisha Road, Shijie Town, Dongguan Tel: 86-076986018114 Fax: 86-076986015646

Http://www.jzcoil.com Document number FilNo: KC-JZ-09-008

DONGGUAN KIMCHEN INDUSTRY INTL LIMITED


**Regulatory content
Specification**Customer
number:
CUST P/N

131.010

Gold Medal
Type:
KC DESE

21.3*42*0.08*80P*11TS*13MM

al dimensions (OVERALL DIMENSIONALITY OF PRODUCTS):



Unit (Unit): mm

A	B	C	D	E	F	G	H
20±0.5	21.3±0.5	42MAX	43+0/-1	3±1.5	13±1.5	1±0.1	2.3MAX

PS: 1.(F) is the length of the magnetic lead; 2.(H) includes the lead and does not include the release paper.

number of turns Turns	Wire diameter Wire Dia.	Winding mode sparse/dense Wdg. Type Spred/Close	direction of winding Wdg.Direction	Do they intersect? Yes/no Intersect Yes/Not	Coil positive/negative mounting Coil Positive/Anti Paste
--------------------------	----------------------------	--	---------------------------------------	--	--

fiction
PREPARED BYProject audit
ENGINEER CHECKED BY

Yan Huilin

Li Jin

Address: No.2 Xisha Road, Shijie Town, Dongguan Tel: 86-076986018114 Fax: 86-076986015646

DONGGUAN KIMCHEN INDUSTRY INTL LIMITED

Regulatory content Specification			Customer number: CUST P/N	131.010	
			Gold Medal Type: KC DESE	21.3*42*0.08*80P*11TS*13MM	
11TS	0.08*80P silk-covered wire (Silk-Covered Wire)	Closet (Close)	anticlockwise (Anticlockwise)	yes (Yes)	Anti/Paste

All materials are required to meet the qualified ROHS standards

2. Electrical characteristics (ELECTRICAL CHARACTERISTICS):

Temperature TEMPERATURE: $25 \pm 10^{\circ}\text{C}$, relative humidity RELATIVE HUMIDITY: $65 \pm 10\%$

order numb er NO.	proje ct ITE M	terminal TERMINA L	standard SPECIFICATION	test condition TEST FREQUENCY	measuring and test instruments TEST EQUIPMENTS
1	IND	S-F	Coil magnetic sheet: $8.1\mu\text{H} \pm 0.1$	100kHz/1V	HY2830
2		working temperatur e	$-20^{\circ}\text{C} \sim 95^{\circ}\text{C}$		

3. Material List (BILL OF MATERIAIS):

order numb er NO.	Name of material Material name	Description of product name Description	Material code Material Code	Vendor code Vendor code
1	wire stock	0.08*80P silk wrapping line	/	/
2	Big magnetic sheet	G43+0/-1*5.3*0.8H \pm 0.1 with holes and double L slots (small slot in the middle)	GCP-T-00189	LX

fiction PREPARED BY	Project audit ENGINEER CHECKED BY
Yan Huilin	Li Jin

Address: No.2 Xisha Road, Shijie Town, Dongguan Tel: 86-076986018114 Fax: 86-076986015646

DONGGUAN KIMCHEN INDUSTRY INTL LIMITED

Regulatory content Specification		Customer number: CUST P/N	131.010	
		Gold Medal Type: KC DESE	21.3*42*0.08*80P*11TS*13MM	
3	Small magnets	Circular hard magnet 20*1.0H no hole and no groove	GCP-T-00264	LX
4	double faced adhesive tape	41.3*0.05H (single-sided back adhesive without holes and grooves)	SMJ-T-0078	HWD
5	Golden finger tape	5mm	High temperature tape 5MM	JRM
6	glue	JS-E7202 (thickening) white glue	E7202W	HZY
7	tin bar	Lead free solder bars for environmental protection	Lead free high temperature tin bar	XC
8	double faced adhesive tape	Circular double-sided adhesive 15*0.08H with hand tear	SMJ-T-0056	HWD

fiction
PREPARED BY

Yan Huilin

Project audit
ENGINEER CHECKED BY

Li Jin

Address: No.2 Xisha Road, Shijie Town, Dongguan Tel: 86-076986018114 Fax: 86-076986015646