

RF Exposure Evaluation

Test report
On Behalf of
Zhejiang Xunshi Technology Co., Ltd.
For
Pro Cure

Model List : Pro Cure, Pro

FCC ID: 2AUE5-PROCURE

Prepared for : **Zhejiang Xunshi Technology Co., Ltd.**
4th Floor, No.2 Qihang Building, Science and Technology Park,
No.586 Xihuan Road, Shaoxing City, Zhejiang, China

Prepared By : **Shenzhen HUAK Testing Technology Co., Ltd.**
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation
Park, Fuhai Street, Bao'an District, Shenzhen City, China

Date of Test: **Mar. 17, 2020 ~ Mar. 28, 2020**

Date of Report: **Mar. 28, 2020**

1 General Description of EUT

Equipment	Pro Cure
Model Name	Pro Cure
Serial No.	Pro
Model Difference	All model's the function, software and electric circuit are the same, only model named different. Test sample model: Pro Cure
Trade Mark	N/A
FCC ID	2AUE5-PROCURE
Hardware Version:	V03.0719
Software Version:	V2.2.3.0
Operation frequency	802.11b/g/n 20: 2412~2462 MHz
Number of Channels	802.11b/g/n20: 11CH
Antenna Type	FPC Antenna
Antenna Gain	5dBi
Modulation Type	CCK/DSSS/OFDM
Power Source	AC 120V/60Hz

2 RF Exposure Compliance Requirement

2.2 Standard Requirement

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz Friis

Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$ Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G =gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

3 EUT RF Exposure

Antenna Gain: 5Bi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data				
802.11b mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	16.38	16±1	17	50.119
Middle(2437MHz)	15.35	16±1	17	50.119
Highest(2462MHz)	15.16	16±1	17	50.119

802.11g mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	17.64	17±1	18	63.096
Middle(2437MHz)	16.96	17±1	18	63.096
Highest(2462MHz)	17.38	17±1	18	63.096

802.11n(HT20)mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	17.48	17±1	18	63.096
Middle(2437MHz)	17.08	17±1	18	63.096
Highest(2462MHz)	17.04	17±1	18	63.096

Worst case: 802.11g mode Lowest channel, Using the maximum value of the test report

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
58.076	5.0	0.0365	1	PASS

Remark: The Max Conducted Peak Output Power data refer to report Report No.: HK2003190349-E
value.:2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (17.64 \cdot 3.162) / (4 \cdot 3.1416 \cdot 20^2) = 0.0365$