

FCC ID: 2AUGF-A106

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:


Antenna Type: PCB Antenna

Antenna Gain: -0.68dBi

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-5.47	0.284	-5±1	-4.0	0.398	<5	0.12340	3.00	YES
	2.441	-4.77	0.333	-5±1	-4.0	0.398	<5	0.12440	3.00	YES
	2.480	-5	0.316	-5±1	-4.0	0.398	<5	0.12539	3.00	YES
π/4-DQPSK	2.402	-4.41	0.362	-4±1	-3.0	0.501	<5	0.15535	3.00	YES
	2.441	-3.67	0.430	-4±1	-3.0	0.501	<5	0.15661	3.00	YES
	2.480	-3.91	0.406	-4±1	-3.0	0.501	<5	0.15785	3.00	YES

Conclusion:

For the max result : $0.15785 \leq 3.0$ for 1-g SAR, No SAR is required.



Signature:

Date: 2019-09-20

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China