

FCC Test Report

Report No: WD-RF-R-220014-C0

Product Name : UST Outdoor LED Projector
Model Name : MG2U
Series Model Name : MG2U-xxxxxx(x can be 0~9 or A~Z or space)
FCC ID : 2AUGVMG2U
Applicant : Elite Screens Visual & Sound Co., Ltd.
Received Date : Aug. 18, 2021
Tested Date : Sep. 22, 2021 ~ Jan. 19, 2022
Applicable Standard : 47 CFR FCC Part 15, Subpart C (Section 15.247)
KDB 558074 D01 DTS Meas. Guidance v05
ANSI C63.10 : 2013



Wendell Industrial Co., Ltd
Wendell EMC & RF Laboratory

Caution:

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment.

Please note that the measurement uncertainty are provided for informational purpose only and are not used in determining the Pass/Fail results.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Wendell Industrial Co., Ltd..

Test Report

Issued Date: January 19, 2022

Project No.: 21Q081803

Product Name	UST Outdoor LED Projector
Trade Name	MosicGO
Model Name	MG2U
Series Model Name	MG2U-xxxxxxx(x can be 0~9 or A~Z or space)
FCC ID	2AUGVMG2U
Applicant	Elite Screens Visual & Sound Co., Ltd.
Manufacturer	Elite Screens Visual & Sound Co., Ltd.
EUT Rated Voltage	AC 100 ~ 230V / 50 or 60Hz
EUT Test Voltage	AC 120V / 60Hz
EUT Supports Radios Application	WLAN 802.11a/b/g WLAN 802.11n (HT20/HT40) WLAN 802.11ac (VHT20/VHT40/VHT80) Bluetooth BR/EDR/LE
Applicable Standard	47 CFR FCC Part 15, Subpart C (Section 15.247) KDB 558074 D01 DTS Meas. Guidance v05 ANSI C63.10 : 2013
Output Power	24.7dBm
Test Result	Complied

Documented :




(Specialist / Emma Lu)

Technical Engineer :



(Deputy Section Manager / Jack Chang)

Approved :



(Project Manager / Gary Wu)

Table of Contents

Document Revision History	5
Summary of Test Result	6
1 Generation Information	7
1.1 Applicant	7
1.2 Manufacturer	7
1.3 Description of Equipment under Test	7
1.4 Test Mode Applicability And Tested Channel Detail	11
1.5 Configuration of Tested System	13
1.6 EUT Exercise Software	13
1.7 Tested System Details	14
1.8 Test Facility	15
1.9 Measurement Uncertainty	16
1.10 List of Test Equipment	17
2 Test Result	20
2.1 Antenna Requirement	20
2.1.1 Applicable Standard	20
2.1.2 Antenna Connected Construction	20
2.1.3 Antenna Gain	20
2.2 Peak Output Power Measurement	22
2.2.1 Limit	22
2.2.2 Test Setup	22
2.2.3 Test Procedure	22
2.2.4 Test Result	23
2.3 6dB Bandwidth Measurement	24
2.3.1 Limit	24
2.3.2 Test Setup	24
2.3.3 Test Procedure	24
2.3.4 Test Result	25
2.4 Power Spectral Density Measurement	28
2.4.1 Limit	28
2.4.2 Test Setup	28
2.4.3 Test Procedure	28
2.4.4 Test Result	29
2.5 Conducted Band Edges and Spurious Emission Measurement	32
2.5.1 Limit	32
2.5.2 Test Setup	32
2.5.3 Test Procedure	32
2.5.4 Test Result	33
2.6 Radiated Band Edges and Spurious Emission Measurement	42
2.6.1 Limit	42
2.6.2 Test Setup	43
2.6.3 Test Procedure	44
2.6.4 Duty Cycle	45
2.6.5 Test Result of Radiated Band Edge Measurement	45
2.6.6 Test Result of Radiated Spurious Emission Measurement	58
2.7 AC Conducted Emissions Measurement	79

2.7.1	Limit	79
2.7.2	Test Setup.....	79
2.7.3	Test Procedure.....	80
2.7.4	Test Result	81

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

Document Revision History

Report No.	Issue date	Description
WD-RF-R-220014-C0	January 19, 2022	Initial report

Summary of Test Result

Ref. Std. Clause	Test Items	Result
15.203 15.247(C)	Antenna Requirement	Pass
15.247(b)	Peak Output Power	Pass
15.247(a)(2)	6dB Bandwidth	Pass
15.247(e)	Power Spectral Density	Pass
15.247(d)	Conducted Band Edges and Conducted Spurious Emission	Pass
15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass
15.207	AC Conducted Emission	Pass

1 Generation Information

1.1 Applicant

Elite Screens Visual & Sound Co., Ltd.
3F., No. 88, Wugong Rd., Xinzhuang Dist., New Taipei City 242, Taiwan (R.O.C.)

1.2 Manufacturer

Elite Screens Visual & Sound Co., Ltd.
3F., No. 88, Wugong Rd., Xinzhuang Dist., New Taipei City 242, Taiwan (R.O.C.)

1.3 Description of Equipment under Test

Product Name	UST Outdoor LED Projector
Model No.	MG2U
Series Model Name	MG2U-xxxxxxx(x can be 0~9 or A~Z or space)
FCC ID	2AUGVMG2U
Frequency Range	802.11b/g/n-20MHz: 2412~2462MHz
Number of Channels	802.11b/g/n-20MHz: 11
Data Rate	802.11b: 1-11Mbps, 802.11g: 6-54Mbps, 802.11n: up to 72.2Mbps
Channel separation	802.11b/g/n: 5 MHz
Type of Modulation	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Information	Refer to the table “Antenna List”
EUT Supports Radios Application	WLAN 802.11a/b/g WLAN 802.11n (HT20/HT40) WLAN 802.11ac (VHT20/VHT40/VHT80) Bluetooth BR/EDR/LE
EUT Rated Voltage	AC 100 ~ 230V / 50 or 60Hz
EUT Test Voltage	AC 120V / 60Hz

Note: Series model difference is market segmentation.

The EUT uses following adapter.

Trade Name	EDAC
Model No.	EA11703F-1900
Input Power	AC 100 ~ 240V / 50 or 60Hz
Output Power	DC 19V
Power Line	Non-shielded, 1 Core, 1.2m

Antenna List

No.	Manufacturer	Model No.	Antenna Type	Peak Gain
1	Passive System Alliance	PFPCA500815IMLB3G4	PCB Antenna	2 dBi for 2.4GHz

Remark: The antenna of EUT is conforming to FCC 15.203

Channel List

802.11b/g/n HT20		802.11n HT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	--	--
02	2417	--	--
03	2422	--	--
04	2427	--	--
05	2432	--	--
06	2437	--	--
07	2442	--	--
08	2447	--	--
09	2452	--	--
10	2457	--	--
11	2462	--	--

Test Frequencies in each operating band

Frequency range over which the device operates in each operating band (Note 1)	Number of test frequencies required	Location of test frequencies inside the operating frequency range (Note 1,2)
≤ 1 MHz	1	near center
> 1 MHz and ≤ 10 MHz	2	1 near high end, 1 near low end
> 10 MHz	3	1 near high end, 1 near center, and 1 near low end

Note 1: The frequency range over which the device operates in a given operating band is the difference between the highest and lowest frequencies on which the device can be tuned within that given operating band. The frequency range can be smaller than or equal to the operating band, but cannot be greater than the operating band.

Note 2: In the third column of table 1, “near” means as close as possible to or at the center / low end / high end of the frequency range over which the device operates.

Firmware / Software Version

1	Product Name	UST Outdoor LED Projector
2	Model No.	MG2U
3	Test SW Version	Ampak RFTest_VER5.8
4	RF power setting in TEST SW	☒ RF power setting was not able to alter during testing. ☐ RF power setting was able to alter during testing. (See the following table)

Parameters of test software setting

Type of Modulation	Channel	Frequency (MHz)	Set Value
802.11b	01	2412	Default
	06	2437	Default
	11	2462	Default
802.11g	01	2412	Default
	06	2437	Default
	11	2462	Default
802.11n HT20	01	2412	Default
	06	2437	Default
	11	2462	Default

1.4 Test Mode Applicability And Tested Channel Detail

1. This device is a UST Outdoor LED Projector with a built-in Wi-Fi 、Bluetooth transceiver.
2. These tests were performed on a sample of equipment to demonstrate compliance with 47 CFR FCC Part 15, Subpart C (Section 15.247).
3. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.
4. The worst case was found when positioned on X axis for radiated emission. Following test modes were selected for the final test, and the final worst case is recorded in the report:

EUT Configure Mode	RE < 1G	RE ≥ 1G	ACM	ACP	Description
--	☒	☒	☒	☐	Transmit WIFI
--	☐	☐	☐	☒	Normal Link

Note : RE<1G: Radiated Emission below 1GHz RE≥1G: Radiated Emission above 1GHz
ACM: Antenna Port Conducted Measurement ACP: AC Power Line Conducted Emission

Following channel(s) was (were) selected for the final test as listed below:

Radiated Spurious Emission Measurement(Below 1GHz):

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
--	802.11g	1 ~ 11	06	OFDM	6

Radiated Spurious Emission Measurement(Above 1GHz):

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
--	802.11b	1 ~ 11	01, 06, 11	DSSS	1
--	802.11g	1 ~ 11	01, 06, 11	OFDM	6
--	802.11n HT20	1 ~ 11	01, 06, 11	OFDM	6.5

Radiated Band Edge Emission Measurement(Above 1GHz):

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
--	802.11b	1 ~ 11	01, 11	DSSS	1
--	802.11g	1 ~ 11	01, 11	OFDM	6
--	802.11n HT20	1 ~ 11	01, 11	OFDM	6.5

Peak Output Power, 6dB Bandwidth, Power Spectral Density, Conducted Spurious Emission:

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
--	802.11b	1 ~ 11	01, 06, 11	DSSS	1
--	802.11g	1 ~ 11	01, 06, 11	OFDM	6
--	802.11n HT20	1 ~ 11	01, 06, 11	OFDM	6.5

Conducted Band Edges:


EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
--	802.11b	1 ~ 11	01, 11	DSSS	1
--	802.11g	1 ~ 11	01, 11	OFDM	6
--	802.11n HT20	1 ~ 11	01, 11	OFDM	6.5

AC Conducted Emission:


EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
--	802.11g	1 ~ 11	06	OFDM	6

1.5 Configuration of Tested System

Radiation



AC Conduction



1.6 EUT Exercise Software

1. Setup the EUT as shown in Section 1.5
2. Execute software "Ampak RFTest_VER5.8".
3. Configure the test mode, the test channel, and the data rate.
4. Press "OK" to start the continuous transmit.
5. Verify that the EUT works properly.

1.7 Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

No.	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook PC	acer	N16Q1	NXVD4TA023742254707600	Non-shielded, 1 Core, 0.8m
2	Notebook PC	acer	N17W3	NXVJ7TA00302301D496600	Non-shielded, 1 Core, 1.6m
3	Adapter	EDAC	EA11703F-1900	N/A	Non-shielded, 1 Core, 1.2m
4	USB Dongle	Tianzun Technology Co., Ltd	P3L	N/A	N/A
5	Cement Resistor	N/A	20W2ΩJ	N/A	N/A
6	USB Mouse	Lemel	M83	201707K31002387	Non-shielded, Non-Core, 1.5m
7	Earphone & Microphone	WD	EarMic-01	N/A	Non-shielded, Non-Core, 1m
8	Remote Control	Bontech Electronics Co., Ltd	90-578100B2702	N/A	N/A
9	Remote Control	Tianzun Technology Co., Ltd	P3L	N/A	N/A
10	TRS 3.5 Lord	Elite Screens Visual & Sound Co., Ltd.	TRS35	N/A	N/A
11	Micro SD Card	SanDisk	UHS-I 16GB	N/A	N/A

No.	Signal Cable Type	Signal cable Description
A	HDMI Cable	Non-shielded, Non-Core, 1.5m
B	USB Cable	Shielded, Non-Core, 1.2m
C	HDMI Cable	Non-shielded, Non-Core, 1.5m
D	USB Cable	Shielded, Non-Core, 0.8m
E	Audio Cable	Non-shielded, Non-Core, 3.4m
--	AC Power Cable	Non-shielded, Non-Core, 1.5m

1.8 Test Facility

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	20~25
Humidity (% RH)	25-75	45~55
Barometric pressure (mbar)	860-1060	990~1020

Description: Accredited by TAF
Accredited Number: 2965

Issued by: Wendell Industrial Co., Ltd

Lab Address: 6F/6F-1, No.188, Baoqiao Rd., Xindian Dist.,
New Taipei City 23145, Taiwan R.O.C

Test Lab: Wendell EMC & RF Laboratory

Test Location: No. 119, Wugong 3rd Rd., Wugu Dist.,
New Taipei City 248, Taiwan (R.O.C.)

Designation Number: TW0025

Test Firm Registration Number: 665221

1.9 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence (level based on a coverage factor K=2)

Measurement Project	Condition	Expended Uncertainty
AC Conducted Emission	0.150 ~ 30 MHz	2.64 dB
Radiated Emission	0.009 ~ 30 MHz	± 4.2 dB
	30 ~ 1000 MHz	± 3.9 dB
	1000 ~ 18000 MHz	± 4.1 dB
	18000 ~ 40000 MHz	± 3.9 dB
RF Power, Conducted	Conducted Measuring	± 0.5 dB
Occupied Bandwidth	Conducted Measuring	± 2.4 %
Power Density	Conducted Measuring	± 1.7 dB
Duty Cycle and Dwell Time	Conducted Measuring	± 1.3 %
Conducted Unwanted Emission Strength	Conducted Measuring	± 1.8 dB
DC Power Supply	--	± 3.2 %
Temperature	--	± 1.1 °C
Humidity	--	± 3.4 %

Note: Please note that the measurement uncertainty are provided for informational purpose only and are not used in determining the Pass/Fail results.

1.10 List of Test Equipment

For Conducted measurements / W08-Conducted Measurement

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
✓	Spectrum analyzer	Keysight	N9010A	SG50420005	2021/08/09	2022/08/08
✓	Wideband Peak Power Meter	Anritsu	ML2495A	1733007	2021/09/07	2022/09/06
✓	Pulse Power Sensor + Precision Adaptor	Anritsu	MA2411B	1726022	2021/09/07	2022/09/06
	Temperature Chamber	TAICHY	MHK-225LK	1061121	2021/4/27	2022/4/26
	Wireless Connectivity Tester	R&S	CMW270	101307	2021/5/24	2022/5/23
✓	Attenuator	MVE	MVE2211-10	CT-9-056	2021/08/18	2022/08/17
	Attenuator	MVE	MVE2211-20	CT-9-057	2021/08/18	2022/08/17
	Attenuator	MVE	MVE2211-30	CT-9-058	2021/08/18	2022/08/17
	Power Divider	MVE	MVE8546	170826003	2021/08/18	2022/08/17
	Power Splitter	MVE	MVE8547	170302047	2021/08/18	2022/08/17
	DC Power Supply	GW INSTEK	GPC-3060D	GER817636	2021/08/19	2022/08/18

Remark:

1. All equipments are calibrated every one year.
2. The test instruments marked with “✓” are used to measure the final test results.

For AC Conduction measurements / W08-CE

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
✓	EMI Test Receiver	R&S	ESR3	102309	2021/6/8	2022/6/7
✓	2-Line V-Network LISN	R&S	ENV216	101185	2021/6/11	2022/6/10
✓	LISN	SCHWARZBECK	NSLK 8127RC	05028	2021/6/11	2022/6/10
✓	Transient Limiter	EM Electronics Corporation	EM-7600	857	2021/6/10	2022/6/9
✓	50ohm Cable	EMCI	EMCCFD300-BM-BM- 5000	170612	2021/6/10	2022/6/9
✓	50 ohm terminal impedance	HUBER+SUHNER	50 ohm terminal impedance	CT-1-109-1	2021/6/11	2022/6/10

Remark:

1. All equipments are calibrated every one year.
2. The test instruments marked with “✓” are used to measure the final test results.
3. Test Software version: FARAD EZ-EMC Ver.EMC-CON 3A1

For Radiated measurements / W08-996-2

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
✓	EMI Receiver	Keysight	N9038A	MY51210173	2021/08/20	2022/08/19
✓	Spectrum Analyzer	Keysight	N9010A	MY52220228	2021/08/24	2022/08/23
✓	Loop Antenna	EMCI	LPA600	277	2021/09/02	2022/09/01
✓	TRILOG super broad Antenna	Schwarzbeck	VULB 9168	VULB 9168-700 & 1421	2021/08/11	2022/08/10
✓	Horn Antenna	Schwarzbeck	BBHA 9120D	01767	2021/08/11	2022/08/10
✓	Horn Antenna	Schwarzbeck	BBHA 9170	703	2021/12/17	2022/12/16
✓	Pre-Amplifier	EM	EMC330	060774	2021/08/24	2022/08/23
✓	Pre-Amplifier	EMEC	EM01G18G	060648	2021/08/24	2022/08/23
✓	Pre-Amplifier	JPT	JPA0118-55-303K	1910001800055003	2021/08/25	2022/08/24
✓	Pre-Amplifier	EMCI	EMC184045SE	980515	2021/08/24	2022/08/23
✓	Cable	EMEC	EM-CB400	105060103	2021/08/24	2022/08/23
✓	Cable	EMEC	EM-CB400	105060102	2021/08/24	2022/08/23
✓	Cable	EMEC	EM-CB400	105060101	2021/08/24	2022/08/23
✓	RF Cable	HUBER+SUHNER	SF102	MY2752/2	2021/08/24	2022/08/23
✓	Cable	MVE	280280.LL266.1200	B60028C	2021/08/24	2022/08/23
✓	RF Cable	HUBER+SUHNER	SF102	MY2751/2	2021/08/24	2022/08/23
✓	Cable	EMCI	EMC102-KM-KM-600	190646	2021/08/24	2022/08/23
✓	RF Filter	EMEC	BRF-2400-2500	002	2021/08/26	2022/08/25
	RF Filter	EMEC	BRF-5150-5350	104	2021/08/26	2022/08/25
	RF Filter	EMEC	BRF-5470-5725	092	2021/08/26	2022/08/25
	RF Filter	EMEC	BRF-5725-5875	091	2021/08/26	2022/08/25
✓	RF Filter	EMEC	HPF-2800	002	2021/08/26	2022/08/25
	RF Filter	EMEC	HPF-5850	059	2021/08/26	2022/08/25
	SMA Notch Filter	MVE	MFN-902.928.S1	190604001	2021/09/02	2022/09/01

Remark:

1. All equipments are calibrated every one year.
2. The test instruments marked with "✓" are used to measure the final test results.
3. Test Software version: FARAD EZ-EMC Ver.WD-03A1-1

2 Test Result

2.1 Antenna Requirement

2.1.1 Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

An intentional radiator shall be designed to ensure that no antenna other than as furnished by the responsible party shall be used with the device. If transmitting antennas of directional gain greater than 6dBi are using the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi, for compliance to FCC 47CFR 15.247 (c) requirements.

2.1.2 Antenna Connected Construction

Non-standard antenna connector is used.

2.1.3 Antenna Gain

No.	Manufacturer	Model No.	Antenna Type	Peak Gain
1	Passive System Alliance	PFPCA500815IMLB3G4	PCB Antenna	2 dBi for 2.4GHz

Description of the operating transmit modes :

- * 802.11b : Only one Antenna mode, this port is Ant-1
- * 802.11g : Only one Antenna mode, this port is Ant-1
- * 802.11n_HT20 : Only one Antenna mode, this port is Ant-1

Directional gain calculation & Conducted Output Power limit after correction :

- * 802.11b : Gain = 2 dBi < 6dBi ;
- * 802.11g : Gain = 2 dBi < 6dBi ;
- * 802.11n_HT20 : Gain = 2 dBi < 6dBi ;

Directional gain calculation & Power Spectral Density limit after correction :

- * 802.11b : Gain = 2 dBi < 6dBi ;
- * 802.11g : Gain = 2 dBi < 6dBi ;


* 802.11n_HT20 : Gain = 2 dBi < 6dBi ;

2.2 Peak Output Power Measurement

2.2.1 Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 1W. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

2.2.2 Test Setup



2.2.3 Test Procedure

1. Reference ANSI C63.10 : 2013 chapter 11.9.1.3
2. Enable the EUT transmit continuously.
3. Let EUT be connected to the power meter, and record the max. reading.
4. Measurement using a gated RF average power meter, since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

2.2.4 Test Result

802.11b

Frequency (MHz)	Peak power (dBm)			Limit (dBm)	Result
	Chain A	Chain B	Total		
2412	19.14	--	--	≤ 30	Pass
2437	19.68	--	--	≤ 30	Pass
2462	19.49	--	--	≤ 30	Pass

Remark:

1. Peak Power = Reading value on power meter + cable loss
2. $10 \log(X/\text{mW}) = \text{dBm}$, $X=1$ watt (Limit)
1 watt = 30 dBm

802.11g

Frequency (MHz)	Peak power (dBm)			Limit (dBm)	Result
	Chain A	Chain B	Total		
2412	23.88	--	--	≤ 30	Pass
2437	24.70	--	--	≤ 30	Pass
2462	24.55	--	--	≤ 30	Pass

Remark:

1. Peak Power = Reading value on power meter + cable loss
2. $10 \log(X/\text{mW}) = \text{dBm}$, $X=1$ watt (Limit)
1 watt = 30 dBm

802.11n HT20

Frequency (MHz)	Peak power (dBm)			Limit (dBm)	Result
	Chain A	Chain B	Total		
2412	23.16	--	--	≤ 30	Pass
2437	23.66	--	--	≤ 30	Pass
2462	23.56	--	--	≤ 30	Pass

Remark:

1. Peak Power = Reading value on power meter + cable loss
2. $10 \log(X/\text{mW}) = \text{dBm}$, $X=1$ watt (Limit)
1 watt = 30 dBm

2.3 6dB Bandwidth Measurement

2.3.1 Limit

The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2 Test Setup



2.3.3 Test Procedure

1. Reference ANSI C63.10 : 2013 chapter 11.8.2
2. Enable the EUT transmit continuously.
3. Spectrum analyzer set:
 - a) RBW = 100 kHz
 - b) VBW $\geq$ 3 RBW
 - c) Detector = peak
 - d) Sweep time = auto couple
 - e) Trace mode = max hold.

2.3.4 Test Result

802.11b

Frequency (MHz)	6dB BW (kHz)		Limit (kHz)	Result
	Chain A	Chain B		
2412	9039	--	≥ 500	Pass
2437	9016	--	≥ 500	Pass
2462	9062	--	≥ 500	Pass




802.11g

Frequency (MHz)	6dB BW (kHz)		Limit (kHz)	Result
	Chain A	Chain B		
2412	16290	--	≥ 500	Pass
2437	16080	--	≥ 500	Pass
2462	15530	--	≥ 500	Pass



802.11n HT20

Frequency (MHz)	6dB BW (kHz)		Limit (kHz)	Result
	Chain A	Chain B		
2412	17100	--	≥ 500	Pass
2437	16920	--	≥ 500	Pass
2462	16280	--	≥ 500	Pass



2.4 Power Spectral Density Measurement

2.4.1 Limit

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

2.4.2 Test Setup



2.4.3 Test Procedure


1. Reference ANSI C63.10 : 2013 chapter 11.10.2
2. Enable the EUT transmit continuously.
3. Spectrum analyzer set:
 - a) RBW = 3 kHz ~ 100 kHz
 - b) VBW $\geq$ 3 RBW
 - c) Span = 1.5 times DTS Channel 6dB Bandwidth
 - d) Detector = peak
 - e) Sweep time = auto couple
 - f) Trace mode = max hold.

2.4.4 Test Result

802.11b

Frequency (MHz)	Power Spectral Density (dBm)			Limit (dBm)	Result
	Chain A	Chain B	Total		
2412	-4.709	--	--	≤ 8	Pass
2437	-3.934	--	--	≤ 8	Pass
2462	-4.176	--	--	≤ 8	Pass


Remark: PSD = Reading value on spectrum analyzer + cable loss



802.11g

Frequency (MHz)	Power Spectral Density (dBm)			Limit (dBm)	Result
	Chain A	Chain B	Total		
2412	-7.181	--	--	≤ 8	Pass
2437	-6.884	--	--	≤ 8	Pass
2462	-6.396	--	--	≤ 8	Pass


Remark: PSD = Reading value on spectrum analyzer + cable loss



802.11n HT20

Frequency (MHz)	Power Spectral Density (dBm)			Limit (dBm)	Result
	Chain A	Chain B	Total		
2412	-8.284	--	--	≤ 8	Pass
2437	-8.440	--	--	≤ 8	Pass
2462	-6.699	--	--	≤ 8	Pass

Remark: PSD = Reading value on spectrum analyzer + cable loss



2.5 Conducted Band Edges and Spurious Emission Measurement

2.5.1 Limit

In any 100 KHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in must also comply with the radiated emission limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB


2.5.2 Test Setup




2.5.3 Test Procedure

1. Reference ANSI C63.10 : 2013 chapter 6.10
2. Enable the EUT transmit continuously.
3. Spectrum analyzer set :
 - a) RBW = 100 kHz
 - b) VBW $\geq$ 3 RBW
 - c) Detector = peak
 - d) Sweep time = auto couple
 - e) Trace mode = max hold.

2.5.4 Test Result






WLAN 802.11b (2462MHz)


Reference Level





Spurious Emission




Band Edge
















2.6 Radiated Band Edges and Spurious Emission Measurement

2.6.1 Limit


Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 – 0.490	$2400/F(\text{kHz})$	300
0.490 – 1.705	$24000/F(\text{kHz})$	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Remarks:


1. RF Voltage (dBuV) = $20 \log \text{RF Voltage}(\mu\text{V})$
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

2.6.2 Test Setup


Below 30MHz



30MHz~1GHz



Above 1GHz



2.6.3 Test Procedure

The EUT was setup according to ANSI C63.10 : 2013 chapter 6.4, 6.5, 6.6 and tested according test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

For Radiated emission below 30MHz

- (1) The EUT was placed on the top of a rotating table 0.8 meters above the ground in a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- (3) Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- (4) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- (5) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

For Radiated emission Above 30MHz

- (1) The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for the test. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The EUT was set 3 meters away from the interference-receiving antenna, the height of the antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength.
- (3) Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- (4) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- (5) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- (6) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets the average limit, measurement with the average detector is unnecessary.

2.6.4 Duty Cycle


Mode	Frequency (MHz)	on time (ms)	on+off time (ms)	Duty cycle	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11b	2412	4.640	4.640	1.000	0.000	0.010
802.11g	2412	1.405	1.440	0.976	0.107	0.712
802.11n HT20	2412	1.314	1.350	0.973	0.117	0.761

2.6.5 Test Result of Radiated Band Edge Measurement

The following tables for radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X axis) were recorded in this report.

Test Frequency	
RF	802.11b / 802.11g / 802.11n HT20
Tx	CH01 (2412MHz) CH11 (2462MHz)

Test Mode :	Transmit(802.11b)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.760	56.63	-6.70	49.93	74.00	-24.07	peak
2	2390.000	56.31	-6.69	49.62	74.00	-24.38	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11b)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

120.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2376.000	56.24	-6.72	49.52	74.00	-24.48	peak
2	2390.000	54.46	-6.69	47.77	74.00	-26.23	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11b)	Test Date :	2021/10/07
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %

120.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	57.44	-6.61	50.83	74.00	-23.17	peak
2	2486.250	59.15	-6.60	52.55	74.00	-21.45	peak
3	2486.250	47.37	-6.60	40.77	54.00	-13.23	AVG

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11b)	Test Date :	2021/10/07
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

120.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	55.52	-6.61	48.91	74.00	-25.09	peak
2	2484.350	56.17	-6.61	49.56	74.00	-24.44	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %

120.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.980	72.66	-6.70	65.96	74.00	-8.04	peak
2	2388.980	54.03	-6.70	47.33	54.00	-6.67	AVG
3	2390.000	73.04	-6.69	66.35	74.00	-7.65	peak
4	2390.000	55.37	-6.69	48.68	54.00	-5.32	AVG

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

120.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.980	66.13	-6.70	59.43	74.00	-14.57	peak
2	2388.980	48.86	-6.70	42.16	54.00	-11.84	AVG
3	2390.000	68.13	-6.69	61.44	74.00	-12.56	peak
4	2390.000	50.28	-6.69	43.59	54.00	-10.41	AVG

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/07
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	71.53	-6.61	64.92	74.00	-9.08	peak
2	2483.500	54.96	-6.61	48.35	54.00	-5.65	AVG
3	2484.650	74.75	-6.61	68.14	74.00	-5.86	peak
4	2484.650	53.71	-6.61	47.10	54.00	-6.90	AVG

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/07
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	67.27	-6.61	60.66	74.00	-13.34	peak
2	2483.500	51.65	-6.61	45.04	54.00	-8.96	AVG
3	2484.900	69.61	-6.61	63.00	74.00	-11.00	peak
4	2484.900	52.16	-6.61	45.55	54.00	-8.45	AVG

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11n HT20)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %

120.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.650	76.17	-6.70	69.47	74.00	-4.53	peak
2	2388.650	54.36	-6.70	47.66	54.00	-6.34	AVG
3	2390.000	75.52	-6.69	68.83	74.00	-5.17	peak
4	2390.000	58.39	-6.69	51.70	54.00	-2.30	AVG

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11n HT20)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

120.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.770	67.97	-6.70	61.27	74.00	-12.73	peak
2	2387.770	48.14	-6.70	41.44	54.00	-12.56	AVG
3	2390.000	69.95	-6.69	63.26	74.00	-10.74	peak
4	2390.000	51.35	-6.69	44.66	54.00	-9.34	AVG

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11n HT20)	Test Date :	2021/10/07
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	75.11	-6.61	68.50	74.00	-5.50	peak
2	2483.500	55.42	-6.61	48.81	54.00	-5.19	AVG
3	2484.000	79.21	-6.61	72.60	74.00	-1.40	peak
4	2484.000	56.76	-6.61	50.15	54.00	-3.85	AVG

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11n HT20)	Test Date :	2021/10/07
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

120.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	69.05	-6.61	62.44	74.00	-11.56	peak
2	2483.500	55.56	-6.61	48.95	54.00	-5.05	AVG
3	2484.700	69.33	-6.61	62.72	74.00	-11.28	peak
4	2484.700	50.46	-6.61	43.85	54.00	-10.15	AVG

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit


2.6.6 Test Result of Radiated Spurious Emission Measurement

- (1) The radiation measurement frequency is 9kHz ~ 30MHz. The interference value of this frequency range is less than the limit value of 20 dB. It is considered that the background noise value is not recorded.
- (2) The following table shows the radiation measurement frequency from 30MHz to 26.5GHz, pre-scanning in the X, Y and Z axes. The worst case (X-axis) is documented in this report.

Test Frequency	
RF	802.11b / 802.11g / 802.11n HT20
Tx	CH01 (2412MHz) CH06 (2437MHz) CH11 (2462MHz)

Above 1GHz Data

Test Mode :	Transmit(802.11b)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	98.97	-30.66	68.31	74.00	-5.69	peak
2	1400.000	64.21	-30.66	33.55	54.00	-20.45	AVG
3	1800.000	91.79	-32.08	59.71	74.00	-14.29	peak
4	1800.000	63.77	-32.08	31.69	54.00	-22.31	AVG
5	4200.000	78.70	-22.66	56.04	74.00	-17.96	peak
6	4200.000	53.78	-22.66	31.12	54.00	-22.88	AVG
7	4824.000	60.27	-20.64	39.63	74.00	-34.37	peak
8	7236.000	66.70	-14.88	51.82	74.00	-22.18	peak
9	9648.000	57.43	-10.91	46.52	74.00	-27.48	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11b)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	101.47	-30.66	70.81	74.00	-3.19	peak
2	1400.000	66.99	-30.66	36.33	54.00	-17.67	AVG
3	1798.000	92.58	-32.09	60.49	74.00	-13.51	peak
4	1798.000	60.63	-32.09	28.54	54.00	-25.46	AVG
5	4200.000	75.48	-22.66	52.82	74.00	-21.18	peak
6	4200.000	52.17	-22.66	29.51	54.00	-24.49	AVG
7	4824.000	60.14	-20.64	39.50	74.00	-34.50	peak
8	7236.000	63.87	-14.88	48.99	74.00	-25.01	peak
9	9648.000	57.77	-10.91	46.86	74.00	-27.14	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11b)	Test Date :	2021/10/04
Test Channel :	CH06(2437MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	99.16	-30.66	68.50	74.00	-5.50	peak
2	1400.000	63.87	-30.66	33.21	54.00	-20.79	AVG
3	1800.000	91.47	-32.08	59.39	74.00	-14.61	peak
4	1800.000	63.65	-32.08	31.57	54.00	-22.43	AVG
5	4874.000	60.78	-20.72	40.06	74.00	-33.94	peak
6	7311.000	66.06	-15.01	51.05	74.00	-22.95	peak
7	9748.000	58.26	-10.73	47.53	74.00	-26.47	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11b)	Test Date :	2021/10/04
Test Channel :	CH06(2437MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	101.54	-30.66	70.88	74.00	-3.12	peak
2	1400.000	66.85	-30.66	36.19	54.00	-17.81	AVG
3	1800.000	91.85	-32.08	59.77	74.00	-14.23	peak
4	1800.000	62.55	-32.08	30.47	54.00	-23.53	AVG
5	4874.000	59.91	-20.72	39.19	74.00	-34.81	peak
6	7311.000	62.53	-15.01	47.52	74.00	-26.48	peak
7	9748.000	57.12	-10.73	46.39	74.00	-27.61	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11b)	Test Date :	2021/10/04
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	98.71	-30.66	68.05	74.00	-5.95	peak
2	1400.000	64.74	-30.66	34.08	54.00	-19.92	AVG
3	1800.000	92.11	-32.08	60.03	74.00	-13.97	peak
4	1800.000	63.63	-32.08	31.55	54.00	-22.45	AVG
5	4924.000	59.82	-20.74	39.08	74.00	-34.92	peak
6	7386.000	65.48	-14.70	50.78	74.00	-23.22	peak
7	9848.000	58.50	-10.63	47.87	74.00	-26.13	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11b)	Test Date :	2021/10/04
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	101.75	-30.66	71.09	74.00	-2.91	peak
2	1400.000	66.81	-30.66	36.15	54.00	-17.85	AVG
3	1800.000	92.88	-32.08	60.80	74.00	-13.20	peak
4	1800.000	60.53	-32.08	28.45	54.00	-25.55	AVG
5	4924.000	59.95	-20.74	39.21	74.00	-34.79	peak
6	7386.000	60.35	-14.70	45.65	74.00	-28.35	peak
7	9848.000	56.96	-10.63	46.33	74.00	-27.67	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	98.48	-30.66	67.82	74.00	-6.18	peak
2	1400.000	64.20	-30.66	33.54	54.00	-20.46	AVG
3	1800.000	91.63	-32.08	59.55	74.00	-14.45	peak
4	1800.000	63.57	-32.08	31.49	54.00	-22.51	AVG
5	4824.000	60.33	-20.64	39.69	74.00	-34.31	peak
6	7236.000	69.32	-14.88	54.44	74.00	-19.56	peak
7	7236.000	55.22	-14.88	40.34	54.00	-13.66	AVG
8	9648.000	57.64	-10.91	46.73	74.00	-27.27	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	102.25	-30.66	71.59	74.00	-2.41	peak
2	1400.000	65.88	-30.66	35.22	54.00	-18.78	AVG
3	1800.000	92.95	-32.08	60.87	74.00	-13.13	peak
4	1800.000	61.59	-32.08	29.51	54.00	-24.49	AVG
5	4824.000	60.30	-20.64	39.66	74.00	-34.34	peak
6	7236.000	65.94	-14.88	51.06	74.00	-22.94	peak
7	9648.000	57.53	-10.91	46.62	74.00	-27.38	peak

Remark :

- Correction Factor = Antenna factor + Cable loss – Amplifier gain
- Result Value = Reading Level + Correct Factor
- Margin Level = Result Value – Limit Value
- The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/04
Test Channel :	CH06(2437MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	98.43	-30.66	67.77	74.00	-6.23	peak
2	1400.000	63.64	-30.66	32.98	54.00	-21.02	AVG
3	1800.000	92.44	-32.08	60.36	74.00	-13.64	peak
4	1800.000	63.15	-32.08	31.07	54.00	-22.93	AVG
5	4874.000	59.57	-20.72	38.85	74.00	-35.15	peak
6	7311.000	68.59	-15.01	53.58	74.00	-20.42	peak
7	7311.000	55.90	-15.01	40.89	54.00	-13.11	AVG
8	9748.000	57.10	-10.73	46.37	74.00	-27.63	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/04
Test Channel :	CH06(2437MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	101.66	-30.66	71.00	74.00	-3.00	peak
2	1400.000	63.84	-30.66	33.18	54.00	-20.82	AVG
3	1800.000	91.63	-32.08	59.55	74.00	-14.45	peak
4	1800.000	61.85	-32.08	29.77	54.00	-24.23	AVG
5	4874.000	59.66	-20.72	38.94	74.00	-35.06	peak
6	7311.000	61.79	-15.01	46.78	74.00	-27.22	peak
7	9748.000	56.71	-10.73	45.98	74.00	-28.02	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/04
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	98.74	-30.66	68.08	74.00	-5.92	peak
2	1400.000	63.94	-30.66	33.28	54.00	-20.72	AVG
3	1800.000	91.78	-32.08	59.70	74.00	-14.30	peak
4	1800.000	63.25	-32.08	31.17	54.00	-22.83	AVG
5	4924.000	61.86	-20.74	41.12	74.00	-32.88	peak
6	7386.000	63.87	-14.70	49.17	74.00	-24.83	peak
7	9848.000	57.85	-10.63	47.22	74.00	-26.78	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/04
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	102.07	-30.66	71.41	74.00	-2.59	peak
2	1400.000	66.88	-30.66	36.22	54.00	-17.78	AVG
3	1800.000	92.36	-32.08	60.28	74.00	-13.72	peak
4	1800.000	61.82	-32.08	29.74	54.00	-24.26	AVG
5	4924.000	60.27	-20.74	39.53	74.00	-34.47	peak
6	7386.000	61.03	-14.70	46.33	74.00	-27.67	peak
7	9848.000	57.47	-10.63	46.84	74.00	-27.16	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11n HT20)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	98.80	-30.66	68.14	74.00	-5.86	peak
2	1400.000	62.30	-30.66	31.64	54.00	-22.36	AVG
3	1800.000	91.73	-32.08	59.65	74.00	-14.35	peak
4	1800.000	65.49	-32.08	33.41	54.00	-20.59	AVG
5	4824.000	60.53	-20.64	39.89	74.00	-34.11	peak
6	7236.000	68.48	-14.88	53.60	74.00	-20.40	peak
7	7236.000	55.43	-14.88	40.55	54.00	-13.45	AVG
8	9648.000	57.49	-10.91	46.58	74.00	-27.42	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11n HT20)	Test Date :	2021/10/04
Test Channel :	CH01(2412MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	102.18	-30.66	71.52	74.00	-2.48	peak
2	1400.000	66.99	-30.66	36.33	54.00	-17.67	AVG
3	1800.000	92.88	-32.08	60.80	74.00	-13.20	peak
4	1800.000	60.29	-32.08	28.21	54.00	-25.79	AVG
5	4824.000	60.49	-20.64	39.85	74.00	-34.15	peak
6	7236.000	64.32	-14.88	49.44	74.00	-24.56	peak
7	9648.000	58.17	-10.91	47.26	74.00	-26.74	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11n HT20)	Test Date :	2021/10/04
Test Channel :	CH06(2437MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	98.25	-30.66	67.59	74.00	-6.41	peak
2	1400.000	64.13	-30.66	33.47	54.00	-20.53	AVG
3	1800.000	91.16	-32.08	59.08	74.00	-14.92	peak
4	1800.000	62.95	-32.08	30.87	54.00	-23.13	AVG
5	4874.000	59.52	-20.72	38.80	74.00	-35.20	peak
6	7311.000	65.91	-15.01	50.90	74.00	-23.10	peak
7	9748.000	56.83	-10.73	46.10	74.00	-27.90	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11n HT20)	Test Date :	2021/10/04
Test Channel :	CH06(2437MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	101.39	-30.66	70.73	74.00	-3.27	peak
2	1400.000	66.83	-30.66	36.17	54.00	-17.83	AVG
3	1800.000	92.35	-32.08	60.27	74.00	-13.73	peak
4	1800.000	61.42	-32.08	29.34	54.00	-24.66	AVG
5	4874.000	59.40	-20.72	38.68	74.00	-35.32	peak
6	7311.000	61.25	-15.01	46.24	74.00	-27.76	peak
7	9748.000	56.88	-10.73	46.15	74.00	-27.85	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11n HT20)	Test Date :	2021/10/04
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	98.42	-30.66	67.76	74.00	-6.24	peak
2	1400.000	64.33	-30.66	33.67	54.00	-20.33	AVG
3	1800.000	91.56	-32.08	59.48	74.00	-14.52	peak
4	1800.000	63.82	-32.08	31.74	54.00	-22.26	AVG
5	4924.000	59.80	-20.74	39.06	74.00	-34.94	peak
6	7386.000	65.68	-14.70	50.98	74.00	-23.02	peak
7	9848.000	58.64	-10.63	48.01	74.00	-25.99	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11n HT20)	Test Date :	2021/10/04
Test Channel :	CH11(2462MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1400.000	71.61	0.00	71.61	74.00	-2.39	peak
2	1400.000	36.22	0.00	36.22	54.00	-17.78	AVG
3	1800.000	60.01	0.00	60.01	74.00	-13.99	peak
4	1800.000	28.94	0.00	28.94	54.00	-25.06	AVG
5	4924.000	38.50	0.00	38.50	74.00	-35.50	peak
6	7386.000	44.72	0.00	44.72	74.00	-29.28	peak
7	9848.000	46.22	0.00	46.22	74.00	-27.78	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Below 1GHz Data

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/05
Test Channel :	CH06(2437MHz)	Temperature :	24 °C
Polarization :	Horizontal	Relative Humidity :	49 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	148.3400	52.35	-11.59	40.76	43.50	-2.74	QP
2	296.7500	52.45	-10.88	41.57	46.00	-4.43	QP
3	359.8000	48.08	-9.16	38.92	46.00	-7.08	QP
4	445.1600	47.04	-6.62	40.42	46.00	-5.58	QP
5	593.5700	39.74	-3.34	36.40	46.00	-9.60	QP
6	741.9800	43.84	-0.59	43.25	46.00	-2.75	QP

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Transmit(802.11g)	Test Date :	2021/10/05
Test Channel :	CH06(2437MHz)	Temperature :	24 °C
Polarization :	Vertical	Relative Humidity :	49 %

100.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	148.3400	42.37	-11.59	30.78	43.50	-12.72	QP
2	359.8000	42.26	-9.16	33.10	46.00	-12.90	QP
3	445.1600	45.69	-6.62	39.07	46.00	-6.93	QP
4	593.5700	42.76	-3.34	39.42	46.00	-6.58	QP
5	741.9800	44.22	-0.59	43.63	46.00	-2.37	QP
6	890.3900	35.34	1.00	36.34	46.00	-9.66	QP

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit


2.7 AC Conducted Emissions Measurement

2.7.1 Limit

Frequency (MHz)	FCC Part 15 Subpart C Paragraph 15.207 (dBμV) Limit	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.50 to 5.0	56	46
5.0 to 30.0	60	50

*Decreases with the logarithm of the frequency

2.7.2 Test Setup




2.7.3 Test Procedure

1. Reference ANSI C63.10 : 2013 chapter 6.2
2. The EUT was placed 0.8 meter height wooden table from the horizontal ground plane with EUT being connected to power source through a line impedance stabilization network (LISN). The LISN at least be 80 cm from nearest chassis of EUT.
3. The line impedance stabilization network (LISN) provides 50 ohm/50uH of coupling impedance for the measuring instrument. All other support equipments powered from additional LISN(s).
4. Interrelating cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle. All I/O cables were positioned to simulate typical usage.
5. All I/O cables that are not connected to a peripheral shall be bundle in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. The EMI test receiver connected to LISN powering the EUT. The actual test configuration, please refer to EUT test photos.
7. The receiver scanned from 150kHz to 30MHz for emissions in each of test modes. A scan was taken on both power lines, Line and Neutral, recording at least six highest emissions.
8. The EUT and cable configuration of the above highest emission levels were recorded. The test data of the worst case was recorded.

2.7.4 Test Result

Test Voltage :	120Vac, 60Hz	Frequency Range:	0.15-30 MHz
Test Mode :	Normal Link	6dB Bandwidth :	9 kHz
Test Date :	2021/12/29	Phase :	L
Temperature :	26°C	Humidity :	38 %




No.	Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measurement (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.288	29.01	9.81	38.82	60.58	-21.76	QP
2	0.288	16.02	9.81	25.83	50.58	-24.75	AVG
3	0.3288	35.34	9.81	45.15	59.48	-14.33	QP
4	0.3288	28.08	9.81	37.89	49.48	-11.59	AVG
5	0.4303	31.13	9.81	40.94	57.25	-16.31	QP
6	0.4303	20.44	9.81	30.25	47.25	-17	AVG
7	0.6475	29	9.82	38.82	56	-17.18	QP
8	0.6475	15.68	9.82	25.5	46	-20.5	AVG
9	2.0097	27.5	9.89	37.39	56	-18.61	QP
10	2.0097	9.55	9.89	19.44	46	-26.56	AVG
11	10.1289	30.04	10.04	40.08	60	-19.92	QP
12	10.1289	22.34	10.04	32.38	50	-17.62	AVG

Remark:

1. QP = Quasi Peak, AVG = Average
2. Correction Factor = Insertion loss of LISN + Cable loss
3. Measurement Value = Reading Level + Correct Factor
4. Margin Level = Measurement Value – Limit Value

Test Voltage :	120Vac, 60Hz	Frequency Range:	0.15-30 MHz
Test Mode :	Normal Link	6dB Bandwidth :	9 kHz
Test Date :	2021/12/29	Phase :	N
Temperature :	26°C	Humidity :	38 %



No.	Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measurement (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3065	35.51	9.82	45.33	60.06	-14.73	QP
2	0.3065	21.25	9.82	31.07	50.06	-18.99	AVG
3	1.7302	26.43	9.86	36.29	56	-19.71	QP
4	1.7302	11.24	9.86	21.1	46	-24.9	AVG
5	1.9934	23.03	9.89	32.92	56	-23.08	QP
6	1.9934	8.53	9.89	18.42	46	-27.58	AVG
7	2.1698	25.41	9.89	35.3	56	-20.7	QP
8	2.1698	10.95	9.89	20.84	46	-25.16	AVG
9	10.2808	32.56	10.04	42.6	60	-17.4	QP
10	10.2808	23.15	10.04	33.19	50	-16.81	AVG
11	18.0819	27.23	10.22	37.45	60	-22.55	QP
12	18.0819	19.2	10.22	29.42	50	-20.58	AVG

Remark:

1. QP = Quasi Peak, AVG = Average
2. Correction Factor = Insertion loss of LISN + Cable loss
3. Measurement Value = Reading Level + Correct Factor
4. Margin Level = Measurement Value – Limit Value

--- END ---