

RF Exposure evaluation

According to 447498 D04 Interim General RF Exposure Guidance v01

$$P_{\text{th}} (\text{mW}) = \begin{cases} \text{ERP}_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ \text{ERP}_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{\text{ERP}_{20 \text{ cm}} \sqrt{f}} \right)$$

$$P_{\text{th}} (\text{mW}) = \text{ERP}_{20 \text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

ERP=Peak Power + Antenna Gain -2.15=1.90+1.65-2.15=1.4dBm

$10^{0.19}=1.55\text{mW} < 2.7\text{mW}$ (Worst case recorded)

Then SAR evaluation is not required