



EMC TEST REPORT

Applicant Sonitus Medical (Shanghai) Co., Ltd.

FCC ID 2AUH801

Product SoundBite Hearing System

Model SoundBite G3, SoundBite G3S

Report No. R1902A0232-E1

Issue Date November 26, 2019

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2018)/ ANSI C63.4 (2014)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Wei Liu

Performed by: Wei Liu/ Manager

Guangchang Fan

Approved by: Guangchang Fan/ Director

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report	4
1.2	Testing Location.....	5
2	General Description of Equipment under Test.....	6
2.1	Client Information	6
2.2	General information.....	6
2.3	Applied Standards.....	7
2.4	Test Mode.....	8
3	Test Case Results	9
3.1	Radiated Emission	9
3.2	Conducted Emission	13
4	Main Test Instrument	16
ANNEX A: The EUT Appearance and Test Configuration.....		17
A.1	EUT Appearance	17
A.2	Test Setup.....	20



Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS
Test Date: June 12, 2019 ~ July 5, 2019			



1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.



1.2 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com



2 General Description of Equipment under Test

2.1 Client Information

Applicant	Sonitus Medical (Shanghai) Co., Ltd.
Applicant address	Bldg. 11-F5, 500 Furonghua Road, Pudong District, 201318 Shanghai, PEOPLE'S REPUBLIC OF CHINA
Manufacturer	Sonitus Medical (Shanghai) Co., Ltd.
Manufacturer address	Bldg. 11-F5, 500 Furonghua Road, Pudong District, 201318 Shanghai, PEOPLE'S REPUBLIC OF CHINA

2.2 General information

EUT Description				
Device Type:	Portable Device			
Model:	SoundBite G3, SoundBite G3S			
IMEI:	/			
HW Version:	1.0			
SW Version:	1.0			
Antenna Type:	Internal Antenna			
Frequency:	Tx (MHz)	Rx (MHz)		
	10.6MHz	10.6MHz		
EUT Accessory				
Adapter 1	Manufacturer: Dongguan Shilong Fuhua Electronic Co., Ltd. Model: UE06WOCPU-050100SPA			
Adapter 2	Manufacturer: Dongguan Shilong Fuhua Electronic Co., Ltd. Model: UES06WOCPU-050100SPA			
Battery	Manufacturer: Tianjin Lishen Battery Jont-Stock Co., Ltd Model: PP031313AB, TLp000A4			
USB Cable	Manufacturer: Dongguan Mepos Electronics			
Note: The information of the EUT is declared by the manufacturer.				
2. There are more than one Adapter, each one should be applied throughout the compliance test respectively, however, only the worst case (Adapter1) will be recorded in this report.				



2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

FCC Code CFR47 Part15B (2018)

ANSI C63.4 (2014)



2.4 Test Mode

Test Mode	
Mode 1	Adapter + EUT +Idle



3 Test Case Results

3.1 Radiated Emission

Ambient condition

Temperature	Relative humidity	Pressure
24°C~26°C	45%~50%	102.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:


(a) PEAK: RBW=1MHz / VBW=3MHz/ Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO


The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

Test Setup

Below 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

**Limits**

Frequency (MHz)	Field Strength (dB μ V/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 th harmonic of the highest frequency or 40GHz,which is lower	54 74	Average Peak

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.


Frequency	Uncertainty
30MHz~200MHz	4.02 dB
200MHz~1000MHz	3.28 dB

Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier, the Emissions are more than 20dB below the limit are not reported.

The following graphs display the maximum values of horizontal and vertical by software.
For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.

RE 0.03-1GHz QP Class B



Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
38.893750	21.7	100.0	V	244.0	16.9	18.3	40.0
60.068750	20.5	200.0	V	34.0	14.0	19.5	40.0
105.861250	15.3	100.0	V	321.0	13.5	24.7	40.0
142.966250	12.3	100.0	V	0.0	9.6	27.7	40.0
278.438750	18.0	200.0	H	119.0	14.7	29.0	47.0
424.421250	25.0	200.0	V	136.0	20.0	22.0	47.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak

3.2 Conducted Emission


Ambient condition

Temperature	Relative humidity	Pressure
24°C ~26°C	50%~55%	102.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

Limits

Frequency (MHz)	Conducted Limits(dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 [*]	56 to 46 [*]
0.5 - 5	56	46
5 - 30	60	50


^{*}: Decreases with the logarithm of the frequency.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$. $U = 2.57$ dB.

Test Results

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.




Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.36	---	22.58	48.69	26.11	1000.0	9.000	L1	ON	19.19
0.36	25.69	---	58.69	33.00	1000.0	9.000	L1	ON	19.19
0.40	---	24.51	47.81	23.30	1000.0	9.000	L1	ON	19.23
0.49	22.93	---	56.25	33.32	1000.0	9.000	L1	ON	19.23
1.45	21.20	---	56.00	34.80	1000.0	9.000	L1	ON	19.18
1.45	---	19.21	46.00	26.79	1000.0	9.000	L1	ON	19.18
2.47	---	19.16	46.00	26.84	1000.0	9.000	L1	ON	19.03
2.52	20.57	---	56.00	35.43	1000.0	9.000	L1	ON	19.02
9.25	---	17.92	50.00	32.08	1000.0	9.000	L1	ON	19.30
9.44	19.58	---	60.00	40.42	1000.0	9.000	L1	ON	19.33
17.34	---	16.92	50.00	33.08	1000.0	9.000	L1	ON	19.60
17.35	19.65	---	60.00	40.35	1000.0	9.000	L1	ON	19.60

Remark: Correct factor=cable loss + LISN factor

L line

Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.36	---	17.84	48.69	30.85	1000.0	9.000	N	ON	19.19
0.36	23.34	---	58.69	35.35	1000.0	9.000	N	ON	19.19
0.41	25.20	---	57.58	32.38	1000.0	9.000	N	ON	19.23
0.45	---	18.13	46.81	28.68	1000.0	9.000	N	ON	19.23
1.18	---	15.01	46.00	30.99	1000.0	9.000	N	ON	19.23
1.19	18.21	---	56.00	37.79	1000.0	9.000	N	ON	19.23
4.37	19.15	---	56.00	36.85	1000.0	9.000	N	ON	19.10
4.41	---	16.53	46.00	29.47	1000.0	9.000	N	ON	19.10
9.25	---	20.25	50.00	29.75	1000.0	9.000	N	ON	19.32
9.28	24.05	---	60.00	35.95	1000.0	9.000	N	ON	19.32
17.28	24.95	---	60.00	35.05	1000.0	9.000	N	ON	19.51
17.34	---	20.74	50.00	29.26	1000.0	9.000	N	ON	19.51

Remark: Correct factor=cable loss + LISN factor

N line

Conducted Emission from 150 KHz to 30 MHz



4 Main Test Instrument

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Time
Spectrum Analyzer	R&S	FSV40	15195-01-00	2019-05-19	2020-05-18
EMI Test Receiver	R&S	ESCI	100948	2019-05-19	2020-05-18
Trilog Antenna	SCHWARZBECK	VULB 9163	9163-201	2017-11-18	2019-11-17
Horn Antenna	R&S	HF907	100126	2018-07-07	2020-07-06
Standard Gain Horn	ETS-Lindgren	3160-09	00102643	2018-06-20	2020-06-19
EMI Test Receiver	R&S	ESR	101667	2019-05-19	2020-05-18
LISN	R&S	ENV216	101171	2016-12-16	2019-12-15
Bore Sight Antenna mast	ETS	2171B	00058752	/	/
Test software	EMC32	R&S	9.26.0	/	/

*****END OF REPORT *****

ANNEX A: The EUT Appearance and Test Configuration

A.1 EUT Appearance





a: EUT



Adapter 1



Adapter 2

b: Adapter

Picture 1 EUT and Accessory

A.2 Test Setup



Picture 2 Radiated Emission Test Setup



Picture 3 Conducted Emission Test Setup