



RF EXPOSURE

EXEMPT REPORT

APPLICANT : Hangzhou Bangtang Network Technology Co., Ltd.

PRODUCT NAME : Femometer Vinca II

MODEL NAME : FM-VC-201

BRAND NAME : Femometer

FCC ID : 2AUHA201

STANDARD(S) : 47CFR 2.1093
: KDB 447498

RECEIPT DATE : 2019-08-30

TEST DATE : 2019-09-17 to 2019-09-20

ISSUE DATE : 2019-09-24

Edited by:

Chen Hao (Rapporteur)

Approved by:

Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLABSHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. ChinaTel: 86-755-36698555 Fax: 86-755-36698525
Http://www.morlab.cn E-mail: service@morlab.cn



DIRECTORY

1. Technical Information	4
1.1 Applicant and Manufacturer Information	4
1.2 Equipment Under Test (EUT) Description	4
1.3 Identification of all used EUT	5
1.4 Applied Reference Documents	5
2. Device Category and RF Exposure Limit	6
3. Measurement of RF Output Power	7
4. RF Exposure Evaluation	8
Annex A General Information	9



REPORT No. : SZ19080266S01

Change History		
Version	Date	Reason for change
1.0	2019-09-24	First edition

MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525
Http://www.morlab.cn E-mail: service@morlab.cn



1. Technical Information

Note: Provide by manufacturer.

1.1 Applicant and Manufacturer Information

Applicant:	Hangzhou Bangtang Network Technology Co., Ltd.
Applicant Address:	F12 No.92 Yueda Valley, Binjiang District, Hangzhou, Zhejiang, China
Manufacturer:	JOYTECH Healthcare Co., Ltd.
Manufacturer Address:	No.365, Wuzhou Road, Yuhang Economic Development Zone, Hangzhou City, 311100 Zhejiang, China

1.2 Equipment Under Test (EUT) Description

EUT Name:	Femometer Vinca II
Hardware Version:	BLE_V1_3 LCD_V1_7
Software Version:	1.1.0
Frequency Bands:	Bluetooth: 2402-2480MHz
Modulation Mode:	GFSK(1Mbps)
Antenna Type:	PIFA Antenna
Antenna Gain:	0 dBi



1.3 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	BLE_V1_3 LCD_V1_7	1.1.0

1.4 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title	Method determination /Remark
1	47 CFR§2.1093	Radio Frequency Radiation Exposure Evaluation: portable devices	No deviation
2	KDB 447498 D01v06	General RF Exposure Guidance	No deviation



2. Device Category and RF Exposure Limit

Per user manual, this device is a Wall Control for HRV unit P/N: 99-MX01. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

Portable Devices:

47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

47CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.



3. Measurement of RF Output Power

1. Bluetooth output power

Mode	Channel	Frequency (MHz)	Average power (dBm)
			GFSK
LE	CH 00	2402	-1.57
	CH 19	2440	-1.63
	CH 39	2480	-1.74
Tune-up Limit			-1.0

Note: According to KDB 447498 Section 4.3, SAR test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.



4. RF Exposure Evaluation

➤ Standalone transmission SAR evaluation:

1. According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation Distances≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(\text{GHz})}$] ≤ 3.0.
 - $f(\text{GHz})$ is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison
2. When the Femometer Vinca II is used on hand/body, 5mm as the most conservative minimum test separation distance was used for evaluating,

Channel	Frequency (GHz)	Max. tune-up Power (dBm)	Max. Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 0	2.402	-1.0	0.79	5	0.24	3.0

3. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2), the following equation must be used to estimate the standalone 1g SAR.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} \cdot \frac{\text{Max. power of channel, mW}}{\text{Min. Separation Distance, mm}}$$

Mode	Max. tune-up Power (dBm)	Exposure Position	
		Test Distance (mm)	Hand/Body
Bluetooth	-1.0	Estimated SAR (W/kg)	0.033

➤ Simultaneous SAR evaluation:

This device only incorporates one Bluetooth transmitter, Therefore simultaneous SAR evaluation is not required.



Annex A General Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

END OF REPORT