

TEST REPORT

Reference No...... : WTX23X10221080W004
FCC ID : 2AUI4-E73
Applicant : Universal Ubiquitous AI Co., Ltd.
Address : Floor 24-26 Building 3, Fashion Vantone City, Cangqian Street, Yuhang District, Hangzhou, Zhejiang, China
Manufacturer : The same as Applicant
Address : The same as Applicant
Product Name : FACE RECOGNITION TERMINAL
Model No...... : E73-1711-OS-V
Standards : FCC Part 15C
Date of Receipt sample : 2023-10-16
Date of Test..... : 2023-10-16 to 2023-12-19
Date of Issue : 2023-12-19
Test Report Form No. : WTX_Part 15CW
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.


Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China


Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Gala Wang

Approved by:



Silin Chen

ABLE OF CONTENTS

1. GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND OPERATION MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	10
3. RF EXPOSURE	11
3.1 STANDARD APPLICABLE.....	11
3.2 TEST RESULT.....	11
4. ANTENNA REQUIREMENT	12
4.1 STANDARD APPLICABLE.....	12
4.2 EVALUATION INFORMATION	12
5. CONDUCTED EMISSIONS	13
5.1 TEST PROCEDURE.....	13
5.2 BASIC TEST SETUP BLOCK DIAGRAM.....	13
5.3 ENVIRONMENTAL CONDITIONS	13
5.4 TEST RECEIVER SETUP	14
5.5 SUMMARY OF TEST RESULTS/PLOTS	14
6. FIELD STRENGTH OF SPURIOUS EMISSIONS	17
6.1 STANDARD APPLICABLE.....	17
6.2 TEST PROCEDURE.....	17
6.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	18
6.4 ENVIRONMENTAL CONDITIONS	19
6. REFERENCE MEASUREMENT AT OPEN FIELD SITE	19
6.5 SUMMARY OF TEST RESULTS/PLOTS	19
7. 20DB EMISSION BANDWIDTH.	23
7.1 STANDARD APPLICABLE.....	23
7.2 TEST PROCEDURE.....	23
7.3 ENVIRONMENTAL CONDITIONS	23
7.4 SUMMARY OF TEST RESULTS/PLOTS	23
APPENDIX PHOTOGRAPHS.....	25

Report version

Version No.	Date of issue	Description
Rev.00	2023-12-19	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	FACE RECOGNITION TERMINAL
Trade Name:	UNIUBI
Model No.:	E73-1711-OS-V
Adding Model:	E73-1701-V, E73-1711-V, E73-1701-OS-V, E73-1701, E73-1711, E73-1701-OS, E73-1711-OS
Battery Capacity	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model E73-1711-OS-V, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	125KHz
Modulation Type:	BPSK
Max. Field Strength:	50.75dBuV/m (at 3m)
Antenna Type:	Coil Antenna
Antenna Gain	0dBi
Rated Voltage:	DC 12V
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

FCC Part 15 Subpart C: Intentional Radiators.

FCC Rules Part 15.207: Conducted limits.

FCC Rules Part 15.209: Radiated emission limits; general requirements.

FCC Rules Part 15.215: Additional provisions to the general radiated emission limitations.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark	Power Supply Mode
TM1	Transmit/ Receiving	125KHz	DC 12V

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	TianYi 100-14IBD	PF0F4ABV
adapter	Xiaoerduo	HMQ-Z24T-12C	/

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
Network Cable	1.0	Unshielded	Without Ferrite
DC Cable	1.0	Unshielded	Without Ferrite

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Conducted Emissions	Conducted	±2.88dB
Transmitter Spurious Emissions	Radiated	±5.1dB

1.7 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1004A 1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2023-02-25	2024-02-24
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2023-02-25	2024-02-24
WTXE1007A 1001	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/00 5	2023-02-25	2024-02-24
WTXE1007A 1001	Amplifier	HP	8447F	2805A034 75	2023-02-25	2024-02-24
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2024-03-19
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2023-03-20	2026-03-19
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2023-02-25	2024-02-24
WTXE1007A 1001	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/00 5	2023-02-25	2024-02-24
WTXE1065A 1001	Amplifier	C&D	PAP-1G18	14918	2023-02-25	2024-02-24
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2021-03-19	2024-03-18
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2021-03-19	2024-03-18
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2023-02-25	2024-02-24
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2024-04-08
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2023-02-25	2024-02-24
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2023-02-25	2024-02-24
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2023-02-25	2024-02-24
WTXE1010A	Trilog	Schwarz beck	VULB 9168	1194	2021-05-28	2024-05-27

1013-1	Broadband Antenna					
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2024-03-19
WTXE1007A 1002	Amplifier	HP	8447F	2944A038 69	2023-02-25	2024-02-24
☒ Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2023-02-25	2024-02-24
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2023-02-25	2024-02-24
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2021-03-19	2024-03-18
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2023-02-25	2024-02-24
☐ Conducted Room 1#						
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2023-02-25	2024-02-24
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2023-02-25	2024-02-24
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2023-02-25	2024-02-24
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2023-02-25	2024-02-24
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2023-02-25	2024-02-24

2. SUMMARY OF TEST RESULTS

Description of Test	Result
§15.207(a) Conducted Emission	Compliant
§15.209(a) Radiated Emission	Compliant
§15.215 20dB Emission Bandwidth	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to §1.1307 and §2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a Coil antenna, fulfill the requirement of this section.


5. Conducted Emissions

5.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

5.2 Basic Test Setup Block Diagram



5.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar


5.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth.....	9 kHz
Quasi-Peak Adapter Mode	Normal


5.5 Summary of Test Results/Plots

Test Mode	TM1(AC120V 60Hz)	Polarity:	Neutral
-----------	------------------	-----------	---------



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector
1	158.000kHz	65.6	48.2	-17.3	27.3	20.9	QP
2	242.000kHz	62.0	37.4	-24.7	17.0	20.4	QP
3	322.000kHz	59.7	38.6	-21.0	18.3	20.3	QP
4	778.000kHz	56.0	37.8	-18.2	17.0	20.8	QP
5	1.090MHz	56.0	33.7	-22.3	12.9	20.8	QP
6	13.558MHz	60.0	54.4	-5.6	33.6	20.8	QP
7*	166.000kHz	55.2	36.7	-18.5	15.9	20.8	AV
8*	234.000kHz	52.3	32.7	-19.6	12.2	20.5	AV
9*	338.000kHz	49.3	33.0	-16.2	12.6	20.4	AV
10*	490.000kHz	46.2	30.0	-16.2	9.3	20.7	AV
11*	778.000kHz	46.0	33.3	-12.7	12.5	20.8	AV
12*	1.410MHz	46.0	29.4	-16.6	8.6	20.8	AV

Test Mode	TM1(AC120V 60Hz)	Polarity:	Line
-----------	------------------	-----------	------



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector
1	150.000kHz	66.0	50.5	-15.5	29.6	20.9	QP
2	158.000kHz	65.6	48.1	-17.4	27.2	20.9	QP
3	334.000kHz	59.4	36.9	-22.4	16.5	20.4	QP
4	682.000kHz	56.0	34.7	-21.3	14.0	20.7	QP
5	1.006MHz	56.0	33.9	-22.1	13.1	20.8	QP
6	13.638MHz	60.0	29.8	-30.2	9.0	20.8	QP
7*	154.000kHz	55.8	36.1	-19.7	15.2	20.9	AV
8*	194.000kHz	53.9	34.1	-19.8	13.4	20.7	AV
9*	338.000kHz	49.3	32.3	-16.9	11.9	20.4	AV
10*	778.000kHz	46.0	34.0	-12.0	13.2	20.8	AV
11*	1.262MHz	46.0	28.9	-17.1	8.1	20.8	AV
12*	13.554MHz	50.0	42.9	-7.1	22.1	20.8	AV

6. Field Strength of Spurious Emissions

6.1 Standard Applicable

According to §15.209(a), Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

6.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

The test setup for emission measurement below 30MHz..



The test setup for emission measurement from 30 MHz to 1 GHz..



Frequency :9kHz-30MHz

RBW=10KHz

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

6.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

6.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

6. Reference Measurement at open field site

The measurement was performed with set-up consisting of a single turn loop antenna with a diameter of 0.15 m, fed by a signal generator. The loop dimension was chosen to simulate the EUT as far as possible. The signal generator was set to a fixed output level with an unmodulated 10 kHz and 14 kHz sinusoidal signal. The radiated H fieldstrength at 10 kHz and 14 kHz generated by this set-up was measured with the same test setup as used in the SAC in 3 m distance first, and then repeated at the open field site in 3 m and 10 m distance


6.5 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Radiated Emissions Test Data (Below 30MHz)(Worst case EUT X axis)


No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	0.0212	48.95	-6.98	41.97	121.06	-79.09	-	-	peak
2	0.0286	48.47	-6.58	41.89	118.46	-76.57	-	-	peak
3	0.1252	57.22	-6.47	50.75	105.65	-54.90	-	-	peak
4	1.3028	45.46	-6.17	39.29	65.33	-26.04	-	-	peak
5	1.5933	43.76	-6.10	37.66	63.59	-25.93	-	-	peak
6	9.3024	42.80	-5.58	37.22	69.50	-32.28	-	-	peak

Plot of Radiated Emissions Test Data (Above 30MHz)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	72.3376	32.22	-11.27	20.95	40.00	-19.05	-	-	peak
2	108.2667	37.37	-8.13	29.24	43.50	-14.26	-	-	peak
3	150.0108	38.58	-11.67	26.91	43.50	-16.59	-	-	peak
4	250.3012	30.28	-6.70	23.58	46.00	-22.42	-	-	peak
5	331.3547	28.75	-4.47	24.28	46.00	-21.72	-	-	peak
6	663.4729	28.26	0.79	29.05	46.00	-16.95	-	-	peak

Test Mode	TM1	Polarity:	Vertical
-----------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	50.9420	33.08	-7.48	25.60	40.00	-14.40	-	-	peak
2	72.8466	41.31	-11.33	29.98	40.00	-10.02	-	-	peak
3	108.2667	36.88	-8.13	28.75	43.50	-14.75	-	-	peak
4	150.0108	40.55	-11.67	28.88	43.50	-14.62	-	-	peak
5	250.3012	32.85	-6.70	26.15	46.00	-19.85	-	-	peak
6	556.7744	28.48	-0.97	27.51	46.00	-18.49	-	-	peak

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

7. 20dB Emission bandwidth.

7.1 Standard Applicable

According to 15.215, 20dB emission bandwidth.

7.2 Test Procedure


- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

7.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

7.4 Summary of Test Results/Plots

Test Channel(kHz)	20dB Emission Bandwidth(Hz)
125	145.4



Date: 13.NOV.2023 15:45:44

Note: The RBW of the analyzer measuring Bandwidth cannot be adjusted to 1%-5% occupied bandwidth, the RBW of the test setting is the closest value.

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****