





Report No.: T190411D03-RP1

Page: 51 / 110
Rev.: 01











Report No.: T190411D03-RP1


Page: 53 / 110
Rev.: 01

















Report No.: T190411D03-RP1

Page: 58 / 110
Rev.: 01














Report No.: T190411D03-RP1

Page: 62 / 110
Rev.: 01











Report No.: T190411D03-RP1


Page: 65 / 110
Rev.: 01








Report No.: T190411D03-RP1







Report No.: T190411D03-RP1

Page: 68 / 110
Rev.: 01



Report No.: T190411D03-RP1









Report No.: T190411D03-RP1

Page: 71 / 110
Rev.: 01





Report No.: T190411D03-RP1



5.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

5.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency	Field Strength (microvolts/m)	Measurement Distance (metres)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

5.6.2 Test Procedure

Test method Refer as KDB 558074 D01.

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

Note: No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz)

Remark:

1. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

4. The SA setting following :

(1) Below 1G : RBW = 100kHz, VBW $\geq$ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2) Above 1G :

(2.1) For Peak measurement : RBW = 1MHz, VBW $\geq$ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2.2) For Average measurement : RBW = 1MHz, VBW

·If Duty Cycle $\geq$ 98%, VBW=10Hz.


·If Duty Cycle < 98%, VBW=1/T.

Configuration	Duty Cycle (%)	T(ms)	1/T (kHz)	VBW Setting
802.11b	100%	1.0000	-	10Hz
802.11g	100%	1.0000	-	10Hz
802.11n HT20	98.02%	4.9500	-	10Hz
802.11n HT40	97.35%	2.4250	0.412	430Hz


Report No.: T190411D03-RP1

5.6.3 Test Setup


9kHz ~ 30MHz



30MHz ~ 1GHz




Above 1 GHz



5.6.4 Test Result


Band Edge Test Data

Test Mode	IEEE 802.11b Low CH	Temp/Hum	20(°C)/ 51%RH
Test Item	Band Edge	Test Date	April 23, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak / Average		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.00	53.65	-3.38	50.27	54.00	-3.73	Average
2390.00	63.82	-3.38	60.44	74.00	-13.56	Peak
2412.00	121.38	-3.35	118.03	74.00	-	-

Test Mode	IEEE 802.11b High CH	Temp/Hum	21(°C)/ 52%RH
Test Item	Band Edge	Test Date	April 23, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak / Average		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2462.00	121.55	-3.03	118.52	74.00	-	-
2483.50	52.31	-2.83	49.48	54.00	-4.52	Average
2483.50	62.86	-2.83	60.03	74.00	-13.97	Peak

Test Mode	IEEE 802.11g Low CH	Temp/Hum	21(°C)/ 53%RH
Test Item	Band Edge	Test Date	April 23, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak / Average		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.00	54.11	-3.38	50.73	54.00	-3.27	Average
2390.00	74.31	-3.38	70.93	74.00	-3.07	Peak
2412.00	117.61	-3.35	114.26	74.00	-	-

Test Mode	IEEE 802.11g High CH	Temp/Hum	21(°C)/ 53%RH
Test Item	Band Edge	Test Date	April 23, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak / Average		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2462.00	117.91	-3.03	114.88	74.00	-	-
2483.50	53.77	-2.83	50.94	54.00	-3.06	Average
2483.50	72.97	-2.83	70.14	74.00	-3.86	Peak

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	21(°C)/ 53%RH
Test Item	Band Edge	Test Date	April 23, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak / Average		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.00	54.33	-3.38	50.95	54.00	-3.05	Average
2390.00	74.22	-3.38	70.84	74.00	-3.16	Peak
2412.00	117.53	-3.35	114.18	74.00	-	-

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	21(°C)/ 50%RH
Test Item	Band Edge	Test Date	April 23, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2462.00	117.48	-3.03	114.45	74.00	-	-
2483.50	53.75	-2.83	50.92	54.00	-3.08	Average
2483.50	70.83	-2.83	68.00	74.00	-6.00	Peak

Test Mode	IEEE 802.11n HT40 Low CH	Temp/Hum	21(°C)/ 51%RH
Test Item	Band Edge	Test Date	April 23, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak / Average		



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390.00	53.61	-3.38	50.23	54.00	-3.77	Average
2390.00	73.90	-3.38	70.52	74.00	-3.48	Peak
2422.00	106.11	-3.31	102.80	74.00	-	-


Test Mode	IEEE 802.11n HT40 High CH	Temp/Hum	21(°C)/ 51%RH
Test Item	Band Edge	Test Date	April 23, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak / Average		



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2452.00	112.20	-3.13	109.07	74.00	-	-
2483.50	53.66	-2.83	50.83	54.00	-3.17	Average
2483.50	71.93	-2.83	69.10	74.00	-4.90	Peak

Below 1G Test Data


Test Mode	Mode 1	Temp/Hum	23(°C)/ 53%RH
Test Item	30MHz-1GHz	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
105.66	46.17	-11.02	35.15	43.50	-8.35	Peak
270.56	38.33	-8.53	29.80	46.00	-16.20	Peak
401.51	36.87	-5.63	31.24	46.00	-14.76	Peak
517.91	41.24	-2.68	38.56	46.00	-7.44	Peak
670.20	33.89	0.21	34.10	46.00	-11.90	Peak
961.20	26.41	4.51	30.92	54.00	-23.08	Peak

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Test Mode	Mode 1	Temp/Hum	23(°C)/ 53%RH
Test Item	30MHz-1GHz	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
52.31	47.28	-15.77	31.51	40.00	-8.49	Peak
105.66	49.48	-11.02	38.46	43.50	-5.04	Peak
165.80	45.79	-10.34	35.45	43.50	-8.05	Peak
400.54	38.03	-5.64	32.39	46.00	-13.61	Peak
575.14	36.77	-1.79	34.98	46.00	-11.02	Peak
951.50	31.43	4.19	35.62	46.00	-10.38	Peak

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Above 1G Test Data

Test Mode	IEEE 802.11b Low CH	Temp/Hum	22(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824.00	46.94	2.84	49.78	74.00	-24.22	Peak
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11b Low CH	Temp/Hum	22(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824.00	45.77	2.84	48.61	74.00	-25.39	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T190411D03-RP1

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	22(°C)/ 52%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4874.00	46.63	2.98	49.61	74.00	-24.39	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	22(°C)/ 52%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4874.00	47.64	2.98	50.62	74.00	-23.38	Peak
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11b High CH	Temp/Hum	22(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4924.00	46.74	3.46	50.20	74.00	-23.80	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T190411D03-RP1

Test Mode	IEEE 802.11b High CH	Temp/Hum	22(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4924.00	47.34	3.46	50.80	74.00	-23.20	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T190411D03-RP1

Test Mode	IEEE 802.11g Low CH	Temp/Hum	23(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824.00	44.31	2.84	47.15	74.00	-26.85	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g Low CH	Temp/Hum	23(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824.00	43.15	2.84	45.99	74.00	-28.01	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	22(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4874.00	45.27	2.98	48.25	74.00	-25.75	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	22(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4874.00	46.78	2.98	49.76	74.00	-24.24	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g High CH	Temp/Hum	22(°C)/ 52%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4924.00	45.89	3.46	49.35	74.00	-24.65	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T190411D03-RP1

Test Mode	IEEE 802.11g High CH	Temp/Hum	22(°C)/ 52%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4924.00	47.47	3.46	50.93	74.00	-23.07	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	23(°C)/ 52%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824.00	45.38	2.84	48.22	74.00	-25.78	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	23(°C)/ 52%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824.00	45.91	2.84	48.75	74.00	-25.25	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	23(°C)/ 51%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4874.00	47.74	2.98	50.72	74.00	-23.28	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	23(°C)/ 51%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4874.00	47.18	2.98	50.16	74.00	-23.84	Peak
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	23(°C)/ 52%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4924.00	45.92	3.46	49.38	74.00	-24.62	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	23(°C)/ 52%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4924.00	46.03	3.46	49.49	74.00	-24.51	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 Low CH	Temp/Hum	23(°C)/ 52%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4844.00	44.93	2.84	47.77	74.00	-26.23	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 Low CH	Temp/Hum	23(°C)/ 52%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4844.00	45.53	2.84	48.37	74.00	-25.63	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 Mid CH	Temp/Hum	23(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4874.00	47.06	2.98	50.04	74.00	-23.96	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 Mid CH	Temp/Hum	23(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4874.00	46.99	2.98	49.97	74.00	-24.03	Peak
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 High CH	Temp/Hum	23(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Vertical	Test Engineer	Kailin Lee
Detector	Peak		




Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4904.00	45.45	3.22	48.67	74.00	-25.33	Peak
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 High CH	Temp/Hum	23(°C)/ 53%RH
Test Item	Harmonic	Test Date	April 24, 2019
Polarize	Horizontal	Test Engineer	Kailin Lee
Detector	Peak		



Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4904.00	45.39	3.22	48.61	74.00	-25.39	Peak
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

- End of Test Report -