

Product Name: IPTV Set-top box

Model No.: MAG420w1, MAG420, MAG420w1 VI, MAG420 VI, MAG420w1 VO, MAG420 VO, MAG420A, MAG420A VI, MAG420A VO, MAG420Aw1, MAG420Aw1 VI, MAG420Aw1 VO, IM4411w1, IM4411, IM4411w1 VI, IM4411 VI, IM4411w1 VO, IM4411 VO, MAG422, MAG422w1, IM4414, IM4414w1, MAG422 VI, MAG422w1 VI, MAG422 VO, MAG422w1 VO, IM4414 VI, IM4414w1 VI, IM4414 VO, IM4414w1 VO, MAG422A, MAG422A VI, MAG422A VO, MAG422Aw1, MAG422Aw1 VI, MAG422Aw1 VO

FCC ID: 2AUIR-IM010AXXX1

RF Exposure Evaluation

1.1 RF Exposure Compliance Requirement

1.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

1.1.3 EUT RF Exposure Evaluation

Antenna Gain: 3.38dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.18 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at $R = 20$ cm (mW/cm ²)	Limit	Result
Lowest	2412	18.51	70.96	0.03	1.0	PASS

Note: Refer to report No. BLA-EMC-201909-A02-03 for EUT test Max Conducted Peak Output Power value. The distance (4th column) calculated from the Friis transmission formula is far greater than 20 cm separation Requirement