

TEST REPORT

Application No.: SZCR2502000592AT
Applicant: Wyze Labs, Inc.
Address of Applicant: 5808 Lake Washington Blvd NE Ste 300, Kirkland, Washington 98033, United States
Manufacturer: Wyze Labs, Inc.
Address of Manufacturer: 5808 Lake Washington Blvd NE Ste 300, Kirkland, Washington 98033, United States
Equipment Under Test (EUT):
EUT Name: Wyze Palm Lock
Model No.: DX_LBP
Trade Mark: WYZE
FCC ID: 2AUIUDXLBP
Standard(s) : 47 CFR Part 15, Subpart C 15.255
Date of Receipt: 2025-02-19
Date of Test: 2025-02-24 to 2025-03-27
Date of Issue: 2025-04-01

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250200059204

Page: 2 of 43

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2025-04-01		Original

Authorized for issue by:				
				
		Charlie Dai/Project Engineer		
				
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Test Item	FCC Rule No.	Test Method	Result
Antenna Requirement	15.203	--	PASS
Transmitter power and Transmitter off-times	15.255(b)(3)	ANSI C63.10-2020 Section 9.2.1/9.2.2	PASS
Occupied bandwidth	15.215 (c), 15.255 (b)(3)	ANSI C63.10-2020 Section 9.4	PASS
Radiated spurious emissions below 40 GHz	15.255 (d)(2)	ANSI C63.10-2020 Section 9.11	PASS
Radiated emissions outside assigned band and above 40 GHz up to 200 GHz	15.255 (d)(3)	ANSI C63.10-2020 Section 9.10	PASS
Frequency stability	15.255 (f)	ANSI C63.10-2020 Section 9.5	PASS



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Test Environment	6
4.4 Measurement Uncertainty	7
4.5 Test Location	8
4.6 Test Facility	8
4.7 Deviation from Standards	8
4.8 Abnormalities from Standard Conditions	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement	11
6.1 Antenna Requirement	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
7 Radio Spectrum Matter Test Results	12
7.1 Transmitter power and Transmitter off-times	12
7.1.1 E.U.T. Operation	12
7.1.2 Test Mode Description	12
7.1.3 Test Setup Diagram	12
7.1.4 Measurement Procedure and Data	13
7.2 Occupied Bandwidth	14
7.2.1 E.U.T. Operation	14
7.2.2 Test Mode Description	14
7.2.3 Test Setup Diagram	14
7.2.4 Measurement Procedure and Data	14
7.3 Radiated spurious emissions below 40 GHz	15
7.3.1 E.U.T. Operation	16
7.3.2 Test Mode Description	16
7.3.3 Test Setup Diagram	17
7.3.4 Measurement Procedure and Data	18
7.4 Radiated emissions outside assigned band and above 40 GHz up to 200 GHz	25
7.4.1 E.U.T. Operation	25
7.4.2 Test Mode Description	25
7.4.3 Test Setup Diagram	26
7.4.4 Measurement Procedure and Data	26
7.5 Frequency Stability	33



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250200059204

Page: 5 of 43

7.5.1	E.U.T. Operation	33
7.5.2	Test Mode Description	33
7.5.3	Test Setup Diagram	33
7.5.4	Measurement Procedure and Data.....	34
8	Test Setup Photo	35
9	EUT Constructional Details (EUT Photos)	35
10	Appendix.....	36



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Powered by rechargeable Li-Ion battery (Model WBAT2/ Nominal voltage 3.6V). Li-Ion battery type-C input: 5V DC/0.8A
Operation Frequency:	57GHz-64GHz
Modulation Type:	FMCW
Antenna Type:	AiP Antenna
Antenna Gain:	7.43dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
DC power supply	ZHAOXIN	PS-3005D	REF. No.SEA27B01

4.3 Test Environment

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Value	Temperature(°C)	Voltage(VDC)
NTNV	25	3.96
LTHV	-20	3.60
LTLV	-20	3.24
HTHV	50	3.96
HTLV	50	3.24

Note:

NV:Normal Voltage

LV:Low Extreme Test Voltage

HV:High Extreme Test Voltage

NT:Normal Temperature

LT:Low Extreme Test Temperature

HT:High Extreme Test Temperature



4.4 Measurement Uncertainty

Test Item	Measurement Uncertainty
Transmitter power and power spectral density	$\pm 4.8\text{dB}$
Occupied bandwidth	$\pm 3\%$
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (Above 18GHz)

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd.

Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



5 Equipment List

Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2024-05-11	2027-05-10
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	SEM004-20	2024-03-30	2025-03-29
Horn Antenna(800MHz-18GHz)	Rohde&Schwarz	HF907	SEM003-07	2023-07-23	2025-07-22
Microwave system amplifier (0.5GHz-26.5GHz)	Agilent	83017A	SEM005-25	2024-09-14	2025-09-13
Broad-Band Horn Antenna(15GHz-40GHz)	SCHWARZBECK	BBHA 9170	SEM003-15	2024-08-10	2025-08-09
Programmable Temperature&Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2024-03-19 2025-02-26	2025-03-18 2026-02-25
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2024-03-15 2025-03-21	2025-03-14 2026-03-20
Coaxial Cable	SGS	N/A	SEM026-01	2024-07-06	2025-07-05
Waveguide(40-60GHz)	REBES	SWG-19025-FB	SEM020-08	N/A	N/A
Waveguide(50-75GHz)	REBES	SWG-15025-FB	SEM020-09	N/A	N/A
Waveguide(75-110GHz)	REBES	SWG-10025-FB	SEM020-10	N/A	N/A
Waveguide(110-170GHz)	REBES	SWG-06025-FB	SEM020-11	N/A	N/A
Waveguide(140-220GHz)	REBES	SWG-05025-FB	SEM020-12	N/A	N/A
Waveguide Harmonic Mixer(40-60GHz)	REBES	STH-19SF-S1	SEM020-14	N/A	N/A
Waveguide Harmonic Mixer(50-75GHz)	KEYSIGHT	M1970V	SEM020-15	N/A	N/A
Waveguide Harmonic Mixer(75-110GHz)	KEYSIGHT	M1970W	SEM020-16	N/A	N/A
Waveguide Harmonic Mixer(110-170GHz)	REBES	STH-06SF-S1	SEM020-17	N/A	N/A
Waveguide Harmonic Mixer(140-220GHz)	Rohde&Schwarz	HM140-220	SEM020-18	N/A	N/A
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250200059204

Page: 10 of 43

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2024-07-24	2025-07-23
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2024-07-24	2025-07-23
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2024-03-18 2025-03-03	2025-03-17 2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement.

Antenna location: Refer to internal photos



7 Radio Spectrum Matter Test Results

7.1 Transmitter power and Transmitter off-times

Test Requirement 47 CFR Part 15C Section 15.255 (c)(2)(iii)(B)

Test Method: ANSI C63.10-2020 Section 9.2.1, 9.2.2

Limit:

The peak EIRP shall not exceed 20 dBm, and The sum of continuous transmitter off-times of at least two milliseconds shall equal at least 16.5 milliseconds within any contiguous interval of 33 milliseconds.

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 21.4 °C Humidity: 52.7 % RH Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	26	TX mode _ Keep the EUT in continuously transmitting mode

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- For transmitter power test, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 1 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to the same high and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor

Spectrum analyser setting during test.

- Place the EUT on the table and set it in the transmitting mode.
- SA set RBW=1MHz, VBW=3*RBW, Detector=Peak Trace: Max Hold, Peak Search.
- During test, the EUT will be rotate for 0 degrees to 360 degrees in X, Y, Z axis to find the maximum reading base on the previous test in different host-specific condition and the worst data was record in the report.



Please Refer to Appendix for Details



7.2 Occupied Bandwidth

Test Requirement 47 CFR Part 15C Section 15.215(c), 15.255 (c)(2)

Test Method: ANSI C63.10-2020 Section 9.4

Limit: 57-64GHz

7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 21.4 °C Humidity: 52.7 % RH Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	26	TX mode _ Keep the EUT in continuously transmitting mode

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

1. Place the EUT on the table and set it in the transmitting mode.
2. SA set RBW=1%~5% OBW, or a minimum of 1 MHz if this is not possible due to a large OBW, VBW=3*RBW and Detector=Peak.
3. Measure and record the result of 20dB and 99% bandwidth.

Please Refer to Appendix for Details



7.3 Radiated spurious emissions below 40 GHz

Test Requirement 47 CFR Part 15C Section 15.255 (d)(2)

Test Method: ANSI C63.10-2020 Section 9.11

Limit:

Below 30MHz:

Frequency	Field Strength (μV/m)	Measurement Distance (metres)
9 - 490 kHz	2,400/F (kHz)	300
490 - 1,705 kHz	24,000/F (kHz)	30
1.705-30 MHz	30	30

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

Above 30MHz:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (metres)
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

Frequency (MHz)	Field strength at 3 m, dB(μV/m)*		
	Within restricted bands		
	Peak	Quasi Peak	Average
0.009 - 0.090	148.5 - 128.5	NA	128.5 - 108.5**
0.090 - 0.110	NA	108.5 - 106.8**	NA
0.110 - 0.490	126.8 - 113.8	NA	106.8 - 93.8**
0.490 - 1.705	NA	73.8 - 63.0**	NA
1.705 - 30.0*		69.5	
30 - 88		40.0	
88 - 216		43.5	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250200059204

Page: 16 of 43

216 - 960		46.0	
Above 960		54.0	
1000 - 200000	74.0	N/A	54.0

*- The limit for 3 m test distance was calculated using the inverse square distance extrapolation factor as follows:

$$\text{LimS2} = \text{LimS1} + 20 \log (S1/S2),$$

where S1 and S2 - standard defined and test distance respectively in meters.

** - The limit decreases linearly with the logarithm of frequency.

Note: The above field strength limits applied from the lowest radio frequency generated in the device, without going below 9 kHz up to the tenth harmonic of the highest fundamental frequency but not exceeding 40 GHz for intentional radiators operated below 10 GHz and up to the fifth harmonic of the highest fundamental frequency but not exceeding 200 GHz for intentional radiators operated above 30 GHz.

Frequency (MHz)	Field strength at 1 m, dB(uV/m)*		
	Within restricted bands		
	Peak	Quasi Peak	Average
1000 - 200000	83.5	N/A	63.5

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 21.4 °C Humidity: 52.7 % RH Atmospheric Pressure: 1000 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	26	TX mode _ Keep the EUT in continuously transmitting mode




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


7.3.3 Test Setup Diagram




30MHz-1GHz



1GHz-18GHz



Below 30MHz



18GHz-40GHz



7.3.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For 1-18GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. For 18-40GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 1 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to the same height (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: Scan from 9kHz to 40GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Test Mode: 26; Polarity: Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : 00592AT/00593AT
Test Mode: 26

	Ant Freq	Cable Factor	Preamp Loss	Read Level	Limit Level	Over Line	Remark
	MHz	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	32.067	20.24	0.70	27.79	24.60	17.75	40.00 -22.25 QP
2	53.882	12.15	0.90	27.72	25.13	10.46	40.00 -29.54 QP
3	188.413	14.30	1.71	27.22	24.30	13.09	43.50 -30.41 QP
4	381.249	20.91	2.52	27.08	23.66	20.01	46.00 -25.99 QP
5	699.305	25.93	3.54	27.73	24.78	26.52	46.00 -19.48 QP
6 q	952.094	28.17	4.26	26.39	24.46	30.50	46.00 -15.50 QP




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 26; Polarity: Vertical




Site : chamber
Condition: 3m VERTICAL
Job No. : 00592AT/00593AT
Test Mode: 26

		Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.638	20.90	0.68	27.79	25.57	19.36	40.00	-20.64	QP
2	58.819	11.61	0.94	27.71	32.09	16.93	40.00	-23.07	QP
3	102.001	12.33	1.24	27.58	32.29	18.28	43.50	-25.22	QP
4	396.242	20.68	2.57	27.14	24.63	20.74	46.00	-25.26	QP
5	682.348	25.80	3.49	27.77	24.24	25.76	46.00	-20.24	QP
6 q	965.542	28.06	4.29	26.30	30.14	36.19	54.00	-17.81	QP



Test Mode: 26; Polarity: Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00592AT\00593AT
Mode : RSE TX


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1206.682	5.46	24.49	54.68	56.68	31.95	74.00	-42.05	Peak
2	2400.753	5.38	29.10	54.95	56.25	35.78	74.00	-38.22	Peak
3	4367.058	7.05	34.54	54.26	55.47	42.80	74.00	-31.20	Peak
4	7898.049	8.90	36.50	53.11	53.06	45.35	74.00	-28.65	Peak
5	11467.000	12.09	37.77	53.10	52.31	49.07	74.00	-24.93	Peak
6	q17793.090	14.74	43.89	52.50	37.64	43.77	54.00	-10.23	Average
7	p17793.090	14.74	43.89	52.50	48.81	54.94	74.00	-19.06	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 26; Polarity: Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 00592AT\00593AT
Mode : RSE TX

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1062.578	5.79	24.45	54.63	57.12	32.73	74.00	-41.27	Peak
2	2400.753	5.38	29.10	54.95	58.25	37.78	74.00	-36.22	Peak
3	4304.400	7.00	34.04	54.27	55.79	42.56	74.00	-31.44	Peak
4	7898.049	8.90	36.50	53.11	53.24	45.53	74.00	-28.47	Peak
5	13481.720	13.24	38.80	53.05	52.09	51.08	74.00	-22.92	Peak
6	p17948.050	14.78	44.09	52.43	48.98	55.42	74.00	-18.58	Peak
7	q17948.050	14.78	44.09	52.43	37.59	44.03	54.00	-9.97	Average



Test Mode:26; Polarity: Horizontal




Site : chamber
Condition: 1m HORIZONTAL
Job No : 00592AT\00593AT
Mode : RSE TX
Note :

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	19126.190	6.08	36.90	54.88	58.61	46.71	83.54	-36.83 Peak
2	23055.610	6.59	36.87	52.56	55.46	46.36	83.54	-37.18 Peak
3	26030.850	7.48	39.06	52.11	52.86	47.29	83.54	-36.25 Peak
4	29910.890	7.35	39.68	53.04	52.72	46.71	83.54	-36.83 Peak
5	33689.970	7.84	40.32	52.05	51.77	47.88	83.54	-35.66 Peak
6	39492.210	7.52	42.69	52.15	51.45	49.51	83.54	-34.03 Peak



Test Mode: 26; Polarity: Vertical



Site : chamber
Condition: 1m VERTICAL
Job No : 00592AT\00593AT
Mode : RSE TX
Note :

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 18793.130	5.81	36.87	54.72	59.40	47.36	83.54	-36.18	Peak
2 23166.340	6.60	37.00	52.87	56.61	47.34	83.54	-36.20	Peak
3 27571.290	7.14	38.56	52.47	54.21	47.44	83.54	-36.10	Peak
4 p32216.670	8.03	40.17	52.17	53.06	49.09	83.54	-34.45	Peak
5 37464.800	7.65	42.20	50.63	49.40	48.62	83.54	-34.92	Peak
6 39968.070	7.73	43.16	51.82	50.00	49.07	83.54	-34.47	Peak



7.4 Radiated emissions outside assigned band and above 40 GHz up to 200 GHz

Test Requirement 47 CFR Part 15C Section 15.255 (d)(3)

Test Method: ANSI C63.10-2020 Section 9.10

Limit:

Above 40GHz:

Frequency (GHz)	Power density at 3 m distance (pW/cm ²)	Distance (m)	Field strength (dBuV/m)*, peak	Field strength (dBuV/m)*, average
40 - 200	90	3.0	105.31	85.31
40 - 200	90	1.0	114.85**	94.85**
* - Field strength was calculated per equation (26) of ANSI C63.10-2020 section 9 as follows: $E = \sqrt{PD \times 377}$, where PD is the power density at the distance specified by the limit in W/m², E- field strength in V/m. ** - The limit for other test distance was calculated using the inverse distance extrapolation factor as follows: $LimS2 = LimS1 + 20 \log (S1/S2)$, where S1 and S2 - standard defined and test distance respectively in meters.				

7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 23.2 °C Humidity: 45.8 % RH Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	26	TX mode _ Keep the EUT in continuously transmitting mode



7.4.3 Test Setup Diagram




7.4.4 Measurement Procedure and Data

- For above 40GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 1 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to the same height (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Test Mode: 26; Polarity: Horizontal



Test Mode: 26; Polarity: Vertical



Frequency (GHz)	Distance (M)	PK Value (dBuV/m)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Polarization	Result
44.807	1	68.886	114.85	94.85	H	PASS
44.849	1	68.764	114.85	94.85	V	PASS




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 26; Polarity: Horizontal




Test Mode: 26; Polarity: Vertical




Frequency (GHz)	Distance (M)	PK Value (dBuV/m)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Polarization	Result
69.055	1	68.045	114.85	94.85	H	PASS
68.808	1	68.353	114.85	94.85	V	PASS

Test Mode: 26; Polarity: Horizontal




Test Mode: 26; Polarity: Vertical




Frequency (GHz)	Distance (M)	PK Value (dBuV/m)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Polarization	Result
94.372	1	73.697	114.85	94.85	H	PASS
82.948	1	73.613	114.85	94.85	V	PASS

Test Mode: 26; Polarity: Horizontal



Test Mode: 26; Polarity: Vertical



Frequency (GHz)	Distance (M)	PK Value (dBuV/m)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Polarization	Result
132.753	1	76.243	114.85	94.85	H	PASS
134.102	1	75.600	114.85	94.85	V	PASS




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 26; Polarity: Horizontal




Test Mode: 26; Polarity: Vertical




Frequency (GHz)	Distance (M)	PK Value (dBuV/m)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Polarization	Result
156.829	1	76.759	114.85	94.85	H	PASS
157.175	1	76.472	114.85	94.85	V	PASS

Test Mode: 26; Polarity: Horizontal



Test Mode: 26; Polarity: Vertical



Frequency (GHz)	Distance (M)	PK Value (dBuV/m)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Polarization	Result
206.258	1	72.613	114.85	94.85	H	PASS
170.392	1	72.859	114.85	94.85	V	PASS

7.5 Frequency Stability

Test Requirement 47 CFR Part 15C Section 15.255 (f)
Test Method: ANSI C63.10-2020 Section 9.5

Limit:

Frequency (GHz)	Limit
57 - 64	The signal must be contained within assigned frequency band.

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 21.4 °C Humidity: 47.4 % RH Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	26	TX mode _ Keep the EUT in continuously transmitting mode

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

1. Temperature conditions:

- a) The RF output port of the EUT was connected to Frequency Meter;
- b) Set the EUT in continuously transmitting mode;
- c) record the 20°C and nominal voltage frequency value as reference point;
- d) vary the temperature from -20°C to 40°C with step 10°C
- e) when reach a temperature point, keep the temperature maintain at least 1 hour to make the product working in this status;
- f) read the frequency at the relative temperature.

2. Voltage conditions:

- a) record the 20°C and nominal voltage frequency value as reference point;
 - b) vary the voltage from -10% nominal voltage to +10% voltage;
- read the frequency at the relative voltage.

Remark: Manufacturer declared that the minimum temperature for normal operation of this product is 0°C.

Please Refer to Appendix for Details



8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2502000592AT

9 EUT Constructional Details (EUT Photos)


Refer to Appendix – External and Internal Photos for SZCR2502000592AT




10 Appendix

1. Transmitter power and Transmitter off-times

Peak Power



AV Power



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250200059204

Page: 37 of 43

Frequency (GHz)	dBuV/m @ 1m	Mesured EIRP (dBm)	Desensitization Factor(dB)	Final EIRP (dBm)	EIRP Limit (dBm)	Result	Remark
59.028	114.569	3.7784	14.978	18.757	20	Pass	Peak
	86.097	-24.6936	14.978	-9.7153	20	Pass	Average

Remark:

$E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{meters}]) + 104.77$, where E = field strength and d = distance at which field strength limit is specified in the rules

$\text{EIRP}[\text{dBm}] = E[\text{dB}\mu\text{V/m}] + 20 \log(d[\text{meters}]) - 104.77$

$\text{Final EIRP}[\text{dBm}] = \text{Mesured EIRP}[\text{dBm}] + \text{Desensitization Factor}[\text{dB}]$

The FMCW Desensitization factor

FMCW Width(MHz)	$T_{\text{chirp}}(\mu\text{s})$	RBW(MHz)	Desensitization Factor(lin)	Desensitization Factor(dB)
4703.8	66	1	0.0318	14.978

FMCW desensitization factor $= -10 \cdot \log(\alpha) = -10 \cdot \log(0.0318) = 14.978\text{dB}$

$$\alpha = \frac{1}{\sqrt{1 + \left(\frac{2 \ln(2)}{\pi}\right)^2 \left(\frac{BW_{\text{Chirp}}}{T_{\text{Chirp}} B^2}\right)^2}}$$

where

α is the reduction in amplitude

F_s is the FMCW Chirp Bandwidth

T_s is the FMCW Chirp Time

B is the 3 dB IF Bandwidth = RBW




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory


Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Transmitter off-times (ms)









Frequency (GHz)	Transmitter off-times in 33ms	Limit (ms)	Result
61.5	32.78	≥ 16.5	Pass

Note: burst number within 33ms is 2, the total time between the two bursts is 1.22ms, which is less than 2ms.

2. Occupied bandwidth

99% Occupied Channel Bandwidth



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250200059204

Page: 42 of 43

Frequency Range (GHz)	99% OCW (GHz)	F _L (GHz)	Limit (GHz)	F _H (GHz)	Limit (GHz)	Result
57-64	4.7038	59.08	57	63.81	64	Pass

Remark: F_L: Frequency Low Band Edge, F_H: Frequency High Band Edge



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3. Frequency stability

Frequency Stability vs temperature:

1. Test for 57GHz to 64GHz

Frequency (GHz)	Temperature (°C)	Voltage (V DC)	F _L (GHz)	Limit (GHz)	F _H (GHz)	Limit (GHz)	Result
57-64	40	3.6	59.084	57	62.816	64	Pass
	30	3.6	59.082	57	62.813	64	Pass
	20	3.6	59.081	57	63.811	64	Pass
	10	3.6	59.079	57	63.807	64	Pass
	0	3.6	59.077	57	62.805	64	Pass
	-10	3.6	59.076	57	62.804	64	Pass
	-20	3.6	59.075	57	62.802	64	Pass

Frequency Stability vs voltage:

1. Test for 57GHz to 64GHz

Frequency (GHz)	Voltage (V DC)	Temperature (°C)	F _L (GHz)	Limit (GHz)	F _H (GHz)	Limit (GHz)	Result
57-64	3.24	20	59.086	57	62.814	64	Pass
	3.6	20	59.083	57	63.812	64	Pass
	3.96	20	59.079	57	63.809	64	Pass

Remark:

F_L: Frequency Low Band Edge, F_H: Frequency High Band Edge

- End of the Report -