



FCC ID:2AUIX-E8

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	2.22	1.67	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	2.47	1.77	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	2.21	1.66	2±1	3.00	2.00	<5	0.62843	3.00	YES
Pi/4 DQPSK	2.402	2.98	1.99	3±1	4.00	2.51	<5	0.77860	3.00	YES
	2.441	3.78	2.39	3±1	4.00	2.51	<5	0.78490	3.00	YES
	2.480	3.42	2.20	3±1	4.00	2.51	<5	0.79114	3.00	YES
8DPSK	2.402	3.22	2.10	3±1	4.00	2.51	<5	0.77860	3.00	YES
	2.441	4.05	2.54	3±1	4.00	2.51	<5	0.78490	3.00	YES
	2.480	3.7	2.34	3±1	4.00	2.51	<5	0.79114	3.00	YES

Conclusion:

For the max result : $0.79114\text{W/Kg} \leq \text{FCC Limit } 3.0$ for 1g SAR.