

Maximum Permissible Exposure Evaluation

FCC ID: 2AUJC-SA-003

1. Client Information

Applicant	:	ShenZhen ZYtec Co., Ltd.
Address	:	8512, 5th Floor, Building 8, Banlihuahui, 32 Tongsha Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China
Manufacturer	:	ShenZhen ZYtec Co., Ltd.
Address	:	8512, 5th Floor, Building 8, Banlihuahui, 32 Tongsha Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China

2. General Description of EUT

EUT Name	:	Zigbee OnOff Controller	
Models No.	:	SA-003-Zigbee	
Model Difference	:	N/A	
Product Description	:	Operation Frequency:	Zigbee: 2405MHz~2480MHz
		Max Output Power:	Zigbee: -1.614 dBm
		Antenna Gain:	1dBi PCB Antenna
Power Supply	:	I Input: AC 85-265V Output: AC 85-265V	
Software Version	:	V1.0.2	
Hardware Version	:	V3.1	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

MPE Calculations for Zigbee

1. Antenna Gain:

Zigbee: 1dBi PCB Antenna

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
Zigbee	-1.614	-1.614±1	-0.614	1	20	0.00022

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For Zigbee:2405-2480 MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as $0.00022\text{mW} / \text{cm}^2 < \text{limit } 1\text{mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----