

FCC PART 22H, PART 24E
MEASUREMENT AND TEST REPORT
For
WEB SALES AND MARKETING LLC

11510 QUEENS BLVD STE LL1, FOREST HILLS, New York 11375 United States

FCC ID: 2AUJQ911Q

Report Type: Original Report	Product Type: 911 calling device
Test Engineer: Jack Jiao <i>Jack Jiao</i>	
Report Number: RXM190925051-00A	
Report Date: 2019-10-18	
Reviewed By:	Oscar Ye <i>Oscar Ye</i> EMC Manager
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
CHANNEL LIST	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS.....	7
TEST EQUIPMENT LIST	8
FCC §1.1307(B) & §2.1093 - RF EXPOSURE INFORMATION.....	10
TEST RESULT	10
FCC §2.1047 - MODULATION CHARACTERISTIC	11
FCC §2.1046; § 22.913 (A); § 24.232 (C); - RF OUTPUT POWER.....	12
APPLICABLE STANDARDS.....	12
TEST PROCEDURE	12
TEST DATA	13
FCC §2.1049, §22.917, §22.905 & §24.238; - OCCUPIED BANDWIDTH.....	15
APPLICABLE STANDARDS.....	15
TEST PROCEDURE	15
TEST DATA	15
FCC § 2.1051; § 22.917 (A); § 24.238 (A); - SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	18
APPLICABLE STANDARDS.....	18
TEST PROCEDURE	18
TEST DATA	18
FCC § 2.1053; § 22.917 (A); § 24.238 (A); - SPURIOUS RADIATED EMISSIONS.....	21
APPLICABLE STANDARDS.....	21
TEST PROCEDURE	21
TEST DATA	22
FCC § 22.917 (A); § 24.238 (A); - BAND EDGES	23
APPLICABLE STANDARDS.....	23
TEST PROCEDURE	23
TEST DATA	23
FCC § 2.1055; § 22.355; § 24.235; - FREQUENCY STABILITY	26
APPLICABLE STANDARDS.....	26
TEST PROCEDURE	26
TEST DATA	27

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	WEB SALES AND MARKETING LLC
Tested Model	911Q
Product Type	911 calling device
Dimension	75mm(L)* 52mm(W)* 17mm(H)
Power Supply	DC 4.5V from battery

**All measurement and test data in this report was gathered from production sample serial number: 20190925051. (Assigned by the BACL. The EUT supplied by the applicant was received on 2019-09-25)*

Objective

This type approval report is prepared on behalf of *WEB SALES AND MARKETING LLC* in accordance with Part 2, Part 22-Subpart H and Part 24-Subpart E of the Federal Communication Commission's rules.

The objective is to determine the compliance of EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, and band edge.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-Part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	5.91dB
	1GHz~6GHz	4.68dB
	6GHz~18GHz	4.92dB
	18GHz~40GHz	5.21dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D.

The final qualification test was performed with the EUT operating at normal mode.

Channel List

Mode	Channel		Frequency (MHz)
GSM 850	Low	128	824.2
	Middle	190	836.6
	High	251	848.8
PCS 1900	Low	512	1850.2
	Middle	661	1880.0
	High	810	1909.8

Equipment Modifications

No modifications were made to the EUT.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Waylens Inc.	Antenna	/	/
Rohde & Schwarz	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	110605

External I/O Cable


Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307(b)(1)& §2.1093	RF Exposure Information	Compliant
§2.1046; § 22.913 (a);§ 24.232 (c);	RF Output Power	Compliant
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905; § 22.917; § 24.238;	Occupied Bandwidth	Compliant
§ 2.1051; § 22.917 (a); § 24.238 (a);	Spurious Emissions at Antenna Terminal	Compliant
§ 2.1053; § 22.917 (a); § 24.238 (a);	Spurious Radiated Emissions	Compliant
§ 22.917 (a); § 24.238 (a);	Band Edge	Compliant
§ 2.1055; § 22.355; § 24.235;	Frequency stability	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2018-11-30	2019-11-29
HP	Signal Generator	HP 8341B	2624A00116	2018-11-30	2019-11-29
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sunol Sciences	Bilog antenna	JB3	A060217	2017-08-04	2020-08-03
Sonoma Instrunent	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Rohde & Schwarz	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	110605	2018-11-12	2019-11-11
Radiated Emission Test (Chamber 2#)					
HP	Signal Generator	HP 8341B	2624A00116	2018-11-30	2019-11-29
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2019-08-27	2020-08-26
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2019-08-27	2020-08-26
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3115	6229	2016-12-12	2019-12-11
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-12-12	2019-12-11
ETS-LINDGREN	Horn Antenna	3116	2516	2016-12-12	2019-12-11
A.H.Systems, inc	Amplifier	2641-1	491	2019-02-20	2020-02-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2019-03-22	2020-03-21
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-16	016	2019-08-15	2020-08-14
Rohde & Schwarz	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	110605	2018-11-12	2019-11-11

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2018-11-30	2019-11-29
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2019-07-23	2020-07-22
Narda	Attenuator	6dB	006	2019-01-10	2020-01-09
Rohde & Schwarz	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	110605	2018-11-12	2019-11-11
Mini-Circuits	Power splitter	ZFRSC-14-S+	SF019411452	2018-11-10	2019-11-09
BACL	Temperature & Humidity Chamber	BTH-150	30023	2019-10-10	2020-10-09
EAST	Regulated DC Power Supply	MCH-303D-II	14070562	2019-10-10	2020-10-09
WEB SALES AND MARKETING LLC	RF Cable	WEB SALES AND MARKETING LLC C01	C01	Each Time	/

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

FCC§1.1307,§2.1093.

Test Result

Compliant, please refer to the SAR report: RXM190925052-SA.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC §2.1046; § 22.913 (a); § 24.232 (c); - RF OUTPUT POWER

Applicable Standards

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts (38.45dBm).


According to FCC §2.1046 and §24.232 (c), mobile and portable stations are limited to 2 watts (33dBm) EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the CMU200 through sufficient attenuation.



Radiated Output Power:

The measurements procedures specified in ANSI/TIA-603-D were applied.

- a) Connect the equipment as illustrated. Mount the equipment with the manufacturer specified antenna in a vertical orientation on a manufacturer specified mounting surface located on a non-conducting rotating platform of a RF anechoic chamber (preferred) or a standard radiation site.
- b) Key the transmitter, then rotate the EUT 360o azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. (Note: several batteries may be needed to offset the effect of battery voltage droop, which should not exceed 5% of the manufactured specified battery voltage during transmission).
- c) Replace the transmitter under test with a vertically polarized half-wave dipole (or an antenna whose gain is known relative to an ideal half-wave dipole). The center of the antenna should be at the same location as the center of the antenna under test.
- d) Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading.
$$\text{LOSS} = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$$
- e) Determine the effective radiated output power at each angular position from the readings in steps b) and d) using the following equation:
$$\text{ERP (dBm)} = \text{LVL (dBm)} + \text{LOSS (dB)}$$
- f) The maximum ERP is the maximum value determined in the preceding step.

(Note: Effective Isotropic Radiated Power (EIRP) can be computed using the following:
 $EIRP \text{ (dBm)} = ERP \text{ (dBm)} + 2.15 \text{ (dB)}$

Test Data

Environmental Conditions

Temperature:	23.7 °C
Relative Humidity:	51 %
ATM Pressure:	102.3 kPa

The testing was performed by Jack Jiao on 2019-10-16.

Conducted Power:

GSM 850 Band

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	128	824.2	32.98	38.45
	190	836.6	32.72	38.45
	251	848.8	32.55	38.45

PCS 1900 Band

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	29.03	33.00
	661	1880.0	29.17	33.00
	810	1909.8	29.31	33.00

Peak-to-average ratio (PAR):**GSM 850**

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	2.30	13.00
	Middle	2.40	13.00
	High	2.50	13.00

PCS 1900

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	2.30	13.00
	Middle	2.50	13.00
	High	2.60	13.00

ERP:**GSM 850 Mode**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (cm)	Polar (H/V)	Submitted Level (dBm)	Cable loss (dB)	Antenna Gain (dBd/dBi)			
Cellular Band (Part 22H), Middle Channel										
836.60	98.27	124	150	H	34.58	0.63	-1.1	32.85	38.45	5.60
836.60	98.58	156	200	V	31.43	0.63	-1.1	29.70	38.45	8.75

EIRP:**PCS1900 Mode**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (cm)	Polar (H/V)	Submitted Level (dBm)	Cable loss (dB)	Antenna Gain (dBd/dBi)			
PCS Band (Part 24E), Middle Channel										
1880.00	82.38	228	150	H	14.50	0.85	8.8	22.45	33.00	10.55
1880.00	82.79	134	150	V	14.48	0.85	8.8	22.43	33.00	10.57


FCC §2.1049, §22.917, §22.905 & §24.238; - OCCUPIED BANDWIDTH**Applicable Standards**

FCC 47 §2.1049, §22.917, §22.905 & §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 5 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.

**Test Data****Environmental Conditions**

Temperature:	23.2 °C
Relative Humidity:	51 %
ATM Pressure:	103.3 kPa

The testing was performed by Jack Jiao on 2019-10-15.

EUT operation mode: Transmitting

Test Result: Compliant.

GSM 850

Mode	Frequency (MHz)	26 dB Emission Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GSM	836.6	0.311	0.242

PCS 1900

Mode	Frequency (MHz)	26 dB Emission Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GSM	1880.0	0.319	0.244

99% Occupied & 26 dB Emissions Bandwidth for GSM Mode



99% Occupied & 26 dB Emissions Bandwidth for GSM Mode




FCC § 2.1051; § 22.917 (a); § 24.238 (a); - SPURIOUS EMISSIONS AT ANTENNA TERMINALS**Applicable Standards**

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for below 1GHz & 1MHz for above 1GHz. sufficient scans were taken to show any out of band emissions up to 10th harmonic.



**Test Data****Environmental Conditions**

Temperature:	23.5 °C
Relative Humidity:	51 %
ATM Pressure:	103.3 kPa

The testing was performed by Jack Jiao on 2019-10-15.


EUT operation mode: Transmitting

Test Result: Compliant.


GSM 850 Band:**30 MHz – 1GHz(GSM Mode)****1 GHz – 10 GHz (GSM Mode)**

PCS 1900 Band:

30 MHz – 1GHz(GSM Mode)



1 GHz – 20 GHz (GSM Mode)



FCC § 2.1053; § 22.917 (a); § 24.238 (a); - SPURIOUS RADIATED EMISSIONS

Applicable Standards

FCC § 2.1053, §22.917(a) and § 24.238(a).

22.917 (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

24.238 (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TX pwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \text{Log}_{10} (\text{power out in Watts})$

Test Data**Environmental Conditions**

Temperature:	23.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

The testing was performed by Jack Jiao on 2019-10-16.

Test mode: Transmitting (Pre-scan with low, middle and high channels, and the worse case data as below)

30 MHz ~ 10 GHz:**GSM 850 Band**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (cm)	Polar (H/V)	Submitted Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd/dBi)			
GSM Mode, Middle channel										
280.02	33.42	67	200	H	-71.48	0.45	-2.2	-74.13	-13.00	61.13
280.02	35.69	321	100	V	-71.81	0.45	-2.2	-74.46	-13.00	61.46
1673.20	53.54	192	100	H	-49.85	0.84	8.5	-42.19	-13.00	29.19
1673.20	50.57	35	200	V	-53.32	0.84	8.5	-45.66	-13.00	32.66
2509.80	50.42	154	100	H	-50.52	0.89	10.1	-41.31	-13.00	28.31
2509.80	48.06	181	200	V	-52.89	0.89	10.1	-43.68	-13.00	30.68

30 MHz ~ 20 GHz:**PCS 1900 Band**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (cm)	Polar (H/V)	Submitted Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd/dBi)			
GSM Mode, Middle channel										
280.02	36.61	230	200	H	-68.29	0.45	-2.2	-70.94	-13.00	57.94
280.02	36.12	25	150	V	-71.38	0.45	-2.2	-74.03	-13.00	61.03
3760.00	37.92	191	150	H	-58.79	0.95	9.7	-50.04	-13.00	37.04
3760.00	36.19	172	200	V	-61.11	0.95	9.7	-52.36	-13.00	39.36
5640.00	31.24	97	200	H	-62.69	1.15	10.5	-53.34	-13.00	40.34
5640.00	29.53	89	100	V	-64.43	1.15	10.5	-55.08	-13.00	42.08

FCC § 22.917 (a); § 24.238 (a); - BAND EDGES**Applicable Standards**


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency.

**Test Data****Environmental Conditions**

Temperature:	23.5 °C
Relative Humidity:	51 %
ATM Pressure:	103.3 kPa


The testing was performed by Jack Jiao on 2019-10-15.

EUT operation mode: Transmitting


Test Result: Compliant.

GSM 850 Band:

GSM Mode, Left Band Edge




GSM Mode, Right Band Edge




PCS 1900 Band:

GSM Mode, Left Band Edge



GSM Mode, Right Band Edge



FCC § 2.1055; § 22.355; § 24.235; - FREQUENCY STABILITY

Applicable Standards

FCC § 2.1055, §22.355, §24.235.

According to FCC §2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile > 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Data**Environmental Conditions**

Temperature:	23.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

The testing was performed by Jack Jiao on 2019-10-16.

EUT operation mode: Transmitting

Test Result: Compliant.

GSM 850 Band

GSM Mode, Middle Channel, f_0 = 836.6 MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	4.5	-2	-0.0024	2.5
-20		5	0.0060	2.5
-10		3	0.0036	2.5
0		-1	-0.0012	2.5
10		8	0.0096	2.5
20		-2	-0.0024	2.5
30		9	0.0108	2.5
40		6	0.0072	2.5
50		8	0.0096	2.5
25	V min. = 3.7	1	0.0012	2.5
25	V max. = 5.4	3	0.0036	2.5

PCS 1900 Band

GSM Mode, Middle Channel, f_0 =1880.0 MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	4.5	5	0.0027	pass
-20		7	0.0037	pass
-10		7	0.0037	pass
0		1	0.0005	pass
10		11	0.0059	pass
20		2	0.0011	pass
30		-1	-0.0005	pass
40		4	0.0021	pass
50		7	0.0037	pass
25	V min.= 3.7	5	0.0027	pass
25	V max.= 5.4	1	0.0005	pass

******* END OF REPORT *******