

FCC SAR Exclusion Report

Product name : Wireless Rootzone Sensor
Applicant : Rockwool B.V. / Grodan
FCC ID : 2AUKP-RZ001

Test report No. : 190800839 FCC RF exposure Ver 1.0



Report number: 190800839 FCC RF exposure Ver 1.0

Laboratory information

Accreditation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2005. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

The Industry Canada registration number for the 3 meter test chamber of Telefication is: 4173A-1.

Telefication is a registered Conformity Assessment body (CAB) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

Testing Location

Test Site	Telefication BV
Test Site location	Edisonstraat 12a 6902 PK Zevenaar The Netherlands Tel. +31889983600 Fax. +31316583189



Report number: 190800839 FCC RF exposure Ver 1.0

Revision History

Version	Date	Remarks	By
v1.0	09-12-2019	Release version	PvW



Report number: 190800839 FCC RF exposure Ver 1.0

Table of Contents

Revision History	2
1 General Description	4
1.1 Applicant	4
1.2 Manufacturer	4
1.3 Tested Equipment Under Test (EUT).....	4
1.4 SAR Measurement Evaluation.....	5
1.4.1 Maximum Output Power	5
1.4.2 SAR Testing Exclusions.....	5
1.5 Summary	5



Report number: 190800839 FCC RF exposure Ver 1.0

1 General Description

1.1 Applicant

Client name: ROCKWOOL B.V. / Grodan
Address: Industrieweg 15, Roermond, the Netherlands
Zip code: 6045 JG
Telephone: +31 475 353846
E-mail: Paul.bouwens@grodan.com
Contact name: Mr. Paul Bouwens

1.2 Manufacturer

Manufacturer name: ROCKWOOL B.V. / Grodan
Address: Industrieweg 15, Roermond, the Netherlands
Zip code: 6045 JG
Telephone: +31 475 353846
E-mail: Paul.bouwens@grodan.com
Contact name: Mr. Paul Bouwens

1.3 Tested Equipment Under Test (EUT)

Product name: Wireless Climate Sensor
Brand name: Grodan
Product type: Wireless Climate Sensor with CO2
FCC ID: 2AUKP-CLC001
IC ID 25447-CLC001
Software version: 1.01
Hardware version: CLC001
CL001

1.4 SAR Measurement Evaluation

1.4.1 Maximum Output Power

The maximum radiated power including tune-up tolerance is shown as below.

Mode	Technology
Bluetooth LE	-14.46 dBm
LoRa	18.82 dBm

* from Telefication report 190800839

Note: BLE and LoRa do not transmit simultaneously.

1.4.2 SAR Testing Exclusions

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

1. For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at } 50 \text{ mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$

3. For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at } 50 \text{ mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Ant. to Surface (mm)	Calculated threshold (mW)	Require SAR Testing?
LoRa	18.82	76.2	200	915	No
BLE	-14.46	0.04	200	1503	No

Note:

1. When separation distance ≤ 50 mm and the calculated result shown in above table is ≤ 3.0 , the SAR testing exclusion is applied.
2. When separation distance > 50 mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.

1.5 Summary

Since the SAR testing for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.