

RF Exposure Evaluation Report

1 RF EXPOSURE

Product Name: automatic pet feeder
 Model No.: T2
 FCC ID: 2AUN9-T2

2. RF Exposure Evaluation

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices.

2.1 LIMITS

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1 to § 1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842/f	4.89/f	*(900/f ²)	<6
30–300	61.4	0.163	1.0	<6
300–1,500			f/300	<6
1,500–100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824/f	2.19/f	*(180/f ²)	<30
30–300	27.5	0.073	0.2	<30
300–1,500			f/1500	<30
1,500–100,000			1.0	<30

F= Frequency in MHz Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$ Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2 EUT RF EXPOSURE EVALUATION

BT and WIFI ANT: 2.54dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.7947 in linear scale.

The Max Conducted Peak Output Power data refer to report Report No.: POCE240314009RL001& POCE240314009RL002

BT mode and channel:

Test channel	Conducted Power(dBm)	Tune-up Power (dbm)	Maximum tune-up Power (dbm)	Maximum tune-up Power (mW)	Calculated value (mW/cm ²)	Limit (mW/cm ²)	Result
2402.00	3.32	3.0±1	4.0	2.512	0.0009	1.0	Pass
2440.00	3.53	3.0±1	4.0	2.512	0.0009	1.0	Pass
2480.00	2.96	3.0±1	4.0	2.512	0.0009	1.0	Pass

Remark: Pd = (Pout*G)/(4* Pi * R²)=(2.512*1.7947)/(4*3.1415*20*20)= 0.0009 , G=10^{gain/10} =1.7947

2.4GWIFI worst mode and channel:

Test channel	Conducted Power(dBm)	Tune-up Power (dbm)	Maximum tune-up Power (dbm)	Maximum tune-up Power (mW)	Calculated value (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b-2412MHz	18.75	18.0±1	19.0	79.4328	0.0284	1.0	Pass
802.11b-2437MHz	18.05	18.0±1	19.0	79.4328	0.0284	1.0	Pass
802.11b-2462MHz	18.67	18.0±1	19.0	79.4328	0.0284	1.0	Pass

Remark: Pd = (Pout*G)/(4* Pi * R²)=(79.4328*1.7947)/(4*3.1415*20*20)= 0.0284 , G=10^{gain/10} =1.7947

EUT RF Exposure Evaluation simultaneous transmission operations

According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits :

Simultaneous transmission mode	The sum of the ratios	SUM	Limit
2.4G WIFI + BT	0.0009+ 0.0284	0.0293	1.0

Conclusion: 0.0293 < 1.0, So there is no sar requirement

NOTE:1. EUT RF module is more than 20cm away from the human body.

2.The sum of the ratios(2.4GWIFI + BT) is less than the limit value of 1.0, so there is no sar requirement.