



# FCC RADIO TEST REPORT

**FCC ID** : 2AUPE-8959  
**Equipment** : Digital Media Receiver  
**Model Name** : T4E4AT  
**Applicant** : Turley White LLC  
35 Village Road, Suite 100  
Middleton, MA 01949  
United States  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on May 07, 2020 and testing was started from May 21, 2020 and completed on Jul. 08, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report.....</b>	<b>3</b>
<b>Summary of Test Result.....</b>	<b>4</b>
<b>1 General Description.....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT .....	5
1.4 Testing Location .....	6
1.5 Applicable Standards.....	6
<b>2 Test Configuration of Equipment Under Test.....</b>	<b>7</b>
2.1 Carrier Frequency Channel .....	7
2.2 Test Mode .....	8
2.3 Connection Diagram of Test System .....	9
2.4 Support Unit used in test configuration and system .....	10
2.5 EUT Operation Test Setup .....	11
2.6 Measurement Results Explanation Example.....	11
<b>3 Test Result.....</b>	<b>12</b>
3.1 6dB and 99% Bandwidth Measurement .....	12
3.2 Output Power Measurement.....	19
3.3 Power Spectral Density Measurement .....	20
3.4 Conducted Band Edges and Spurious Emission Measurement .....	27
3.5 Radiated Band Edges and Spurious Emission Measurement .....	36
3.6 AC Conducted Emission Measurement.....	41
3.7 Antenna Requirements.....	43
<b>4 List of Measuring Equipment .....</b>	<b>44</b>
<b>5 Uncertainty of Evaluation.....</b>	<b>46</b>
<b>Appendix A. Conducted Test Results</b>	
<b>Appendix B. AC Conducted Emission Test Result</b>	
<b>Appendix C. Radiated Spurious Emission</b>	
<b>Appendix D. Radiated Spurious Emission Plots</b>	
<b>Appendix E. Duty Cycle Plots</b>	



## History of this test report



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)
3.1	15.247(a)(2)	6dB Bandwidth	Pass
3.1	2.1049	99% Occupied Bandwidth	Reporting only
3.2	15.247(b)(3)	Output Power	Pass
3.3	15.247(e)	Power Spectral Density	Pass
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass
3.6	15.207	AC Conducted Emission	Pass
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Wii Chang****Report Producer: Vivian Hsu**



## 1 General Description

### 1.1 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Digital Media Receiver
<b>Model Name</b>	T4E4AT
<b>FCC ID</b>	2AUPE-8959
<b>EUT supports Radios application</b>	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE Zigbee/FSK/LoRa

### 1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Frequency Range</b>	2402 MHz ~ 2480 MHz
<b>Number of Channels</b>	40
<b>Carrier Frequency of Each Channel</b>	40 Channel (37 hopping + 3 advertising channel)
<b>Maximum Output Power to Antenna</b>	5.90 dBm (0.0039 W) for 1Mbps 5.90 dBm (0.0039 W) for 2Mbps
<b>99% Occupied Bandwidth</b>	1.040MHz for 1Mbps 2.080MHz for 2Mbps
<b>Antenna Type / Gain</b>	Inverted F type Antenna with gain 2.34 dBi
<b>Type of Modulation</b>	Bluetooth LE : GFSK

### 1.3 Modification of EUT

No modifications are made to the EUT during all test items.



## 1.4 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	03CH16-HY	

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

## 1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-



## 2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in two degrees (0 and 40). The worst cases (Degree 40) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + Zigbee Link + Motor + Adapter + H-Pattern + Audio + Display 40 Mode 2: Lora Tx + Adapter + Display 40


**Remark:** The worst case of conducted emission is mode 2; only the test data of it was reported.

## 2.3 Connection Diagram of Test System


### <AC Conducted Emission with WLAN(2.4GHz)/Bluetooth/Zigbee Mode>



### <AC Conducted Emission Lora Tx Mode>



## &lt;Bluetooth - LE Tx Mode&gt;



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
2.	Notebook	DELL	Latitude E3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Zigbee Bulb	OSRAM	73674	DZO-IQHOME	N/A	N/A
4.	Bluetooth Earphone	Sony Ericsson	MW600	PY700A2029	N/A	N/A



## 2.5 EUT Operation Test Setup

The RF test items, utility “Compliance v1.0.0.80” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

*Offset(dB) = RF cable loss(dB) + attenuator factor(dB).*

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW)  $\geq 3 * \text{RBW}$ .
6. Measure and record the results in the test report.

##### 3.1.4 Test Setup




### 3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


**<1Mbps>**

#### 6 dB Bandwidth Plot on Channel 00




Date: 19.JUN.2020 06:58:33

#### 6 dB Bandwidth Plot on Channel 19



Date: 19.JUN.2020 07:03:48


## 6 dB Bandwidth Plot on Channel 39



Date: 19.JUN.2020 07:08:57


## &lt;2Mbps&gt;

## 6 dB Bandwidth Plot on Channel 00




Date: 19.JUN.2020 07:15:01

## 6 dB Bandwidth Plot on Channel 19



Date: 19.JUN.2020 07:22:15

## 6 dB Bandwidth Plot on Channel 39




Date: 19.JUN.2020 07:28:41

### 3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


**<1Mbps>**

#### 99% Bandwidth Plot on Channel 00



Date: 19.JUN.2020 07:00:37


#### 99% Occupied Bandwidth Plot on Channel 19



Date: 19.JUN.2020 07:06:45




## 99% Occupied Bandwidth Plot on Channel 39



Date: 19.JUN.2020 07:07:45


&lt;2Mbps&gt;

## 99% Bandwidth Plot on Channel 00




Date: 19.JUN.2020 07:17:41

## 99% Occupied Bandwidth Plot on Channel 19



Date: 19.JUN.2020 07:24:41

## 99% Occupied Bandwidth Plot on Channel 39



Date: 19.JUN.2020 07:26:38

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup




#### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)


<1Mbps>

#### PSD 100kHz Plot on Channel 00



Date: 19.JUN.2020 06:59:09


#### PSD 100kHz Plot on Channel 19



Date: 19.JUN.2020 07:05:56




## PSD 100kHz Plot on Channel 39



Date: 19.JUN.2020 07:09:27

&lt;2Mbps&gt;


## PSD 100kHz Plot on Channel 00



Date: 19.JUN.2020 07:15:57




## PSD 100kHz Plot on Channel 19



Date: 19.JUN.2020 07:23:11

## PSD 100kHz Plot on Channel 39




Date: 19.JUN.2020 07:30:27

### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)


<1Mbps>

#### PSD 3kHz Plot on Channel 00



Date: 19.JUN.2020 06:58:52


#### PSD 3kHz Plot on Channel 19



Date: 19.JUN.2020 07:05:42




## PSD 3kHz Plot on Channel 39



Date: 19.JUN.2020 07:09:15

## &lt;2Mbps&gt;


## PSD 3kHz Plot on Channel 00



Date: 19.JUN.2020 07:15:19




## PSD 3kHz Plot on Channel 19



Date: 19.JUN.2020 07:22:41

## PSD 3kHz Plot on Channel 39



Date: 19.JUN.2020 07:30:03

## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


### 3.4.4 Test Setup



### 3.4.5 Test Result of Conducted Band Edges Plots


<1Mbps>

#### Low Band Edge Plot on Channel 00



Date: 19.JUN.2020 06:59:41


#### High Band Edge Plot on Channel 39



Date: 19.JUN.2020 07:10:12


&lt;2Mbps&gt;

## Low Band Edge Plot on Channel 00



Date: 19.JUN.2020 07:17:19


## High Band Edge Plot on Channel 39



Date: 19.JUN.2020 07:30:53


### 3.4.6 Test Result of Conducted Spurious Emission Plots

#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 19.JUN.2020 06:59:59


#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 19.JUN.2020 07:00:15




**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19**




Date: 19.JUN.2020 07:06:12

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19**




Date: 19.JUN.2020 07:06:27

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39**




Date: 19.JUN.2020 07:11:52

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39**




Date: 19.JUN.2020 07:12:08

### Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00




Date: 19.JUN.2020 07:16:49

### Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00




Date: 19.JUN.2020 07:17:05

### Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19




Date: 19.JUN.2020 07:24:04

### Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19




Date: 19.JUN.2020 07:24:21

**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps  
GFSK Channel 39**



Date: 19.JUN.2020 07:31:14

**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps  
GFSK Channel 39**



Date: 19.JUN.2020 07:31:38



## 3.5 Radiated Band Edges and Spurious Emission Measurement

### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.5.2 Measuring Instruments

See list of measuring equipment of this test report.



### 3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.

For average measurement:


- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



## For radiated emissions above 1GHz



## For radiated emissions above 18GHz





### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

### 3.5.7 Duty Cycle

Please refer to Appendix E.

### 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



## 3.6 AC Conducted Emission Measurement

### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


### 3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## 3.7 Antenna Requirements

### 3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### 3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

### 3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 09, 2020	May 21, 2020~Jun. 18, 2020	Jan. 08, 2021	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL6111D&0 0802N1D01N-06	47020&06	30MHz to 1GHz	Oct. 12, 2019	May 21, 2020~Jun. 18, 2020	Oct. 11, 2020	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1522	1G~18GHz	Sep. 19, 2019	May 21, 2020~Jun. 18, 2020	Sep. 18, 2020	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 980	18GHz~40GHz	Jan.10, 2020	May 21, 2020~Jun. 18, 2020	Jan. 09, 2021	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1G	Oct. 01, 2019	May 21, 2020~Jun. 18, 2020	Sep. 30, 2020	Radiation (03CH16-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	171000180 0055006	1GHz~18GHz	May 07, 2020	May 21, 2020~Jun. 18, 2020	May 06, 2021	Radiation (03CH16-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~40GHz	Dec. 13, 2019	May 21, 2020~Jun. 18, 2020	Dec. 12, 2020	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY532702 64	1GHz~26.5GHz	Dec. 11, 2019	May 21, 2020~Jun. 18, 2020	Dec. 10, 2020	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY572901 11	3Hz~26.5GHz	Dec. 05, 2019	May 21, 2020~Jun. 18, 2020	Dec. 04, 2020	Radiation (03CH16-HY)
Spectrum Analyzer	Agilent	E4446A	MY501801 36	3Hz~44GHz	May 04, 2020	May 21, 2020~Jun. 18, 2020	May 03, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11680/ 4PE	NA	Aug. 30, 2019	May 21, 2020~Jun. 18, 2020	Aug. 29, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11688/ 4PE	NA	Aug. 30, 2019	May 21, 2020~Jun. 18, 2020	Aug. 29, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	EC-A5-300 -5757	NA	Aug. 30, 2019	May 21, 2020~Jun. 18, 2020	Aug. 29, 2020	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	May 21, 2020~Jun. 18, 2020	N/A	Radiation (03CH16-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	May 30, 2020~Jul. 08, 2020	Mar. 01, 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054S NO10	10MHz~6GHz	Dec. 23, 2019	May 30, 2020~Jul. 08, 2020	Dec. 22, 2020	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Jul. 15, 2019	May 30, 2020~Jul. 08, 2020	Jul. 14, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Dec. 30, 2019	May 30, 2020~Jul. 08, 2020	Dec. 29, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC130048 4	N/A	Aug. 22, 2019	May 30, 2020~Jul. 08, 2020	Aug. 21, 2020	Conducted (TH05-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 22, 2020~ Jul. 08, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Jun. 22, 2020~ Jul. 08, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	Jun. 22, 2020~ Jul. 08, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Jun. 22, 2020~ Jul. 08, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 22, 2020~ Jul. 08, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Jun. 22, 2020~ Jul. 08, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Jun. 22, 2020~ Jul. 08, 2020	Jan. 01, 2021	Conduction (CO05-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	2.3
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	4.9
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	6.7
---	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	3.9
---	-----

## Appendix A. Test Result of Conducted Test Items

Test Engineer:	Hank Hsu	Temperature:	23.1~24.1	°C
Test Date:	2020/5/30~2020/7/8	Relative Humidity:	51~53.8	%

<b><u>TEST RESULTS DATA</u></b> <b><u>6dB and 99% Occupied Bandwidth</u></b>								
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.040	0.678	0.50	Pass
BLE	1Mbps	1	19	2440	1.038	0.684	0.50	Pass
BLE	1Mbps	1	39	2480	1.040	0.690	0.50	Pass

<b><u>TEST RESULTS DATA</u></b> <b><u>Average Power Table</u></b>										
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	5.80	30.00	2.34	8.14	36.00	Pass
BLE	1Mbps	1	19	2440	5.90	30.00	2.34	8.24	36.00	Pass
BLE	1Mbps	1	39	2480	5.70	30.00	2.34	8.04	36.00	Pass

<b><u>TEST RESULTS DATA</u></b> <b><u>Peak Power Density</u></b>									
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	5.05	-9.32	2.34	8.00	Pass
BLE	1Mbps	1	19	2440	5.07	-9.53	2.34	8.00	Pass
BLE	1Mbps	1	39	2480	4.97	-9.41	2.34	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.080	1.160	0.50	Pass
BLE	2Mbps	1	19	2440	2.080	1.152	0.50	Pass
BLE	2Mbps	1	39	2480	2.080	1.164	0.50	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	5.80	30.00	2.34	8.14	36.00	Pass
BLE	2Mbps	1	19	2440	5.90	30.00	2.34	8.24	36.00	Pass
BLE	2Mbps	1	39	2480	5.90	30.00	2.34	8.24	36.00	Pass

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	4.96	-13.28	2.34	8.00	Pass
BLE	2Mbps	1	19	2440	4.99	-13.24	2.34	8.00	Pass
BLE	2Mbps	1	39	2480	5.59	-13.20	2.34	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




## **Appendix B. AC Conducted Emission Test Results**

<b>Test Engineer :</b>	Tom Lee	<b>Temperature :</b>	23~25°C
		<b>Relative Humidity :</b>	42~50%

## EUT Information

Report NO : 020110-01  
 Test Mode : Mode 2  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	33.20	56.00	22.80	L1	OFF	19.6
0.150000	46.93	---	66.00	19.07	L1	OFF	19.6
0.233430	---	35.04	52.33	17.29	L1	OFF	19.6
0.233430	39.08	---	62.33	23.25	L1	OFF	19.6
0.498750	---	32.13	46.02	13.89	L1	OFF	19.6
0.498750	36.16	---	56.02	19.86	L1	OFF	19.6
0.566520	---	36.70	46.00	9.30	L1	OFF	19.6
0.566520	41.46	---	56.00	14.54	L1	OFF	19.6
0.634560	---	30.36	46.00	15.64	L1	OFF	19.6
0.634560	33.49	---	56.00	22.51	L1	OFF	19.6
14.364510	---	27.10	50.00	22.90	L1	OFF	20.2
14.364510	30.34	---	60.00	29.66	L1	OFF	20.2

## EUT Information

Report NO : 020110-01  
 Test Mode : Mode 2  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	32.84	56.00	23.16	N	OFF	19.6
0.150000	47.00	---	66.00	19.00	N	OFF	19.6
0.233250	---	33.74	52.33	18.59	N	OFF	19.5
0.233250	38.70	---	62.33	23.63	N	OFF	19.5
0.296070	---	28.81	50.35	21.54	N	OFF	19.5
0.296070	33.04	---	60.35	27.31	N	OFF	19.5
0.502620	---	31.54	46.00	14.46	N	OFF	19.5
0.502620	35.19	---	56.00	20.81	N	OFF	19.5
0.561750	---	31.73	46.00	14.27	N	OFF	19.5
0.561750	36.33	---	56.00	19.67	N	OFF	19.5
12.601500	---	25.30	50.00	24.70	N	OFF	19.9
12.601500	26.59	---	60.00	33.41	N	OFF	19.9



## Appendix C. Radiated Spurious Emission

Test Engineer :	Karl Hou, Andy Yang and CR Liao	Temperature :	20~25°C
		Relative Humidity :	50~60%

&lt;1Mbps&gt;

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2387.385	58.75	-15.25	74	42.79	27.65	18.09	29.78	242	302	P	H
		2377.83	47.21	-6.79	54	31.23	27.69	18.07	29.78	242	302	A	H
	*	2402	110.69	-	-	94.77	27.6	18.11	29.79	242	302	P	H
	*	2402	110.1	-	-	94.18	27.6	18.11	29.79	242	302	A	H
		2329.53	57.95	-16.05	74	41.84	27.88	17.99	29.76	101	258	P	V
		2315.775	47.38	-6.62	54	31.22	27.94	17.97	29.75	101	258	A	V
	*	2402	107.3	-	-	91.38	27.6	18.11	29.79	101	258	P	V
	*	2402	106.68	-	-	90.76	27.6	18.11	29.79	101	258	A	V
BLE CH 19 2440MHz		2323.72	57.47	-16.53	74	41.34	27.91	17.98	29.76	267	304	P	H
		2333.1	46.6	-7.4	54	30.49	27.87	18	29.76	267	304	A	H
	*	2440	112.38	-	-	96.41	27.6	18.17	29.8	267	304	P	H
	*	2440	111.69	-	-	95.72	27.6	18.17	29.8	267	304	A	H
		2493.77	57.19	-16.81	74	41.25	27.51	18.26	29.83	267	304	P	H
		2491.6	46.93	-7.07	54	30.98	27.52	18.26	29.83	267	304	A	H
		2384.34	57.12	-16.88	74	41.16	27.66	18.08	29.78	104	95	P	V
		2357.6	46.58	-7.42	54	30.54	27.77	18.04	29.77	104	95	A	V
	*	2440	108.5	-	-	92.53	27.6	18.17	29.8	104	95	P	V
	*	2440	107.84	-	-	91.87	27.6	18.17	29.8	104	95	A	V
		2484.04	56.96	-17.04	74	41.01	27.53	18.24	29.82	104	95	P	V
		2485.72	46.59	-7.41	54	30.63	27.53	18.25	29.82	104	95	A	V



BLE CH 39 2480MHz	*	2480	112.39	-	-	96.43	27.54	18.24	29.82	261	302	P	H
	*	2480	111.89	-	-	95.93	27.54	18.24	29.82	261	302	A	H
		2486.04	63.23	-10.77	74	47.27	27.53	18.25	29.82	261	302	P	H
		2484.52	48.49	-5.51	54	32.53	27.53	18.25	29.82	261	302	A	H
	*	2480	108.02	-	-	92.06	27.54	18.24	29.82	100	294	P	V
	*	2480	107.53	-	-	91.57	27.54	18.24	29.82	100	294	A	V
		2484.2	60.33	-13.67	74	44.38	27.53	18.24	29.82	100	294	P	V
		2486.48	47.17	-6.83	54	31.21	27.53	18.25	29.82	100	294	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## BLE (Harmonic @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
<b>BLE CH 00 2402MHz</b>		4804	41.06	-32.94	74	56.63	31.11	12.4	59.08	100	0	P	H
		4804	40.34	-33.66	74	55.91	31.11	12.4	59.08	100	0	P	V
<b>BLE CH 19 2440MHz</b>		4880	40.87	-33.13	74	56.44	31.08	12.48	59.13	100	0	P	H
		7320	46.83	-27.17	74	53.22	36.48	15.68	58.55	100	0	P	H
		4880	40.58	-33.42	74	56.15	31.08	12.48	59.13	100	0	P	V
		7320	46.59	-27.41	74	52.98	36.48	15.68	58.55	100	0	P	V
<b>BLE CH 39 2480MHz</b>		4960	40.74	-33.26	74	56.1	31.26	12.56	59.18	100	0	P	H
		7440	47.45	-26.55	74	53.47	36.58	15.78	58.38	100	0	P	H
		4960	40.65	-33.35	74	56.01	31.26	12.56	59.18	100	0	P	V
		7440	47.01	-26.99	74	53.03	36.58	15.78	58.38	100	0	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



&lt;2Mbps&gt;

## 2.4GHz 2400~2483.5MHz

## BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2381.4	58.12	-15.88	74	42.15	27.67	18.08	29.78	248	304	P	H
		2384.55	45.7	-8.3	54	29.74	27.66	18.08	29.78	248	304	A	H
	*	2402	111.03	-	-	95.11	27.6	18.11	29.79	248	304	P	H
	*	2402	109.45	-	-	93.53	27.6	18.11	29.79	248	304	A	H
		2346.96	57.27	-16.73	74	41.21	27.81	18.02	29.77	100	97	P	V
		2367.645	45.7	-8.3	54	29.68	27.73	18.06	29.77	100	97	A	V
	*	2402	106.76	-	-	90.84	27.6	18.11	29.79	100	97	P	V
	*	2402	104.67	-	-	88.75	27.6	18.11	29.79	100	97	A	V
BLE CH 19 2440MHz		2322.04	57.68	-16.32	74	41.55	27.91	17.98	29.76	272	304	P	H
		2372.58	45.63	-8.37	54	29.64	27.71	18.06	29.78	272	304	A	H
	*	2440	112.39	-	-	96.42	27.6	18.17	29.8	272	304	P	H
	*	2440	110.41	-	-	94.44	27.6	18.17	29.8	272	304	A	H
		2483.83	58.51	-15.49	74	42.56	27.53	18.24	29.82	272	304	P	H
		2484.11	45.76	-8.24	54	29.81	27.53	18.24	29.82	272	304	A	H
		2388.12	56.95	-17.05	74	40.99	27.65	18.09	29.78	105	95	P	V
		2383.5	45.7	-8.3	54	29.73	27.67	18.08	29.78	105	95	A	V
	*	2440	108.74	-	-	92.77	27.6	18.17	29.8	105	95	P	V
	*	2440	106.61	-	-	90.64	27.6	18.17	29.8	105	95	A	V
		2484.39	57.17	-16.83	74	41.21	27.53	18.25	29.82	105	95	P	V
		2495.17	45.66	-8.34	54	29.72	27.51	18.26	29.83	105	95	A	V



BLE CH 39 2480MHz	*	2480	112.45	-	-	96.49	27.54	18.24	29.82	259	302	P	H
	*	2480	109.99	-	-	94.03	27.54	18.24	29.82	259	302	A	H
		2483.68	63.68	-10.32	74	47.73	27.53	18.24	29.82	259	302	P	H
		2483.52	53.21	-0.79	54	37.26	27.53	18.24	29.82	259	302	A	H
	*	2480	107.85	-	-	91.89	27.54	18.24	29.82	100	294	P	V
	*	2480	105.93	-	-	89.97	27.54	18.24	29.82	100	294	A	V
		2483.6	59.9	-14.1	74	43.95	27.53	18.24	29.82	100	294	P	V
		2483.52	49.51	-4.49	54	33.56	27.53	18.24	29.82	100	294	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## BLE (Harmonic @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
<b>BLE CH 00 2402MHz</b>		4804	40.34	-33.66	74	55.91	31.11	12.4	59.08	100	0	P	H
		4804	40.99	-33.01	74	56.56	31.11	12.4	59.08	100	0	P	V
<b>BLE CH 19 2440MHz</b>		4880	40.45	-33.55	74	56.02	31.08	12.48	59.13	100	0	P	H
		7320	46.66	-27.34	74	53.05	36.48	15.68	58.55	100	0	P	H
		4880	40.56	-33.44	74	56.13	31.08	12.48	59.13	100	0	P	V
		7320	47.16	-26.84	74	53.55	36.48	15.68	58.55	100	0	P	V
<b>BLE CH 39 2480MHz</b>		4960	40.57	-33.43	74	55.93	31.26	12.56	59.18	100	0	P	H
		7440	47.1	-26.9	74	53.12	36.58	15.78	58.38	100	0	P	H
		4960	40.74	-33.26	74	56.1	31.26	12.56	59.18	100	0	P	V
		7440	46.82	-27.18	74	52.84	36.58	15.78	58.38	100	0	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## Emission above 18GHz

## 2.4GHz BLE (SHF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
<b>2.4GHz BLE SHF</b>		18182	38.72	-35.28	74	44.69	37.28	10.93	54.18	150	0	P	H
		24398	40.07	-33.93	74	40.11	40.16	13.26	53.46	150	0	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against limit line.												



## Emission below 1GHz

## 2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
2.4GHz BLE LF		71.71	29.65	-10.35	40	48.25	12.31	1.44	32.35	-	-	P	H	
		112.45	34.95	-8.55	43.5	48.4	16.99	1.82	32.26	100	0	P	H	
		189.08	23.87	-19.63	43.5	39.08	14.71	2.39	32.31	-	-	P	H	
		576.11	28.57	-17.43	46	30.63	25.79	4.11	31.96	-	-	P	H	
		711.91	30.36	-15.64	46	31.32	26.64	4.58	32.18	-	-	P	H	
		894.27	36.75	-9.25	46	34.58	28.98	5.14	31.95	-	-	P	H	
		43.58	33.26	-6.74	40	47.14	17.38	1.09	32.35	100	0	P	V	
		113.42	36.34	-7.16	43.5	49.68	17.09	1.83	32.26	-	-	P	V	
		184.23	26.61	-16.89	43.5	41.79	14.77	2.36	32.31	-	-	P	V	
		729.37	31.81	-14.19	46	31.84	27.54	4.64	32.21	-	-	P	V	
		885.54	32.35	-13.65	46	30.18	29.04	5.12	31.99	-	-	P	V	
		946.65	34.64	-11.36	46	30.12	30.59	5.3	31.37	-	-	P	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													

**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak or Average</b>
H/V	<b>Horizontal or Vertical</b>



**A calculation example for radiated spurious emission is shown as below:**

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
			Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
<b>BLE CH 00 2402MHz</b>		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dB $\mu$ V/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB $\mu$ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB $\mu$ V/m) – Limit Line(dB $\mu$ V/m)

#### For Peak Limit @ 2390MHz:

1. Level(dB $\mu$ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB $\mu$ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dB $\mu$ V) – 35.86 (dB)

= 55.45 (dB $\mu$ V/m)

2. Over Limit(dB)

= Level(dB $\mu$ V/m) – Limit Line(dB $\mu$ V/m)

= 55.45(dB $\mu$ V/m) – 74(dB $\mu$ V/m)

= -18.55(dB)

#### For Average Limit @ 2390MHz:

1. Level(dB $\mu$ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB $\mu$ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dB $\mu$ V) – 35.86 (dB)

= 43.54 (dB $\mu$ V/m)

2. Over Limit(dB)

= Level(dB $\mu$ V/m) – Limit Line(dB $\mu$ V/m)

= 43.54(dB $\mu$ V/m) – 54(dB $\mu$ V/m)

= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix D. Radiated Spurious Emission Plots

<b>Test Engineer :</b>	Karl Hou, Andy Yang and CR Liao	<b>Temperature :</b>	20~25°C
		<b>Relative Humidity :</b>	50~60%





### Note symbol


-L	<b>Low channel location</b>
-R	<b>High channel location</b>




&lt;1Mbps&gt;



**2.4GHz 2400~2483.5MHz**  
**BLE (Band Edge @ 3m)**


BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 <p>Site : 02CH16-HY Condition : PEAK_BE_74 3m 9120D_1522 HORIZONTAL : RBW:1000.000kHz VBW:3000.000Hz SWT:Auto Detector : Peak Project : 020110-01</p>	 <p>Site : 02CH16-HY Condition : PEAK_74 3m 9120D_1522 HORIZONTAL : RBW:1000.000kHz VBW:3000.000Hz SWT:Auto Detector : Peak Project : 020110-01</p>
Avg.	 <p>Site : 02CH16-HY Condition : AVG_BE_54 3m 9120D_1522 HORIZONTAL : RBW:1000.000kHz VBW:3.000Hz SWT:Auto Detector : Peak Project : 020110-01</p>	 <p>Site : 02CH16-HY Condition : AVG_54 3m 9120D_1522 HORIZONTAL : RBW:1000.000kHz VBW:3.000Hz SWT:Auto Detector : Peak Project : 020110-01</p>











BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 9120D_1522 HORIZONTAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 020110-01</p>	Left blank
Avg.	 <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 9120D_1522 HORIZONTAL Detector : R8W:1000.000KHz VBW:3.000KHz SWT:Auto Project : 020110-01</p>	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Vertical	Fundamental
Peak	 <p>Level (dBm/Vm)</p> <p>Date: 2020-05-25</p> <p>2430 2440 2450 2460 2470 2480 2490 2500 Frequency (MHz)</p> <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 9120D_1522 VERTICAL : 88MHz-1000.000KHz VBW-3000.000KHz SWT:Auto Detector : Peak Project : 020110-01</p>	Left blank
Avg.	 <p>Level (dBm/Vm)</p> <p>Date: 2020-05-25</p> <p>2430 2440 2450 2460 2470 2480 2490 2500 Frequency (MHz)</p> <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 9120D_1522 VERTICAL : 88MHz-1000.000KHz VBW-3000.000KHz SWT:Auto Detector : Peak Project : 020110-01</p>	Left blank










## 2.4GHz 2400~2483.5MHz

## BLE (Harmonic @ 3m)















&lt;2Mbps&gt;



**2.4GHz 2400~2483.5MHz**  
**BLE (Band Edge @ 3m)**


BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL : RBW:1000.000kHz VBW:3000.000Hz SWT:Auto Detector : Peak Project : 020110-01</p>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL : RBW:1000.000kHz VBW:3000.000Hz SWT:Auto Detector : Peak Project : 020110-01</p>
Avg.	 <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL : RBW:1000.000kHz VBW:1000Hz SWT:Auto Detector : Peak Project : 020110-01</p>	 <p>Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 HORIZONTAL : RBW:1000.000kHz VBW:1000Hz SWT:Auto Detector : Peak Project : 020110-01</p>











BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Horizontal	Fundamental
Peak	 <p>Level (dBc/1m) vs Frequency (MHz) from 2430 to 2500. The graph shows a sharp peak at 2440MHz reaching approximately 110 dBc/1m. A red step line indicates the band edge. The text 'PEAK_BE_74' is highlighted in red. The graph is dated 2020-05-25.</p> <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 9120D_1522 HORIZONTAL : 88MHz-1000.000KHz VBW-3000.000KHz SWT:Auto Detector : Peak Project : 020110-01</p>	Left blank
Avg.	 <p>Level (dBc/1m) vs Frequency (MHz) from 2430 to 2500. The graph shows a sharp peak at 2440MHz reaching approximately 100 dBc/1m. A red step line indicates the band edge. The text 'AVG_BE_54' is highlighted in red. The graph is dated 2020-05-25.</p> <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 9120D_1522 HORIZONTAL : 88MHz-1000.000KHz VBW-1000KHz SWT:Auto Detector : Peak Project : 020110-01</p>	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Vertical	Fundamental
Peak	 <p>Level (dBc/1m) vs Frequency (MHz) from 2430 to 2500. The graph shows a sharp peak at 2440 MHz reaching approximately 110 dBc/1m. A red line highlights the peak. The date is 2020-05-25.</p> <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 9120D_1522 VERTICAL : 88MHz:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 020110-01</p>	Left blank
Avg.	 <p>Level (dBc/1m) vs Frequency (MHz) from 2430 to 2500. The graph shows a sharp peak at 2440 MHz reaching approximately 100 dBc/1m. A red line highlights the peak. The date is 2020-05-25.</p> <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 9120D_1522 VERTICAL : 88MHz:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 020110-01</p>	Left blank










## 2.4GHz 2400~2483.5MHz

## BLE (Harmonic @ 3m)











## Emission above 18GHz


## 2.4GHz BLE (SHF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE SHF	
	Horizontal	Vertical
Peak	 <p>Graph showing Level (dBuV/m) vs Frequency (MHz) for Horizontal emission. The x-axis ranges from 18000 to 25000 MHz, and the y-axis ranges from 10 to 140 dBuV/m. A blue line represents the measurement, and a red line indicates the peak level. The peak is labeled 'PEAK_74' at approximately 2483.5 MHz. A horizontal line at 54 dB is labeled 'AVG_54'.</p> <p>Date: 2020-06-19</p> <p>Site : 03QH16-I-Y Condition : PEAK_74 In SHF HORN 88H-A9170584 HORIZONTAL Detector : Peak Project : 020110-01</p>	 <p>Graph showing Level (dBuV/m) vs Frequency (MHz) for Vertical emission. The x-axis ranges from 18000 to 25000 MHz, and the y-axis ranges from 10 to 140 dBuV/m. A blue line represents the measurement, and a red line indicates the peak level. The peak is labeled 'PEAK_74' at approximately 2483.5 MHz. A horizontal line at 54 dB is labeled 'AVG_54'.</p> <p>Date: 2020-06-19</p> <p>Site : 03QH16-I-Y Condition : PEAK_74 In SHF HORN 88H-A9170584 VERTICAL Detector : Peak Project : 020110-01</p>



## Emission below 1GHz

## 2.4GHz BLE (LF)






## Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth -LE for 1Mbps	61.15	384	2.60	3kHz	2.14
Bluetooth -LE for 2Mbps	56.5	1065	0.94	1kHz	2.48




## Bluetooth -LE for 1Mbps



Date: 30.MAY.2020 02:26:37

## Bluetooth -LE for 2Mbps



Date: 30.MAY.2020 02:32:30

—THE END—