



# RF EXPOSURE

# Test Report

**Report No.:** MTi230519006-01E2

**Date of issue:** 2023-11-03

**Applicant:** Shenzhen Smartrol Technology Limited

**Product:** SMART CAMERA

**Model(s):** ZX-C23B, ZX-C24

**FCC ID:** 2AURI-ZX-C23B

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>



## Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



<b>Test Result Certification</b>	
<b>Applicant:</b>	<b>Shenzhen Smartrol Technology Limited</b>
Address:	6F, Leishi Industrial Park, NO.1119, Guanlan Guanguang Road, Longhua District, Shenzhen, China
<b>Manufacturer:</b>	<b>Shenzhen Smartrol Technology Limited</b>
Address:	6F, Leishi Industrial Park, NO.1119, Guanlan Guanguang Road, Longhua District, Shenzhen, China
<b>Product description</b>	
Product name:	SMART CAMERA
Trademark:	N/A
Model name:	ZX-C23B
Serial Model:	ZX-C24
Standards:	N/A
Test procedure:	KDB 447498 D01 v06
<b>Date of Test</b>	
Date of test:	2023-06-02 ~ 2023-11-03
Test result:	Pass

**Test Engineer :**

(Maleah Deng)

**Reviewed By :**

(Leon Chen)

**Approved By :**

(Tom Xue)



## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

### MPE Calculation Method

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

$P_d$  = Power density in  $\text{mW/cm}^2$

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi = 3.1415926$

$R$  = distance between observation point and center of the radiator in cm (20cm)

$P_d$  the limit of MPE,  $1\text{mW/cm}^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



## Measurement Result

### 2.4GWiFi:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

802.11n HT40: 2422-2452MHz,

Power density limited: 1mW/ cm<sup>2</sup>

### 2.4GWiFi:

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power	Gain			
				(dBm)	(mW)	Numeric		
2412	802.11b	15.26	15±1	16	39.811	2.24	0.01773	1
2437		15.14	15±1	16	39.811	2.24	0.01773	1
2462		14.02	14±1	15	31.623	2.24	0.01408	1
2412	802.11g	14.42	14±1	15	31.623	2.24	0.01408	1
2437		14.53	14±1	15	31.623	2.24	0.01408	1
2462		13.30	13±1	14	25.119	2.24	0.01119	1
2412	802.11n H20	14.54	14±1	15	31.623	2.24	0.01408	1
2437		14.14	14±1	15	31.623	2.24	0.01408	1
2462		13.19	13±1	14	25.119	2.24	0.01119	1
2412	802.11n H40	14.56	14±1	15	31.623	2.24	0.01408	1
2437		14.19	14±1	15	31.623	2.24	0.01408	1
2462		13.88	13±1	14	25.119	2.24	0.01119	1

### Conclusion:

For the max result: 0.01773≤ 1.0, No SAR is required.

----END OF REPORT----